

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

SECTION 1. IDENTIFICATION

Product name : WHITE LITHIUM GREASE SPRAY, 300 g

Product code : 893.870300

Other means of identification : No data available

Manufacturer or supplier's details

Company name of supplier : Würth Canada Limited

Address : 345 Hanlon Creek Blvd
GUELPH, ON N1C 0A1

Telephone : +1 (905) 564 6225

Telefax : +1 (905) 564 3671

Emergency telephone : Emergencies involving a spill, fire, explosion or exposure:
CHEMTREC (24/7): 1-800-424-9300
Transport related emergencies:
CANUTEC (24/7): 1-613-996-6666 or * 666 (cell)

Urgences impliquant un déversement, incendie, explosion ou exposition:
CHEMTREC (24/7): 1-800-424-9300
Urgences liées au transport:
CANUTEC (24/7): 1-613-996-6666 ou * 666 (cellulaire)

E-mail address : prodsafe@wurth.ca

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : Not applicable

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the Hazardous Products Regulations**

Flammable aerosols : Category 1

Gases under pressure : Liquefied gas

Skin irritation : Category 2

Carcinogenicity (Inhalation) : Category 2

Specific target organ toxicity : Category 3

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue:
3.2	05/19/2022	10696677-00007	09/21/2021
			Date of first issue: 01/26/2018

- single exposure

GHS label elements

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H222 Extremely flammable aerosol.
H280 Contains gas under pressure; may explode if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer if inhaled.

Precautionary Statements

: **Prevention:**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves, protective clothing, eye protection and face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a doctor if you feel unwell.
P308 + P313 IF exposed or concerned: Get medical attention.
P332 + P313 If skin irritation occurs: Get medical attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C (122 °F).

Disposal:

P501 Dispose of contents and container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

WHITE LITHIUM GREASE SPRAY, 300 g

Version 3.2 Revision Date: 05/19/2022 SDS Number: 10696677-00007 Date of last issue: 09/21/2021
 Date of first issue: 01/26/2018

Substance / Mixture : Mixture

Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Naphtha (petroleum), hydrotreated light	Naphtha (petroleum), hydrotreated light	64742-49-0	$\geq 30 - < 60$ *
Liquified petroleum gas (LPG)	Petroleum gases, liquefied	68476-85-7	$\geq 30 - < 60$ *
Distillates (petroleum), solvent-dewaxed heavy paraffinic	No data available	64742-65-0	$\geq 10 - < 30$ *
Residual oils (petroleum), solvent-dewaxed	No data available	64742-62-7	$\geq 5 - < 10$ *
12-Hydroxy lithium stearate	Octadecanoic acid, 12-hydroxy-, lithium salt (1:1)	7620-77-1	$\geq 1 - < 5$ *
Titanium dioxide	Titanic anhydride	13463-67-7	$\geq 0.1 - < 1$ *

* Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
 When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
 Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
 Get medical attention.
 Wash clothing before reuse.
 Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.
 Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.
 Get medical attention if symptoms occur.
 Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
 May cause drowsiness or dizziness.
 Suspected of causing cancer if inhaled.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

when the potential for exposure exists (see section 8).

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire fighting : Flash back possible over considerable distance.
Vapors may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g., by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapors/mists with a water spray jet.
For large spills, provide diking or other appropriate contain-

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

ment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

- | | | |
|-----------------------------|---|--|
| Technical measures | : | See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section. |
| Local/Total ventilation | : | If sufficient ventilation is unavailable, use with local exhaust ventilation.
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation. |
| Advice on safe handling | : | Do not get on skin or clothing.
Avoid breathing spray.
Do not swallow.
Avoid contact with eyes.
Wash skin thoroughly after handling.
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Take precautionary measures against static discharges.
Take care to prevent spills, waste and minimize release to the environment.
Do not spray on an open flame or other ignition source. |
| Conditions for safe storage | : | Store locked up.
Keep in a cool, well-ventilated place.
Store in accordance with the particular national regulations.
Do not pierce or burn, even after use.
Keep cool. Protect from sunlight. |
| Materials to avoid | : | Do not store with the following product types:
Self-reactive substances and mixtures
Organic peroxides
Oxidizing agents
Flammable solids
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Substances and mixtures which in contact with water emit flammable gases
Explosives |

WHITE LITHIUM GREASE SPRAY, 300 g

Version 3.2 Revision Date: 05/19/2022 SDS Number: 10696677-00007 Date of last issue: 09/21/2021
 Date of first issue: 01/26/2018

Gases

Recommended storage temperature : < 40 °C

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Naphtha (petroleum), hydrotreated light	64742-49-0	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
Liquified petroleum gas (LPG)	68476-85-7	TWA	1,000 ppm	CA AB OEL
		STEL	1,500 ppm	CA AB OEL
		TWAEV	1,000 ppm 1,800 mg/m ³	CA QC OEL
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
Residual oils (petroleum), solvent-dewaxed	64742-62-7	TWA (Mist)	5 mg/m ³	CA AB OEL
		STEL (Mist)	10 mg/m ³	CA AB OEL
		TWAEV (Mist)	5 mg/m ³	CA QC OEL
		STEV (Mist)	10 mg/m ³	CA QC OEL
		TWA (Mist)	1 mg/m ³	CA BC OEL
		TWA (Inhalable particulate matter)	5 mg/m ³	ACGIH
12-Hydroxy lithium stearate	7620-77-1	TWA	10 mg/m ³	CA AB OEL
		TWAEV	10 mg/m ³	CA QC OEL
		TWA (Inhalable)	10 mg/m ³	CA BC OEL
		TWA (Respirable)	3 mg/m ³	CA BC OEL
		TWA (Inhalable particulate matter)	10 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	3 mg/m ³	ACGIH

WHITE LITHIUM GREASE SPRAY, 300 g

Version 3.2 Revision Date: 05/19/2022 SDS Number: 10696677-00007 Date of last issue: 09/21/2021
 Date of first issue: 01/26/2018

		late matter)		
Titanium dioxide	13463-67-7	TWA	10 mg/m ³	CA AB OEL
		TWA (Total dust)	10 mg/m ³	CA BC OEL
		TWA (respirable dust fraction)	3 mg/m ³	CA BC OEL
		TWAEV (total dust)	10 mg/m ³	CA QC OEL
		TWA	10 mg/m ³ (Titanium dioxide)	ACGIH

Engineering measures : Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

Hand protection

Material : Neoprene gloves

Material : Nitrile rubber

Remarks : Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the product. Change gloves often!

Eye protection : Wear the following personal protective equipment:
 Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
 Wear the following personal protective equipment:
 If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
 Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
When using do not eat, drink or smoke.
Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Aerosol containing a liquefied gas

Propellant : Liquefied petroleum gas (LPG), Isobutane

Color : white

Odor : mild

Odor Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : 7 °C
Method: closed cup
Flash point is only valid for liquid portion in the aerosol can.

Evaporation rate : Not applicable

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : > 1

Relative density : 0.75 (15 °C)

Density : 0.75 g/cm³ (15 °C)

Solubility(ies)

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

Water solubility	:	practically insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity	:	
Viscosity, kinematic	:	> 14 mm ² /s
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.
Particle size	:	Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	Not classified as a reactivity hazard.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Extremely flammable aerosol. Vapors may form explosive mixture with air. If the temperature rises there is danger of the vessels bursting due to the high vapor pressure. Can react with strong oxidizing agents.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation
Skin contact
Ingestion
Eye contact

Acute toxicity

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated light:**

Acute oral toxicity	:	LD50 (Rat): > 5,840 mg/kg
Remarks: Based on data from similar materials		

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

Acute inhalation toxicity : LC50 (Rat): > 25.2 mg/l
Exposure time: 4 h
Test atmosphere: vapor
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,800 - 3,100 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: Based on data from similar materials

Liquified petroleum gas (LPG):

Acute inhalation toxicity : LC50 (Mouse): 520400 ppm
Exposure time: 2 h
Test atmosphere: gas
Remarks: Based on data from similar materials

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

Residual oils (petroleum), solvent-dewaxed:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 hrs
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Method: OECD Test Guideline 402
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

Assessment: The substance or mixture has no acute oral toxicity

Titanium dioxide:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 6.82 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Skin corrosion/irritation

Causes skin irritation.

Components:**Naphtha (petroleum), hydrotreated light:**

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Residual oils (petroleum), solvent-dewaxed:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

12-Hydroxy lithium stearate:

Species : Rabbit
Result : No skin irritation
Remarks : Based on data from similar materials

Titanium dioxide:

Species : Rabbit
Result : No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated light:**

Species : Rabbit
Result : No eye irritation

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species	:	Rabbit
Result	:	No eye irritation
Method	:	OECD Test Guideline 405
Remarks	:	Based on data from similar materials

Residual oils (petroleum), solvent-dewaxed:

Species	:	Rabbit
Result	:	No eye irritation
Remarks	:	Based on data from similar materials

12-Hydroxy lithium stearate:

Species	:	Rabbit
Result	:	No eye irritation
Remarks	:	Based on data from similar materials

Titanium dioxide:

Species	:	Rabbit
Result	:	No eye irritation

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated light:**

Test Type	:	Maximization Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Result	:	negative
Remarks	:	Based on data from similar materials

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative
Remarks	:	Based on data from similar materials

Residual oils (petroleum), solvent-dewaxed:

Test Type	:	Buehler Test
Routes of exposure	:	Skin contact
Species	:	Guinea pig
Method	:	OECD Test Guideline 406
Result	:	negative

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

12-Hydroxy lithium stearate:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Method	: OECD Test Guideline 429
Result	: negative

Titanium dioxide:

Test Type	: Local lymph node assay (LLNA)
Routes of exposure	: Skin contact
Species	: Mouse
Result	: negative

Germ cell mutagenicity

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated light:**

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro
	Result: negative
	Remarks: Based on data from similar materials

Liquified petroleum gas (LPG):

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro
	Method: OECD Test Guideline 473
	Result: negative
	Remarks: Based on data from similar materials

Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
	Species: Rat
	Application Route: inhalation (gas)
	Method: OECD Test Guideline 474
	Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Genotoxicity in vitro	: Test Type: Bacterial reverse mutation assay (AMES)
	Method: OECD Test Guideline 471
	Result: negative
	Remarks: Based on data from similar materials

Genotoxicity in vivo	: Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
	Species: Mouse
	Application Route: Intraperitoneal injection
	Method: OECD Test Guideline 474
	Result: negative
	Remarks: Based on data from similar materials

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

Residual oils (petroleum), solvent-dewaxed:

Genotoxicity in vitro	:	Test Type: Chromosome aberration test in vitro Result: negative Remarks: Based on data from similar materials
Genotoxicity in vivo	:	Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay) Species: Mouse Application Route: Intraperitoneal injection Method: OECD Test Guideline 474 Result: negative

Titanium dioxide:

Genotoxicity in vitro	:	Test Type: Bacterial reverse mutation assay (AMES) Result: negative
Genotoxicity in vivo	:	Test Type: In vivo micronucleus test Species: Mouse Result: negative

Carcinogenicity

Suspected of causing cancer if inhaled.

Components:**Liquified petroleum gas (LPG):**

Species	:	Mouse
Application Route	:	inhalation (gas)
Exposure time	:	103 weeks
Result	:	negative
Remarks	:	Based on data from similar materials

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species	:	Mouse
Application Route	:	Skin contact
Exposure time	:	78 weeks
Method	:	OECD Test Guideline 451
Result	:	negative

Residual oils (petroleum), solvent-dewaxed:

Species	:	Mouse
Application Route	:	Skin contact
Exposure time	:	78 weeks
Result	:	negative
Remarks	:	Based on data from similar materials

Titanium dioxide:

Species	:	Rat
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	2 Years
Method	:	OECD Test Guideline 453

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

Result	:	positive
Remarks	:	The mechanism or mode of action may not be relevant in humans.
Carcinogenicity - Assessment	:	Limited evidence of carcinogenicity in inhalation studies with animals.

Reproductive toxicity

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated light:**

Effects on fertility	:	Test Type: Two-generation reproduction toxicity study Species: Rat Application Route: inhalation (vapor) Result: negative Remarks: Based on data from similar materials
----------------------	---	---

Effects on fetal development	:	Test Type: Embryo-fetal development Species: Mouse Application Route: inhalation (vapor) Result: negative Remarks: Based on data from similar materials
------------------------------	---	---

Residual oils (petroleum), solvent-dewaxed:

Effects on fertility	:	Test Type: Reproduction/Developmental toxicity screening test Species: Rat Application Route: Ingestion Result: negative
Effects on fetal development	:	Test Type: Embryo-fetal development Species: Rat Application Route: Skin contact Result: negative

STOT-single exposure

May cause drowsiness or dizziness.

Components:**Naphtha (petroleum), hydrotreated light:**

Assessment	:	May cause drowsiness or dizziness.
Remarks	:	Based on data from similar materials

Liquified petroleum gas (LPG):

Assessment	:	May cause drowsiness or dizziness.
------------	---	------------------------------------

STOT-repeated exposure

Not classified based on available information.

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

Components:**12-Hydroxy lithium stearate:**

Routes of exposure	:	Ingestion
Assessment	:	No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Repeated dose toxicity**Components:****Naphtha (petroleum), hydrotreated light:**

Species	:	Rat
NOAEL	:	24,300 mg/m ³
Application Route	:	inhalation (vapor)
Exposure time	:	13 Weeks
Remarks	:	Based on data from similar materials

Liquified petroleum gas (LPG):

Species	:	Rat
NOAEL	:	10000 ppm
Application Route	:	inhalation (gas)
Exposure time	:	13 Weeks

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species	:	Rabbit
NOAEL	:	1,000 mg/kg
Application Route	:	Skin contact
Exposure time	:	4 Weeks
Method	:	OECD Test Guideline 410
Remarks	:	Based on data from similar materials

Species	:	Rat
NOAEL	:	> 980 mg/m ³
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	4 Weeks
Remarks	:	Based on data from similar materials

Residual oils (petroleum), solvent-dewaxed:

Species	:	Rat
NOAEL	:	1,000 mg/kg
Application Route	:	Skin contact
Exposure time	:	13 Weeks
Method	:	OECD Test Guideline 411
Remarks	:	Based on data from similar materials

Species	:	Rat
NOAEL	:	> 980 mg/m ³
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	4 Weeks
Remarks	:	Based on data from similar materials

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

12-Hydroxy lithium stearate:

Species	:	Rat
NOAEL	:	> 88 mg/kg
Application Route	:	Ingestion
Exposure time	:	90 Days

Titanium dioxide:

Species	:	Rat
NOAEL	:	24,000 mg/kg
Application Route	:	Ingestion
Exposure time	:	28 Days

Species	:	Rat
NOAEL	:	10 mg/m ³
Application Route	:	inhalation (dust/mist/fume)
Exposure time	:	2 y

Aspiration toxicity

Not classified based on available information.

Components:**Naphtha (petroleum), hydrotreated light:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Naphtha (petroleum), hydrotreated light:**

Toxicity to fish	:	LL50 (Oncorhynchus mykiss (rainbow trout)): 12 mg/l Exposure time: 96 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 203 Remarks: Based on data from similar materials
Toxicity to daphnia and other aquatic invertebrates	:	EL50 (Daphnia magna (Water flea)): 3 mg/l Exposure time: 48 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 202 Remarks: Based on data from similar materials
Toxicity to algae/aquatic plants	:	EL50 (Pseudokirchneriella subcapitata (green algae)): 30 - 100 mg/l Exposure time: 72 h Test substance: Water Accommodated Fraction Method: OECD Test Guideline 201 Remarks: Based on data from similar materials
Toxicity to daphnia and other	:	NOEC (Daphnia magna (Water flea)): 0.17 mg/l

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

aquatic invertebrates (Chronic toxicity)

Exposure time: 21 d
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Method: DIN 38 412 Part 8
Remarks: Based on data from similar materials

Residual oils (petroleum), solvent-dewaxed:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 203
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 48 h
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test substance: Water Accommodated Fraction
Method: OECD Test Guideline 201
Remarks: Based on data from similar materials

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l
Exposure time: 21 d
Test substance: Water Accommodated Fraction
Remarks: Based on data from similar materials

Toxicity to microorganisms : NOEC: > 1.93 mg/l
Exposure time: 10 min
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOELR (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Titanium dioxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Skeletonema costatum (marine diatom)): > 10,000 mg/l
Exposure time: 72 h

Toxicity to microorganisms : EC50: > 1,000 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

Persistence and degradability**Components:****Naphtha (petroleum), hydrotreated light:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 77 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Liquified petroleum gas (LPG):

Biodegradability : Result: Readily biodegradable.
Biodegradation: 70 %

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 8 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Residual oils (petroleum), solvent-dewaxed:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 2 - 4 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
Remarks: Based on data from similar materials

12-Hydroxy lithium stearate:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 78 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Bioaccumulative potential**Components:****Naphtha (petroleum), hydrotreated light:**

Partition coefficient: n- : log Pow: > 4
octanol/water
Remarks: Expert judgment

Liquified petroleum gas (LPG):

Partition coefficient: n- : log Pow: 1.09
octanol/water

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

Please ensure aerosol cans are sprayed completely empty
(including propellant)

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1

IATA-DGR

UN/ID No.	: UN 1950
Proper shipping name	: Aerosols, flammable
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: Flammable Gas
Packing instruction (cargo aircraft)	: 203
Packing instruction (passenger aircraft)	: 203

IMDG-Code

UN number	: UN 1950
Proper shipping name	: AEROSOLS (Naphtha (petroleum), hydrotreated light, Zinc oxide)
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
EmS Code	: F-D, S-U
Marine pollutant	: yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**TDG**

UN number	: UN 1950
Proper shipping name	: AEROSOLS
Class	: 2.1
Packing group	: Not assigned by regulation
Labels	: 2.1
ERG Code	: 126
Marine pollutant	: yes(Naphtha (petroleum), hydrotreated light, Zinc oxide)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

SECTION 15. REGULATORY INFORMATION

Volatile organic compounds (VOC) content CANADIAN ENVIRONMENTAL PROTECTION ACT, 1999 - Guidelines for VOC in Consumer Products
VOC content: 80 % / 511.5 g/l

The ingredients of this product are reported in the following inventories:

DSL : All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).

SECTION 16. OTHER INFORMATION**Full text of other abbreviations**

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
CA AB OEL	:	Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	:	Canada. British Columbia OEL
CA QC OEL	:	Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for air-borne contaminants
ACGIH / TWA	:	8-hour, time-weighted average
CA AB OEL / TWA	:	8-hour Occupational exposure limit
CA AB OEL / STEL	:	15-minute occupational exposure limit
CA BC OEL / TWA	:	8-hour time weighted average
CA QC OEL / TWA EV	:	Time-weighted average exposure value
CA QC OEL / STEV	:	Short-term exposure value

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No

WHITE LITHIUM GREASE SPRAY, 300 g

Version	Revision Date:	SDS Number:	Date of last issue: 09/21/2021
3.2	05/19/2022	10696677-00007	Date of first issue: 01/26/2018

1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 05/19/2022
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

CA / Z8