



SAFETY DATA SHEET

Revision Date 09-01-2019

Version 4

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Code(s) 21377200-M
Product Name RUST VETO 377 HF

Recommended Use Antirust
Uses advised against Any other purpose.

Manufacturer, Importer, Supplier

Houghton International Inc. Madison & Van Buren Aves. Valley Forge, PA 19482 Telephone: 610-666-4000 FAX: 610-666-1376 Website: www.houghtonintl.com Customer Service: 888-459-9844	Houghton Canada 915 Meyerside Drive Mississauga ON L5T 1R8
--	--

Emergency telephone number

United States of America/Canada : 3E Company - 1-866-519-4752 (Code 333938)

SECTION 2: HAZARDS IDENTIFICATION

Classification

This product is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) and the Workplace Hazardous Materials Information System (WHMIS) 2015

Skin sensitization	Category 1
Aspiration toxicity	Category 1
Flammable liquids	Category 4

Label elements

Signal word
DANGER

Hazard statements

May cause an allergic skin reaction
May be fatal if swallowed and enters airways
Combustible liquid



Precautionary Statements

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
 Contaminated work clothing should not be allowed out of the workplace
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Specific treatment (see .? on this label)

Skin

IF ON SKIN: Wash with plenty of soap and water
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
 Do NOT induce vomiting

Fire

In case of fire: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Health Not Applicable.
Physical Not Applicable.

Other Information

Harmful to aquatic life with long lasting effects
 Harmful to aquatic life
 Prolonged skin contact may defat the skin and produce dermatitis
 Repeated exposure may cause skin dryness or cracking

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture. Health hazard information is based on its ingredients.

Chemical name	CAS No	Weight-%
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)	-	60% - 80%
Petrolatum	8009-03-8	10% - 30%
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	1% - 5%
2-(2-Butoxyethoxy)ethanol	112-34-5	1% - 5%
Sulfonic acids, petroleum, sodium salts	68608-26-4	1% - 5%
N-1-naphthylaniline	90-30-2	0.1% - 1%

The exact percentage (concentration) of composition has been withheld as a trade secret.

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346. See Section 15 for additional information on base oils.

SECTION 4: FIRST AID MEASURES

Description of first-aid measures

General advice	Immediate medical attention is required. Do not get in eyes, on skin, or on clothing.
Inhalation	Move to fresh air. Get medical attention immediately if symptoms occur. Potential for aspiration if swallowed.
Skin contact	Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing before re-use.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.
Ingestion	If symptoms persist, call a physician. Do not induce vomiting without medical advice. Clean mouth with water and afterwards drink plenty of water. Aspiration hazard if swallowed - can enter lungs and cause damage.
Protection of First-aiders	Use personal protective equipment. Avoid contact with skin, eyes and clothing.

Most important symptoms and effects, both acute and delayed

Main Symptoms May be fatal if swallowed and enters airways

Indication of immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment: Use CO₂, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray

Extinguishing media which shall not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire

Special hazards arising from the substance or mixture

Special Hazard

In the event of fire and/or explosion do not breathe fumes. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Water runoff can cause environmental damage. Thermal decomposition can lead to release of irritating gases and vapors. This material creates a fire hazard because it floats on water.

Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

Advice for firefighters

Special protective equipment for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Remove all sources of

ignition.

Advice for non-emergency personnel Eliminate all ignition sources if safe to do so.

Advice for emergency responders For personal protection see section 8.

Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dike to collect large liquid spills. After cleaning, flush away traces with water.

Reference to other sections

See Section 8/12/13 for additional information

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Remove all sources of ignition.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep out of the reach of children.

Recommended Shelf Life

Shelf life 12 months.

Incompatible materials

Strong oxidizing agents, Strong acids, Strong bases

Specific end uses

Specific use(s) Antirust

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Legend:

(s) - Skin; TWA - Time-Weighted Average; STEL - Short Term Exposure Limit; Ceiling - Ceiling Value; TLV® - Threshold Limit Value; PEL (Permissible Exposure Limit); IDLH (immediately dangerous to life and health); WEEL (Workplace Environmental Exposure Level Guides)

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH	AIHA WEEL
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)	5 mg/m ³ (mist)	5 mg/m ³ (mist)		
-				

Petrolatum 8009-03-8	5 mg/m ³ (mist)	5 mg/m ³ (mist)		
Highly refined base oil (Viscosity >20.5 cSt @40°C)	5 mg/m ³ (mist)	5 mg/m ³ (mist)		
2-(2-Butoxyethoxy)ethanol 112-34-5	TWA: 10 ppm (inhalable fraction and vapor)			

ACGIH - American Conference of Governmental Industrial Hygienists

Hydrocarbon solvent vapor mixtures which do not have substance specific occupational exposure limits may be evaluated by the Reciprocal Calculation Procedure (RCP) which assigns a recommended occupational exposure limit based on the mass composition and hydrocarbon group guidance values (GGVs). Applicable recommended occupational exposure limits are shown in the table below.

Chemical name	RCP OEL	Manufacturer
Distillates (petroleum), hydrotreated middle 64742-46-7	RCP: TWA 1200 mg/m ³ 143ppm	
Distillates (petroleum), hydrotreated light 64742-47-8	RCP: TWA 1200 mg/m ³ 182ppm	
Naphtha (petroleum), hydrotreated heavy 64742-48-9	RCP: TWA 1000 mg/m ³	
C12-C14 isoalkanes 68551-19-9	RCP: TWA 1200 mg/m ³	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	RCP C9-C15 aliphatics: 600mg/m ³	
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	TWA: 600 mg/m ³	
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0.03% aromatics NOT AVAILABLE	RCP C9-C15 aliphatics: 600mg/m ³	
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	TWA: 150ppm TWA: 1200 mg/m ³	
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics NOT AVAILABLE	TWA: 171 ppm TWA: 1200 mg/m ³	
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics NOT AVAILABLE	RCP C9-C15 aliphatics: 600mg/m ³	
Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	TWA: 165 ppm TWA: 1200 mg/m ³	
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	RCP: TWA 1200 mg/m ³ 182ppm	
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics NOT AVAILABLE	RCP: TWA 600 mg/m ³	
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics NOT AVAILABLE	RCP: TWA 600 mg/m ³	
Hydrocarbons, C13-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics NOT AVAILABLE	RCP: TWA 600 mg/m ³	CEFIC-HSPA: 1200 mg/m ³

Exposure controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Safety glasses with side-shields.

Skin and body protection	Wear protective gloves/clothing.
Respiratory protection	No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Hygiene measures	Regular cleaning of equipment, work area and clothing is recommended.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Appearance	Dark
Odor	Not Determined	Odor threshold	Not Determined
<u>Property</u>	<u>Values</u>	<u>Remarks</u>	
pH	Not Determined		
Melting point / freezing point	Not Determined		
Boiling point / boiling range	Not Determined		
Flash point	79 °C / 174 °F	ASTM D 92	
Evaporation rate	Not Determined		
Flammability (solid, gas)	Not Determined		
Flammability Limit in Air			
Upper flammability limit:	Not Determined		
Lower flammability limit:	Not Determined		
Vapor pressure	Not Determined		
Vapor density	Not Determined		
Relative density	0.8400	g/cm3 @15°C	
Solubility(ies)	Insoluble in water		
Partition coefficient	Not Determined		
Autoignition temperature	Not Determined		
Decomposition temperature	Not Determined		
Kinematic viscosity	6.46 cSt @ 40 °C		
Explosive properties	Not applicable		
Oxidizing Properties	Not applicable		
<u>Other Information</u>			
Viscosity, kinematic (100°C)	Not Determined		
Pour Point	Not Determined		
VOC Content (ASTM E-1868-10)	574 g/L		
VOC content	Not Determined		

SECTION 10: STABILITY AND REACTIVITY

Reactivity

None under normal use conditions

Chemical stability

Stable under normal conditions

Possibility of hazardous reactions

None under normal use conditions

Conditions to avoid

Heat, flames and sparks. Keep away from open flames, hot surfaces and sources of ignition. Heat (temperatures above flash point), sparks, ignition points, flames, static electricity.

Incompatible materials

Strong oxidizing agents. Strong acids. Strong bases.

Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	May be harmful if swallowed and enters airways.
Inhalation	Risk of serious damage to the lungs (by aspiration)
Eye contact	Based on available data, the classification criteria are not met
Skin contact	Repeated exposure may cause skin dryness or cracking; Prolonged skin contact may defat the skin and produce dermatitis
Ingestion	Risk of product entering the lungs on vomiting after ingestion

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C) -	>2000 mg/kg	>2000 mg/kg	
Petrolatum 8009-03-8		= 3600 mg/kg (Rabbit)	
Highly refined base oil (Viscosity >20.5 cSt @40°C) -	>2000 mg/kg	>2000 mg/kg	
2-(2-Butoxyethoxy)ethanol 112-34-5	3384 mg/kg (Rat)	= 2700 mg/kg (Rabbit)	
Sulfonic acids, petroleum, sodium salts 68608-26-4	>6000 mg/kg (Rat)	>2000 mg/kg (Rabbit)	
N-1-naphthylaniline 90-30-2	= 1625 mg/kg (Rat)	>5000 mg/kg (Rabbit)	

Information on toxicological effects

Symptoms	May be fatal if swallowed and enters airways. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Prolonged skin contact may defat the skin and produce dermatitis.
-----------------	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Based on available data, the classification criteria are not met.
Serious eye damage/eye irritation	Based on available data, the classification criteria are not met
Sensitization	Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
Germ cell mutagenicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Reproductive toxicity	Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure) Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure) Based on available data, the classification criteria are not met.

Aspiration hazard Risk of serious damage to the lungs (by aspiration).

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

No special environmental measures are necessary

Chemical name	Algae/aquatic plants	Fish	Crustacea
2-(2-Butoxyethoxy)ethanol	100: 96 h Desmodesmus subspicatus mg/L EC50	1300: 96 h Lepomis macrochirus mg/L LC50 static	2850: 24 h Daphnia magna mg/L EC50 100: 48 h Daphnia magna mg/L EC50
Sulfonic acids, petroleum, sodium salts	>100: 72 h Desmodesmus subspicatus mg/L EC50		
N-1-naphthylaniline	0.25: 72 h Desmodesmus subspicatus mg/L EC50	0.44: 96 h Oncorhynchus mykiss mg/l LC50	0.32: 48 h Daphnia magna mg/L EC50

Persistence and degradability The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

Bioaccumulation No information available

Mobility The product is insoluble and floats on water. Is not likely mobile in the environment due its low water solubility.

Other adverse effects No information available

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste Disposal Methods Dispose of in accordance with federal, state and local regulations.

Contaminated packaging Observe all label precautions until container is cleaned, reconditioned or destroyed.

SECTION 14: TRANSPORT INFORMATION

DOT

UN/ID no	NA1993
Proper shipping name	COMBUSTIBLE LIQUID, N.O.S.
Hazard Class	Combustible liquid
Packing Group	III
Emergency Response Guide Number	128
Description	NA1993, COMBUSTIBLE LIQUID, N.O.S. (Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C), COMBUSTIBLE LIQUID, III
Remarks	DOT Ground - "Non-bulk shipments may be non-regulated per 49CFR 173.150(f)(2) if they are not a hazardous waste, hazardous substance or marine pollutant"

TDG Not Regulated

IATA Not Regulated

IMDG Not Regulated

SECTION 15: REGULATORY INFORMATION

International Inventories

Inventory information may be utilizing alternative CAS#s or exemptions beyond those stated within this document For further information, please contact: ProductStewardship@houghtonintl.com

TSCA	Complies
DSL	Complies
AICS	Complies
PICCS	Complies
KECL	Complies
IECSC	Complies
ENCS	Does not Comply
TCSI	Complies
NZIoC	Does not Comply

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
AICS - Australian Inventory of Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
ENCS - Japan Existing and New Chemical Substances
TCSI - Taiwan National Existing Chemical Inventory
NZIoC - New Zealand Inventory of Chemicals

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical name	CAS No	SARA 313 - Threshold Values %
2-(2-Butoxyethoxy)ethanol	112-34-5	1.0
Naphthenic acids, zinc salts	12001-85-3	1.0

SARA 311/312 Hazard Categories

- Flammable (gases, aerosols, liquids, or solids)
- Respiratory or skin sensitization
- Aspiration Hazard

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Naphthenic acids, zinc salts		X		
Aniline	5000 lb			X

CERCLA

To the best of our knowledge, this product does not contain chemicals at levels which require reporting under this regulation, Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional,

or state level pertaining to releases of this material.

U.S. State Regulations

SCAQMD Rule 1144

The sale or distribution in the SCAQM District of California for metal working fluids or direct-contact lubricants is allowed if EITHER the VOC of the product itself OR the VOC of the diluted product at the point of use is less than the following limits: (1) 75 g VOC/L for metal forming, metal removal, metal treating; (2) 50 g VOC/L for metal protection, direct-contact lubricant. The VOC of this product as sold is: 574 g/L

California Proposition 65

WARNING: This product contains a chemical(s) known to the State of California to cause cancer and/or birth defects or other reproductive harm.

Chemical name	CAS No	California Prop. 65
Aniline	62-53-3	Carcinogen
2-naphthylamine	91-59-8	Carcinogen

International Regulations

Ozone-depleting substances (ODS)

Not applicable

Persistent Organic Pollutants

Not applicable

Chemicals Subject to Prior Informed Consent (PIC)

Not applicable

Other Information

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical name	CAS No
Lubricating oils (petroleum), C24-50, solvent-extd., dewaxed, hydrogenated	101316-72-7
Lubricating oils (petroleum), used, noncatalytically refined	101316-73-8
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4
Residual oils (petroleum), solvent-refined	64742-01-4
Extracts (petroleum), residual oil solvent	64742-10-5
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Residual oils (petroleum), hydrotreated	64742-57-0
Lubricating oils (petroleum), hydrotreated spent	64742-58-1
Residual oils (petroleum), solvent-dewaxed	64742-62-7
Distillates (petroleum), solvent-dewaxed heavy, paraffinic	64742-65-0
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0
Lubricating oils (petroleum), C20-C50, hydrotreated neutral oil-based	72623-87-1
Lubricating oils	74869-22-0
Paraffin oils	8012-95-1
White mineral oil (petroleum)	8042-47-5
C18-C50 branched, cyclic and linear hydrocarbons – Distillates	848301-69-9

The highly refined, low viscosity base oil (Viscosity <7 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical name	CAS No
---------------	--------

Distillates (petroleum), hydrotreated middle	64742-46-7
Hydrocarbons, C13-C23, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	64742-46-7
Distillates (petroleum), hydrotreated light	64742-47-8
Naphtha (petroleum), hydrotreated heavy	64742-48-9
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9
C12-C14 isoalkanes	68551-19-9
White mineral oil (petroleum)	8042-47-5
C18-C50 branched, cyclic and linear hydrocarbons – Distillates	848301-69-9
Alkanes, C14-16	90622-46-1
Alkanes, C12-26-branched and linear	90622-53-0
Alkanes, C11-15-iso-	90622-58-5
Alkanes, C16-20-iso-	90622-59-6
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, <0.03% aromatics	NOT AVAILABLE
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C11-C14, n-alkanes, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C11-C13, isoalkanes, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C14-C18, n-alkanes, cyclics, aromatics (2-30%)	NOT AVAILABLE
Hydrocarbons, C11-C12, isoalkanes, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C11-C14, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C12-C16, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C13-C16, isoalkanes, cyclics, < 2% aromatics	NOT AVAILABLE
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, <0.03% aromatics	NOT AVAILABLE
Hydrocarbons, C14-C18, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE
Hydrocarbons, C13-C18, n-alkanes, isoalkanes, cyclics, < 2% aromatics	NOT AVAILABLE

SECTION 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

STOT SE - Specific target organ systemic toxicity (Single exposure)
 STOT RE - Specific target organ systemic toxicity (repeated exposure)
 VOC - Volatile organic compounds
 NIOSH IDLH: Immediately Dangerous to Life or Health

Revision Date 09-01-2019

Revision Note Company Logo

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet