



GTX High Mileage 20W-50

GTX High Mileage 20W-50

Description

Castrol GTX High Mileage

Castrol GTX High Mileage is the premium engine oil for engines with over 75,000 miles. As your engine ages, its performance decreases and oil breaks down faster. Over time, seals deteriorate, gaskets become brittle and oil consumption increases, leading to reduced performance. Castrol GTX High Mileage combats this aging process and provides superior protection against harmful deposit build-up in higher mileage engines to help extend engine life.

Application

Features and Benefits:

- Contains superior detergency that fights harmful deposits in higher mileage engines*
- Utilizes special base oils to provide superior protection against oil burn-off compared to leading oils**
- Contains seal conditioners that provide added level of protection and help reduce leakage
- Reduces deposit formation to minimize compression loss and maximize engine performance

* As measured in VG sludge test

** As measured in NOACK laboratory volatility test

Conditions of Use

Warranty and Protection Requirements

- Exceeds engine manufacturer's warranty requirements for applications requiring API SN, SM and SL

Characteristics

Castrol GTX High Mileage

Specifications:	5W-20	5W-30	10W-30	10W-40	20W-50
API SN	X	X	X	X	X
SM	X	X	X	X	X
SL	X	X	X	X	X
SJ	X	X	X	X	X

Typical Physical Characteristics

Typical Properties:

Castrol GTX High Mileage

	Method	5W-20	5W-30	10W-30	10W-40	20W-50
Viscosity @ 100C, cSt	ASTM D445	9.03	11.99	11.93	16.1	20.3
Viscosity @ 210F, SUS	ASTM D2161	55.9	66.4	66.1	82.3	99.8
Viscosity @ 40C, cSt	ASTM D445	51.5	77.2	82.3	109.4	187.7
Viscosity Index	ASTM D2270	157	151	139	154	126
Low temperature (C) Cranking Viscosity, cP max	ASTM D5293	6,600 @ -30	6,600 @ -30	7,000 @ -25	7,000 @ -25	9,500 @ -
Low temperature (C) Pumping Viscosity, cP max	ASTM D4684	60,000 @ -35	60,000 @ -35	60,000 @ -30	60,000 @ -30	60,000 @
HT/HS Viscosity, cP min	ASTM D4683	2.6	2.9	2.9	2.9	3.7
Pour Point, F (C) max	ASTM D97	-33 (-36)	-33 (-36)	-38 (-39)	-33 (-36)	-11 (-24)
Flash Point, PMCC, C min	ASTM D93	>200	>200	>200	>200	>200
Density @ 15C, Relative	ASTM D4052	0.861	0.864	0.871	0.875	0.883
Pounds per Gallon		7.17	7.19	7.31	7.31	7.35

* Due to continual product research and development, the information contained herein is based on products purchased in U.S. subject to change and without notification. Typical properties may vary slightly.

Product Performance Claims

API SN

Recommended Concentrations

Part Numbers and UPC's:

Packaged Goods

SAE Grades		5W-20		5W-30			
Case Size	6/1 Qt	6 gal E-dispense e-pk	6 gal Manual e-pk	6/1 Qt	3/1 Gal	6 gal E-dispense e-pk	6 gal Manual e-pk
Case Part #	06148	60032	60017	06440	03430	60075	60005
Bottle/Unit UPC	0-79191-00148-6	-----	-----	0-79191-00440-1	0-79191-00430-2	-----	-----
Case UPC	0-79191-06148-0	0-79191-60032-0	0-79191-60017-7	0-79191-06440-5	0-79191-03441-5	0-79191-60075-7	0-79191-60005-4

Packaged Goods

SAE Grades		10W-30		10W-40		20W-50	
Case Size	6/1 Qt	3/1 Gal	6 gal E-dispense e-pk	6 gal Manual e-pk	6/1 Qt	3/1 Gal	6/1 Qt
Case Part #	06450	03440	60080	60010	06460	03445	06470
Bottle/Unit UPC	0-79191-00450-0	0-79191-00454-8	-----	-----	0-79191-00460-9	0-79191-00464-7	0-79191-00470-8
Case UPC	0-79191-06450-4	0-79191-03454-5	0-79191-60080-1	0-79191-60010-8	0-79191-06460-3	0-79191-03464-4	0-79191-06470-2

Bulk/Drum

SAE Grades		5W-30	10W-30	10W-40	20W-50
Unit Size		55 gal drum	Bulk	55 gal drum	55 gal drum
Part #		5544000075	55450	55460	55470

Concentrations Control

Health and Safety:

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet at www.castrol.com/us. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment, return used oil to collection center.

GTX High Mileage 20W-50

30 Mar 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com