

Transmax Full Synthetic Multi-vehicle ATF

Automatic Transmission Fluid

Description

Castrol Transmax Full Synthetic Multi-Vehicle Automatic Transmission Fluid is a technologically advanced, low viscosity formulation specially designed to deliver performance and maximum fuel efficiency for modern automatic transmissions. It is blended with premium base stocks, a balanced additive package and is fully approved by both Ford and GM for use in vehicles requiring their latest ATF specifications. In addition to approval from the two major US auto manufacturers, Transmax Full Synthetic Multi-Vehicle ATF exceeds the requirements of the JASO-1A performance standard created by Japanese automobile manufacturers. This standard is recognized by Japanese OEM's in certifying ATF for use in their vehicles.

Advantages

- Full Synthetic, low viscosity formulation
- OEM approved and licensed by Ford (MERCON® LV) and GM (DEXRON® -VI)
- Low viscosity formula for maximum fuel efficiency in modern automatic transmissions
- Enhanced friction durability for smooth transmission performance
- Superior high temperature protection to effectively resist oxidation
- Unsurpassed protection against copper corrosion

Warranty and Protection Requirements

- Exceeds all passenger car and light truck manufacturer's warranty requirements for vehicles, transmissions or power steering service where a DEXRON®-VI or MERCON® LV type ATF is specified

Recommended for use in vehicles as indicated below:

Manufacturer	Specification
Hyundai	All applications that require automatic transmission fluid
Isuzu	All applications that require automatic transmission fluid
Kia	All applications that require automatic transmission fluid
Mitsubishi	All applications that require automatic transmission fluid
Nissan / Infiniti	All applications that require automatic transmission fluid
Subaru	All applications that require automatic transmission fluid
Toyota / Lexus	All applications that require automatic transmission fluid
Suzuki	All applications that require automatic transmission fluid

Suitable for use in vehicles as indicated below:

Manufacturer	Specification
Honda/Acura	ATF-Z1, ATF DW-1, (except in CVTs)
Mazda	ATF M-III, MV
Saab	T IV (JWS 3309)
Saturn	T IV (JWS 3309)
Volvo	T IV (JWS 3309)
Various Aisin-Warner Transmissions	JWS-3309
Various Domestic/European vehicles	where DEXRON® IIIH or prior is required

Note: Castrol does not recommend Transmax Full Synthetic Multi-Vehicle ATF for use in continuously variable transmissions (CVTs).

Typical Characteristics

Name	Method	Units	Typical Value
Density @ 15°C, Relative	ASTM D4052	g/ml	0.841
Appearance	Visual	-	Red/Clear & Bright
Viscosity, Kinematic 100°C	ASTM D445	cSt	5.9
Color Typical	ASTM D1500		7
Pour Point	ASTM D97	°C	-50
Viscosity, Brookfield @ -40°C (75W)	ASTM D2983	mPa.s (cP)	10000
Viscosity, Kinematic 40°C	ASTM D445	cSt	30.2
Viscosity Index	ASTM D2270	None	161
Specific Gravity, 60°F	ASTM D1298		0.841
Flash Point, COC	ASTM D92	°C	177
Pounds per Gallon	ASTM D287		7.01

Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

Product Performance Claims

MERCON® LV

DEXRON® VI

Suitable for use where JASO 1A(03)

JASO 1A LV(13) is required including:

Toyota T III, T IV, WS

Mitsubishi SP II, IIM, III, IV, PA, J3

Mazda ATF M-III, M-V, FZ

Honda/Acura DW 1/Z 1

Nissan Matic D, J, S

JWS 3314/3317/ 3309, Suzuki AT Oil 5D06, 2384K

Isuzu

Subaru F6, Red 1

Daihatsu AMMIX ATF D-III Multi, D3-SP

Hyundai/Kia SP III, SP IV

Also suitable for use in 6-speed automatics from Audi, BMW, Mini-Cooper, Jaguar, Peugeot/Citroen, Saab, Volvo, VW, Porsche, and all vehicles where Dexron III or Mercon SP is required.

Transmax Full Synthetic Multi-vehicle ATF

22 May 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This Data Sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication. No statement made in this publication shall be construed as a permission, recommendation or authorization given or implied to practice any patented invention without a valid license. It is the User's obligation to evaluate and use products safely and within the scope advised in the Data Sheet, to assess suitability for the intended application, and to comply with all applicable laws and regulations. Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the products. The Seller shall not be responsible for any loss, damage or injury resulting from any abnormal use of the product, from any failure to adhere to recommendations, nor from any hazards or risks which are i) identified in the Data Sheet, ii) inherent in the nature of petroleum products or iii) associated with the petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned). All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road , Wayne, NJ 07470

www.castrol.com