

# TECHNICAL DATA SHEET

## HOUGHTO-SAFE® 200X

### FIRE RESISTANT HYDRAULIC FLUID (ISO6743-4 TYPE HFC – WATER GLYCOL)

HOUGHTO-SAFE® 200X is a premium performance, water containing, synthetic hydraulic fluid.

HOUGHTO-SAFE® 200X greatly reduces risks where hydraulic equipment operates near flames, hot surfaces or molten metals.

#### Applications

HOUGHTO-SAFE® 200X is particularly suited to oil hydraulic systems that require a balanced combination of fire resistance and good lubrication and where there is the possibility of contamination by sea water.

HOUGHTO-SAFE® 200X has been successfully used for many years in naval vessels, both surface and submarine, and it is approved to current UK Navy Standards for such applications.

#### Recommendation For Use

Use as supplied, without dilution.

#### Additional Product Data

- HOUGHTO-SAFE® 200X passes ISO20763 standard tests in a Vickers V104 Vane Pump, giving under 50mg weight loss.
- HOUGHTO-SAFE® 200X passes ISO4404-1 corrosion tests and is suitable for use with steel, copper, brass and anodised aluminium.
- HOUGHTO-SAFE® 200X is free from vapour phase corrosion inhibitors, as required by submarine applications.
- HOUGHTO-SAFE® 200X is low foaming, to minimise the risk of cavitation and air entrainment. In tests to ISO6247 it gives a result of 230/0 at 25°C.
- HOUGHTO-SAFE® 200X is approved to Defence Standard 91-110/Issue 2 (Joint Service Designation OX40).

#### Benefits

- High security against fire
- Increased operator safety
- Tolerant to sea water ingress
- Increased plant security and availability
- Increased productivity

#### Health, Safety And Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and disposal of the product are beyond our reasonable control - we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions.

#### Typical Physical Properties

| PROPERTY                   | TYPICAL VALUE                   | UNIT          |
|----------------------------|---------------------------------|---------------|
| Appearance                 | Clear, fluorescent green liquid |               |
| Specific Gravity @ 15.5°C  | 1.08                            |               |
| pH                         | 9.5                             |               |
| Water content              | 40                              | %             |
| Kinematic Viscosity @ 40°C | 46                              | cSt           |
| Pour Point                 | -45                             | °C            |
| Flash Point                | None                            | °C (ASTM D92) |
| Fire Point                 | None                            | °C (ASTM D92) |

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet (SDS) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose. 01012001

