

## Section 1. Identification

**GHS product identifier** Rustilo DW 901

**Product code** 451256-IN02

**SDS no.** 451256

**Relevant identified uses of the substance or mixture and uses advised against**

**Use of the substance/mixture** Rust preventive / Water displacement fluid  
For specific application advice see appropriate Technical Data Sheet or consult our company representative.

**Manufacturer**

**Supplier** Castrol India Ltd  
Technopolis Knowledge Park Office  
PO Box 19411  
Mahakali Caves Rd  
Chakala, Andheri (E)  
Mumbai 400093

Telephone: +91 (022) 66984111/66984112

**EMERGENCY TELEPHONE NUMBER**

Toll free: 000800 100 7479 (for use in India only - 24/7)  
Carechem Singapore: +65 3158 1198 (24/7)

## Section 2. Hazards identification

**GHS Classification**

FLAMMABLE LIQUIDS - Category 3  
SKIN CORROSION/IRRITATION - Category 2  
SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2A  
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Respiratory tract irritation) - Category 3  
ASPIRATION HAZARD - Category 1  
SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 2  
LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

**GHS label elements**

**Hazard pictograms**



**Signal word**

Danger

**Hazard statements**

H226 - Flammable liquid and vapour.  
H304 - May be fatal if swallowed and enters airways.  
H315 - Causes skin irritation.  
H319 - Causes serious eye irritation.  
H335 - May cause respiratory irritation.  
H411 - Toxic to aquatic life with long lasting effects.

**Precautionary statements**

**General**

Not applicable.

**Prevention**

P280 - Wear protective gloves, protective clothing and eye or face protection.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241 - Use explosion-proof electrical, ventilating or lighting equipment.  
P242 - Use non-sparking tools.  
P243 - Take action to prevent static discharges.  
P271 - Use only outdoors or in a well-ventilated area.  
P273 - Avoid release to the environment.  
P261 - Avoid breathing vapour.  
P264 - Wash hands thoroughly after handling.

## Section 2. Hazards identification

### Response

 P391 - Collect spillage.  
P304 + P340, P312 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.  
P301 + P310, P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting.  
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.  
P332 + P313 - If skin irritation occurs: Get medical attention.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P313 - If eye irritation persists: Get medical attention.

### Storage

 P405 - Store locked up.  
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 - Keep cool.

### Disposal

P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.

### Other hazards which do not result in classification

Defatting to the skin.

## Section 3. Composition/information on ingredients

### Substance/mixture

Mixture

Hydrocarbon solvent, film forming corrosion preventives and additives

| Ingredient name                                                                                        | %         | CAS number |
|--------------------------------------------------------------------------------------------------------|-----------|------------|
|  2,4-Trimethylbenzene | ≥25 - ≤39 | 95-63-6    |
| Distillates (petroleum), solvent-refined heavy paraffinic                                              | ≥10 - ≤25 | 64741-88-4 |
| Mesitylene                                                                                             | ≥10 - <20 | 108-67-8   |
| xylene                                                                                                 | ≥10 - ≤25 | 1330-20-7  |
| 1,2,3-trimethylbenzene                                                                                 | ≤10       | 526-73-8   |
| propylbenzene                                                                                          | ≤10       | 103-65-1   |
| cumene                                                                                                 | ≤10       | 98-82-8    |
| Residual oils (petroleum), solvent-dewaxed                                                             | ≤3        | 64742-62-7 |
| Residual oils (petroleum), hydrotreated                                                                | ≤3        | 64742-57-0 |

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

#### Eye contact

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and remove any contact lenses. Get medical attention.

#### Inhalation

If inhaled, remove to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention.

#### Skin contact

 In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Drench contaminated clothing with water before removing. This is necessary to avoid the risk of sparks from static electricity that could ignite contaminated clothing. Contaminated clothing is a fire hazard. Contaminated leather, particularly footwear, must be discarded. Clean shoes thoroughly before reuse. Get medical attention. If skin irritation or rash occurs: Get medical advice/attention.

## Section 4. First aid measures

|                                   |                                                                                                                                                                                                                                                                                                              |
|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Ingestion</b>                  | Do not induce vomiting. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Aspiration hazard if swallowed. Can enter lungs and cause damage. Get medical attention immediately.                                        |
| <b>Protection of first-aiders</b> | No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. |

### Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### Indication of immediate medical attention and special treatment needed, if necessary

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Specific treatments</b> | No specific treatment.                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Notes to physician</b>  | Treatment should in general be symptomatic and directed to relieving any effects. Product can be aspirated on swallowing or following regurgitation of stomach contents, and can cause severe and potentially fatal chemical pneumonitis, which will require urgent treatment. Because of the risk of aspiration, induction of vomiting and gastric lavage should be avoided. Gastric lavage should be undertaken only after endotracheal intubation. Monitor for cardiac dysrhythmias. |

## Section 5. Firefighting measures

### Extinguishing media

|                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Suitable</b>                                       | Use foam or all-purpose dry chemical to extinguish.                                                                                                                                                                                                                                                                                                                                                                |
| <b>Not suitable</b>                                   | Do not use water jet.                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Specific hazards arising from the chemical</b>     | Flammable liquid and vapour. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard. This material is toxic to aquatic life with long lasting effects. |
| <b>Hazardous thermal decomposition products</b>       | Combustion products may include the following:<br>metal oxide/oxides<br>carbon oxides (CO, CO <sub>2</sub> ) (carbon monoxide, carbon dioxide)<br>sulphur oxides (SO, SO <sub>2</sub> , etc.)                                                                                                                                                                                                                      |
| <b>Special precautions for fire-fighters</b>          | No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.                                                                                                 |
| <b>Special protective equipment for fire-fighters</b> | Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear. Fire-fighters' protective clothing will only provide limited protection.                                                                                                                                                                                                                              |

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>For non-emergency personnel</b> | Immediately contact emergency personnel. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. No flares, smoking or flames in hazard area. Avoid breathing vapour or mist. Provide adequate ventilation. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling. Eliminate all ignition sources. |
| <b>For emergency responders</b>    | Entry into a confined space or poorly ventilated area contaminated with vapour, mist or fume is extremely hazardous without the correct respiratory protective equipment and a safe system of work. Wear self-contained breathing apparatus. Wear a suitable chemical protective suit. Chemical resistant boots. See also the information in "For non-emergency personnel".                                                                                                                                    |
| <b>Environmental precautions</b>   | Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.                                                                                                                                                                           |

### Methods and material for containment and cleaning up

## Section 6. Accidental release measures

### Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. The method and equipment used must be in conformance with appropriate regulations and industry practice on explosive atmospheres.

### Large spill

Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Use spark-proof tools and explosion-proof equipment. Contaminated absorbent material may pose the same hazard as the spilt product. The method and equipment used must be in conformance with appropriate regulations and industry practice on explosive atmospheres. Dispose of via a licensed waste disposal contractor.

## Section 7. Handling and storage

### Precautions for safe handling

#### Protective measures

Put on appropriate personal protective equipment (see Section 8). Do not swallow. Aspiration hazard if swallowed. Can enter lungs and cause damage. Never siphon by mouth. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by earthing and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container. Avoid contact of spilt material and runoff with soil and surface waterways. Avoid prolonged or repeated contact with skin. During metal working, solid particles from workpieces or tools will contaminate the fluid and may cause abrasions of the skin. Where such abrasions result in a penetration of the skin, first aid treatment should be applied as soon as reasonably possible. The presence of certain metals in the workpiece or tool, such as chromium, cobalt and nickel, can contaminate the metalworking fluid and as a result may induce allergic skin reactions. Keep away from ignition sources such as heat/sparks/open flame. - No smoking. Concentrations of mist, fumes and vapours in enclosed spaces may result in the formation of explosive atmospheres. Excessive splashing, agitation or heating must be avoided.

#### Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. Contaminated work clothing should not be allowed out of the workplace. See also Section 8 for additional information on hygiene measures.

#### Conditions for safe storage

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidising materials. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination.

#### Not suitable

Prolonged exposure to elevated temperature

Ensure product is stored in covered area away from direct sunlight, heat, rain and water exposure.



## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

| Ingredient name                                                                                        | Exposure limits                                                                                                                                                                                                                                                          |
|--------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  2,4-Trimethylbenzene | ACGIH TLV (United States, 1/2024).<br>TWA: 10 ppm 8 hours.                                                                                                                                                                                                               |
| Distillates (petroleum), solvent-refined heavy paraffinic                                              | Directorate General Factory Advice<br>Service & Labour Institutes, Factories Act<br>(India, 4/2001). [oil mist mineral]<br>STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: mist<br>TWA: 5 mg/m <sup>3</sup> 8 hours. Form: mist                                             |
| Mesitylene                                                                                             | ACGIH TLV (United States, 1/2024).<br>[trimethyl benzene, isomers]<br>TWA: 10 ppm 8 hours.                                                                                                                                                                               |
| xylene                                                                                                 | Directorate General Factory Advice<br>Service & Labour Institutes, Factories Act<br>(India, 4/2001). [xylene (o-,m-, p-isomers)]<br>STEL: 655 mg/m <sup>3</sup> 15 minutes.<br>STEL: 150 ppm 15 minutes.<br>TWA: 435 mg/m <sup>3</sup> 8 hours.<br>TWA: 100 ppm 8 hours. |
| 1,2,3-trimethylbenzene                                                                                 | ACGIH TLV (United States, 1/2024).<br>[trimethyl benzene, isomers]<br>TWA: 10 ppm 8 hours.                                                                                                                                                                               |
| cumene                                                                                                 | ACGIH TLV (United States, 1/2024).<br>TWA: 5 ppm 8 hours.                                                                                                                                                                                                                |
| Residual oils (petroleum), solvent-dewaxed                                                             | Directorate General Factory Advice<br>Service & Labour Institutes, Factories Act<br>(India, 4/2001). [oil mist mineral]<br>STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: mist<br>TWA: 5 mg/m <sup>3</sup> 8 hours. Form: mist                                             |
| Residual oils (petroleum), hydrotreated                                                                | Directorate General Factory Advice<br>Service & Labour Institutes, Factories Act<br>(India, 4/2001). [oil mist mineral]<br>STEL: 10 mg/m <sup>3</sup> 15 minutes. Form: mist<br>TWA: 5 mg/m <sup>3</sup> 8 hours. Form: mist                                             |

Whilst specific OELs for certain components may be shown in this section, other components may be present in any mist, vapour or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

#### Biological exposure indices

| Ingredient name            | Exposure indices |
|----------------------------|------------------|
| No exposure indices known. |                  |

#### Recommended monitoring procedures

 Reference should be made to appropriate monitoring standards. Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

#### Appropriate engineering controls

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits. All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained.

Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

#### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### Individual protection measures

|              |                |               |             |        |                  |
|--------------|----------------|---------------|-------------|--------|------------------|
| Product name | Rustilo DW 901 | Product code  | 451256-IN02 | Page:  | 5/10             |
| Version      | 2              | Date of issue | 25/10/2024. | Format | GHS - India      |
|              |                |               |             |        | Language ENGLISH |
|              |                |               |             |        | (ENGLISH)        |
|              |                | Build         | 6.1.1       |        | (GHS -India)     |

## Section 8. Exposure controls/personal protection

### Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Eye protection

Safety glasses with side shields.

### Skin protection

#### Hand protection

Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

#### Skin protection

Use of protective clothing is good industrial practice. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Wear clothing and footwear that cannot be penetrated by chemicals or oil. Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

#### Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

### Respiratory protection

Use with adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment. Recommended: half-face mask - organic vapor filter (Type A). The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

## Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

### Appearance

#### Physical state

Liquid.

#### Colour

Amber. [Light]

#### Odour

Not available.

#### Odour threshold

Not available.

#### pH

Not applicable.

#### Melting point/freezing point

Not available.

#### Boiling point, initial boiling point, and boiling range

Not available.

#### Drop Point

Not available.

#### Flash point

Open cup: 40°C (104°F) [Cleveland]

#### Evaporation rate

Not available.

#### Flammability

Not available.

#### Flammability

Not applicable. Based on - Physical state

#### Lower and upper explosion limit/flammability limit

Not available.

#### Vapour pressure



## Section 9. Physical and chemical properties

| Ingredient name        | Vapour Pressure at 20°C |      |        | Vapour pressure at 50°C |     |        |
|------------------------|-------------------------|------|--------|-------------------------|-----|--------|
|                        | mm Hg                   | kPa  | Method | mm Hg                   | kPa | Method |
| 1,2,4-Trimethylbenzene | 2.25018                 | 0.3  |        |                         |     |        |
| Mesitylene             | 2.4002                  | 0.32 |        |                         |     |        |
| xylene                 | 6.7                     | 0.89 |        |                         |     |        |
| 1,2,3-trimethylbenzene | 1.35011                 | 0.18 |        |                         |     |        |
| cumene                 | 3.72032                 | 0.5  |        |                         |     |        |

Relative vapour density

Not available.

Relative density

Not available.

Density

<1000 kg/m<sup>3</sup> (<1 g/cm<sup>3</sup>) at 29.5°C

Solubility(ies)

| Media | Result      |
|-------|-------------|
| Water | Not soluble |

Partition coefficient: n-octanol/water

Not applicable.

Auto-ignition temperature

| Ingredient name        | °C  | °F    | Method |
|------------------------|-----|-------|--------|
| 1,2,4-Trimethylbenzene | 500 | 932   |        |
| xylene                 | 432 | 809.6 |        |
| 1,2,3-trimethylbenzene | 470 | 878   |        |
| propylbenzene          | 450 | 842   |        |
| cumene                 | 424 | 795.2 |        |

Decomposition temperature

Not available.

Viscosity

Kinematic: 3 mm<sup>2</sup>/s (3 cSt) at 40°C

Particle characteristics

Median particle size

Not applicable.

## Section 10. Stability and reactivity

Reactivity

No specific test data available for this product. Refer to Conditions to avoid and Incompatible materials for additional information.

Chemical stability

The product is stable.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.  
Under normal conditions of storage and use, hazardous polymerisation will not occur.

Conditions to avoid

Avoid all possible sources of ignition (spark or flame).

Incompatible materials

Reactive or incompatible with the following materials: oxidising materials.

Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

Information on toxicological effects

Specific target organ toxicity (single exposure)

| Name                   | Category   | Route of exposure | Target organs                |
|------------------------|------------|-------------------|------------------------------|
| 1,2,4-Trimethylbenzene | Category 3 | -                 | Respiratory tract irritation |
| Mesitylene             | Category 3 | -                 | Narcotic effects             |
| propylbenzene          | Category 3 | -                 | Respiratory tract irritation |
| cumene                 | Category 3 | -                 | Respiratory tract irritation |

Aspiration hazard

| Name          | Result                         |
|---------------|--------------------------------|
| propylbenzene | ASPIRATION HAZARD - Category 1 |
| cumene        | ASPIRATION HAZARD - Category 1 |

Product name Rustilo DW 901

Product code 451256-IN02

Page: 7/10

Version 2

Date of issue 25/10/2024.

Format GHS - India

Language ENGLISH

Build 6.1.1

(GHS -India)

(ENGLISH)

## Section 11. Toxicological information

### Information on likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation, Eyes.

### Potential acute health effects

#### Eye contact

Causes serious eye irritation.

#### Inhalation

May cause respiratory irritation.

#### Skin contact

Causes skin irritation. Defatting to the skin.

#### Ingestion

Irritating to mouth, throat and stomach. Aspiration hazard if swallowed -- harmful or fatal if liquid is aspirated into lungs. Ingestion of large quantities may cause nausea and diarrhoea.

### Symptoms related to the physical, chemical and toxicological characteristics

#### Eye contact

Adverse symptoms may include the following:  
pain or irritation  
watering  
redness

#### Inhalation

Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
Exposure to high concentrations can cause dizziness, lightheadedness, headache, nausea and blurred vision. Higher levels may cause unconsciousness.  
May be harmful by inhalation if exposure to vapour, mists or fumes resulting from thermal decomposition products occurs.

#### Skin contact

Adverse symptoms may include the following:  
irritation  
redness  
dryness  
cracking

#### Ingestion

Adverse symptoms may include the following:  
nausea or vomiting

### Potential chronic health effects

#### General

Xylenes: Xylene has been reported to cause central nervous system effects at concentrations above the recommended exposure limit. Xylene vapour becomes irritating at relatively high levels. In one study, eye irritation was reported at exposures of 460 ppm and in one person at 230 ppm after 15 minutes. In another study, no one reported eyes, nose and throat irritation at mixed xylene exposures up to 230 ppm for 30 minutes. Dermal LD50 is expected to be greater than 10g/kg in rabbits, based on test results from similar materials.

Mixed xylenes caused slight hearing loss in rats exposed to 800 ppm in the air for 14 hours/day for six weeks. There is no information available for lower concentrations; however, similar chemicals that have caused these hearing effects at similar concentrations have not caused effects at lower concentrations.

Pregnant animals exposed to xylene or its isomers have been reported to cause development toxicity in rodents when exposed by inhalation. The developmental effects observed consisted of delayed development and minor skeletal variations, but no malformations. Because of the high exposure levels used in these studies, we do not believe that these results imply an increased risk of reproductive toxicity to workers exposed to xylene levels at or below the exposure limits.

Xylene and its isomers are not genotoxic.

Technical grade xylene has been tested in a National Toxicology Program carcinogenicity study in rats and mice dosed orally for two years. There was no evidence of carcinogenicity.

#### Carcinogenicity

No known significant effects or critical hazards.

#### Mutagenicity

No known significant effects or critical hazards.

#### Teratogenicity

No known significant effects or critical hazards.

#### Developmental effects

No known significant effects or critical hazards.

#### Fertility effects

No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

##### Route

##### ATE value

Product name Rustilo DW 901

Product code 451256-IN02

Page: 8/10

Version 2

Date of issue 25/10/2024.

Format GHS - India

Language ENGLISH

Build 6.1.1

(GHS -India)

(ENGLISH)



## Section 11. Toxicological information

|                              |               |
|------------------------------|---------------|
| Oral                         | 11976.8 mg/kg |
| Dermal                       | 7762.65 mg/kg |
| Inhalation (vapours)         | 77.63 mg/l    |
| Inhalation (dusts and mists) | 5.28 mg/l     |

## Section 12. Ecological information

**Environmental effects** Water polluting material. May be harmful to the environment if released in large quantities. This material is toxic to aquatic life with long lasting effects.

**Persistence and degradability**

Not readily biodegradable.

**Bioaccumulative potential**

This product may bioaccumulate through food chains in the environment.

**Mobility** Volatile. Liquid. insoluble in water.

**Other adverse effects** No known significant effects or critical hazards.

## Section 13. Disposal considerations

**Disposal methods** The generation of waste should be avoided or minimised wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

|                                   | IMDG                                                                                                                            | IATA                                                                                                     |
|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| <b>UN number</b>                  | UN1300                                                                                                                          | UN1300                                                                                                   |
| <b>UN proper shipping name</b>    | Turpentine substitute. Marine pollutant (1,2,4-Trimethylbenzene, Mesitylene)                                                    | Turpentine substitute                                                                                    |
| <b>Transport hazard class(es)</b> | 3<br>                                        | 3<br>                 |
| <b>Packing group</b>              | III                                                                                                                             | III                                                                                                      |
| <b>Environmental hazards</b>      | Yes.                                                                                                                            | Yes. The environmentally hazardous substance mark is not required.                                       |
| <b>Additional information</b>     | The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg.<br><b>Emergency schedules</b><br>F-E, S-E | The environmentally hazardous substance mark may appear if required by other transportation regulations. |

**Special precautions for user** Not available.

**Transport in bulk according to IMO instruments** Not available.

## Section 15. Regulatory information

### Regulation according to other foreign laws

|                                                    |                                                                                                       |
|----------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| <b>REACH Status</b>                                | For the REACH status of this product please consult your company contact, as identified in Section 1. |
| <b>Australia inventory (AIIIC)</b>                 | At least one component is not listed.                                                                 |
| <b>Canada inventory status</b>                     | All components are listed or exempted.                                                                |
| <b>China inventory (IECSC)</b>                     | All components are listed or exempted.                                                                |
| <b>Japan inventory (CSCL)</b>                      | At least one component is not listed.                                                                 |
| <b>Korea inventory (KECI)</b>                      | All components are listed or exempted.                                                                |
| <b>Philippines inventory (PICCS)</b>               | At least one component is not listed.                                                                 |
| <b>Taiwan Chemical Substances Inventory (TCSI)</b> | Not determined.                                                                                       |
| <b>United States inventory (TSCA 8b)</b>           | At least one component is not listed.                                                                 |

## Section 16. Other information

### History

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|---------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Date of issue/Date of revision</b> | 25/10/2024.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Date of previous issue</b>         | 21/03/2023.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Prepared by</b>                    | Product Stewardship                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>Key to abbreviations</b>           | ACGIH = American Conference of Industrial Hygienists<br>CAS Number = Chemical Abstracts Service Registry Number<br>GHS = Globally Harmonized System of Classification and Labelling of Chemicals<br>IATA = International Air Transport Association<br>IMDG = International Maritime Dangerous Goods<br>OEL = Occupational Exposure Limit<br>REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]<br>SDS = Safety Data Sheet<br>STEL = Short term exposure limit<br>TWA = Time weighted average<br>UN Number = United Nations Number, a four digit number assigned by the United Nations Committee of Experts on the Transport of Dangerous Goods.<br>Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0, 64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1 |

 Indicates information that has changed from previously issued version.

### Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.