

PROBLEM SHEET 4

Alex Kavvos

The following questions are about the simply-typed λ -calculus (STLC).

1. Draw derivations that evidence the following typing judgements.
 - (i) $x : \text{Str} + (\text{Str} \times \text{Num}) \vdash \text{case}(x; y. y; z. \pi_1(z)) : \text{Str}$
 - (ii) $\vdash \lambda x : \text{Str} + \text{Num}. \text{case}(x; y. \text{inr}(y); z. \text{inl}(z)) : \text{Str} + \text{Num} \rightarrow \text{Num} + \text{Str}$
 - (iii) $f : \text{Num} \times \text{Str} \rightarrow \text{Num}, x : \text{Str} \vdash f(\langle \text{num}[0], x \rangle) : \text{Num}$
2. Write down transition sequences that reduce the following terms to values.
 - (i) $\text{case}(\text{inr}(\langle \text{str}[\text{'hi'}], \text{num}[0] \rangle); y. y; z. \pi_1(z))$
 - (ii) $(\lambda x : \text{Str} + \text{Num}. \text{case}(x; y. \text{inr}(y); z. \text{inl}(z)))(\text{inl}(\text{num}[0]))$
 - (iii) $(\lambda z. \pi_1(z))(\langle \text{num}[0], \text{str}[\text{'hi'}] \rangle)$
3. This question is about modelling the following Haskell data type in the simply-typed λ -calculus.

`data MaybeString = Nothing | Just String`

Intuitively, we expect this data type `MaybeStr` to have the following typing rules.

$$\begin{array}{c}
 \text{NOTHING} \\
 \hline
 \Gamma \vdash \text{Nothing} : \text{MaybeStr}
 \end{array}
 \qquad
 \begin{array}{c}
 \text{JUST} \\
 \Gamma \vdash e : \text{Str} \\
 \hline
 \Gamma \vdash \text{Just}(e) : \text{MaybeStr}
 \end{array}$$

$$\begin{array}{c}
 \text{MATCH} \\
 \Gamma \vdash e : \text{MaybeStr} \quad \Gamma \vdash e_n : \tau \quad \Gamma, x : \text{Str} \vdash e_j : \tau \\
 \hline
 \Gamma \vdash \text{match}(e; e_n; x. e_j) : \tau
 \end{array}$$

The first term represents `Nothing`, and the second term that represents `Just e`, where $e :: \text{String}$.

The third term performs **pattern matching**. It first examines e : if that is a `Nothing` it returns e_n ; if it is a `Just(e)` with $e : \text{Str}$, it substitutes e for x in e_j . Thus $\text{match}(-; e_n; x. e_j)$ corresponds to the definition

`f Nothing = e_n`
`f (Just x) = e_j` — *this clause can use the variable $x :: \text{String}$*

- (i) Write down a representation of this type in the STLC. [Hint: use `1`.]
- (ii) Show that the three rules **NOTHING**, **JUST** and **MATCH** above are **definable**. That is, show the terms `Nothing`, `Just(e)` and `match(e; e_n; x. e_j)` can be expanded into some term of the STLC, which is such that the typing rules are **derivable** if we assume that weakening is a typing rule of the system.

4. (*) Prove progress and preservation for the **constants-and-functions fragment** of the STLC.

[Hint: The constants-and-function fragment of the STLC is an extension to the language of numbers and strings: we reached it by *adding* the rules for function types. Thus, to establish these theorems **you only need to show them for the new rules**, as last week's proofs cover the rest!]

Do this in steps. First extend the inversion, substitution, and canonical form lemmas to function types. You will need weakening; you may assume it, but you can also prove it if you feel like it. Then, prove preservation and progress. Pretend there are no products or sums throughout.]