

# Homework Week 2

MATHEMATICS OF DEEP LEARNING  
MASH & IASD 2025

**Lecturer:** Bruno Loureiro, [bruno.loureiro@di.ens.fr](mailto:bruno.loureiro@di.ens.fr)

**Instructions:** This homework is **due on Monday 27/01/2025**. Please send your solutions in a PDF file named HW2\_NOM\_PRENOM.PDF to the above address with the subject “[MATHSDL2025] Homework 2”. Formats accepted: LaTeX or a **readable** scan of handwritten solutions.

## 1 Exercises

### Exercise 1.

Show that the  $L^p(\mu)$  norm:

$$\|f\|_p := \left( \int \mu(d\mathbf{x}) |f(\mathbf{x})|^p \right)^{1/p} \quad (1)$$

is an increasing function of  $p \in [1, \infty]$ :

$$\|f\|_{L^\infty(\mu)} \leq \cdots \|f\|_{L^2(\mu)} \leq \|f\|_{L^1(\mu)} \quad (2)$$

where we recall  $\|f\|_{L^\infty(\mu)} = \sup_{x \in \text{supp}(\mu)} |f(x)|$ . Conclude that we have the inclusion:

$$L^\infty(\mu) \subset \cdots \subset L^2(\mu) \subset L^1(\mu) \quad (3)$$

### Exercise 2.

Give an example of a probability measure on  $\mu$  on  $\mathbb{R}^d$  and compact set  $K \subset \mathbb{R}^d$  such that:

$$\|f\|_{L^\infty(\mu)} \leq \|f\|_{L^\infty(K)} \quad (4)$$

### Exercise 3.

Consider the following continuous function on  $[0, 1]$ :

$$g(x) = \begin{cases} 0 & x < 1/2 \\ 2x & x \in [1/2, 1] \end{cases} \quad (5)$$

How many neurons  $p$  are needed to approximate  $g$  within a precision  $\epsilon > 0$  using the two-layer neural network with step-size activation from Proposition 2 in the lectures? Show that we could do as well by using less neurons if we adapt the partition to the function.

### Exercise 4.

Show that:

$$\inf_{f_\theta \in \mathcal{F}_{\text{relu},1}} \sup_{x \in \mathbb{R}} |f_\theta(x) - \sin(x)| \geq 1 \quad (6)$$

where  $\mathcal{F}_{\text{relu},1}$ , the class of two-layer neural networks over  $\mathbb{R}$  with relu activation and unbounded width. Conclude that the compactness assumption in the definition of a universal approximator is crucial to define meaningful approximation results.