ssGSEA3: from permutation testing to gene-level bootstrap resampling

Contents

Overview 1
Why bootstrap instead of permutation? 1
Example 1: ssGSEA on tumor NMF factors 2
Example 2: PTM-SEA on a PI3K-inhibitor perturbation dataset 5
Session info 9

Overview

`ssGSEA3` runs single-sample Gene Set Enrichment Analysis (ssGSEA) on gene-centric expression data, and PTM-Signature Enrichment Analysis (PTM-SEA) on site-centric phosphoproteomics data scored against the directional PTM signatures database (PTMsigDB). Significance is assessed via a gene-level bootstrap, replacing the gene-label permutation testing used by the original `ssGSEA2.0`.

This vignette:

1. explains why that replacement happened,
2. walks through an ordinary ssGSEA analysis (tumor NMF factors vs. HALLMARK gene sets), and
3. walks through a directional PTM-SEA analysis (a phosphoproteomics perturbation dataset vs. PTMsigDB), comparing the result to the original `ssGSEA2.0`.

```
library(ssGSEA3)
```

Why bootstrap instead of permutation?

A known problem with weighted scoring under permutation

`ssGSEA2.0`'s significance testing permuted gene labels to build a null distribution for each gene set's enrichment score. This works cleanly when every gene contributes equally to the score (`weight = 0`), but is known to produce badly miscalibrated p-values whenever the score is weighted by actual expression magnitude (`weight > 0`) – documented as GitHub issue #45 against the original `ssGSEA2.0` repository. Testing purely random, biologically meaningless gene sets at `weight = 0.75` gave a mean p-value of about 0.001 (i.e. almost always called "significant") instead of the ~0.5 expected under a true null.

An informal fix – stop reordering the correlation vector along with the permuted gene ranks – corrected that calibration problem, but at a real cost: on a real PI3K-perturbation dataset, the same fix reduced detection of expected cell-cycle pathways at `weight = 0.75` from 6/14 down to 0/14 at 6 hours, and from 10/14 down to 3/14 at 24 hours. Fixing the false-positive problem this way also suppressed real signal – a fundamental validity-vs-power tension that a purely permutation-based approach could not resolve.

`ssGSEA3` sidesteps this entirely by resampling genes (not gene labels) with replacement and deriving significance from the resulting bootstrap distribution. Because gene identity is resampled rather than reshuffled, a gene's own expression-derived weight is never artificially preserved across replicates the way it was under permutation – closing the calibration gap without sacrificing power.

Directional (PTM-SEA) scoring gets an extra benefit

PTM-SEA's directional gene sets (with `;u`/`;d`-labeled "up" and "down" members) benefit from bootstrap resampling in a second, independent way. Permutation always preserves the exact up/down membership counts of a gene set, only ever moving where they fall in the ranking. Bootstrap resampling with replacement lets some members drop out (and others duplicate) in any given replicate, so the up- and down-regulated counts genuinely vary from replicate to replicate – a richer, two-sided source of resampling variability with no permutation-based analogue.

A controlled simulation with known ground truth (embedding a real, moderate, correctly-oriented effect) confirmed this: both methods are well-calibrated under a true null, but bootstrap shows a real, statistically robust power advantage specifically for directional scoring (McNemar p = 0.0001, odds ratio 1.85) that does not replicate for non-directional scoring at the same sample size. The two worked examples below show both regimes on real data.

Example 1: ssGSEA on tumor NMF factors

The bundled example is a PANOPLY LUAD (lung adenocarcinoma) NMF factorization (4 factors, CPTAC/ICPC v6.1) scored against the MSigDB HALLMARK collection – an ordinary (non-directional) ssGSEA analysis.

```
res <- ssGSEA3(
  input.ds = "example/LUAD_matrix_W_combined_signed_gc.gct",
  output.prefix = "luad",
  gene.set.databases = "db/msigdb/h.all.v7.0.symbols.gmt",
  sample.norm.type = "rank", weight = 1, correl.type = "z.score",
  statistic = "area.under.RES", min.overlap = 10, nperm = 1000, seed = 42
)
```

```
## the call above takes ~30 min at the default nperm=1000 -- loading its
## precomputed output here keeps this vignette's own build fast, and keeps
## the displayed results consistent with the full-nperm comparison below
## (rather than a faster-but-different reduced-nperm run)
res <- readRDS(system.file("extdata", "luad_ssgsea3_result.rds", package = "ssGSEA3"))
res
#> <ssgsea_result> 50 gene sets x 4 samples
#>   score type: NES
```


The four factors are labeled by their NMF cluster number; renaming them to their published biological identities makes the heatmap self-explanatory:

```
cluster.names <- c(
  "1" = "Unstable-proliferative", "2" = "Quiescent-EGFR",
  "3" = "Immune-active-KRAS", "4" = "Stable-early-stage"
)

rename_cols <- function(x, map) {
  colnames(x) <- unname(map[colnames(x)])
  x
}
```

```
res$scores <- rename_cols(res$scores, cluster.names)
res$pvalues <- rename_cols(res$pvalues, cluster.names)
res$fdr <- rename_cols(res$fdr, cluster.names)
res$sample.names <- unname(cluster.names[res$sample.names])
```

```
ht <- plot_ssgsea_heatmap(res, top_n = 10, fdr.max = 0.05,
                          title = "LUAD PANOPLY -- HALLMARK (ssGSEA3)")
ComplexHeatmap::draw(ht)
```



The proliferation program (`MYC_TARGETS`, `E2F_TARGETS`, `MTORC1_SIGNALING`, `OXIDATIVE_PHOSPHORYLATION`, `GLYCOLYSIS`) is strongly and specifically enriched in the "Unstable-proliferative" factor, matching its published biological identity – a useful sanity check that the scoring and reporting pipeline agree with the underlying biology.

Comparison against the original ssGSEA2.0


This dataset is scored at `weight = 1` – exactly the regime affected by the weight-dependent calibration issue described above, so it demonstrates the other side of the bootstrap's benefit: rather than finding more real signal (as in the directional PTM-SEA example below), it trims down some of the original ssGSEA2.0's likely-inflated calls while retaining the large majority of them. As above, these are precomputed results (`nperm = 1000`, run outside this vignette):

```
cmp.luad <- readRDS(system.file(
  "extdata", "luad_ssgsea2_vs_ssgsea3_comparison.rds", package = "ssGSEA3"
))
nes2.luad <- as.vector(cmp.luad$ssgsea2.nes)
nes3.luad <- as.vector(cmp.luad$ssgsea3.nes)
```

```r
cat("Gene sets compared:", length(cmp.luad$gene.set.names), "\n")
#> Gene sets compared: 49
cat("NES Pearson r:    ", round(cor(nes2.luad, nes3.luad), 3), "\n")
#> NES Pearson r:     0.947
cat("NES Spearman rho: ", round(cor(nes2.luad, nes3.luad, method = "spearman"), 3), "\n")
#> NES Spearman rho:  0.979

## a gene set counts as "significant" if FDR<0.05 in >=1 of the 4 samples --
## NOT the same as counting gene-set x sample cells, which would double-count
## any gene set significant in multiple samples
sig2.luad <- apply(cmp.luad$ssgsea2.fdr < 0.05, 1, any)
sig3.luad <- apply(cmp.luad$ssgsea3.fdr < 0.05, 1, any)
cat("\nGene sets significant (FDR < 0.05 in >=1 sample), of",
 ↪  length(cmp.luad$gene.set.names), "total:\n")
#>
#> Gene sets significant (FDR < 0.05 in >=1 sample), of 49 total:
cat("  ssGSEA2.0:", sum(sig2.luad), " ssGSEA3:", sum(sig3.luad),
    " both:", sum(sig2.luad & sig3.luad), " ssGSEA2.0-only:", sum(sig2.luad &
     ↪  !sig3.luad),
    " ssGSEA3-only:", sum(!sig2.luad & sig3.luad), "\n")
#>   ssGSEA2.0: 46  ssGSEA3: 41  both: 41  ssGSEA2.0-only: 5  ssGSEA3-only: 0
```

```r
plot(nes2.luad, nes3.luad,
     xlab = "ssGSEA2.0 NES", ylab = "ssGSEA3 NES", pch = 16, col = "#00000066",
     main = "LUAD PANOPLY, HALLMARK: NES agreement")
abline(0, 1, col = "firebrick", lty = 2)
```



`ssGSEA3` agrees with `ssGSEA2.0` on the overwhelming majority of significant calls (41 shared), while dropping 5 calls unique to `ssGSEA2.0` and adding almost none of its own – consistent with correcting a false-positive-prone regime rather than disagreeing with it.

Example 2: PTM-SEA on a PI3K-inhibitor perturbation dataset

The second example (bundled in the package's `example/` directory, alongside its source) is a site-centric phosphoproteomics dataset from the original PTM-SEA publication itself (Krug et al. 2019 – see the package `README` for the full citation): T47D breast cancer cells treated with the PI3Kα inhibitor BYL719 (vs. a DMSO control) for 6h and 24h (`PI3K_pert_logP_n2x23936.gct`), scored against PTMsigDB v2.0.0's flanking-sequence human signatures – a directional PTM-SEA analysis. The call is the same shape as the ssGSEA example above:


```
res.ptmsea <- ssGSEA3(
  input.ds = "example/PI3K_pert_logP_n2x23936.gct",
  output.prefix = "pi3k",
  gene.set.databases = "example/ptm.sig.db.all.flanking.human.v2.0.0.gmt",
  sample.norm.type = "rank", weight = 0, correl.type = "rank",
  statistic = "area.under.RES", min.overlap = 5, nperm = 1000, seed = 42
)
```

```
## as above, loading the precomputed (nperm=1000) output instead of
## re-running the ~3 hour scoring call live
res.ptmsea <- readRDS(system.file("extdata", "pi3k_ssgsea3_result.rds", package =
 ↪  "ssGSEA3"))
res.ptmsea
#> <ssgsea_result> 569 gene sets x 2 samples
```

```
#>   score type: NES
```

PTMsigDB's `CATEGORY-name` convention (`KINASE-`, `PERT-`, `PATH-`, `DISEASE-`) drives its own row-grouping in `plot_ssgsea_heatmap()`, distinct from the HALLMARK-category grouping used above:

```
ht.ptmsea <- plot_ssgsea_heatmap(res.ptmsea, top_n = 10, fdr.max = 0.05,
                                 title = "PI3K perturbation -- PTMsigDB v2.0.0
                                  ↪  (ssGSEA3)")
ComplexHeatmap::draw(ht.ptmsea)
```



Comparison against the original ssGSEA2.0

Unlike the LUAD comparison above, `weight = 0` is used here deliberately, to isolate the bootstrap-vs-permutation effect on directional scoring from the separate weight-dependent issue that comparison demonstrated. The results below use the default `nperm = 1000` (run outside this vignette, since a full comparison run against the original, unmodified `ssGSEA2.0` code takes several hours and depends on software not part of this package):


```
cmp <- readRDS(system.file(
  "extdata", "pi3k_ssgsea2_vs_ssgsea3_comparison.rds", package = "ssGSEA3"
))
nes2 <- as.vector(cmp$ssgsea2.nes)
nes3 <- as.vector(cmp$ssgsea3.nes)
fdr2 <- as.vector(cmp$ssgsea2.fdr)
fdr3 <- as.vector(cmp$ssgsea3.fdr)

cat("Gene sets compared:", length(cmp$gene.set.names), "\n")
```

```
#> Gene sets compared: 569
cat("NES Pearson r:    ", round(cor(nes2, nes3), 3), "\n")
#> NES Pearson r:     0.907
cat("NES Spearman rho: ", round(cor(nes2, nes3, method = "spearman"), 3), "\n")
#> NES Spearman rho:  0.993
cat("FDR Pearson r:    ", round(cor(fdr2, fdr3), 3), "\n")
#> FDR Pearson r:     0.965
cat("FDR Spearman rho: ", round(cor(fdr2, fdr3, method = "spearman"), 3), "\n")
#> FDR Spearman rho:  0.971

## a gene set counts as "significant" if FDR<0.05 in >=1 of the 2 samples --
## NOT the same as counting gene-set x sample cells, which would double-count
## any gene set significant in both samples
sig2 <- apply(cmp$ssgsea2.fdr < 0.05, 1, any)
sig3 <- apply(cmp$ssgsea3.fdr < 0.05, 1, any)
cat("\nGene sets significant (FDR < 0.05 in >=1 sample), of", length(cmp$gene.set.names),
 ↪  "total:\n")
#>
#> Gene sets significant (FDR < 0.05 in >=1 sample), of 569 total:
cat("  ssGSEA2.0:", sum(sig2), " ssGSEA3:", sum(sig3),
    " both:", sum(sig2 & sig3), " ssGSEA2.0-only:", sum(sig2 & !sig3),
    " ssGSEA3-only:", sum(!sig2 & sig3), "\n")
#>   ssGSEA2.0: 82  ssGSEA3: 126  both: 75  ssGSEA2.0-only: 7  ssGSEA3-only: 51
```

```
plot(nes2, nes3,
     xlab = "ssGSEA2.0 NES", ylab = "ssGSEA3 NES", pch = 16, col = "#00000066",
     main = "PI3K perturbation, PTMsigDB v2.0.0: NES agreement")
abline(0, 1, col = "firebrick", lty = 2)
```



ssGSEA3 retains the large majority of ssGSEA2.0's significant calls (75 of 82) while finding substantially more overall (126 vs. 82) – consistent with the confirmed power advantage for directional scoring described above, now demonstrated on a real, published dataset.

Are the additional calls biologically plausible?

A real power advantage should surface signatures that make sense for this specific perturbation, not an arbitrary scattering of unrelated biology. Of the 51 signatures significant under ssGSEA3 but never significant (in either sample) under ssGSEA2.0, several sit directly on the PI3K/AKT/mTOR axis this dataset perturbs:

```
gained <- c(
  "KINASE-iKiP_PIK3R5", "KINASE-PSP_PDK1/PDPK1", "KINASE-PSP_SGK1",
  "KINASE-PSP_p70S6K/RPS6KB1", "PERT-PSP_TORIN1", "DISEASE-PSP_tuberous_sclerosis"
)
data.frame(
  signature = gained,
  NES_06h = round(cmp$ssgsea3.nes[gained, 1], 2),
  NES_24h = round(cmp$ssgsea3.nes[gained, 2], 2),
  FDR_06h = signif(cmp$ssgsea3.fdr[gained, 1], 2),
  FDR_24h = signif(cmp$ssgsea3.fdr[gained, 2], 2),
  row.names = NULL
)
#>                       signature NES_06h NES_24h FDR_06h FDR_24h
#> 1             KINASE-iKiP_PIK3R5   -0.75    3.73   0.820 2.5e-02
#> 2          KINASE-PSP_PDK1/PDPK1   -0.17    5.27   0.960 6.8e-04
#> 3               KINASE-PSP_SGK1   -4.22   -0.96   0.014 6.9e-01
#> 4      KINASE-PSP_p70S6K/RPS6KB1   -3.28   -3.65   0.092 3.4e-02
```

```
#> 5                 PERT-PSP_TORIN1    4.18    3.86   0.047 2.8e-02
#> 6 DISEASE-PSP_tuberous_sclerosis    -2.07   -6.49   0.380 8.5e-06
```

PIK3R5 is a PI3K regulatory subunit itself; PDK1 and SGK1 are AKT-family kinases immediately downstream of PI3K; p70S6K is the canonical mTORC1 output kinase; TORIN1 is a PTMsigDB perturbation signature for an mTOR inhibitor; tuberous_sclerosis is a disease signature driven by TSC1/2, a direct mTORC1 regulator. This lines up with the original paper's own reported result for this exact experiment: PTM-SEA "detected signatures of compounds inhibiting PI3K as well as targets downstream of PI3K (AKT, MAPK/ERK) covering a substantial fraction of the PI3K pathway" (Krug et al. 2019). p70S6K and SGK1's substrate signatures moving negative is consistent with declining mTORC1/AKT-family output as BYL719 inhibition takes hold; PDK1 and PIK3R5 trending positive by 24h instead is consistent with the compensatory feedback reactivation of upstream RTK/PI3K-node signaling well documented as a response to PI3K inhibitors specifically (rather than a random, unrelated direction) – so even the "wrong-direction" hits are still on-pathway. The additional calls cluster around the perturbed pathway rather than appearing as unrelated noise, which is exactly what ssGSEA2.0 under-detected here.

A related, separate observation: PERT-PSP_WORTMANNIN – a PTMsigDB signature for an unrelated experiment's treatment with wortmannin, another PI3K inhibitor – was already significant under ssGSEA2.0 at 24h (FDR 0.013), so it is not part of the "newly significant" tally above. But ssGSEA3 closes a near-miss at 6h (FDR 0.061 under ssGSEA2.0, 0.033 under ssGSEA3) and dramatically strengthens the 24h call (NES 4.4 to 31.6) – close to a positive control for the same PI3K/mTOR-inhibitor resemblance the newly-significant calls above point to.

Session info

```
sessionInfo()
#> R version 4.4.2 (2024-10-31)
#> Platform: aarch64-apple-darwin20
#> Running under: macOS Sequoia 15.7.7
#>
#> Matrix products: default
#> BLAS:
 ↪  /Library/Frameworks/R.framework/Versions/4.4-arm64/Resources/lib/libRblas.0.dylib
#> LAPACK:
 ↪  /Library/Frameworks/R.framework/Versions/4.4-arm64/Resources/lib/libRlapack.dylib;
 ↪  LAPACK version 3.12.0
#>
#> locale:
#> [1] C
#>
#> time zone: America/New_York
#> tzcode source: internal
#>
#> attached base packages:
#> [1] stats     graphics  grDevices utils     datasets  methods   base
#>
#> other attached packages:
#> [1] ssGSEA3_0.1.0  testthat_3.3.2
#>
#> loaded via a namespace (and not attached):
#>   [1] remotes_2.5.0               rlang_1.1.7
#>   [3] magrittr_2.0.4              clue_0.3-66
#>   [5] GetoptLong_1.0.5            otel_0.2.0
```

```
#>   [7] verification_1.45          matrixStats_1.4.1
#>   [9] compiler_4.4.2             png_0.1-8
#>  [11] vctrs_0.6.5                maps_3.4.3
#>  [13] profvis_0.4.0              pkgconfig_2.0.3
#>  [15] shape_1.4.6.1              crayon_1.5.3
#>  [17] fastmap_1.2.0              magick_2.9.1
#>  [19] XVector_0.46.0             ellipsis_0.3.2
#>  [21] promises_1.5.0             rmarkdown_2.30
#>  [23] sessioninfo_1.2.2          UCSC.utils_1.2.0
#>  [25] tinytex_0.58               purrr_1.2.1
#>  [27] xfun_0.55                  zlibbioc_1.52.0
#>  [29] cachem_1.1.0               GenomeInfoDb_1.42.1
#>  [31] jsonlite_2.0.0             later_1.4.5
#>  [33] DelayedArray_0.32.0        parallel_4.4.2
#>  [35] cluster_2.1.8              R6_2.6.1
#>  [37] RColorBrewer_1.1-3         boot_1.3-31
#>  [39] pkgload_1.4.0              brio_1.1.5
#>  [41] GenomicRanges_1.58.0       knitr_1.51
#>  [43] Rcpp_1.1.1                 SummarizedExperiment_1.36.0
#>  [45] iterators_1.0.14           fields_17.1
#>  [47] usethis_3.1.0              IRanges_2.40.1
#>  [49] flowCore_2.18.0            httpuv_1.6.16
#>  [51] Matrix_1.7-4               tidyselect_1.2.1
#>  [53] yaml_2.3.12                rstudioapi_0.17.1
#>  [55] abind_1.4-8                doParallel_1.0.17
#>  [57] codetools_0.2-20           dtw_1.23-1
#>  [59] miniUI_0.1.2               pkgbuild_1.4.5
#>  [61] lattice_0.22-6             tibble_3.3.1
#>  [63] Biobase_2.66.0             shiny_1.12.1
#>  [65] withr_3.0.2                evaluate_1.0.5
#>  [67] desc_1.4.3                 proxy_0.4-29
#>  [69] urlchecker_1.0.1           circlize_0.4.16
#>  [71] pillar_1.11.1              MatrixGenerics_1.18.0
#>  [73] foreach_1.5.2              stats4_4.4.2
#>  [75] generics_0.1.4             rprojroot_2.1.1
#>  [77] S4Vectors_0.44.0           gtools_3.9.5
#>  [79] xtable_1.8-4               glue_1.8.0
#>  [81] tools_4.4.2                fs_1.6.6
#>  [83] dotCall64_1.2              grid_4.4.2
#>  [85] CircStats_0.2-7            RProtoBufLib_2.18.0
#>  [87] devtools_2.4.5             colorspace_2.1-2
#>  [89] GenomeInfoDbData_1.2.13    cmapR_1.18.0
#>  [91] cli_3.6.5                  spam_2.11-3
#>  [93] cytolib_2.18.2             S4Arrays_1.6.0
#>  [95] viridisLite_0.4.2          ComplexHeatmap_2.22.0
#>  [97] dplyr_1.1.4                digest_0.6.39
#>  [99] BiocGenerics_0.52.0        SparseArray_1.6.0
#> [101] rjson_0.2.23               htmlwidgets_1.6.4
#> [103] memoise_2.0.1              htmltools_0.5.9
#> [105] lifecycle_1.0.5            httr_1.4.7
#> [107] GlobalOptions_0.1.2        mime_0.13
#> [109] MASS_7.3-64
```