Readiness diagnostic: what it measures, at a glance

Readiness diagnostic: what it measures, at a glance

Generated by `scripts/readiness_rollup_build.py` from the framework record and the cycle of record.

The readiness diagnostic checks whether a program acting for a member of the public can get an agency's data and the documentation that goes with it.

Its checks descend from the four criteria of the USAFacts guide to AI-ready data; the diagnostic measures the criteria that can be measured from outside and adds one check from release practice.

Criterion	What the framework asks for	Checks	Quality concern	Agencies passing every check in this bucket^a
Accessible	Data Must Be Machine-Readable and Easy to Access	Twelve checks: Data offered as a file a program can read (Scored); The whole dataset in one download (Scored); The data page is in the site's list of pages (Scored); A published description of the agency's data service; Whether the site's visitor rules let AI tools in; The page labels itself as a dataset; The release date, and a link to the latest release; A front door built for programs; The interactive data tool answers honestly; What the site states about automated access; The site serves what its own rules permit; From a data page to the data service, terms, change log and inventory	Find and obtain; understand; usable format; metadata	two of sixteen
Understandable	Data Must Be Machine Understandable with Easily Retrievable, WellStructured Documentation and Metadata	One check: The methods are readable as plain text	Understand	two of sixteen
Accurate	Agencies Should Provide Clear Evaluation Benchmarks and Make Them Public	None		no check yet; needs an evaluation harness
Open	Data Must Be Unencumbered and Open to All Citizens	Two checks: The product is listed in the agency's data inventory (Scored); The terms of reuse, under a recognised name	Find and obtain; metadata	zero of sixteen
Release engineering (added)	Pre-release gates, contract stability, vintage-transition regression, change legibility, staged rollout, release authenticity.	One check: A change history a program can follow	Metadata	zero of sixteen

^a An agency passes a bucket when none of the bucket's checks that could be measured for it comes back fail; a check not measured for an agency, or not measured on the cycle of record at all, is left out of that agency's count and is never read as a fail.
Checks descend from USAFacts (2026), *AI-ready data*; concerns from FCSM 20-04, Accessibility dimension, after Webb 2026.
Standard user: no key. API user: a free key by open registration, a person completes an email step.