

jQuery and AJAX for Responsive Web Sites

Lecture 3 JavaScript

October 2012

82

Objectives

- Loose ends
- JavaScript overview
- Types and scope
- Objects, prototype-based inheritance
- Arrays
- First class functions
- Closures
- This

October 2012


83

Loose Ends

- Office Hours
 - Uptown Espresso, 4th and Wall St.
 - Mon and Thurs, 6pm till 7:30pm
 - “niekjsanders” on Skype
- Assignment 1
 - Grading, question feedback, answer sheet
- Assignment 2
 - Posting tomorrow

October 2012

84



developer.mozilla.org

October 2012

85

Big Picture....

- Interpreted
- Weakly typed
- Garbage collected
- Prototype-based inheritance
- First class functions, closures

October 2012

86

Interpreted vs. Compiled

... but with JIT.

October 2012

87

Interpreted vs. Compiled

- Interpreted, usually
 - JavaScript
 - Java
 - C#
 - Python
 - PHP
- Compiled
 - C++
 - C
 - Fortran
- n/a
 - Machine code (x86 instructions)

October 2012

88

Weak vs. Strong Typing

```
// C++ or Java
int cppFunc( int a, double b ) {
    return a / b;
}

// JavaScript
function cppFunc( a, b ) {
    return a / b;
}
```

October 2012

89

Weak vs. Strong Typing



Image from Wikipedia

Waddles?
Swims?
Quacks?

“Duck Typing”

October 2012

90

Weak vs. Strong Typing



Image from Wikipedia

```
// Javascript
function myFunc( obj ) {
    return obj.quack();
}
```

```
// C++ and polymorphism
std::string myFunc( DuckBase& duck ) {
    return duck.quack();
}
```

October 2012

91

Weak vs. Strong Typing

The downside of being weak...

October 2012

92

Garbage Collected



Image from Wikipedia

October 2012

93

Garbage Collected

- Manual management
- GC pauses
- Cyclic references, closures




Image from Wikipedia

October 2012

94

Prototype Inheritance



October 2012


95

First Class Functions, Closures

October 2012

96

JavaScript in Perspective



October 2012

97

JavaScript Types

- Number *
- String
- Boolean
- Null
- Undefined
- Object

October 2012

98

Data Types - Numbers

- Everything is a double precision float
- Normal languages have separate type for integers
- Usually not an issue in practice

October 2012

99

< Integer Division Demo >

October 2012

100

Scope

```

foo = 7;           // global scope, implicit
window.foo = 7;   // global scope, explicit
var foo = 7;       // global scope, from context

function square( num ) {
  var result = num * num; // function scope
  return result;
}

square( 3 )

```

October 2012

101

Not block scope!

```

function dangerDanger() {
  var x = 3;

  {
    var x = 5;
    console.log( x );    // prints 5
  }
  console.log( x );      // prints 5
}

```

October 2012

102

var

October 2012

103

“use strict”;

October 2012

104

< Strict Demo >

October 2012

105

Strings are immutable

```
var myString = "Hi ";
myString += "there";
```

October 2012

106

Immutable Strings

var myString → "Hi "

 ↓ "Hi there"

```
var myString = "Hi ";
myString += "there";
```

October 2012

107

Shallow object copies

October 2012

108

Shallow Objects



Image from Wikipedia

October 2012

109

var wheezy =



Wheezy the cat.

October 2012

110

var wheezy =
var bella =



Dave says "Wheezy"
Morgan says "Bella"

October 2012

111

Two names, one cat.

... remember this separation of name and value

October 2012

112

var wheezy

var bella



October 2012

113

wheezy.shave() ?

October 2012

114

var wheezy

var bella



October 2012

115

< Shallow Copy Demo >

```
var foo = [1,2,3];
var bar = foo;
bar.push( 4 );
// what is foo?
```

October 2012

116

Objects Pass by Reference

```
var foo = [1,2,3];
function myFunc( bar ) {
  bar.push( 4 );
  bar = 100;
}
myFunc( foo );
```

October 2012

117

Everything Else by Value

```
var foo = 7;

function myFunc( bar ) {
  bar = 100;
}

myFunc( foo );
```

October 2012

118

Exploiting Pass by Reference

```
var $ = 5000;

(function( $ ) {
  $('p').hide();
})(jQuery)
```

October 2012

119

< Object Demo >

October 2012

120

Objects

Key/Value + Prototype

```
var cheese = new Object();

cheese.name = "Gouda";
cheese.age = 3;

cheese['yumminess'] = "extreme";
```

October 2012

121

Object literal notation

```
// setting properties explicitly
var cheese = new Object();

cheese.name = "Gouda";
cheese.age = 3;
cheese.yumminess = "extreme";

// object literal notation
var cheese = { "name": "Gouda",
               "age": 3,
               "yumminess": "extreme" };
```

October 2012

122

JSON!

... kinda

October 2012

123

< Nested Objects Demo >

October 2012

124

Prototypes

October 2012

125

Prototype-based Inheritance

Object

`{"hasOwnProperty": }`

Car

`{"foo": 7,
"bar": function(a) { return a+1; } }`

NiekMobile

`{"foo": 5,
"meow": 100 }`

October 2012

126

Prototypes

- We walk up prototype chain to resolve property lookups
- Either another object or null as our prototype
- Prototype changes seen by all child objects
- Not standard: `__proto__`
- Normally set via constructor functions

October 2012

127

Constructors

October 2012

128

Constructors

- Just functions
- First letter of name capitalized by default
- Interact with the **new** operator

October 2012

129


```
// base class
var Car = function() {
}

// derived class
var NiekMobile = function() {
  this.topSpeed = 250;
}

// set our prototype "parent" object
NiekMobile.prototype = new Car();

// make an instance of Niek car
var myCar = new NiekMobile();
```

October 2012

130

new operator

October 2012

131

New operator

```
var niekMobile = new Car();
```

1. Create new object, prototype is Car.prototype
2. Invoke Car() with this set to new object
3. Return newly created object

October 2012

132