

Instituto Politécnico Nacional

Escuela Superior de Cómputo

Bioinformatics

## Practice 9 - Docking

Group: 3CV9

*Student:*

Ramos Diaz Enrique

*Professor:*

Rosas Trigueros Jorge Luis

*Development Date:*

December 9th 2020

*Due Date:*

December 16th 2020

# 1 Theoretical Framework

In the field of molecular modeling, **docking** is a method which predicts the preferred orientation of one molecule to a second when bound to each other to form a stable complex. Knowledge of the preferred orientation in turn may be used to predict the strength of association or binding affinity between two molecules using, for example, scoring functions [1]. Figure 1 shows a docking representation.

The associations between biologically relevant molecules such as proteins, peptides, nucleic acids, carbohydrates, and lipids play a central role in signal transduction. Furthermore, the relative orientation of the two interacting partners may affect the type of signal produced. Therefore, docking is useful for predicting both the strength and type of signal produced [1].

Molecular docking is one of the most frequently used methods in structure-based drug design, due to its ability to predict the binding-conformation of small molecule ligands to the appropriate target binding site. Characterisation of the binding behaviour plays an important role in rational design of drugs as well as to elucidate fundamental biochemical processes [1].




Figure 1: Schematic illustration of docking a small molecule ligand (green) to a protein target (black) producing a stable complex [1].

Molecular docking research focuses on computationally simulating the molecular recognition process. It aims to achieve an optimized conformation for both the protein and ligand and relative orientation between protein and ligand such that the free energy of the overall system is minimized [1].

Two approaches are particularly popular within the molecular docking community. One approach uses a matching technique that describes the protein and the ligand as complementary surfaces. The second approach simulates the actual docking process in which the ligand-protein pairwise interaction energies are calculated [1].

## 2 Material and Equipment

- RCSB PDB: Homepage - PDB [2].
- ZDOCK web server [3].
- ZINC15 database [4].
- SwissDock web server [5].
- VMD Software [6].
- Crystal and Molecular Structure of Barley Alpha-Amylase model - 1AMY [7].
- Thioredoxin h2 (HvTrxh2) in a mixed disulfide complex with the target protein BASI model - 2IWT [8].
- AMY2/BASI protein-protein complex from Barley Seed model - 1AVA [9].
- Human cyclin-dependent kinase 2 in complex with roscovitine model - 2A4L [10].
- Seliciclib ligand - ZINC1649340 [11].
- Crystal structure of the truncated human cytomegalovirus pUL50-pUL53 complex model - 6T3X [12].
- Ganciclovir ligand - ZINC1505 [13].

## 3 Practice Development

The objective of this practice is to perform two dockings using specialized servers for this task:

- Between two proteins: **1AMY** [7] and **2IWT** [8].
- Between a drug and a protein: **Ganciclovir** [13] and **Cytomegalovirus - 6T3X** [12].

### 3.1 Perform a Docking between two proteins

Go to the **PDB** web page [2], search for the two selected proteins for this docking, which its models loaded in the VMD software [6] are shown in Figure 2:

1. Crystal and Molecular Structure of Barley Alpha-Amylase Protein - **1AMY** [7].
2. Thioredoxin h2 (HvTrxh2) in a mixed disulfide complex with the target protein BASI - **2IWT** [8].

Download its .pdb files and then go to the docking server **ZDOCK** web page [3] and as shown in Figure 3, in the *Input Protein 1* field select the *PDB File* option and then upload the **1AMY .pdb file**. Do the same with the *Input Protein 2* field uploading the **2IWT .pdb file**. Enter your email and check the *Skip residue selection* option. Finally click on the *Submit* button to start the process; this could take some hours until it finishes.





Figure 2: Proteins selected for a docking between them.



**ZDOCK SERVER**

[ZDOCK](#) [M-ZDOCK](#) [Help](#) [Tools](#) [References](#)

**Input Protein 1**

**Input Protein 2**

**Enter your email:**

**Optional:**

[Select ZDOCK version](#)

[Skip residue selection](#) ☒

Figure 3: ZDOCK server interface [3].

The top 5 predictions from this docking are shown in Figures 4 and 5, where its resulted PDB files are visualized with the same ZDOCK server [3] and with the VMD software [6] respectively.

These generated models should resemble to the **AMY2/BASI protein-protein complex from Barley Seed model - 1AVA protein** [9], shown in Figure 6. The more accurate are these generated models with this protein the better is the server.




Figure 4: Docking results for **1AMY** - **2IWT** proteins in ZDOCK [3].




Figure 5: Docking results for **1AMY** - **2IWT** proteins in VMD [6].





Figure 6: **1AVA** protein model [9].

### 3.2 Perform a Docking between a drug and a protein

In the lab session, a docking between the **Human cyclin-dependent kinase 2 in complex with roscovitine - 2A4L** protein [10] and the **Seliciclib - Riscovitine** drug [11] was performed. The results of this prediction are shown in Figure 7.



(a) Swiss Dock.



(b) VMD.

Figure 7: Docking results for **Human cyclin-dependent kinase 2 in complex with roscovitine - Seliciclib**.

In this report this docking won't be reported, instead there will be used a virus protein and a potential drug that could attack it.

It is known that **Ganciclovir** has activity against the **Cytomegalovirus or CMV**, a virus that can cause blindness by affecting the retina.

For this reason, these are the selected drug and protein for this docking. Go to the **PDB** web page [2], search for the **6T3X Cytomegalovirus** protein [12] and download its .pdb file, which is loaded in the VMD Software [6] as shown in Figure 8.

After that, go to the **ZINC15** database [4], and search for the **Ganciclovir** drug [13], displayed in Figure 9. Save the ZINC code of this drug for later: **ZINC000000001505** [13].




Figure 8: **6T3X** protein model [12].

ZINC Substances Catalogs Tranches Biological More About

/ substances / ZINC000000001505


### ZINC1505 (Ganciclovir)

In: anodyne bb fda for-sale in-stock  
Google Wikipedia PubMed

Added	Availability	Since	Mwt	logP	Download
2005-09-26	In-Stock	2015-08-07	255.234	-1.971	<a href="#">Download</a>

Mol Formula	Rings	Heavy Atoms	Hetero Atoms	Fraction sp <sup>3</sup>	Tranche
C9H13N5O4	2	18	9	0.44	CAAA

SMILES	<chem>Nc1nc2c(ncn2COC(CO)CO)c(=O)[nH]1</chem>	
InChI	InChI=1S/C9H13N5O4/c10-9-12-7-6(8(17)13-9)11-3-14(7)4-18-5(1-15)2-16/h3,5,15-16H,1-2,4H2,(H3,10,12,13,17)	
InChI Key	IRSCQMHWYFCW-UHFFFAOYSA-N	



Draw

Figure 9: **Ganciclovir** entry in ZINC15 [13]

Go to the *Submit Docking* tool on the SwissDock web server [5]. In the *Target selection* section click on the **upload file (max 5MB)** link and upload the **6T3X** .pdb file. Wait until the server setups the target protein successfully.

Next, in the *Ligand selection* enter the **Ganciclovir** ZINC code **ZINC000000001505** into the *Search for ligands:* field and click on the *Search* button. A new window like the shown in Figure 10 will open, select the **1505** option and click on the *Dock 1 selected ligand* button. Wait until the server setups the ligand drug successfully.




Figure 10: SwissDock interface for ligand selection [5].

Now the interface should look like Figure 11. Click on the **Submit** button to start the docking; this could take some hours or even few days until it finishes.

The screenshot shows the 'Submit Docking' interface in SwissDock. It is divided into three main sections: 'Target selection', 'Ligand selection', and 'Description'.  
 - **Target selection:** Includes a 'Select target structure file:' label, a 'Seleccionar archivo' button, and a text field containing '6t3x.pdb'. Below this, it says '(e.g. single PDB, CHARM, or multiple PDBs, CHARMMs files)' and 'or search for targets'. A green checkmark and 'Successful setup - inspect' are shown.  
 - **Ligand selection:** Includes a 'Search for ligands:' label, a text field containing 'ZINC000000001505', and a 'Search' button. Below this, it says 'ie. ZINC AC, ligand name or category (like scaffolds or sidechains), or URL' and 'or upload file (max 5MB)'. A green checkmark and 'Successful setup - inspect' are shown.  
 - **Description:** Includes a 'Job name (required):' label, a text field containing 'ejemplo6T3XGanciclovir', an 'E-mail address (optional):' label, an empty text field, a 'Show extra parameters' link, and a 'Start Docking' button.

Figure 11: SwissDock interface for the Submit Docking tool with the **6T3X** protein and the **Ganciclovir** drug [5].



The top 5 clusters from this docking displayed with the same SwissDock server are shown in Figure 12, and its resulted PDB file with all the clusters predicted is visualized with the VMD software in Figure 13.




Figure 12: Docking results for **Cytomegalovirus - Ganciclovir** in SwissDock [5].




Figure 13: Docking result for **Cytomegalovirus - Ganciclovir** in VMD [6].

## 4 Conclusions and recommendations

The recommended actions to take in order to predict the effect of a drug on a protein, supposing that all we know about the protein is its primary structure, consists on performing a BLAST on this protein to acknowledge other similar and have a better understanding of its nature. A virtual screening is very used to reduce all the possible drugs that can have the searched effect on the protein. However, the docking results are not definitive, so there must be make tests on animals and next on humans to identify if the drug is effective or not against the protein in question.

## 5 References

- [1] Wikipedia, "Docking (molecular)," [https://en.wikipedia.org/wiki/Docking\\_\(molecular\)](https://en.wikipedia.org/wiki/Docking_(molecular)), [Online; last access December 15, 2020].
- [2] R. PDB, "About RCSB PDB: Enabling Breakthroughs in Scientific and Biomedical Research and Education," <https://www.rcsb.org/pages/about-us/index>, [Online; last access October 13, 2020].
- [3] U. of Massachusetts, "ZDOCK Server," <http://zdock.umassmed.edu/>, [Online; last access December 12, 2020].
- [4] T. Sterling and J. J. Irwin, "ZINC 15 – Ligand Discovery for Everyone," <https://zinc.docking.org/>, [Online; last access December 12, 2020].
- [5] S. I. of Bioinformatics, "SwissDock," <http://www.swissdock.ch/docking>, [Online; last access December 12, 2020].
- [6] "Download VMD," <https://www.ks.uiuc.edu/Development/Download/download.cgi?PackageName=VMD>, [Online; last access October 13, 2020].
- [7] R. PDB, "1AMY CRYSTAL AND MOLECULAR STRUCTURE OF BARLEY ALPHA-AMYLASE," <https://www.rcsb.org/structure/1AMY>, [Online; last access December 12, 2020].
- [8] —, "2IWT Thioredoxin h2 (HvTrxh2) in a mixed disulfide complex with the target protein BASI," <https://www.rcsb.org/structure/2IWT>, [Online; last access December 12, 2020].
- [9] —, "1AVA AMY2/BASI PROTEIN-PROTEIN COMPLEX FROM BARLEY SEED," <https://www.rcsb.org/structure/1AVA>, [Online; last access December 12, 2020].
- [10] —, "2A4L Human cyclin-dependent kinase 2 in complex with roscovitine," <https://www.rcsb.org/structure/2A4L>, [Online; last access December 12, 2020].
- [11] Z. 15, "ZINC1649340 (Seliciclib)," <https://zinc.docking.org/substances/ZINC000001649340/>, [Online; last access December 12, 2020].

- 
- [12] R. PDB, "6T3X Crystal structure of the truncated human cytomegalovirus pUL50-pUL53 complex," <https://www.rcsb.org/structure/6T3X>, [Online; last access December 12, 2020].
- [13] Z. 15, "ZINC1505 (Ganciclovir)," <https://zinc.docking.org/substances/ZINC000000001505/>, [Online; last access December 12, 2020].