

	Description	Qty	Unit	Rate	Amount
	<u>SURFACE PAVINGS, FENCING AND LANDSCAPING</u>				
	IN-SITU SURFACE PAVINGS				
	<u>50mm thick wearing course of 30% hot rolled asphalt to BS 594; 14mm nominal aggregate and 50 pen binder; topped with 20mm nominal size precoated chippings; surface texture to Clause 921 of Engineers Specification; on and including 80mm basecourse to BS 4987; 20mm nominal aggregate and 100 pen binder; on and including 230mm roadbase to BS 4987; 28mm nominal aggregate and 50 pen binder; laid level or to falls, crossfalls or slopes; all in accordance with the Engineer's Specification</u>				
	Roads; on blinded hardcore base				
A	360mm overall thickness	61	m2		
B	extra; junction with existing	25	m		
C	extra; sealing at junction with kerbs	29	m		
	<u>Tegula Sett Blocks & Circles paving supplied by 'Tobermore' ; colour - Bracken; 80mm thick laid on sand blinding on compacted hardcore; include for leveling; filling joints as per manufacturers instructions; compacted with plate compactor ;incl all cutting around openings; curved cutting; etc; to be laid as per the Engineer's and Architect's instructions; all in strict accordance with the manufactures instructions</u>				
	Pavings				
D	240mm x 120mm x 80mm thick paving	69	m2		
	Extra over for				
E	extra over for reinstatement of block paving lifted from rear of existing building; laid on sand blinding as per Architects Drawing No. 770-T-12	471	m2		
	Kerbs				
F	240mm x 120mm x 80mm thick; curved	92	m		

	Description	Qty	Unit	Rate	Amount
	Granular filling; with Hardcore Clause 804 as specified; laid and compacted to clause 802; to be obtained off site; all in accordance with specification: to make up levels				
	Filling; depositing in layers; compacting to Clause 802				
A	to make up levels; average thickness less than or equal to but not exceeding 250mm	13	m3		
	Surface Treatments				
B	Surface treatments: blinding filling with sand to BS EN 12620; 50mm thick	98	m2		
<u>SURFACE PAVINGS, FENCING AND LANDSCAPING</u>					
<u>IN-SITU SURFACE PAVINGS</u>					
	<u>Tegula Sett Blocks & Circles paving supplied by 'Tobermore' ; colour - Bracken; 80mm thick laid on sand blinding on compacted hardcore; include for leveling; filling joints as per manufacturers instructions; compacted with plate compactor ;incl all cutting around openings; curved cutting; etc; to be laid as per the Engineer's and Architect's instructions; all in strict accordance with the manufactures instructions</u>				
	Pavings				
C	240mm x 120mm x 80mm thick paving	98	m2		
<u>METALWORK</u>					
<u>NON-STRUCTURAL</u>					
	<u>Aco 'Hexdrain Brickslot' door drain or equal and approved; bedding and surrounding in concrete, stainless steel hellsafe grating and frame, with DPC around drain sealed to threshold of doorway; incl. all assessories; all to Architect's drawing 770-T-12 & specification.</u>				
	Aco Drains				
D	generally	27	m		
E					
F					