
Scheme EdDSA

The EdDSA signature scheme [Sch91] for $ed25519(\mathbb{G}, q, G, I)$ and hash function H (often Sha512). Signer run holds private key $x \in \mathbb{Z}_2^{[q]}$ and public key $Q \in \mathbb{G}$.

Inputs: m , a message to sign

KeyGen $() \dashrightarrow (x, Q)$

- 1: Sample $a \xleftarrow{\$} \{0, 1\}^{2|q|}$
- 2: $Q \leftarrow a \cdot G$
- 3: $x \leftarrow \{a_{(i+|q|)}\}_{i \in [|q|]}$
 return (x, Q) as the key pair

Sign $(m, x \in \mathbb{Z}_q^*, Q \in \mathbb{G}) \dashrightarrow \sigma$

- 4: $k \leftarrow H(x \parallel m)$ (Nonce generation)
- 5: $R \leftarrow k \cdot G$ (Commitment)
- 6: $e \leftarrow H(R \parallel Q \parallel H(m))$ (Challenge)
- 7: $s \leftarrow (x \cdot e) + k$ (Signature composition)
 return $\sigma = \{R, s\}$ as the signature

Verify $(m, Q \in \mathbb{G}, \sigma = \{R \in \mathbb{G}, s \in \mathbb{Z}_{q^*}\}) \dashrightarrow \text{valid}$

- 1: $e' \leftarrow H(G \parallel R \parallel Q \parallel H(m))$
 - 2: $R' \leftarrow s \cdot G + (-e) \cdot Q$
 - 3: Check if $R' \stackrel{?}{=} R$, otherwise **ABORT**.
 return *valid*
-

References

- [Sch91] C. P. Schnorr. Efficient signature generation by smart cards. In *Journal of Cryptology*, 1991.