



Menu

Authentication

Authentication

To ensure secure access to the Allstar Partner API, authentication is required for all API requests. This section explains how to authenticate your requests using your API key.

Obtaining Your API Keys

Upon completing the onboarding process with Allstar, you will receive two API keys. These keys are essential for accessing the API and must be included in the headers of all your requests. Keep your secret API key confidential to prevent unauthorized access.

Using Your API Keys

To authenticate your requests, include your API key in the header of each request with the header name ``X-Api-Key``. Here is an example of how to include it in a request:

```
GET /api/endpoint HTTP/1.1
Host: prt.allstar.gg
X-Api-Key: your_api_key_here
```

Ensure that you replace ``your_api_key_here`` with your actual API key.

Public API Key Usage

Select API endpoints allow the use of either a secret API key or a semi-public API key. These endpoints include (but may not be limited to) ``/user/clips`` (fetching all clips for a given user) and ``/{game}/clips`` (fetching all clips for a given game associated with your partner account).

“Note: It is important to never use your secret API key for requests that are client-side or visible to the user. The secret key should only be used for server-side requests that require post operations.”

Secured Communication

The Allstar Partner API enforces secured communication through HTTPS. Any HTTP requests will automatically be redirected to HTTPS with a 301 status code. Always ensure your requests are made over HTTPS to maintain security.

Rate Limiting

To provide a fair usage policy, the API enforces rate limits on the number of requests that can be made within a specific time frame. These limits are applied per API key. If you exceed your allocated rate limit, the API will respond with a status code of 429, indicating too many requests.

Please refer to your onboarding documentation for the specific rate limits applicable to your API key.

Handling Rate Limiting

When you encounter a 429 status code, it is advised to implement a backoff strategy in your request logic. Consider waiting for a certain period before attempting to resend your request. Additionally, optimizing the efficiency of your requests can help in staying within the rate limits.

For further assistance or questions regarding authentication and rate limits, please contact Allstar Partner API support at partners@allstar.gg.