



League of Legends Clips

Quickstart Guide

Current Matches

Allstar is able to generate clips shortly after a current League of Legends match ends. However, in order to know that we should be spectating a current match, we need a signal that a specific player is currently playing in that match.

Therefore, it's imperative that we are notified in a timely fashion relative to the start of the match a particular LoL player is about to start (or has just recently started) playing. We provide the [spectate](#) endpoint to do just that.

See our [Current Matches](#) documentation for more details.

Completed Matches

We are also able to generate clips from matches completed within the past 30 days (give or take, somewhat dependent League patch/release cycle). We support generating two use cases for these matches.

- BP : [Best Play](#)
 - Requires match, region, and riotID
- POTG : [Play of the Game](#)
 - Requires matchId and region

See our [Completed Matches](#) documentation for more details.

Current Matches API

Registering League of Legends players

First and foremost, please confirm that you have access to the `REGISTER` use case to register LoL players. This will be listed under *Use Case* in [your dashboard](#). If it is not, you will need to request access by [opening a support ticket](#).

Once enabled for your partner account, you'll be able to post API calls to the [/league/register](#) endpoint.

The required arguments are:

- riotID
- region
 - NA1 (or one of the other regions from the accepted list in the api reference)

Sample HTTP request

```
POST /league/register HTTP/1.1
Host: prt.allstar.gg
X-API-Key: YOUR_API_KEY_HERE
Content-Type: application/json

{
  "riotID": "makeClips#ASGG",
```

```
"region": "NA1",  
}
```

Spectating a League of Legends match for a specific player

A call to the [/league/spectate](#) signals to us that we need to identify the next match the specified player is playing in and to start the process of spectating that match.

The required arguments are:

- riotID
- region
 - NA1 (or one of the other regions from the accepted list in the api reference)

Sample HTTP Request

```
POST /league/spectate HTTP/1.1  
Host: prt.allstar.gg  
X-API-Key: YOUR_API_KEY_HERE  
Content-Type: application/json  
  
{  
  "riotID": "makeClips#ASGG",  
  "region": "NA1",  
}
```

This call will trigger a job that checks for a live match the specified player is participating in. Once a live match is found, we begin spectating the match.

Ideally, this call should be made as soon as you know that a player has started a match.

In some cases, we may automatically identify the best play for the specified player during the spectated match and send a clip to you via a webhook. Please see [automatic prerenders](#) below.

If no clip is returned, you can still manually generate one by making a request to generate a clip from the spectated match. To generate a different or additional clip from a specific match, please refer to the [League API Reference](#). You may also want to request access to the relevant [use case](#).

Automatic Pre-Renders

Automatic prerenders use our algorithm to identify key moments in a match that are likely to generate entertaining content with a higher chance of being viewed.

When such a moment is detected, a clip is automatically created and sent to the partner's webhook.

This feature is beneficial because it allows partners to proactively surface exciting content, driving engagement and alerting users to highlight-worthy moments without requiring manual intervention.

In addition to the webhook event, automatically prerendered clips will also be available when using the `GET` methods to retrieve clips by [match](#) or [player](#).

See [Displaying Clips](#) for more detail on how to use these methods to retrieve information on clips already generated. Please note, we provide a way to display pending clips as well. See [Pending Spectate Clips](#).

Pending Spectate Clips

Matches being spectated operate on a three minute delay (as part of Riot's anti-cheat and integrity efforts). Because of this delay, a player may exit the match before we've fully spectated the match. If a request for a clip for a specific match or player and we're still spectating,

we'll return a virtual clip object that can be used to communicate estimated time to clip production.

E.g. a request for a user's clips whose match we're still spectating

```
curl -H 'X-API-Key: *****' https://prt.allstar.gg/user/clips/?limit=30&page=1&riotID=playerName%23tagL
```

will produce a clip object with a status of `SPECTATING`. The `clipUrl` can be shown to the user and we'll provide an ETA for the clip. Once ready, the clip will be displayed.

```
{
  "message": "OK",
  "requestId": "1d46dc6d-29cf-4605-a5fd-ae5e82421395",
  "data": {
    "clips": [
      {
        "_id": "670581d8d0b0c27ca3e45d4f",
        "clipUrl": "https://allstar.gg/iframe?clip=670581d8d0b0c27ca3e45d4f&known=false&platform=ALLSTAR",
        "roundNumber": null,
        "matchId": "RG_11111111",
        "status": "SPECTATING",
        "clipTitle": "Spectating RG:11111111",
        "shareId": "670581d8d0b0c27ca3e45d4f",
        "createdDate": "2024-10-08T19:02:48.381Z",
        "clipSnapshotURL": "https://mediacdn.allstar.gg/static/thumbnails/Allstar_LogoSnapshot_2.jpg",
        "clipImageThumbURL": "https://mediacdn.allstar.gg/static/thumbnails/Allstar_LogoThumb_2.jpg",
        "metadata": []
      }
    ],
    "currentPage": 1,
    "count": 0,
    "limit": 30
  }
}
```

Completed Matches API

Best Play

A call to the [/league/clip/bp](#) with the required arguments will trigger us to retrieve and analyze the specified match for the specified RiotID and select the best moment of that player's game play.

Upon analysis of the match, we'll trigger a [Submitted webhook](#) indicating the clip has been submitted for processing and then, once a clip has been generated, we'll deliver a [Processed webhook](#) event indicating the clip is ready for display to the user.

Once you've received the `Submitted` webhook though, you can display our iframe to the user (as specified in the webhook).

The required arguments are:

- riotID
- region
- matchId

Sample HTTP Request

```
POST /league/clip/bp HTTP/1.1
Host: prt.allstar.gg
X-API-Key: YOUR_API_KEY_HERE
Content-Type: application/json
```

```
{
  "riotID": "makeClips#ASGG",
  "matchId": 5551212,
  "region": "NA1",
}
```

Play of the Game

A call to the [/league/clip/potg](#) with the required arguments will trigger us to retrieve and analyze the specified match for the best moment of the match.

Upon analysis of the match, we'll trigger a [Submitted webhook](#) indicating the clip has been submitted for processing and then, once a clip has been generated, we'll deliver a [Processed webhook](#) event indicating the clip is ready for display to the user.

Once you've received the `Submitted` webhook though, you can display our iframe to the user (as specified in the wehook).

The required arguments are:

- region
- matchId

Sample HTTP Request

```
POST /league/clip/potg HTTP/1.1
Host: prt.allstar.gg
X-API-Key: YOUR_API_KEY_HERE
Content-Type: application/json

{
  "matchId": 5551212,
  "region": "NA1",
}
```

API

See our [API Reference here](#)

Support

If you encounter any issues or have questions, please [contact our support team](#).