



Menu

Clip Types/Statuses

Clip Types/Statuses

In addition to fully rendered video clips of your players' games' highlights, Allstar.gg also supports two additional types of clips.

We support On Demand clips which are placeholders for rendered video. We've parsed all the match data, determined where and how to clip the replay, and are awaiting user interaction to trigger a request to render the video. Displaying the Allstar.gg iframe to the user will provide them with the ability to trigger video processing and will subsequently provide the user with an estimate of availability. On demand clips are available for any of our supported games.

For League of Legends, we also support a special Spectating clip. Clips that are in this state indicate that we are in the process of gathering, recording and analyzing match data from LoL's near real time live replay APIs. These clips can be used to indicate to a player that their clip is pending and will soon be ready. When the Allstar.gg iframe is displayed to the user, an estimated time to complete spectating will be provided, followed by an estimate for processing the video, and ultimately, the clip itself.

On Demand

A clip will be created as On Demand when a combination of conditions (e.g. highlight score is below a specified threshold) and/or configurations are met (e.g. create 1 rendered and 2 on demand clips per player per match). We don't currently support an explicit way to request a clip be created as On Demand.

An On Demand clip can be identified when the clip status is `Pruned` and the `onDemand` attribute is true, e.g.:

```
{
  "message": "OK",
  "requestId": "a6bb7421-9e61-42a8-a274-82806e9c646d",
  "data": {
    "clips": [
      {
        ...
        "status": "Pruned",
        "onDemand": true,
        ...
      }
    ],
    "currentPage": 1,
    "count": 60,
    "limit": 30
  }
}
```



End points

The following end points support the `onDemand` parameter. If the parameter is a non-zero integer value, onDemand clips will be returned.

User clips

- [/user/clip](#)
 - On Demand Clips default: off
- [/user/clips](#)
 - On Demand Clips default: on

CS Clips

- [/cs/clip](#)
 - On Demand Clips default: off

- [/cs/clips](#)
 - On Demand Clips default: off

League Clips

- [/league/clip](#)
 - On Demand Clips default: off
- [/league/clips](#)
 - On Demand Clips default: off

Fortnite Clips

- [/fortnite/clip](#)
 - On Demand Clips default: off
- [/fortnite/clips](#)
 - On Demand Clips default: off

Spectating

This type of clip is specific to our League product. If we receive a request for a specific Riot ID in conjunction with the ``spectating`` request parameter and we are still spectating a match for that player, a virtual clip object will be returned. That clip object will have a status of ``SPECTATING``; the ``clipUrl`` property will provide the user with an estimate for spectate completion, followed by an ETA for the video production, and then the clip itself.

A ``SPECTATING`` clip will always be the first in returned list of clips, e.g.:

```
{
  "message": "OK",
  "requestId": "84c7522a-6ade-4eb5-b2b9-54e7dc6aacbc",
  "data": {
    "clips": [
      {
        ...
      }
    ]
  }
}
```

```
    "status": "SPECTATING",
    "clipTitle": "Spectating NA1:5131207925",
    ...
  },
  {
    ...
    "status": "Processed",
    ...
  }
],
"currentPage": 1,
"count": 0,
"limit": 30
}
```

End points

User clips

Will only be included if the user identifier as a Riot ID:

- [/user/clips](#)



League Clips

Will only be included if a Riot ID is included as a request parameter

- [/league/clips](#)
 - Spectating Clips default: off