

Final Report

Group 1: Jiawen Chen, Brooke Felsheim, Elena Kharitonova, Jairui Tang, and Xinjie Qian

4/29/2022

Introduction

```
library(usethis)
library(devtools)
load_all("package/bikeSharing/")

## i Loading bikeSharing

set.seed(1)

str(london)

## 'data.frame': 2185 obs. of 14 variables:
## $ Date : chr "01-01" "01-01" "01-01" "01-01" ...
## $ Hour_chunks : Factor w/ 3 levels "[0,8)","[8,16)",...: 1 1 2 2 3 3 1 1 2 2 ...
## $ Day : num 1 1 1 1 1 1 2 2 2 2 ...
## $ Is_weekend : Factor w/ 2 levels "0","1": 1 2 1 2 1 2 1 2 1 2 ...
## $ Is_holiday : Factor w/ 2 levels "0","1": 2 1 2 1 2 1 2 1 2 1 ...
## $ Season : Factor w/ 4 levels "Spring","Summer",...: 4 4 4 4 4 4 4 4 4 4 ...
## $ Min_temp : num 3 5 3 5 3 5 1 9 1 9 ...
## $ Max_temp : num 9 10 9 10 9 10 6 11.5 6 11.5 ...
## $ Min_humidity: num 76 81 76 81 76 81 71 82 71 82 ...
## $ Max_humidity: num 87 93 87 93 87 93 93 94 93 94 ...
## $ Year : chr "Year 1" "Year 2" "Year 1" "Year 2" ...
## $ Wind_speed : num 2.48 3.65 4.83 4.08 6.63 ...
## $ Rain_or_snow: Factor w/ 2 levels "0","1": 1 2 2 2 2 2 1 2 1 2 ...
## $ Bike_count : int 2715 2962 4460 2450 2622 1009 438 475 7756 4263 ...

str(dc)

## 'data.frame': 2187 obs. of 14 variables:
## $ Date : chr "01-01" "01-01" "01-01" "01-01" ...
## $ Hour_chunks : Factor w/ 3 levels "[0,8)","[8,16)",...: 1 1 2 2 3 3 1 1 2 2 ...
## $ Day : num 1 1 1 1 1 1 2 2 2 2 ...
## $ Is_weekend : Factor w/ 2 levels "0","1": 2 2 2 2 2 2 1 2 1 2 ...
## $ Is_holiday : Factor w/ 2 levels "0","1": 1 1 1 1 1 1 2 1 2 1 ...
## $ Season : Factor w/ 4 levels "Spring","Summer",...: 1 1 1 1 1 1 1 1 1 1 ...
## $ Min_temp : num 1.4 4.22 1.4 4.22 1.4 4.22 2.34 2.34 2.34 2.34 ...
## $ Max_temp : num 13.6 14.6 13.6 14.6 13.6 ...
## $ Min_humidity: num 72 48 72 48 72 48 32 39 32 39 ...
## $ Max_humidity: num 94 93 94 93 94 93 45 100 45 100 ...
## $ Year : chr "Year 1" "Year 2" "Year 1" "Year 2" ...
## $ Wind_speed : num 0.208 1.458 3.958 3.75 4.791 ...
## $ Rain_or_snow: Factor w/ 2 levels "0","1": 1 1 1 1 2 2 1 2 1 2 ...
```

```
## $ Bike_count : int 108 290 508 1218 369 786 96 55 1102 452 ...
str(seoul)

## 'data.frame': 1059 obs. of 13 variables:
## $ Date : chr "01-01" "01-01" "01-01" "01-02" ...
## $ Hour_chunks : Factor w/ 3 levels "[0,8)","[8,16)",...: 1 2 3 1 2 3 1 2 3 1 ...
## $ Day : num 1 1 1 2 2 2 3 3 3 4 ...
## $ Is_weekend : Factor w/ 2 levels "0","1": 1 1 1 1 1 1 1 1 1 1 ...
## $ Is_holiday : Factor w/ 2 levels "0","1": 2 2 2 1 1 1 1 1 1 1 ...
## $ Season : Factor w/ 4 levels "Spring","Summer",...: 4 4 4 4 4 4 4 4 4 4 ...
## $ Min_temp : num -5 -5 -5 -3.8 -3.8 -3.8 -7 -7 -7 -8.6 ...
## $ Max_temp : num 3.7 3.7 3.7 1.7 1.7 1.7 -0.4 -0.4 -0.4 -0.8 ...
## $ Min_humidity: int 20 20 20 20 20 20 29 29 29 31 ...
## $ Max_humidity: int 56 56 56 71 71 71 54 54 54 57 ...
## $ Wind_speed : num 0.9 1.85 1.61 0.65 2.26 ...
## $ Rain_or_snow: Factor w/ 2 levels "0","1": 1 1 1 1 1 1 1 1 1 1 ...
## $ Bike_count : int 1002 1633 1655 938 2610 2898 1022 2624 2866 1015 ...

london_train <- london[london$Year == "Year 1",]
london_test <- london[london$Year == "Year 2",]
```

Methods

Negative Binomial Generalized Linear Mixed Model

Random Forest

Results

Negative Binomial Generalized Linear Mixed Model

```
glmm_fit <- MCEM_algorithm( beta_initial = c(8.3, 1.5, 1.5, -0.25, -0.50, 0,
                                           0, -0.25, 0, 0, 0, 0, 0, -0.25),
                           theta_initial = 10,
                           s2gamma_initial = 0.2,
                           M = 1000,
                           burn.in = 200,
                           tol = 10^-4,
                           maxit = 100,
                           data = london_train
                           )
```

```
str(glmm_fit)
```

```
## List of 7
## $ beta : num [1:14] 8.353 1.534 1.415 -0.337 -0.393 ...
## $ s2gamma : num 0.0296
## $ theta : num 18.4
## $ eps : num 5.15e-05
## $ qfunction: num -9520
## $ day_ranef: num [1:365] 0.0653 -0.398 -0.5165 -0.2612 -0.0374 ...
## $ iter : num 23

glmm_model_fit(glmm_fit, london_train, scale_to_london_mean = "no")
```

```
##          RMSE          MAE          R2
## 1 1886.267 1291.106 0.8831618
glmm_model_fit(glmm_fit, london_test, scale_to_london_mean = "no")
```

```
##          RMSE          MAE          R2
## 1 2491.293 1647.064 0.8142036
glmm_model_fit(glmm_fit, dc, scale_to_london_mean = "yes")
```

```
##          RMSE          MAE          R2
## 1 845.741 605.217 0.521788
glmm_model_fit(glmm_fit, seoul, scale_to_london_mean = "yes")
```

```
##          RMSE          MAE          R2
## 1 3519.413 2719.021 0.4999935
```

Random Forest

```
rf_fit <- train_random_forest(data = london_train)
```

```
## Loading required package: ggplot2
```


```
## Loading required package: lattice
```

```
rf_fit
```

```
## Random Forest
##
## 1095 samples
## 11 predictor
##
## No pre-processing
## Resampling: Cross-Validated (5 fold)
## Summary of sample sizes: 876, 878, 875, 875, 876
## Resampling results across tuning parameters:
##
##  mtry  RMSE      Rsquared  MAE
##    2   2262.068  0.8841247 1721.956
##    6   1797.963  0.8980543 1174.833
##   11   1789.815  0.8964189 1167.026
##
## RMSE was used to select the optimal model using the smallest value.
## The final value used for the model was mtry = 11.
```

```
plot_rf_importance(london_train)
```

```
## Warning: ggrepel: 1 unlabeled data points (too many overlaps). Consider
## increasing max.overlaps
```



```
rf_model_fit(rf_fit, london_train, scale_to_london_mean = "no")
```

```
##      RMSE      MAE      R2
## 1 714.5723 445.2132 0.9838003
```

```
rf_model_fit(rf_fit, london_test, scale_to_london_mean = "no")
```

```
##      RMSE      MAE      R2
## 1 1780.33 1172.378 0.9063308
```

```
rf_model_fit(rf_fit, dc, scale_to_london_mean = "yes")
```

```
##      RMSE      MAE      R2
## 1 737.5336 524.7186 0.641438
```

```
rf_model_fit(rf_fit, seoul, scale_to_london_mean = "yes")
```

```
##      RMSE      MAE      R2
## 1 3465.028 2630.914 0.544965
```

Discussion