


N.T.S.

	•	
DATE	REVISION DESCRIPTION	APP
8/5/05	CHANGED SETBACK	TMK
5/17/12	DEPARTMENT NAME	TLM

CITY	OF	CLEARWATER \
ENG	SINEER	ING DEPARTMENT
	LAI	NDSCAPE
		ETAILS

PLANT SPACING DETAIL (NO-OFFSET)

INDEX NO.	PAGE NO.
903	1 of 2
LATEST REVISION	2/22/2016





5/17/12	DEPARTMENT NAME	TLM
DATE	REVISION DESCRIPTION	APP

CITY	OF	CLEARWATER	1
ENC	SINEER	ING DEPARTMENT	
	LAI	NDSCAPE	
		ETAILS	1

PLANT SPACING DETAIL (24" OFFSET)

_	
INDEX NO.	PAGE NO.
903	2 of 2
LATEST REVISION	2/22/2016





N.T.S.

			M
5/17/12	DEPARTMENT NAME	TLM	╟
DATE	REVISION DESCRIPTION	APP	Il
			' 🖊

CITY	OF	CLEARWATER
ENG	INEER	ING DEPARTMENT
	LAI	NDSCAPE
	D	ETAILS

SHRUB AND GROUNDCOVER PLANTING DETAIL

_	
INDEX NO.	PAGE NO.
905	1 of 1
LATEST REVISION	2/22/2016

## GENERAL LANDSCAPE NOTES

- 1. The Landscape Contractor shall grade planting beds, as required, to provide positive drainage and promote optimum plant growth.
- 2. All recommended trees and plant materials will be graded as Nursery Grade No. 1 or better as outlined by the Florida Department of Agriculture and Consumer Services, Division of Plant Industry "Grades and Standards for Nursery Plants", 7th Edition, 1998 as revised from time to time.
- 3. All planting shall be done in accordance with the Florida Nurserymen's and Grower's Associations approved practices.
- 4. All plants shall be fertilized with Agriform 20-10-5 tablets as per the manufacturers specifications in conjunction with note # 5.
- 5. The planting soil shall be the approximate proportions as follows: 50% sand and 50% organic material consisting of native peat, well—decomposed sawdust, leaf mold and top soil. It shall provide a good pliable and thoroughly mixed medium with adequate aeration, drainage and water—holding capacity. It shall also be free of all extraneous debris, such as roots, stones, weeds, etc.
- 6. All planting areas shall receive a 3" layer of recycled hardwood log mulch, which is to be watered—in after installation.
- 7. The plant material schedule is presented for the convenience of the Landscape Contractor. In the event of a discrepancy between the plan and the plant key, the plan shall prevail.
- 8. Plants shall meet size, container, and spacing specifications. Any material not meeting specifications shall be removed and replaced at the contractor's expense.
- 9. All tree and shrub locations are subject to change. All locations shall be approved by the City Project Manager prior to planting.
- 10. The Landscape Contractor shall be responsible for examining fully both the site and the bid documents. Discrepancies in the documents or the actual site conditions shall be reported to the City Project Manager in writing at the time of bidding or discovery. No account shall be made after contract completion for failure to report such condition, or for errors on the part of the Landscape Contractor at the time of bidding.
- 11. The Landscape Contractor shall be responsible for securing all necessary applicable permits and licenses to perform the work set forth in this plan set and the specifications.
- 12. Plant material shall be bid as specified unless unavailable, at which time the City Project Manager will be notified by telephone and in writing of intended changes.
- 13. Any and all questions concerning the plan set and/or specifications shall be directed to the City Project Manager at (727) 562-4737
- 14. There shall be no additions, deletions or substitutions without the written approval of the City Project Manager.
- 15. The Landscape Contractor shall guarantee, in writing, plant survivability for a period of twelve (12) months from final acceptance by the City Project Manager.
- 16. All dimensions to be field—checked by the Landscape Contractor prior to landscape material installation. Discrepancies shall be reported immediately to the City Project Manager.
- 17. All materials must be as specified on the landscape plan. If materials or labor do not adhere to specifications, they will be rejected by the City Project Manager with proper installation carried out by Landscape Contractor at no additional cost.
- 18. All permits necessary are to be provided by the installing contractor unless otherwise specifically stated in the specifications.
- 19. No contractor identification signs shall be permitted on the project, except for the project information signs.
- 20. Existing sod shall be removed as necessary to accompdate new plantings.
- 21. Any existing sod areas that are unnecessarily disturbed during the landscape installation shall be resodded to match existing.
- 22. The Landscape Contractor will be responsible for the collection, removal, and proper disposal of any and all debris generated during the installation of this project.

5/17/12	DEPARTMENT NAME	TLM
DATE	REVISION DESCRIPTION	APP

CITY OF CLEARWATER
ENGINEERING DEPARTMENT
LANDSCAPE
DETAILS

GENERAL LANDSCAPING NOTES

INDEX NO.	PAGE NO.
906	1 of 3
LATEST	2/22/2016

## IRRIGATION NOTES

- 1. A low volume irrigation system, that provides 100% coverage of all plantings and sod, will be designed and installed by contractor.
- 2. The proposed irrigation system must meet or exceed all applicable City code requirements (ie., Back Flow Prevention, Automatic Rain Shutoff Device, etc...)
- 3. Contractor must coordinate location and size of irrigation water meter with the City Project Manager.
- 4. Contractor must coordinate the placement and power supply for the irrigation control timer with the City Project Manager.
- The proposed irrigation system must use irrigation components from the Parks & Recreation Department's most current approved products list, available from the City Project Manager.
- 6. The proposed irrigation system must be designed in compliance with the Parks & Recreation Department's Irrigation System Design guidelines, available from the City Project Manager.
- 7. Irrigation Shop Drawings must be prepared and submitted for approval by the City Project Manager prior to commencement of work.
- The irrigation system must be inspected and accepted by the City Project Manager prior to backfilling trenches or installation of mulch.
- 9. İrrigation As—Built drawings, which accurately and clearly identify any and all modifications and/or substitutions, must be submitted to the City Project Manager prior to final inspection and acceptance.

5/17/12	DEPARTMENT NAME	TLM
DATE	REVISION DESCRIPTION	APP

CITY OF CLEARWATER
ENGINEERING DEPARTMENT
LANDSCAPE
DETAILS

IRRIGATION NOTES

INDEX NO.	PAGE NO.
906	2 of 3
LATEST REVISION	2/22/201

## FERTILIZATION NOTES

### SHRUBS AND TREES

All trees and shrubs shall be fertilized with "Agriform" 20-15-5 planting tablets at time of installation and prior to completion of pit backfilling. Tablets shall be placed uniformly around the root mass at a depth that is between the middle and bottom of the root mass.

#### APPLICATION RATE:

1 Gallon can:1 - 21 gram tablet3 Gallon can:2 - 21 gram tablets5 Gallon can:3 - 21 gram tablets7 Gallon can:4 - 21 gram tablets

Trees: 3 - 21 gram tablets each 1/2" of

caliper

Palms: 7 - 21 gram tablets

## **GROUNDCOVER AREAS**


All groundcover areas shall receive fertilization with "Ozmocote" time release fertilizer as per manufacturer's specifications.

5/17/12	DEPARTMENT NAME	TLM
DATE	REVISION DESCRIPTION	APP

CITY	OF	CI	LEA	RWA	\TER
ENG	INEER	NG	DEP/	ARTMEN	١T
LANDSCAPE					
	D	ET/	AILS		

<b>FERTILIZATION</b>
NOTES

INDEX NO.	PAGE NO.
906	3 of 3
LATEST REVISION	2/22/201




N.T.S.

5/17/12	DEPARTMENT NAME	TLM
DATE	REVISION DESCRIPTION	APP


CITY	OF	CLEARWAT	ER 🤊
EN(	GINEER	ING DEPARTMENT	
	LA	NDSCAPE	
		DETAILS	

PINE TREE PLANTING DETAIL

INDEX NO.	PAGE NO.
907	1 of 1
LATEST REVISION	2/22/2016



#### HARDWOODS




#### <u>SPECIFICATIONS - WOOD BARRIER</u>

- 1. Minimum radius to be protected:

  - A. Hardwoods 2/3 drip line
    B. Conifers & Sabal Palms Entire drip line.
- 2. Uprights No less than 2" X 2" lumber.
- 3. Horizontals No less than 1" X 4" lumber.
- 4. Barriers shall be erected around all protected trees and palms, and inspected by city representative before construction begins.
- 5. Upright posts are to be at least 4 feet in length with a minimum of 1 foot anchored in ground and 3 feet above ground.
- 6. Barriers to remain in place until all paving, construction and heavy equipment is out of area.

Further information may be obtained from the Land Resource Specialists at 562-4575 and 562-4558.



DATE	REVISION DESCRIPTION	APP
5/17/12	DEPARTMENT NAME	TLM
10/22/18	PHONE NUMBERS	JS


(	CITY OF CLEARWATER
	ENGINEERING DEPARTMENT
	LANDSCAPE
l	DETAILS

TREE BARRICADES

INDEX NO.	PAGE NO.
909	1 of 1
LATEST REVISION	10/22/18

# STREET WITH CURB

# STREET WITHOUT CURB



#### NOTE:

2" PVC marking columns to be set 12" above existing grade at each end of PVC sleeves.

		$\overline{}$	OIT
			CII
DATE	REVISION DESCRIPTION	APP	l
			<u> </u>

CITY					
ENGINEERING DEPARTMENT					
LANDSCAPE					
DETAILS					

TYPICAL IRRIGATION SLEEVE

INDEX NO.	PAGE NO.		
910	1 of 1		
LATEST A REVISION	2/22/2016		