

ez_urlalias

Description

`ez_urlalias()` is a Twig helper for generating URLs for a location, from the given parameters.

Prototype and Arguments

`ez_urlalias(eZ\Publish\API\Repository\Values\Content\Location name[, array parameters][, bool absolute])`

Argument name	Type	Description
name	string <code>eZ\Publish\API\Repository\Values\Content\Location</code>	The name of the route or a Location instance
parameters	array	An array of parameters
absolute	boolean	Whether to generate an absolute URL

Working with Location

Linking to other locations is fairly easy and is done with [native `path\(\)` Twig helper](#) (or `url()` if you want to generate absolute URLs). You just have to pass it the Location object and `path()` will generate the URLAlias for you.

```
{# Assuming "location" variable is a valid
eZ\Publish\API\Repository\Values\Content\Location object #}
<a href="{ { path( location ) } }">Some link to a location</a>
```

I don't have the Location object

If you don't have the Location object, but only its ID, you can generate the URLAlias the following way:

```
<a href="{ { path( "ez_urlalias", { "locationId": 123 } ) } }">Some link to a location,
with its Id only</a>
```

The parameter for the second `path()` argument is the `locationId` for URLAlias.

Error management

For Location alias setup 301 redirect to Location's current URL when:

1. alias is history
2. alias is custom with forward flag true
3. requested URL is not case-sensitive equal with the one loaded



Under the hood

In the backend, `path()` uses the Router to generate links.

This makes also easy to generate links from PHP, via the `router` service.