SAFETY DATA SHEET

Issuing Date: 22-Dec-2011 **Revision Date:** 18-Jun-2014 **Revision Number:** 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: 31324APX-T1

Product Name: CHILEAN AIR FORCE GRAY URETHANE MIL-PRF-85285E,TYPE I,CLASS H,PART A

Hentzen Coatings, Inc.
6937 West Mill Road, Milwaukee, WI 53218-1225
Company Phone Number: 1-414-353-4200
Emergency telephone number ChemTrec 1-800-424-9300
Recommended use of the chemical and restrictions on use Industrial paint (Paint or Paint-Related), Restricted to professional users

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status
This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Serious eye damage/eye irritation	Category 2
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1B
Flammable Liquids	Category 2

Label Elements

Emergency Overview

DANGER

Hazard Statements
harmful if inhaled
Causes serious eye irritation
May cause genetic defects
May cause cancer
Highly flammable liquid and vapor

Appearance Opaque **Physical state** Liquid **Odor** Solvent

Precautionary Statements - Prevention
Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Wash face, hands and any exposed skin thoroughly after handling
Wear eye/face protection
Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed
Ground/Bond container and receiving equipment
Use explosion-proof electrical/ ventilating/ lighting/ equipment
Use only non-sparking tools
Take precautionary measures against static discharge

Precautionary Statements - Response
IF exposed or concerned: Get medical advice/attention
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If eye irritation persists: Get medical advice/attention
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage
Store in a well-ventilated place. Keep cool
Store in accordance with local regulations

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)
Other information
• May be harmful if swallowed

3. COMPOSITION/INFORMATION ON INGREDIENTS

Contains a known or suspected carcinogen

This product contains substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. See Section 15 for list of HAPS.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
METHYL AMYL KETONE	110-43-0	20% - 30%	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m³
TITANIUM DIOXIDE	13463-67-7	20% - 30%	TWA: 10 mg/m³	TWA: 15 mg/m³ total dust
METHYL ACETATE	79-20-9	10% - 20%	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 610 mg/m³
ACETYLACETONE	123-54-6	1% - 5%	TWA: 25 ppm S*	N/A
CARBON BLACK	1333-86-4	0% - 1%	TWA: 3 mg/m³ inhalable fraction	TWA: 3.5 mg/m³
LIGHT AROMATIC NAPHTHA	64742-95-6	0% - 1%	N/A	N/A
ETHYLBENZENE	100-41-4	0% - 1%	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³

4. FIRST AID MEASURES

First Aid Measures

General advice — Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

Eye Contact — Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to do, remove contact lenses. Keep eye wide open while rinsing. If symptoms persist, call a physician.

Skin Contact — Wash off immediately with plenty of water.

Inhalation Consult a physician if necessary. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

Ingestion Do NOT induce vomiting.

Self-protection of the first aider Remove all sources of ignition.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects No information available.

Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media No information available.

Specific hazards arising from the chemical
Extremely flammable.

Explosion Data
Sensitivity to Mechanical Impact no data available.
Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment as required. Avoid breathing vapors or mists. Ventilate the area.

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of

ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks and flame.

Incompatible Products None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines .

Chemical Name	ACGIH	OSHA	NIOSH IDLH
METHYL AMYL KETONE 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m³	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m³
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m³	TWA: 15 mg/m³ total dust	IDLH: 5000 mg/m³
METHYL ACETATE 79-20-9	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 610 mg/m³	IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m³ STEL: 250 ppm STEL: 760 mg/m³
ACETYLACETONE 123-54-6	TWA: 25 ppm S*	N/A	
XYLENE(PURE) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m³	
CARBON BLACK 1333-86-4	TWA: 3 mg/m³ inhalable fraction	TWA: 3.5 mg/m³	IDLH: 1750 mg/m³ TWA: 3.5 mg/m³ TWA: 0.1 mg/m³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
ETHYLBENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³

NIOSH IDLH: Immediately Dangerous to Life or Health

Exposure controls

Engineering Measures Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Use personal protective equipment as required.

Skin and Body Protection Chemical resistant apron.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work

area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	**Appearance**	Opaque
Odor	Solvent.	**Odor Threshold**	No data available
pH	No data available	**Flash Point**	14 °F / -10 °C
Decomposition temperature	No data available	**Boiling Point**	133 °F / 56 °C
Melting Point / Melting Range	No data available	**Freezing Point**	No data available
Vapor Pressure @20°C (kPa)	No data available	**Partition coefficient:**	No data available
Vapor Density	No data available	**Density**	No data available
Bulk density	No data available	**Specific Gravity**	1.16
Evaporation Rate	No data available	**Water solubility**	No data available
Dynamic viscosity	No data available	**Weight per Gallon (lbs/gal):**	9.66
		Flammability Limits in Air	
		Upper	4.91 %
		Lower	0.85 %

10. STABILITY AND REACTIVITY

Reactivity
No data available

Chemical stability
Stable under recommended storage conditions.
Conditions to Avoid
Extremes of temperature and direct sunlight.
Incompatible Materials
None known based on information supplied.
Hazardous Decomposition Products
None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information The product has not been tested

Inhalation There is no data for this product.

Eye Contact There is no data for this product.

Skin Contact There is no data for this product.

Ingestion There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
METHYL AMYL KETONE 110-43-0	1600 mg/kg (Rat)	12.6 mL/kg (Rabbit)	2000 ppm (Rat) 4 h
TITANIUM DIOXIDE 13463-67-7	10000 mg/kg (Rat)	N/A	N/A
METHYL ACETATE 79-20-9	5 g/kg (Rat)	5 g/kg (Rabbit)	16000 ppm (Rat) 4 h
ACETYLACETONE 123-54-6	N/A	N/A	1224 ppm (Rat) 4 h
XYLENE(PURE) 1330-20-7	3500 mg/kg (Rat)	4350 mg/kg (Rabbit)	29.08 mg/L (Rat) 4 h
1,2,4-TRIMETHYLBENZENE 95-63-6	3280 mg/kg (Rat)	3160 mg/kg (Rabbit)	18 g/m^3 (Rat) 4 h

CARBON BLACK 1333-86-4	15400 mg/kg (Rat)	N/A	N/A
ETHYLBENZENE 100-41-4	3500 mg/kg (Rat)	15400 mg/kg (Rabbit)	17.2 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
MUTAGENIC EFFECTS No information available.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE 13463-67-7	N/A	Group 2B	N/A	X
XYLENE(PURE) 1330-20-7	N/A	Group 3	N/A	N/A
CARBON BLACK 1333-86-4	A3	Group 2B	N/A	X
ETHYLBENZENE 100-41-4	A3	Group 2B	N/A	X

Legend:
ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 2B - Possibly Carcinogenic to Humans
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Reproductive Toxicity No information available.
Specific target organ systemic toxicity (single exposure) No information available.
Specific target organ systemic toxicity (repeated exposure) No information available.
Target Organ Effects Central nervous system (CNS), Eyes, Lungs, Peripheral Nervous System (PNS), Respiratory system, Skin.
Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .
ATEmix (oral) 2499 mg/kg
ATEmix (dermal) 13304 mg/kg
ATEmix (inhalation-dust/mist) 4.6 mg/l
Oral LD50 3536 mg/kg (rat) Estimated
Dermal LD50 18018 mg/kg (rat) Estimated
Inhalation LC50 235390 mg/l (mist) (dust) mg/m^3 Estimated
Inhalation LC50 ml/m^3 (vapor) Estimated

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
METHYL AMYL KETONE 110-43-0	N/A	126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
METHYL ACETATE 79-20-9	120: 72 h Desmodesmus subspicatus mg/L EC50	295 - 348: 96 h Pimephales promelas mg/L LC50 flow-through 250 - 350: 96 h Brachydanio rerio mg/L LC50 static	1026.7: 48 h Daphnia magna mg/L EC50
ACETYLACETONE	N/A	98.3 - 110: 96 h Pimephales	34.4: 48 h Daphnia magna mg/L

123-54-6		promelas mg/L LC50 flow-through 50.3 - 71.8: 96 h Lepomis macrochirus mg/L LC50 flow-through 64.1 - 80.1: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	EC50
XYLENE(PURE) 1330-20-7	N/A	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 19: 96 h Lepomis macrochirus mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
1,2,4-TRIMETHYLBENZENE 95-63-6	N/A	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
ETHYLBENZENE 100-41-4	1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static 11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

Persistence and degradability
No information available.

Bioaccumulation
No information available.

Chemical Name	Partition coefficient
METHYL AMYL KETONE 110-43-0	1.98
METHYL ACETATE 79-20-9	0.18
ACETYLACETONE 123-54-6	0.34
ETHYLBENZENE 100-41-4	3.118

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste treatment methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

US EPA Waste Number U140 U220 U239 D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE(PURE) 1330-20-7	N/A	Included in waste stream: F039	N/A	U239

ETHYLBENZENE 100-41-4	N/A	Included in waste stream: F039	N/A	N/A

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
METHYL ACETATE 79-20-9	Toxic Ignitable
XYLENE(PURE) 1330-20-7	Toxic Ignitable
ETHYLBENZENE 100-41-4	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN-No	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
Special Provisions	149, B52, IB2, T4, TP1, TP8, TP28
Description	UN1263, Paint, Marine Pollutant, 3, II, RQ
Emergency Response Guide Number	128

TDG

UN-No	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
Description	UN1263, Paint, Marine Pollutant, 3, II

MEX

UN-No	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
Description	UN1263, Paint, 3, II

ICAO

UN-No	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
Special Provisions	A3, A72
Description	UN1263, Paint, 3, II

IATA

UN-No	UN1263
Hazard class	3
Packing Group	II
ERG Code	3L
Special Provisions	A3, A72, A192

IMDG/IMO

UN-No	UN1263
Hazard class	3
Packing Group	II
EmS-No	F-E, S-E
Special Provisions	163, 367

RID

UN-No	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
Classification Code	F1
Description	UN1263, Paint, Environmentally Hazardous, 3, II

ADR/RID

UN-No	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
Classification Code	F1
Tunnel restriction code	(D/E)
Special Provisions	163, 640C, 650, 367
Description	UN1263, Paint, Environmentally Hazardous, 3, II, (D/E)
ADR/RID-Labels	3

ADN

Proper shipping name	Paint
Hazard class	3
Packing Group	II
Classification Code	F1
Special Provisions	163, 640C, 650
Description	UN1263, Paint, Environmentally Hazardous, 3, II
Hazard Labels	3
Limited Quantity (LQ)	5 L
Ventilation	VE01

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	SARA 313 - Threshold Values %
ETHYLBENZENE	100-41-4	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CAA (Clean Air Act)

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants This product contains the following HAPs:

Chemical Name	CAS No	Hazardous air pollutants (HAPs) content
XYLENE(PURE)	1330-20-7	Present
ETHYLBENZENE	100-41-4	Present

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE(PURE)	100 lb	N/A	N/A	X
ETHYLBENZENE	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
XYLENE(PURE)	100 lb	N/A	RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYLBENZENE	1000 lb	N/A	RQ 1000 lb final RQ RQ 454 kg final RQ

State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
TITANIUM DIOXIDE	13463-67-7	Carcinogen
CARBON BLACK	1333-86-4	Carcinogen
ETHYLBENZENE	100-41-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
METHYL AMYL KETONE	X	X	X	N/A	X
TITANIUM DIOXIDE	X	X	X	N/A	X
METHYL ACETATE	X	X	X	N/A	X
ACETYLACETONE	X	X	X	N/A	N/A
XYLENE(PURE)	X	X	X	X	X
CARBON BLACK	X	X	X	X	X
BUTYL ACETATE	X	X	X	N/A	X
ETHYLBENZENE	X	X	X	X	X

International Regulations

Mexico - Grade Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
METHYL AMYL KETONE	N/A	Mexico: TWA 50 ppm Mexico: TWA 235 mg/m^3

		Mexico: STEL 100 ppm Mexico: STEL 465 mg/m³
TITANIUM DIOXIDE	N/A	Mexico: TWA 10 mg/m³ Mexico: STEL 20 mg/m³
METHYL ACETATE	N/A	Mexico: TWA 200 ppm Mexico: TWA 610 mg/m³ Mexico: STEL 250 ppm Mexico: STEL 760 mg/m³
XYLENE(PURE)	N/A	Mexico: TWA 100 ppm Mexico: TWA 435 mg/m³ Mexico: STEL 150 ppm Mexico: STEL 655 mg/m³
CARBON BLACK	N/A	Mexico: TWA 3.5 mg/m³ Mexico: STEL 7 mg/m³
ETHYLBENZENE	N/A	Mexico: TWA 100 ppm Mexico: TWA 435 mg/m³ Mexico: STEL 125 ppm Mexico: STEL 545 mg/m³

16. OTHER INFORMATION

NFPA **Health Hazard** 0 **Flammability** 3 **Instability** 0 **Physical and Chemical Hazards** -

NFPA Rating

HMIS **Health Hazard** 1 * **Flammability** 3 **Physical Hazard** 0 **Personal protection** X

Chronic Hazard Star Legend ** Chronic Health Hazard*

Issuing Date: 22-Dec-2011
Revision Date: 18-Jun-2014
Revision Note
No information available

Disclaimer
The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. 31324APX-T1

end