



# SAFETY DATA SHEET

Issuing Date: 28-Feb-2012

Revision Date: 15-Oct-2013

Revision Number: 1

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: 18773WEP-ZVOC

Product Name: OFF WHITE LOW VOC EPOXY PRIMER

MIL-DTL-53022E, TYPE IV, PART A

Hentzen Coatings, Inc.

Company Phone Number: 1-414-353-4200

6937 West Mill Road, Milwaukee, WI 53218-1225

Emergency telephone number ChemTrec 1-800-424-9300

Recommended use of the chemical and restrictions on use

Industrial paint (Paint or Paint-Related), Restricted to professional users

## 2. HAZARDS IDENTIFICATION

### Classification

#### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin Corrosion/Irritation	Category 2 Sub-category B
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 2
Flammable Liquids	Category 2

### Label Elements

#### Emergency Overview

#### DANGER

#### Hazard Statements

Harmful if swallowed

Harmful in contact with skin

harmful if inhaled

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

Suspected of causing cancer

Highly flammable liquid and vapor



Appearance Opaque

Physical state Liquid

Odor Solvent

#### **Precautionary Statements - Prevention**

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Wash face, hands and any exposed skin thoroughly after handling  
Do not eat, drink or smoke when using this product  
Use only outdoors or in a well-ventilated area  
Do not breathe dust/fume/gas/mist/vapors/spray  
Contaminated work clothing should not be allowed out of the workplace  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed  
Ground/Bond container and receiving equipment  
Use explosion-proof electrical/ ventilating/ lighting/ equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Wear protective gloves/protective clothing/eye protection/face protection

#### **Precautionary Statements - Response**

Immediately call a POISON CENTER or doctor/physician  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
Call a POISON CENTER or doctor/physician if you feel unwell  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
If skin irritation or rash occurs: Get medical advice/attention  
Wash contaminated clothing before reuse  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell  
Rinse mouth  
Do NOT induce vomiting  
In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep cool  
Store in accordance with local regulations

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### **Hazards not otherwise classified (HNOC)**

##### **Other information**

- Harmful to aquatic life with long lasting effects

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### **Contains a known or suspected carcinogen**

This product contains substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. See Section 15 for list of HAPS.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
BARIUM SULFATE	7727-43-7	10% - 20%	TWA: 5 mg/m <sup>3</sup> inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction
BISPHENOL A/ EPICHLOROHYDRIN BASED EPOXY RESIN	25068-38-6	5% - 10%	N/A	N/A
XYLENE(PURE)	1330-20-7	1% - 5%	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>

#### 4. FIRST AID MEASURES

##### First Aid Measures

<b>General advice</b>	Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.
<b>Eye Contact</b>	Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to do, remove contact lenses. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin Contact</b>	Remove and wash contaminated clothing and gloves, including the inside, before re-use. If skin irritation persists, call a physician. Immediate medical attention is not required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
<b>Inhalation</b>	Remove to fresh air. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is irregular or stopped, administer artificial respiration. Consult a physician if necessary. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapors. If symptoms persist, call a physician.
<b>Ingestion</b>	Do NOT induce vomiting. Drink plenty of water. If symptoms persist, call a physician. Rinse mouth. Clean mouth with water and afterwards drink plenty of water. Never give anything by mouth to an unconscious person. Consult a physician if necessary.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Use personal protective equipment as required.
<b>Most important symptoms and effects, both acute and delayed</b>	
<b>Most Important Symptoms and Effects</b>	No information available.
<b>Indication of any immediate medical attention and special treatment needed</b>	
<b>Notes to physician</b>	Treat symptomatically. May cause sensitization of susceptible persons.

#### 5. FIRE-FIGHTING MEASURES

##### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** No information available.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by inhalation and skin contact. Flammable.

##### Explosion Data

**Sensitivity to Mechanical Impact** no data available.

**Sensitivity to Static Discharge** Yes.

##### Protective equipment and precautions for firefighters

Wear self-contained breathing apparatus and protective suit.

#### 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists. Ventilate the area.

### Environmental Precautions

**Environmental Precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

### Methods and materials for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later disposal.

**Methods for Cleaning Up** Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert absorbent material.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use with local exhaust ventilation. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe vapor or mist. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks and flame. Keep containers tightly closed in a cool, well-ventilated place.

**Incompatible Products** None known based on information supplied.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

### Exposure Guidelines

Chemical Name	ACGIH	OSHA	NIOSH IDLH
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
BARIUM SULFATE 7727-43-7	TWA: 5 mg/m <sup>3</sup> inhalable fraction, particulate matter containing no asbestos and <1% crystalline silica	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
BENZENE,1-CHLORO-4 (TRIFLUOROMETHYL) 98-56-6	TWA: 2.5 mg/m <sup>3</sup> F	TWA: 2.5 mg/m <sup>3</sup> F TWA: 2.5 mg/m <sup>3</sup> dust	
TERTIARY BUTYL ACETATE 540-88-5	TWA: 200 ppm	TWA: 200 ppm TWA: 950 mg/m <sup>3</sup>	IDLH: 1500 ppm TWA: 200 ppm TWA: 950 mg/m <sup>3</sup>

TALC (HYDROUS MAGNESIUM SILICATE) 14807-96-6	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup> containing no Asbestos and <1% Quartz respirable dust
XYLENE(PURE) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	

NIOSH IDLH: Immediately Dangerous to Life or Health

### Exposure controls

#### Engineering Measures

Showers  
Eyewash stations  
Ventilation systems.

### Individual protection measures, such as personal protective equipment

#### Eye/Face Protection

Use personal protective equipment as required.

#### Skin and Body Protection

Chemical resistant apron.

#### Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

#### Hygiene Measures

Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	Liquid	<b>Appearance</b>	Opaque
<b>Odor</b>	Solvent.	<b>Odor Threshold</b>	No data available
<b>pH</b>	No data available	<b>Flash Point</b>	40 °F / 4 °C
<b>Decomposition temperature</b>	No data available	<b>Boiling Point</b>	208 °F / 98 °C
<b>Melting Point / Melting Range</b>	No data available	<b>Freezing Point</b>	No data available
<b>Vapor Pressure @20°C (kPa)</b>	No data available	<b>Partition coefficient:</b>	No data available
<b>Vapor Density</b>	No data available	<b>Density</b>	No data available
<b>Bulk density</b>	No data available	<b>Specific Gravity</b>	1.74
<b>Evaporation Rate</b>	No data available	<b>Water solubility</b>	No data available
<b>Dynamic viscosity</b>	No data available	<b>Weight per Gallon (lbs/gal):</b>	14.52
		<b>Flammability Limits in Air</b>	
		Upper	1.68 %
		Lower	0.21 %

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Conditions to Avoid

Extremes of temperature and direct sunlight.

### Incompatible Materials

None known based on information supplied.

### Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	The product has not been tested
<b>Inhalation</b>	There is no data for this product.
<b>Eye Contact</b>	There is no data for this product.
<b>Skin Contact</b>	There is no data for this product.
<b>Ingestion</b>	There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
TITANIUM DIOXIDE 13463-67-7	10000 mg/kg ( Rat )	N/A	N/A
BENZENE,1-CHLORO-4 (TRIFLUOROMETHYL) 98-56-6	13 g/kg ( Rat )	2 mL/kg ( Rabbit )	33 mg/L ( Rat ) 4 h
TERTIARY BUTYL ACETATE 540-88-5	N/A	N/A	2230 mg/m <sup>3</sup> ( Rat ) 4 h
XYLENE(PURE) 1330-20-7	3500 mg/kg ( Rat )	4350 mg/kg ( Rabbit )	29.08 mg/L ( Rat ) 4 h

### Information on toxicological effects

<b>Symptoms</b>	No information available.
-----------------	---------------------------

### Delayed and immediate effects as well as chronic effects from short and long-term exposure

<b>Sensitization</b>	No information available.
<b>MUTAGENIC EFFECTS</b>	No information available.
<b>Carcinogenicity</b>	This product contains one or more substances which are classified by IARC as carcinogenic to humans (Group I), probably carcinogenic to humans (Group 2A) or possibly carcinogenic to humans (Group 2B).

Chemical Name	ACGIH	IARC	NTP	OSHA
TITANIUM DIOXIDE 13463-67-7	N/A	Group 2B	N/A	X
TALC (HYDROUS MAGNESIUM SILICATE) 14807-96-6	N/A	Group 3	N/A	N/A
XYLENE(PURE) 1330-20-7	N/A	Group 3	N/A	N/A

#### Legend:

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

<b>Reproductive Toxicity</b>	No information available.
<b>Specific target organ systemic toxicity (single exposure)</b>	No information available.
<b>Specific target organ systemic toxicity (repeated exposure)</b>	No information available.

**Chronic Toxicity**

Prolonged or repeated exposure increases the risk. Avoid repeated exposure. Repeated contact may cause allergic reactions in very susceptible persons.

**Target Organ Effects**

Central nervous system (CNS), Central Vascular System (CVS), Eyes, Lungs, Respiratory system, Skin.

**Aspiration hazard**

No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1353 mg/kg

ATEmix (dermal) 1946 mg/kg

ATEmix (inhalation-dust/mist) 3.3 mg/l

Oral LD50 22489 mg/kg (rat) Estimated

Dermal LD50 14232 mg/kg (rat) Estimated

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
BENZENE,1-CHLORO-4 (TRIFLUOROMETHYL) 98-56-6	N/A	N/A	3.68: 48 h Daphnia magna mg/L EC50
TERTIARY BUTYL ACETATE 540-88-5	N/A	296 - 362: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
TALC (HYDROUS MAGNESIUM SILICATE) 14807-96-6	N/A	100: 96 h Brachydanio rerio g/L LC50 semi-static	N/A
XYLENE(PURE) 1330-20-7	N/A	30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
XYLENE(PURE) 1330-20-7	3.15

**Other adverse effects**

No information available

## 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

**Waste treatment methods** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**US EPA Waste Number** D001  
U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE(PURE) 1330-20-7	N/A	Included in waste stream: F039	N/A	U239

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
BARIUM SULFATE 7727-43-7	Toxic soluble
XYLENE(PURE) 1330-20-7	Toxic Ignitable

### 14. TRANSPORT INFORMATION

#### DOT

UN-No UN1263  
Proper shipping name Paint  
Hazard class 3  
Packing Group II  
Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28  
Description UN1263, Paint, 3, II, RQ  
Emergency Response Guide Number 128

#### TDG

UN-No UN1263  
Proper shipping name Paint  
Hazard class 3  
Packing Group II  
Description UN1263, Paint, 3, II

#### MEX

UN-No UN1263  
Proper shipping name Paint  
Hazard class 3  
Packing Group II  
Description UN1263, Paint, 3, II

#### ICAO

UN-No UN1263  
Proper shipping name Paint  
Hazard class 3  
Packing Group II  
Special Provisions A3, A72  
Description UN1263, Paint, 3, II

#### ICAO



UN-No	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
Special Provisions	A3, A72
Description	UN1263, Paint, 3, II

#### IMDG/IMO

UN-No	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
EmS-No	F-E, S-E
Special Provisions	163
Description	UN1263, Paint, 3, II

#### RID

UN-No	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
Classification Code	F1
Description	UN1263, Paint, 3, II

#### ADR/RID

UN-No	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
Classification Code	F1
Tunnel restriction code	(D/E)
Special Provisions	163, 640C, 650
Description	UN1263, Paint, 3, II, (D/E)
ADR/RID-Labels	3

#### ADN

Proper shipping name	Paint
Hazard class	3
Packing Group	II
Classification Code	F1
Special Provisions	163, 640C, 650
Description	UN1263, Paint, 3, II
Limited Quantity (LQ)	5 L
Ventilation	VE01

### 15. REGULATORY INFORMATION

#### International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

## **US Federal Regulations**

### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	SARA 313 - Threshold Values %
XYLENE(PURE)	1330-20-7	1.0

### **SARA 311/312 Hazard Categories**

<b>Acute Health Hazard</b>	Yes
<b>Chronic Health Hazard</b>	Yes
<b>Fire Hazard</b>	Yes
<b>Sudden Release of Pressure Hazard</b>	No
<b>Reactive Hazard</b>	No

### **CAA (Clean Air Act)**

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants This product contains the following HAPs:

Chemical Name	CAS No	Hazardous air pollutants (HAPs) content
XYLENE(PURE)	1330-20-7	Present

### **Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TERTIARY BUTYL ACETATE	N/A	N/A	N/A	X
XYLENE(PURE)	100 lb	N/A	N/A	X

### **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
TERTIARY BUTYL ACETATE	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE(PURE)	100 lb	N/A	RQ 100 lb final RQ RQ 45.4 kg final RQ

## **State Regulations**

### **California Proposition 65**

This product does not contain any Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
TITANIUM DIOXIDE	13463-67-7	Carcinogen

ETHYLBENZENE	100-41-4	Carcinogen
QUARTZ CRYSTALLINE SILICA	14808-60-7	Carcinogen

### U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
TITANIUM DIOXIDE	X	X	X	N/A	X
BARIUM SULFATE	X	X	X	N/A	X
BENZENE,1-CHLORO-4 (TRIFLUOROMETHYL)	N/A	X	X	N/A	X
TERTIARY BUTYL ACETATE	X	X	X	N/A	X
TALC (HYDROUS MAGNESIUM SILICATE)	X	X	X	N/A	X
XYLENE(PURE)	X	X	X	X	X
BUTYL ACETATE	X	X	X	N/A	X

### International Regulations

#### Mexico - Grade

Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
TITANIUM DIOXIDE	N/A	Mexico: TWA 10 mg/m <sup>3</sup> Mexico: STEL 20 mg/m <sup>3</sup>
TERTIARY BUTYL ACETATE	N/A	Mexico: TWA 200 ppm Mexico: TWA 950 mg/m <sup>3</sup> Mexico: STEL 250 ppm Mexico: STEL 1190 mg/m <sup>3</sup>
TALC (HYDROUS MAGNESIUM SILICATE)	N/A	Mexico: TWA 2 mg/m <sup>3</sup>
XYLENE(PURE)	N/A	Mexico: TWA 100 ppm Mexico: TWA 435 mg/m <sup>3</sup> Mexico: STEL 150 ppm Mexico: STEL 655 mg/m <sup>3</sup>

## 16. OTHER INFORMATION

#### NFPA


Health Hazard 2

Flammability 3

Instability 0

Physical and Chemical  
Hazards -

#### NFPA Rating



#### HMIS

Health Hazard 1 \* Flammability 3

Physical Hazard 0 Personal protection X

Chronic Hazard Star Legend

\* Chronic Health Hazard

Issuing Date:  
Revision Date:

28-Feb-2012  
15-Oct-2013

---

**Revision Note**

No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**end**