



# SAFETY DATA SHEET

Issuing Date: 08-Mar-2012

Revision Date: 25-Jul-2014

Revision Number: 1

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: 32204KPX-T2

Product Name: 17038 BLACK URETHANE,  
MIL-PRF-85285D(3),TYPE II,CLASS H,PART A

Hentzen Coatings, Inc.  
6937 West Mill Road, Milwaukee, WI 53218-1225

Company Phone Number: 1-414-353-4200

Emergency telephone number ChemTrec 1-800-424-9300

Recommended use of the chemical and restrictions on use Industrial paint (Paint or Paint-Related), Restricted to professional users

## 2. HAZARDS IDENTIFICATION

### Classification

#### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Serious eye damage/eye irritation	Category 2
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2

### Label Elements

#### Emergency Overview

**DANGER**

#### Hazard Statements

harmful if inhaled  
Causes serious eye irritation  
May cause genetic defects  
May cause cancer  
May cause drowsiness or dizziness  
Highly flammable liquid and vapor



**Appearance** Opaque

**Physical state** Liquid

**Odor** Solvent

#### Precautionary Statements - Prevention

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Use personal protective equipment as required  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed  
Ground/Bond container and receiving equipment  
Use explosion-proof electrical/ ventilating/ lighting/ equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Keep cool

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed  
Store in accordance with local regulations

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### **Hazards not otherwise classified (HNOC)**

##### **Other information**

- May be harmful if swallowed

### **3. COMPOSITION/INFORMATION ON INGREDIENTS**

#### **Contains a known or suspected carcinogen**

This product contains substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. See Section 15 for list of HAPS.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
METHYL ACETATE	79-20-9	20% - 30%	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 610 mg/m <sup>3</sup>
METHYL AMYL KETONE	110-43-0	20% - 30%	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>
ACETYLACETONE	123-54-6	1% - 5%	TWA: 25 ppm S*	N/A
CARBON BLACK	1333-86-4	1% - 5%	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m <sup>3</sup>
LIGHT AROMATIC NAPHTHA	64742-95-6	0% - 1%	N/A	N/A
ETHYLBENZENE	100-41-4	0% - 1%	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>

### **4. FIRST AID MEASURES**

#### **First Aid Measures**

##### **General advice**

Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.

##### **Eye Contact**

Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to do, remove contact lenses. Keep eye wide open while rinsing. If symptoms persist, call a physician.

##### **Skin Contact**

Immediate medical attention is not required. Wash off immediately with soap and plenty of

	water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. Consult a physician if necessary. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Immediate medical attention is not required. Move to fresh air in case of accidental inhalation of vapors. If symptoms persist, call a physician.
Ingestion	Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Do NOT induce vomiting. Clean mouth with water and afterwards drink plenty of water. Never give anything by mouth to an unconscious person. Consult a physician if necessary.
Self-protection of the first aider	Remove all sources of ignition. Use personal protective equipment as required.
Most important symptoms and effects, both acute and delayed	
Most Important Symptoms and Effects	No information available.
Indication of any immediate medical attention and special treatment needed	
Notes to physician	Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

### Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable Extinguishing Media** No information available.

### Specific hazards arising from the chemical

Extremely flammable.

#### Explosion Data

**Sensitivity to Mechanical Impact** no data available.

**Sensitivity to Static Discharge** Yes.

### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

**Personal Precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation. Use personal protective equipment as required. Keep people away from and upwind of spill/leak. Avoid breathing vapors or mists. Ventilate the area.

### Environmental Precautions

**Environmental Precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread along floors and form explosive mixtures with air.

### Methods and materials for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for Cleaning Up** Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert

absorbent material.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

#### Advice on safe handling

Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use with local exhaust ventilation. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe vapor or mist. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

### Conditions for safe storage, including any incompatibilities

#### Storage Conditions

Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks and flame.

#### Incompatible Products

None known based on information supplied.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH	OSHA	NIOSH IDLH
METHYL ACETATE 79-20-9	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 610 mg/m <sup>3</sup>	IDLH: 3100 ppm TWA: 200 ppm TWA: 610 mg/m <sup>3</sup> STEL: 250 ppm STEL: 760 mg/m <sup>3</sup>
METHYL AMYL KETONE 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m <sup>3</sup>
ACETYLACETONE 123-54-6	TWA: 25 ppm S*	N/A	
CARBON BLACK 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
XYLENE(PURE) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	
ETHYLBENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

NIOSH IDLH: Immediately Dangerous to Life or Health

### Exposure controls

#### Engineering Measures

Showers  
Eyewash stations  
Ventilation systems.

### Individual protection measures, such as personal protective equipment

#### Eye/Face Protection

Use personal protective equipment as required.

**Skin and Body Protection** Chemical resistant apron.

**Respiratory Protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene Measures** Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	Liquid	<b>Appearance</b>	Opaque
<b>Odor</b>	Solvent.	<b>Odor Threshold</b>	No data available
<b>pH</b>	No data available	<b>Flash Point</b>	14 °F / -10 °C
<b>Decomposition temperature</b>	No data available	<b>Boiling Point</b>	133 °F / 56 °C
<b>Melting Point / Melting Range</b>	No data available	<b>Freezing Point</b>	No data available
<b>Vapor Pressure @20°C (kPa)</b>	No data available	<b>Partition coefficient:</b>	No data available
<b>Vapor Density</b>	No data available	<b>Density</b>	No data available
<b>Bulk density</b>	No data available	<b>Specific Gravity</b>	0.99
<b>Evaporation Rate</b>	No data available	<b>Water solubility</b>	No data available
<b>Dynamic viscosity</b>	No data available	<b>Weight per Gallon (lbs/gal):</b>	8.26
		<b>Flammability Limits in Air</b>	
		<b>Upper</b>	6.99 %
		<b>Lower</b>	1.26 %

## 10. STABILITY AND REACTIVITY

**Reactivity**  
No data available

**Chemical stability**  
Stable under recommended storage conditions.

**Conditions to Avoid**  
Extremes of temperature and direct sunlight.

**Incompatible Materials**  
None known based on information supplied.

**Hazardous Decomposition Products**  
None known based on information supplied.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

<b>Product Information</b>	The product has not been tested
<b>Inhalation</b>	There is no data for this product.
<b>Eye Contact</b>	There is no data for this product.
<b>Skin Contact</b>	There is no data for this product.
<b>Ingestion</b>	There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
METHYL ACETATE 79-20-9	5 g/kg ( Rat )	5 g/kg ( Rabbit )	16000 ppm ( Rat ) 4 h
METHYL AMYL KETONE 110-43-0	1600 mg/kg ( Rat )	12.6 mL/kg ( Rabbit )	2000 ppm ( Rat ) 4 h

ACETYLACETONE 123-54-6	N/A	N/A	1224 ppm ( Rat ) 4 h
CARBON BLACK 1333-86-4	15400 mg/kg ( Rat )	N/A	N/A
XYLENE(PURE) 1330-20-7	3500 mg/kg ( Rat )	4350 mg/kg ( Rabbit )	29.08 mg/L ( Rat ) 4 h
1,2,4-TRIMETHYLBENZENE 95-63-6	3280 mg/kg ( Rat )	3160 mg/kg ( Rabbit )	18 g/m <sup>3</sup> ( Rat ) 4 h
ETHYLBENZENE 100-41-4	3500 mg/kg ( Rat )	15400 mg/kg ( Rabbit )	17.2 mg/L ( Rat ) 4 h

#### Information on toxicological effects

**Symptoms** No information available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Sensitization** No information available.

**MUTAGENIC EFFECTS** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
CARBON BLACK 1333-86-4	A3	Group 2B	N/A	X
XYLENE(PURE) 1330-20-7	N/A	Group 3	N/A	N/A
ETHYLBENZENE 100-41-4	A3	Group 2B	N/A	X

#### Legend:

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Reproductive Toxicity** No information available.

**Specific target organ systemic toxicity (single exposure)** No information available.

**Specific target organ systemic toxicity (repeated exposure)** No information available.

**Chronic Toxicity** Avoid repeated exposure.

**Target Organ Effects** Central nervous system (CNS), Eyes, Lymphatic System, Peripheral Nervous System (PNS), Respiratory system, Skin.

**Aspiration hazard** No information available.

#### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 2198 mg/kg

ATEmix (dermal) 8209 mg/kg

ATEmix (inhalation-dust/mist) 4.6 mg/l

Oral LD50 3388 mg/kg (rat) Estimated

Dermal LD50 12392 mg/kg (rat) Estimated

## 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
METHYL ACETATE 79-20-9	120: 72 h Desmodesmus subspicatus mg/L EC50	295 - 348: 96 h Pimephales promelas mg/L LC50 flow-through 250 - 350: 96 h Brachydanio rerio mg/L LC50 static	1026.7: 48 h Daphnia magna mg/L EC50

METHYL AMYL KETONE 110-43-0	N/A	126 - 137: 96 h Pimephales promelas mg/L LC50 flow-through	N/A
ACETYLACETONE 123-54-6	N/A	98.3 - 110: 96 h Pimephales promelas mg/L LC50 flow-through 50.3 - 71.8: 96 h Lepomis macrochirus mg/L LC50 flow-through 64.1 - 80.1: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	34.4: 48 h Daphnia magna mg/L EC50
XYLENE(PURE) 1330-20-7	N/A	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 19: 96 h Lepomis macrochirus mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
1,2,4-TRIMETHYLBENZENE 95-63-6	N/A	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
ETHYLBENZENE 100-41-4	1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static 11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
METHYL ACETATE 79-20-9	0.18
METHYL AMYL KETONE 110-43-0	1.98
ACETYLACETONE 123-54-6	0.34
ETHYLBENZENE 100-41-4	3.118

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Waste treatment methods**

This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**US EPA Waste Number**

D001  
U140 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
XYLENE(PURE) 1330-20-7	N/A	Included in waste stream: F039	N/A	U239
ETHYLBENZENE 100-41-4	N/A	Included in waste stream: F039	N/A	N/A

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
METHYL ACETATE 79-20-9	Toxic Ignitable
XYLENE(PURE) 1330-20-7	Toxic Ignitable
ETHYLBENZENE 100-41-4	Toxic Ignitable

#### 14. TRANSPORT INFORMATION

##### DOT

UN-No UN1263  
 Proper shipping name Paint  
 Hazard class 3  
 Packing Group II  
 Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28  
 Description UN1263, Paint, Marine Pollutant, 3, II, RQ  
 Emergency Response Guide Number 128

##### TDG

UN-No UN1263  
 Proper shipping name Paint  
 Hazard class 3  
 Packing Group II  
 Description UN1263, Paint, Marine Pollutant, 3, II

##### MEX

UN-No UN1263  
 Proper shipping name Paint  
 Hazard class 3  
 Packing Group II  
 Description UN1263, Paint, 3, II

##### ICAO

UN-No UN1263  
 Proper shipping name Paint  
 Hazard class 3  
 Packing Group II  
 Special Provisions A3, A72  
 Description UN1263, Paint, 3, II

##### IATA

UN-No UN1263  
 Hazard class 3  
 Packing Group II  
 ERG Code 3L  
 Special Provisions A3, A72, A192

##### IMDG/IMO

UN-No UN1263



Hazard class	3
Packing Group	II
EmS-No	F-E, S-E
Special Provisions	163, 367

#### RID

UN-No	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
Classification Code	F1
Description	UN1263, Paint, Environmentally Hazardous, 3, II

#### ADR/RID

UN-No	UN1263
Proper shipping name	Paint
Hazard class	3
Packing Group	II
Classification Code	F1
Tunnel restriction code	(D/E)
Special Provisions	163, 640C, 650, 367
Description	UN1263, Paint, Environmentally Hazardous, 3, II, (D/E)
ADR/RID-Labels	3

#### ADN

Proper shipping name	Paint
Hazard class	3
Packing Group	II
Classification Code	F1
Special Provisions	163, 640C, 650
Description	UN1263, Paint, Environmentally Hazardous, 3, II
Hazard Labels	3
Limited Quantity (LQ)	5 L
Ventilation	VE01

### 15. REGULATORY INFORMATION

#### International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### US Federal Regulations

##### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	SARA 313 - Threshold Values %
ETHYLBENZENE	100-41-4	0.1

#### SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

#### CAA (Clean Air Act)

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants This product contains the following HAPs:

Chemical Name	CAS No	Hazardous air pollutants (HAPs) content
XYLENE(PURE)	1330-20-7	Present
ETHYLBENZENE	100-41-4	Present

#### Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE(PURE)	100 lb	N/A	N/A	X
ETHYLBENZENE	1000 lb	X	X	X

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
XYLENE(PURE)	100 lb	N/A	RQ 100 lb final RQ RQ 45.4 kg final RQ
ETHYLBENZENE	1000 lb	N/A	RQ 1000 lb final RQ RQ 454 kg final RQ

#### State Regulations

##### California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
CARBON BLACK	1333-86-4	Carcinogen
ETHYLBENZENE	100-41-4	Carcinogen

#### U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
METHYL ACETATE	X	X	X	N/A	X
METHYL AMYL KETONE	X	X	X	N/A	X
ACETYLACETONE	X	X	X	N/A	N/A
CARBON BLACK	X	X	X	X	X
XYLENE(PURE)	X	X	X	X	X
BUTYL ACETATE	X	X	X	N/A	X
ETHYLBENZENE	X	X	X	X	X

#### International Regulations

Mexico - Grade

Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
METHYL ACETATE	N/A	Mexico: TWA 200 ppm Mexico: TWA 610 mg/m <sup>3</sup> Mexico: STEL 250 ppm Mexico: STEL 760 mg/m <sup>3</sup>
METHYL AMYL KETONE	N/A	Mexico: TWA 50 ppm Mexico: TWA 235 mg/m <sup>3</sup> Mexico: STEL 100 ppm Mexico: STEL 465 mg/m <sup>3</sup>
CARBON BLACK	N/A	Mexico: TWA 3.5 mg/m <sup>3</sup> Mexico: STEL 7 mg/m <sup>3</sup>
XYLENE(PURE)	N/A	Mexico: TWA 100 ppm Mexico: TWA 435 mg/m <sup>3</sup> Mexico: STEL 150 ppm Mexico: STEL 655 mg/m <sup>3</sup>
ETHYLBENZENE	N/A	Mexico: TWA 100 ppm Mexico: TWA 435 mg/m <sup>3</sup> Mexico: STEL 125 ppm Mexico: STEL 545 mg/m <sup>3</sup>

## 16. OTHER INFORMATION

**NFPA** Health Hazard 0 Flammability 3 Instability 0 Physical and Chemical Hazards -

NFPA Rating



**HMIS** Health Hazard 1 \* Flammability 3 Physical Hazard 0 Personal protection X

Chronic Hazard Star Legend

\* Chronic Health Hazard

Issuing Date: 08-Mar-2012

Revision Date: 25-Jul-2014

Revision Note

No information available

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. 32204KPX-T2

end