

SAFETY DATA SHEET

Issuing Date: 22-Dec-2011 Revision Date: 17-Feb-2015 Revision Number: 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: 16932CMU Product Name: CATALYST FOR WATER REDUCIBLE
MIL-DTL-64159B, TYPE II, PART B

Company Phone Number: 1-414-353-4200

Hentzen Coatings, Inc. 6937 West Mill Road, Milwaukee, WI 53218-1225

Emergency telephone number ChemTrec 1-800-424-9300

Recommended use of the chemical and restrictions on use

Industrial paint (Paint or Paint-Related), Restricted to professional users

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 3
Flammable Liquids	Category 4

Label Elements

Emergency Overview

DANGER

Hazard Statements

Toxic if inhaled Combustible liquid



Appearance Clear Physical state Liquid Odor Solvent

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapors/spray
Use only outdoors or in a well-ventilated area
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Wear protective gloves/protective clothing/eye protection/face protection
Keep cool

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store in accordance with local regulations

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

3. COMPOSITION/INFORMATION ON INGREDIENTS

There are no known carcinogenic chemicals in this product

This product contains substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. See Section 15 for list of HAPS.

Chemical Name	CAS No	Weight-%	ACGIH	OSHA
HOMOPOLYMER OF HEXAMETHYLENE DIISOCYANATE	28182-81-2	70% - 80%	N/A	N/A
HEXAMETHYLENE DIISOCYANATE	822-06-0	0% - 1%	TWA: 0.005 ppm	N/A

4. FIRST AID MEASURES

First Aid Measures

General advice If symptoms persist, call a physician.

Eye Contact Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to

do, remove contact lenses. Keep eye wide open while rinsing. If symptoms persist, call a

Revision Date: 17-Feb-2015

physician.

Skin Contact Wash off immediately with soap and plenty of water. Consult a physician if necessary. IF

ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

Inhalation Immediate medical attention is not required. If symptoms persist, call a physician. Move to

fresh air in case of accidental inhalation of vapors or decomposition products. Asthma-like

and/ or skin allergy-like symptoms.

Ingestion Clean mouth with water and afterwards drink plenty of water. Never give anything by mouth

to an unconscious person. Consult a physician if necessary. Do NOT induce vomiting.

Self-protection of the first aiderUse personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and

No information available.

Effects

Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use:. Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol-resistant foam.

Unsuitable Extinguishing Media No information available.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition. Containers may explode when heated or if contaminated with water.

Explosion Data

Sensitivity to Mechanical Impact no data available.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Pay

attention to flashback. Take precautionary measures against static discharges. Avoid breathing vapors or mists. Ventilate the area. Use personal protective equipment as

required. Remove all sources of ignition.

Other information DECONTAMINATION SOLUTION: Concentrated ammonia (3 - 8%), detergent (2%) and

water (90 - 95%), a solution of Union Carbide's Tergitol TMN-10 (20%) and water (80%) or a solution of 50% isopropanol, 45% water, and 5% concentrated ammonia solution(% by

Revision Date: 17-Feb-2015

weight).

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.

Vapors are heavier than air, spread along floors and form explosive mixtures with air. Do

not flush into surface water or sanitary sewer system.

Methods and materials for containment and cleaning up

Methods for ContainmentDecontaminate floor with decontamination solution letting stand for at least 15 minutes.

Soak up with inert absorbent material.

Methods for Cleaning Up With clean shovel place material into clean, dry container and cover loosely; move

containers from spill area. Do not contaminate ponds, waterways or ditches with chemical or used container. Dam up. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges. Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Avoid contact with skin and eyes. Do not breathe vapor or mist. Use with local exhaust ventilation. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Keep away from heat and sparks - No Smoking. Wear protective gloves/protective clothing/eye protection/face protection. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep containers tightly closed in a cool, well-ventilated place. Keep

in properly labeled containers. Keep away from heat, sparks and flame.

Revision Date: 17-Feb-2015

Incompatible Products Water. Glycol ethers. Alcohols. Epoxies. Bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH	OSHA	NIOSH IDLH
HEXAMETHYLENE DIISOCYANATE 822-06-0	TWA: 0.005 ppm	N/A	Ceiling: 0.020 ppm 10 min Ceiling: 0.140 mg/m³ 10 min TWA: 0.005 ppm TWA: 0.035 mg/m³

NIOSH IDLH: Immediately Dangerous to Life or Health

Exposure controls

Engineering Measures Persons allergic to isocyanates, and particularly those suffering from asthma or other

respiratory conditions, should not work with isocyanates.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Use personal protective equipment as required.

Skin and Body Protection Chemical resistant apron.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

Hygiene Measures Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work

area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state Liquid Appearance Clear

Odor Solvent. **Odor Threshold** No data available pН No data available **Flash Point** 160 °F / 71 °C 378 °F / 192 °C **Decomposition temperature** No data available **Boiling Point** Melting Point / Melting Range No data available **Freezing Point** No data available Vapor Pressure @20°C (kPa) No data available Partition coefficient: No data available **Vapor Density** No data available No data available Density

Bulk density No data available Specific Gravity 1.07

Evaporation Rate No data available Water solubility No data available

Dynamic viscosity No data available **Weight per Gallon (lbs/gal):** 8.95

Flammability Limits in Air

Upper 1.96 % **Lower** 0.17 %

10. STABILITY AND REACTIVITY

16932CMU - CATALYST FOR WATER REDUCIBLE MIL-DTL-64159B, TYPE II, PART B

Revision Date: 17-Feb-2015

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Conditions to Avoid

Heat, flames and sparks.

Incompatible Materials

Water. Glycol ethers. Alcohols. Epoxies. Bases.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information The product has not been tested

Inhalation There is no data for this product.

Eye Contact There is no data for this product.

Skin Contact There is no data for this product.

Ingestion There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
HEXAMETHYLENE DIISOCYANATE	738 mg/kg (Rat)	593 mg/kg(Rabbit)	0.06 mg/L (Rat)4 h
822-06-0			

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

MUTAGENIC EFFECTS No information available.

Legend:

Reproductive Toxicity

Specific target organ systemic

No information available.

No information available.

toxicity (single exposure)

Specific target organ systemic

No information available.

toxicity (repeated exposure)

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (inhalation-dust/mist) 0.5 mg/l

Oral LD50 486743 mg/kg (rat) Estimated Dermal LD50 391109 mg/kg (rat) Estimated

Inhalation LC50 27805 mg/l (mist) (dust) mg/m³ Estimated

Inhalation LC50

Revision Date: 17-Feb-2015

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
HEXAMETHYLENE DIISOCYANATE 822-06-0	N/A	26.1: 96 h Brachydanio rerio mg/L LC50 static	N/A

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste treatment methods Dispose of in accordance with federal, state and local regulations.

US EPA Waste Number No information available

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO Not regulated

ICAO Not regulated

IMDG/IMO Not regulated

RID Not regulated

ADR/RID Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies

16932CMU - CATALYST FOR WATER REDUCIBLE MIL-DTL-64159B, TYPE II, PART B

Revision Date: 17-Feb-2015

ENCS Complies
IECSC Complies
KECL Complies
PICCS Complies
AICS Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	No
Fire Hazard	Yes
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CAA (Clean Air Act)

U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants This product contains the following HAPs:

Chemical Name	CAS No	Hazardous air pollutants (HAPs) content
HEXAMETHYLENE DIISOCYANATE	822-06-0	Present

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
HEXAMETHYLENE DIISOCYANATE	100 lb	N/A	RQ 100 lb final RQ RQ 45.4 kg final RQ

State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

U.S. State Right-to-Know Regulations

Revision Date: 17-Feb-2015

International Regulations

Mexico - Grade Moderate risk, Grade 2

16. OTHER INFORMATION

NFPA Health Hazard 0 Flammability 2 Instability 0 Physical and Chemical Hazards -



HMIS Health Hazard 2 Flammability 2 Physical Hazard 1 Personal protection X

Issuing Date: 22-Dec-2011 **Revision Date:** 17-Feb-2015

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

end