

Date Printed: 8/30/2007

Page: 1

Product Code: AD9318-FD

Product Name: FAST DRY YELLOW EPOXY PRIMER, MIL-PRF-23377J, TYPE I, CLASS C

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

(See top of page)

2. COMPOSITION/INFORMATION ON INGREDIENTS

This product contains one or more reported carcinogens or suspected carcinogens which are noted below and in Section 11.

This product contains a component or components that are Federally classified as a hazardous air pollutant.

Component/Exposure Limits	CAS#	% by Wt.
METHYL AMYL KETONE	110-43-0	21.18
ACGIH TLV/TWA - 50 PPM, 233 MG/M3		
OSHA PEL - 100 PPM, 465 MG/M3		
OTHER LIMITS:		
NIOSH REL: 100 PPM, 465 MG/M3		
BARIUM SULFATE	7727-43-7	10-20%
ACGIH TLV/TWA - 10 MG/M3		
OSHA PEL - 15 MG/M3 (TOTAL DUST)		
OTHER INFORMATION:		
The EPA Delisted Barium Sulfate from SARA 313 per the June 28th, 1994 Federal Register. (59FR33205).		
STRONTIUM CHROMATE	7789-06-02	12.470
ACGIH TLV/TWA : 0.0005 MG/M3 as Cr(VI)		
OSHA PEL : 0.005 MG/M3 as Cr(VI), ACTION LEVEL is 0.0025 MG		
PEL IS THE CEILING LIMIT		
OTHER LIMITS:		
NIOSH REL:TWA 0.001MG/M3 as Cr		
OTHER INFORMATION:		
Hexavalent Chrome is listed as a carcinogen by IARC (Group 1		
See Section 11 for more information.		
Hexavxlent Chrome is Slightly water soluble - 2.4gms/liter		
CONTAINS: 24% Cr(VI)		
ACETONE	67-64-1	6.24
ACGIH TLV/TWA - 500PPM, STEL - 750PPM		
OSHA PEL - 1000PPM		
TITANIUM DIOXIDE	13463-67-7	0-10%
ACGIH TLV/TWA - 10 MG/M3		
OSHA PEL - 15 MG/M3		
OTHER INFORMATION: IARC has listed TiO2 as		
a Group 2B, possibly carcinogenic to humans.		
See Section 11.		
TALC (HYDROUS MAGNESIUM SILICATE)	14807-96-6	4.99
ACGIH TLV/TWA - 2 MG/M3		

Date Printed: 8/30/2007

Page: 2

Product Code: AD9318-FD

Product Name: FAST DRY YELLOW EPOXY PRIMER, MIL-PRF-23377J, TYPE I, CLASS C

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

OSHA PEL - N/A

OTHER INFORMATION

20 MPPFC

AMORPHOUS PRECIPITATED SILICA 112926-00-8 0-10%

ACGIH TLV/TWA - 10 MG/M3 Total dust

OSHA PEL - 6 MG/M3 Total dust

XYLENE(PURE) 1330-20-7 1.28

ACGIH TLV/TWA - 100 PPM, 434 MG/M3; STEL: 150 PPM

OSHA PEL - 100 PPM(TWA), 435 MG/M3(TWA)

OTHER LIMITS:

NIOSH REL: 100 PPM(TWA), 435 MG/M3(TWA)

ETHYLBENZENE 100-41-4 .296

ACGIH TLV/TWA - 100 PPM, 434 MG/M3 STEL: 125PPM

OSHA PEL - 100 PPM, 435 MG/M3

OTHER INFORMATION: Listed by IARC as Group 2B,
possibly carcinogenic to humans. See Section 11.

OTHER LIMITS:

NIOSH REL: 100 PPM(TWA), 435 MG/M3(TWA)

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Harmful if inhaled. May cause the following effects:

Nose, throat and respiratory tract irritation. Allergic respiratory reaction.

May cause lung damage. Eye and skin irritation. Allergic skin reaction.

FLAMMABLE LIQUID

Keep away from heat, sparks, and flame.

Vapors may cause flash fire.

Toxic gases/fumes are given off during burning or thermal decomposition.

EYE CONTACT:

Severe irritant. Prolonged contact may result in chemical
burns to the eyes. Blindness may occur.

SKIN CONTACT:

Severe irritant. Contact with skin causes severe irritation
and pain. Prolonged contact may result in chemical burns.
Product may be absorbed through the skin in harmful amounts.

PRIMARY ROUTES OF ENTRY:

Skin absorption.

Dermal and inhalation.

Date Printed: 8/30/2007

Page: 3

Product Code: AD9318-FD

Product Name: FAST DRY YELLOW EPOXY PRIMER, MIL-PRF-23377J, TYPE I, CLASS C

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

INGESTION:

If swallowed, consult a physician immediately.

INHALATION:

Anesthetic. Can cause irritation of the respiratory tract or acute nervous system depression characterized by the following progressive steps if severe overexposure is continued: headache, dizziness, staggering gait, confusion or unconsciousness.

CHRONIC INFORMATION:

See Section 11.

CARCINOGENICITY:

See Section 11.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:

Asthma and other respiratory ailments; chemical sensitization.

4. FIRST AID MEASURES

EYE CONTACT:

Flush immediately with large amounts of running water for at least 15 minutes while lifting eyelids. Take to a physician for medical treatment.

SKIN CONTACT:

Wash affected areas with soap and water. Remove contaminated clothing and wash before reuse. Consult a physician if irritation develops or persists.

INGESTION:

If swallowed, CALL A PHYSICIAN OR POISON CONTROL CENTER IMMEDIATELY.

INHALATION:

Remove from exposure. Restore breathing. Keep warm and quiet. Notify a physician.

5. FIRE FIGHTING MEASURES

FIRE AND EXPLOSION PROPERTIES:

Date Printed: 8/30/2007

Page: 4

Product Code: AD9318-FD

Product Name: FAST DRY YELLOW EPOXY PRIMER, MIL-PRF-23377J, TYPE I, CLASS C

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

FLASH POINT (deg.F):

-4.0

METHOD:

Tag Closed Cup

FLAMMABLE LIMITS % :

Lower limit: 1.1

Upper limit: 12.8

AUTOIGNITION TEMPERATURE:

N/A

EXTINGUISHING MEDIA:

Carbon Dioxide, Dry Chemical or Foam.

FIREFIGHTING PROCEDURES AND EQUIPMENT:

Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flames. Closed container may explode when exposed to extreme heat. Do not apply to hot surfaces. Never use welding or cutting torch on or near product container (even empty) because product (even residue) can ignite explosively. Full protective equipment including self-contained breathing apparatus should be worn. Water spray may be ineffective. Water may be used to cool closed containers to prevent pressure build-up or possible autoignition or explosion when exposed to extreme heat. If water is used, fog nozzles are preferable.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED :

Evacuate all non-essential personnel and remove all sources of ignition (flames, hot surfaces, electrical, static and frictional sparks). Ventilate area. Equip clean-up crew with appropriate protective equipment. Avoid breathing vapors. Avoid skin contact. Prevent entry into drains, sewers and waterways. Notify appropriate authorities if necessary. Contain and remove with inert absorbent and nonsparking tools.

7. HANDLING AND STORAGE

HANDLING:

Use only with adequate ventilation. Avoid prolonged breathing of vapors. Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application unless air monitoring demonstrates that vapor/

Date Printed: 8/30/2007

Page: 5

Product Code: AD9318-FD

Product Name: FAST DRY YELLOW EPOXY PRIMER, MIL-PRF-23377J, TYPE I, CLASS C

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

mist levels are below applicable exposure limits. Follow respirator manufacturer's directions for use. Use grounding and bonding connection when transferring material to prevent static discharge, fire or explosion. Avoid free fall of liquid in excess of a few inches. Use sparkproof tools and explosion proof equipment.

STORAGE:

Do not store above 120 F or below 32 F. Store large quantities in buildings designed to comply with OSHA's 29 CFR 1910.106. Keep away from heat, sparks and open flame. Keep containers closed when not in use. Keep closures tight and upright to prevent leakage. Emptied containers may retain hazardous residue. Follow all hazard precautions in this data sheet until container is thoroughly cleaned or destroyed. To avoid spontaneous combustion during temporary storage, soak soiled rags and waste immediately after use in a water-filled, closed container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

Provide general dilution or local exhaust ventilation in volume and pattern to keep the air contaminant concentration below current applicable OSHA safety and health requirements in the mixing, application and curing areas; and to remove decomposition products during welding and flame cutting on surfaces coated with this product.

RESPIRATORY PROTECTION:

When spray applied and when used in limited ventilation areas, wear a NIOSH/MSHA approved organic vapor/particulate respirator designed to remove a combination of particulate, gas and vapor. When used in confined areas or poorly ventilated areas, use a NIOSH/MSHA approved air line type respirator or hood. During sanding or grinding operations, use a NIOSH approved particulate respirator to remove solid airborne particles of sanding dust. Use NIOSH approved respirators when flame cutting, welding or hazing material coated with this product. Observe OSHA regulations for respirator use (29 CFR 1910.134). Air monitoring of the workplace may be required to determine appropriate respirator selection.

EYE PROTECTION:

Date Printed: 8/30/2007

Page: 6

Product Code: AD9318-FD

Product Name: FAST DRY YELLOW EPOXY PRIMER, MIL-PRF-23377J, TYPE I, CLASS C

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

Use safety eyewear with splash guards or side shields. A full face shield may be appropriate. Contact lenses should not be worn.

SKIN PROTECTION:

It is good industrial hygiene practice to minimize skin contact. Chemical resistant gloves are required for prolonged or repeated contact. An apron may be appropriate to protect against skin contact. Prevent prolonged skin contact with contaminated clothing. Wash contaminated clothing before reuse.

OTHER PROTECTIVE EQUIPMENT AND GUIDLINES:

Safety showers and eye wash stations should be available. Educate and train employees in the safe use of this product.

9. PHYSICAL AND CHEMICAL PROPERTIES**PHYSICAL STATE:**

Liquid.

APPEARANCE:

Opaque.

ODOR:

Solvent odor.

VOC (LB/GL):

3.17 lb/gl

VOC (grams/liter):

380 g/l

WEIGHT PER GALLON:

12.0332 lb/gl

SPECIFIC GRAVITY:

1.4451

%EXEMPT SOLVENT by WEIGHT:

6.235

%EXEMPT SOLVENT by VOLUME:

11.305

BOILING POINT (deg. F):

133

WATER SOLUBILITY:

Negligible.

FREEZING POINT (deg. F):

N/A

10. STABILITY AND REACTIVITY**STABILITY:**

Date Printed: 8/30/2007

Page: 7

Product Code: AD9318-FD

Product Name: FAST DRY YELLOW EPOXY PRIMER, MIL-PRF-23377J, TYPE I, CLASS C

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

Stable under normal conditions.

HAZARDOUS POLYMERIZATION:

Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS:

May produce hazardous fumes when heated to decomposition as in welding. Fumes may contain the following:
Carbon Monoxide, Carbon Dioxide and other toxic vapors depending upon the temperature reached.

INCOMPATIBILITIES (MATERIALS TO AVOID):

Strong oxidizers.

11. TOXICOLOGICAL INFORMATION

ACUTE EFFECTS:

Xylene (Mixed Isomers):

LD50 Oral Rat = 4300mg/kg

LC50 Inhalation Rat = 6700 ppm for 4 hours

LD50 Dermal Rabbit = >2000mg/kg

Talc:

Rat Inhalation, TC(LO) = 11 mg/cu.m

Rat Dermal, TD(LO) = 200 mg/cu.m

Titanium Dioxide:

Oral ALD Rat = >24,000 mg/kg

Dermal ALD Rabbit = >10,000 mg/m³

Inhalation 4-hour ALC Rat = >6.82 mg/l

Strontium Chromate:

Oral Rat LD50 = 3118 mg/kg

Ethyl Benzene:

Oral Rat LD50 = 3.5 g/kg

Dermal Rabbit LD50 = 17 g/kg

Has not been tested as a whole for acute effects.

CHRONIC EFFECTS:

Reports have associated repeated and prolonged occupational

Date Printed: 8/30/2007

Page: 8

Product Code: AD9318-FD

Product Name: FAST DRY YELLOW EPOXY PRIMER, MIL-PRF-23377J, TYPE I, CLASS C

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

overexposure to solvents with permanent brain and nervous system damage, liver and kidney damage. Long term overexposure effects are not currently known. There are reports that long-term repeated exposure to Xylene may result in some loss of hearing.

Has not been tested as a whole for chronic effects.

CARCINOGENICITY:

Contains Hexavalent Chrome which is listed as a carcinogen by OSHA, NTP and IARC. Hexavalent Chrome may also cause allergic dermatitis and/or nasal irritation. Contains Ethylbenzene which IARC has listed as Group 2B, possibly carcinogenic to humans, based upon laboratory animal studies. IARC has listed titanium dioxide as Group 2B, possible human carcinogen. The listing is based on the opinion by IARC that there is inadequate evidence of carcinogenicity to humans, but there is sufficient evidence of cancer in experimental animals.

Has not been tested as a whole for carcinogenicity effects.

MUTAGENICITY:

This product contains talc, which is a suspected tumorigen. Has not been tested as a whole for mutagenicity effects.

REPRODUCTIVE EFFECTS:

Has not been tested as a whole for reproductive effects.

DEVELOPMENTAL EFFECTS:

Has not been tested as a whole for developmental effects.

12. ECOLOGICAL INFORMATION

ECOLOGICAL EFFECTS:

Has not been tested as a whole for ecological effects.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHODS:

Recycle, fuel blend or incinerate. Dispose of in accordance with applicable laws and regulations. It is the responsibility of the owner of the waste to dispose of it properly. Laboratory analysis is recommended to profile the waste for proper disposal determination.

Date Printed: 8/30/2007

Page: 9

Product Code: AD9318-FD

Product Name: FAST DRY YELLOW EPOXY PRIMER, MIL-PRF-23377J, TYPE I, CLASS C

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

U.S E.P.A WASTE NUMBER AND DESCRIPTION:

D001 Waste Paint

HAZARDOUS WASTE CHARACTERISTICS:

Ignitable.

14. TRANSPORT INFORMATION

UN NUMBER:

UN 1263

DOT PROPER SHIPPING NAME:

Paint

DOT HAZARD CLASS:

3

DOT LABEL:

Flammable Liquid

DOT PACKAGING GROUP:

PG II

U.S POSTAL SERVICE:

Will not handle.

15. REGULATORY INFORMATION

(Not meant to be all inclusive - selected regulations represented)

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:

CAS#100-41-4	Ethyl Benzene
CAS#1330-20-7	Xylene
CAS#7789-06-02	Strontium Chromate
CAS#7440-47-3	Hexavalent Chrome

TSCA STATUS:

All ingredients are listed on the TSCA inventory.

STATE REGULATIONS:

This product may contain chemicals that fall under individual state Right-to-Know regulatory requirements. See Section 2 for material listings. For details on regulatory requirements, contact the

Date Printed: 8/30/2007

Page: 10

Product Code: AD9318-FD

Product Name: FAST DRY YELLOW EPOXY PRIMER, MIL-PRF-23377J, TYPE I, CLASS C

Hentzen Coatings, Inc., 6937 W. Mill Road, Milwaukee, WI 53218-1225

Chemtrec 24-hour Emergency Phone: 800-424-9300

appropriate agency in your state.

16. OTHER INFORMATION

Date of issue: 8/30/2007

Last Revision Date: 01/26/07

HMIS Information

HEALTH: 2

FLAMMABILITY: 3

REACTIVITY: 1

PERSONAL PROTECTIVE EQUIPMENT:

DISCLAIMER:

This MSDS is provided as an informational resource only. The information is received from a combination of sources, including raw material suppliers and is believed to be reliable and accurate. It does not intend to be all-inclusive and shall only be used as a guide. Changing reporting requirements and other uncontrolled variables make it impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to verify its information as well as determine the proper personal protection based on conditions of use. The buyer assumes all responsibility for the use and handling of this product in accordance with the Federal, State and Local laws and regulations. Hentzen Coatings, Inc. makes no representation or warranty regarding the accuracy of this information nor that the information or data will not change.