

SAFETY DATA SHEET

Issuing Date: 22-Dec-2011 Revision Date: 30-Jan-2014 Revision Number: 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Code: 02110GVP Product Name: METAL PRETREATMENT WASH PRIMER

DOD-P-15328D AMEND 1, 1983, PART A

Hentzen Coatings, Inc.

Company Phone Number: 1-414-353-4200

6937 West Mill Road, Milwaukee, WI 53218-1225 Emergency telephone number ChemTrec 1-800-424-9300

Recommended use of the chemical and restrictions on use Industrial paint (Paint or Paint-Related), Restricted to

professional users

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Skin Corrosion/Irritation	Category 2 Sub-category B
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Carcinogenicity	Category 1A
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2

Label Elements

Emergency Overview

DANGER

Hazard Statements

Harmful if swallowed

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

May cause cancer

May cause respiratory irritation. May cause drowsiness or dizziness

Highly flammable liquid and vapor



Appearance Opaque Physical state Liquid Odor Solvent

Revision Date: 30-Jan-2014

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Do not breathe dust/fume/gas/mist/vapors/spray

Contaminated work clothing should not be allowed out of the workplace

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/Bond container and receiving equipment

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Immediately call a POISON CENTER or doctor/physician

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

If skin irritation or rash occurs: Get medical advice/attention

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

Rinse mouth

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Store in accordance with local regulations

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other information

- May be harmful if swallowed
- · Causes mild skin irritation
- Toxic to aquatic life with long lasting effects
- · Toxic to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

Contains a known or suspected carcinogen

This product contains substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990. See Section 15 for list of HAPS.

C	Chemical Name	CAS No	Weight-%	ACGIH	OSHA
ISOP	PROPYL ALCOHOL	67-63-0	50% - 60%	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m³
Bl	JTYL ALCOHOL	71-36-3	10% - 20%	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m ³

			•	
ZINC TETRAOXYCHROMATE	49663-84-5	5% - 10%	N/A	TWA: 5 μg/m ³
				Ceiling: 0.1 mg/m ³ CrO3
				applies to any operations
				or sectors for which the
				Hexavalent Chromium
				standard [29 CFR
				1910.1026] is stayed or is
				otherwise not in effect

4. FIRST AID MEASURES

First Aid Measures

General advice Show this safety data sheet to the doctor in attendance. If symptoms persist, call a

physician.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If

symptoms persist, call a physician. Immediately flush eyes with water for at least 15 minutes. Get medical attention. If easy to do, remove contact lenses. Keep eye wide open

Revision Date: 30-Jan-2014

while rinsing.

Skin Contact Immediate medical attention is not required. Wash off immediately with soap and plenty of

water while removing all contaminated clothes and shoes. If skin irritation persists, call a

physician.

Inhalation If symptoms persist, call a physician. Remove to fresh air. Immediate medical attention is

not required. Move to fresh air in case of accidental inhalation of vapors.

Immediate medical attention is not required. Do NOT induce vomiting. Rinse mouth. Drink

plenty of water. Clean mouth with water and afterwards drink plenty of water. Never give

anything by mouth to an unconscious person. Consult a physician if necessary.

Self-protection of the first aider Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and

Effects

No information available.

Indication of any immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media No information available.

Specific hazards arising from the chemical

Flammable.

Explosion Data

Sensitivity to Mechanical Impact no data available.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation. Use personal protective equipment as required. Keep people away from and

Revision Date: 30-Jan-2014

upwind of spill/leak. Avoid breathing vapors or mists. Ventilate the area.

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do

not flush into surface water or sanitary sewer system. Vapors are heavier than air, spread

along floors and form explosive mixtures with air.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent

material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Soak up with inert

absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation. Keep away from open flames, hot surfaces and sources of

ignition. Take precautionary measures against static discharges. Use explosion-proof electrical (ventilation and lighting) equipment. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use with local exhaust ventilation. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe vapor or mist. To dissipate static electricity during transfer, ground drum and connect to receiving container with bonding strap. Use only non-sparking tools.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep

containers tightly closed in a cool, well-ventilated place. Keep away from heat, sparks and

flame.

Incompatible ProductsNone known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH	OSHA	NIOSH IDLH
ISOPROPYL ALCOHOL	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m ³	TWA: 400 ppm
			TWA: 980 mg/m ³
			STEL: 500 ppm
			STEL: 1225 mg/m ³
BUTYL ALCOHOL	TWA: 20 ppm	TWA: 100 ppm	IDLH: 1400 ppm
71-36-3		TWA: 300 mg/m ³	Ceiling: 50 ppm
			Ceiling: 150 mg/m ³

١	ZINC TETRAOXYCHROMATE	N/A	TWA: 5 µg/m³	IDLH: 15 mg/m ³ Cr(VI)
	49663-84-5	-	Ceiling: 0.1 mg/m ³ CrO3 applies to	o , ,
			any operations or sectors for which	
-			the Hexavalent Chromium standard	
-			[29 CFR 1910.1026] is stayed or is	
			otherwise not in effect	ļ

NIOSH IDLH: Immediately Dangerous to Life or Health

Exposure controls

Engineering Measures Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Use personal protective equipment as required.

Skin and Body Protection Chemical resistant apron.

Respiratory Protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

Revision Date: 30-Jan-2014

provided in accordance with current local regulations.

Hygiene Measures Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work

area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical stateLiquidAppearanceOpaqueOdorSolvent.Odor ThresholdNo data available

No data available 53 °F / 12 °C рH **Flash Point** 177 °F / 81 °C No data available Decomposition temperature **Boiling Point** Melting Point / Melting Range No data available **Freezing Point** No data available Vapor Pressure @20°C (kPa) No data available Partition coefficient: No data available **Density Vapor Density** No data available No data available

Bulk density No data available Specific Gravity 0.89

Evaporation Rate No data available Water solubility No data available

Dynamic viscosity No data available Weight per Gallon (lbs/gal): 7.44

Flammability Limits in Air

Upper 9.09 % **Lower** 1.43 %

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Conditions to Avoid

Extremes of temperature and direct sunlight.

Incompatible Materials

None known based on information supplied.

Revision Date: 30-Jan-2014

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information The product has not been tested

Inhalation There is no data for this product.

Eye Contact There is no data for this product.

Skin Contact There is no data for this product.

Ingestion There is no data for this product.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
ISOPROPYL ALCOHOL 67-63-0	1870 mg/kg (Rat)	4059 mg/kg (Rabbit)	72600 mg/m³(Rat)4 h
BUTYL ALCOHOL 71-36-3	700 mg/kg (Rat)	3402 mg/kg (Rabbit)	8000 ppm (Rat)4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

MUTAGENIC EFFECTS No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
ISOPROPYL ALCOHOL	N/A	Group 1	N/A	X
67-63-0		Group 3		

Legend:

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity
Specific target organ systemic toxicity (single exposure)

No information available. No information available.

Specific target organ systemic toxicity (repeated exposure)

No information available.

oxicity (repeated exposure Chronic Toxicity

Avoid repeated exposure. May cause adverse effects on the bone marrow and

blood-forming system. May cause adverse liver effects.

Target Organ Effects Blood, Central nervous system (CNS), Eyes, Kidney, Liver, Lungs, Respiratory system,

Skin.

Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 1358 mg/kg
ATEmix (dermal) 4001 mg/kg
ATEmix (inhalation-dust/mist) 18103.9 mg/l

Revision Date: 30-Jan-2014

Oral LD504536 mg/kg (rat) EstimatedDermal LD5013480 mg/kg (rat) Estimated

Inhalation LC50 122330 mg/l (mist) (dust) mg/m³ Estimated

Inhalation LC50

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to daphnia and other aquatic invertebrates
ISOPROPYL ALCOHOL 67-63-0	1000: 96 h Desmodesmus subspicatus mg/L EC50 1000: 72 h Desmodesmus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 1400000: 96 h Lepomis macrochirus µg/L LC50 11130: 96 h Pimephales promelas mg/L LC50 static	13299: 48 h Daphnia magna mg/L EC50
BUTYL ALCOHOL 71-36-3	500: 72 h Desmodesmus subspicatus mg/L EC50 500: 96 h Desmodesmus subspicatus mg/L EC50	1730 - 1910: 96 h Pimephales promelas mg/L LC50 static 1740: 96 h Pimephales promelas mg/L LC50 flow-through 100000 - 500000: 96 h Lepomis macrochirus μg/L LC50 static 1910000: 96 h Pimephales promelas μg/L LC50 static	Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
ISOPROPYL ALCOHOL 67-63-0	0.05
BUTYL ALCOHOL 71-36-3	0.785

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste treatment methods This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

US EPA Waste Number U031 D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
BUTYL ALCOHOL	N/A	Included in waste stream:	N/A	U031
71-36-3		F039		

California Hazardous Waste Codes 561

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
ISOPROPYL ALCOHOL	Toxic
67-63-0	Ignitable

Revision Date: 30-Jan-2014

BUTYL ALCOHOL 71-36-3	Toxic
ZINC TETRAOXYCHROMATE	Toxic
49663-84-5	Corrosive
	Ignitable

14. TRANSPORT INFORMATION

DOT

UN-NoUN1263Proper shipping namePaintHazard class3Packing GroupII

Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28

Description UN1263, Paint, 3, II, RQ

Emergency Response Guide

Number

TDG

UN-NoUN1263Proper shipping namePaintHazard class3Packing GroupII

Description UN1263, Paint, 3, II

MEX

UN-NoUN1263Proper shipping namePaintHazard class3Packing GroupII

Description UN1263, Paint, 3, II

ICAO

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II

Special Provisions A3, A72

Description UN1263, Paint, 3, II

ICAO

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Special Provisions A3, A72

Description UN1263, Paint, 3, II

IMDG/IMO

UN-NoUN1263Proper shipping namePaintHazard class3Packing GroupIIEmS-NoF-E, S-ESpecial Provisions163

Revision Date: 30-Jan-2014

Description UN1263, Paint, 3, II

RID

UN-No UN1263
Proper shipping name Paint
Hazard class 3
Packing Group II
Classification Code F1

Description UN1263, Paint, 3, II

ADR/RID

UN-NoUN1263Proper shipping namePaintHazard class3Packing GroupIIClassification CodeF1Tunnel restriction code(D/E)

Special Provisions 163, 640C, 650

Description UN1263, Paint, 3, II, (D/E)

ADR/RID-Labels 3

ADN

Proper shipping namePaintHazard class3Packing GroupIIClassification CodeF1

Special Provisions 163, 640C, 650 **Description** UN1263, Paint, 3, II

Limited Quantity (LQ) 5 L Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies DSL/NDSL Complies **EINECS/ELINCS** Complies Complies **ENCS** Complies **IECSC** Complies **KECL PICCS** Complies **AICS** Complies

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Revision Date: 30-Jan-2014

Chemical Name	CAS No	SARA 313 - Threshold Values %
ISOPROPYL ALCOHOL	67-63-0	1.0
BUTYL ALCOHOL	71-36-3	1.0
ZINC TETRAOXYCHROMATE	49663-84-5	0.1 1.0

SARA 311/312 Hazard Categories

Acute Health Hazard Yes
Chronic Health Hazard No
Fire Hazard Yes
Sudden Release of Pressure Hazard No
Reactive Hazard No

CAA (Clean Air Act)

This product contains the following HAPs:

Chemical Name	CAS No	Hazardous air pollutants (HAPs) content
ZINC TETRAOXYCHROMATE	49663-84-5	Present

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ZINC	N/A	X	N/A	N/A
TETRAOXYCHROMATE				

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ (reportable quantity)
BUTYL ALCOHOL	5000 lb	N/A	RQ 5000 lb final RQ RQ 2270 kg final RQ

State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals

Chemical Name	CAS No	California Proposition 65
ZINC TETRAOXYCHROMATE	49663-84-5	Carcinogen
		Developmental
		Female Reproductive
		Male Reproductive
CARBON BLACK	1333-86-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
ISOPROPYL ALCOHOL	X	X	X	N/A	X
BUTYL ALCOHOL	X	Х	X	N/A	X
ZINC TETRAOXYCHROMATE	N/A	X	Х	Х	N/A

International Regulations

Revision Date: 30-Jan-2014

Mexico - Grade Serious risk, Grade 3

Chemical Name	Carcinogenic Status	Exposure Limits
ISOPROPYL ALCOHOL	N/A	Mexico: TWA 400 ppm
		Mexico: TWA 980 mg/m ³
		Mexico: STEL 500 ppm
		Mexico: STEL 1225 mg/m ³
BUTYL ALCOHOL	N/A	Mexico: Ceiling 50 ppm
		Mexico: Ceiling 150 mg/m ³
ZINC TETRAOXYCHROMATE	A1	Mexico: TWA 0.01 mg/m3 Mexico: TWA 0.5
		mg/m³

16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 3 Instability 0 Physical and Chemical Hazards -



HMIS Health Hazard 2 * Flammability 3 Physical Hazard 0 Personal protection X

Chronic Hazard Star Legend * Chronic Health Hazard

Issuing Date: 22-Dec-2011 **Revision Date:** 30-Jan-2014

Revision Note

No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

end