



Material Safety Data Sheet

10P4-2NF_FR Epoxy Primer Green BAC 452 #719727

Code: 10P4-2NF

Akzo Nobel Coatings Inc. encourages and expects you to read and understand this entire MSDS, as there is important information throughout the document. Further, Akzo Nobel Coatings Inc. expects you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

To promote safe handling, each customer or recipient should: 1) Notify its employees, agents, contractors, and others whom it knows or believes will use this material of the information contained in this MSDS and any other information regarding hazards and safety; 2) Furnish this same information to each of its customers for the product; 3) Request its customers to notify their employees, customers, and other users of the product of this information; and 4) Notify its employees, agents, contractors, and others that the precautions identified for this product and any other products with which mixtures may be created are transferable and cumulative to the mixture.

Section 1. Chemical product and company identification

Manufacturer

Akzo Nobel Coatings, Inc.
1 East Water Street
Waukegan, IL 60085
USA
+1(847) 625-4200

IN CASE OF EMERGENCY (HEALTH OR SPILLS):

CHEMTREC 1 (800) 424-9300 (Inside the US)

CHEMTREC International +1 (703) 527-3887 (Outside the US, collect calls accepted)

Product code : 10P4-2NF

Product name : 10P4-2NF_FR Epoxy Primer Green BAC 452 #719727

Product use : Coatings or Coatings Component

Date of issue : 12-11-2012.

Version : 2

Date of printing : 12-11-2012.

For the most recent update to this Material Safety Data Sheet, visit our website at <http://www.akzonobel.com/aerospace>
For additional information call (847) 625-4200.

Section 2. Hazards identification

Emergency overview

: WARNING!

FLAMMABLE LIQUID AND VAPOR. HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED. CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA. CANCER HAZARD - CONTAINS MATERIAL WHICH CAN CAUSE CANCER. POSSIBLE BIRTH DEFECT HAZARD - CONTAINS MATERIAL WHICH MAY CAUSE BIRTH DEFECTS, BASED ON ANIMAL DATA.

Potential acute health effects

- Inhalation** : Irritating to respiratory system.
- Ingestion** : Toxic if swallowed.
- Skin** : Toxic in contact with skin. Severely irritating to the skin.
- Eyes** : Severely irritating to eyes. Risk of serious damage to eyes.

Potential chronic health effects

Section 2. Hazards identification

Chronic effects	: Contains material that may cause target organ damage, based on animal data.
Carcinogenicity	: Contains material which can cause cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: Contains material which may cause birth defects, based on animal data.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Target organs	: Contains material which may cause damage to the following organs: blood, kidneys, lungs, the nervous system, liver, mucous membranes, spleen, peripheral nervous system, gastrointestinal tract, cardiovascular system, upper respiratory tract, skin, bones, central nervous system (CNS), ears, eye, lens or cornea.

Over-exposure signs/symptoms

Inhalation	: Adverse symptoms may include the following: respiratory tract irritation coughing reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin	: Adverse symptoms may include the following: irritation redness reduced fetal weight increase in fetal deaths skeletal malformations
Eyes	: Adverse symptoms may include the following: pain or irritation watering redness reduced fetal weight increase in fetal deaths skeletal malformations
<u>Medical conditions aggravated by over-exposure</u>	: Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

NOTICE: Reports have associated repeated and prolonged OVEREXPOSURE to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents of this package may be harmful or fatal.

See toxicological information (Section 11)

Section 3. Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>% by weight</u>
butanone	78-93-3	10 - 25
strontium chromate	7789-06-2	5 - 10
4-methylpentan-2-one	108-10-1	5 - 10
Xylene	1330-20-7	5 - 10
talc (non-asbestos form)	14807-96-6	5 - 10
Titanium dioxide	13463-67-7	1 - 5
cyclohexanone	108-94-1	1 - 5
silica, amorphous, fumed	7631-86-9	1 - 5
ethylbenzene	100-41-4	1 - 5

Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Section 4. First aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

Section 5. Fire-fighting measures

- Flammability of the product** : Flammable liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.
- Extinguishing media**
- Suitable** : Use dry chemical, CO₂, water spray (fog) or foam.
- Not suitable** : Do not use water jet.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
- Special remarks on fire hazards** : Not available.
- Special remarks on explosion hazards** : Not available.

Section 6. Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

Section 7. Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use non-sparking tools. Take precautionary measures against electrostatic discharges. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Product name

butanone

Exposure limits

ACGIH TLV (United States, 3/2012).

STEL: 885 mg/m³ 15 minute(s).

STEL: 300 ppm 15 minute(s).

TWA: 590 mg/m³ 8 hour(s).

TWA: 200 ppm 8 hour(s).

NIOSH REL (United States, 6/2009).

STEL: 885 mg/m³ 15 minute(s).

STEL: 300 ppm 15 minute(s).

TWA: 590 mg/m³ 10 hour(s).

TWA: 200 ppm 10 hour(s).

OSHA PEL (United States, 6/2010).

TWA: 590 mg/m³ 8 hour(s).

TWA: 200 ppm 8 hour(s).

strontium chromate

ACGIH TLV (United States, 3/2012).

TWA: 0,0005 mg/m³, (measured as Cr) 8 hour(s).

OSHA PEL Z2 (United States, 11/2006).

CEIL: 1 mg/10m³

OSHA PEL (United States, 6/2010).

TWA: 0,005 mg/m³, (as Cr) 8 hour(s).

NIOSH REL (United States, 6/2009).

TWA: 0,001 mg/m³, (as CR) 10 hour(s).

4-methylpentan-2-one

ACGIH TLV (United States, 3/2012).

STEL: 75 ppm 15 minute(s).

TWA: 20 ppm 8 hour(s).

NIOSH REL (United States, 6/2009).

STEL: 300 mg/m³ 15 minute(s).

STEL: 75 ppm 15 minute(s).

TWA: 205 mg/m³ 10 hour(s).

TWA: 50 ppm 10 hour(s).

OSHA PEL (United States, 6/2010).

TWA: 410 mg/m³ 8 hour(s).

TWA: 100 ppm 8 hour(s).

xylene

ACGIH TLV (United States, 3/2012).

STEL: 651 mg/m³ 15 minute(s).

STEL: 150 ppm 15 minute(s).

TWA: 434 mg/m³ 8 hour(s).

TWA: 100 ppm 8 hour(s).

OSHA PEL (United States, 6/2010).

TWA: 435 mg/m³ 8 hour(s).

TWA: 100 ppm 8 hour(s).

Talc , not containing asbestiform fibres

ACGIH TLV (United States, 3/2012).

TWA: 2 mg/m³ 8 hour(s). Form: Respirable fraction

NIOSH REL (United States, 6/2009).

TWA: 2 mg/m³ 10 hour(s). Form: Respirable fraction

OSHA PEL Z3 (United States, 9/2005).

STEL: 1 f/cc 30 minute(s). Form: not containing asbestos

TWA: 20 mppcf 8 hour(s). Form: not containing asbestos

TWA: 0,1 f/cc 8 hour(s).

STEL: 1 f/cc 30 minute(s).

titanium dioxide

OSHA PEL (United States, 6/2010).

TWA: 15 mg/m³ 8 hour(s). Form: Total dust

ACGIH TLV (United States, 3/2012).

TWA: 10 mg/m³ 8 hour(s).

cyclohexanone

ACGIH TLV (United States, 3/2012). Absorbed through skin.

STEL: 50 ppm 15 minute(s).

TWA: 20 ppm 8 hour(s).

NIOSH REL (United States, 6/2009). Absorbed through skin.

TWA: 100 mg/m³ 10 hour(s).

Section 8. Exposure controls/personal protection

	TWA: 100 mg/m ³ 10 hour(s).
	TWA: 25 ppm 10 hour(s).
	OSHA PEL (United States, 6/2010).
	TWA: 200 mg/m ³ 8 hour(s).
	TWA: 50 ppm 8 hour(s).
silicon dioxide	NIOSH REL (United States, 6/2009).
	TWA: 6 mg/m ³ 10 hour(s).
ethylbenzene	ACGIH TLV (United States, 3/2012).
	TWA: 20 ppm 8 hour(s).
	NIOSH REL (United States, 6/2009).
	STEL: 545 mg/m ³ 15 minute(s).
	STEL: 125 ppm 15 minute(s).
	TWA: 435 mg/m ³ 10 hour(s).
	TWA: 100 ppm 10 hour(s).
	OSHA PEL (United States, 6/2010).
	TWA: 435 mg/m ³ 8 hour(s).
	TWA: 100 ppm 8 hour(s).
crystalline silica respirable	OSHA PEL Z3 (United States, 9/2005).
	TWA: 250 mppcf 8 hour(s). Form: Respirable
	TWA: 10 mg/m ³ 8 hour(s). Form: Respirable
	TWA: 30 mg/m ³ 8 hour(s). Form: Total dust.
	ACGIH TLV (United States, 3/2012).
	TWA: 0,025 mg/m ³ 8 hour(s). Form: Respirable fraction
	NIOSH REL (United States, 6/2009).
	TWA: 0,05 mg/m ³ 10 hour(s). Form: respirable dust

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

Engineering measures : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flatting should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

Personal protection

Respiratory : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Hands : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eyes : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Section 8. Exposure controls/personal protection

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Section 9. Physical and chemical properties

Physical state	: Liquid.
Flash point	: Closed cup: -3,9°C (25°F)
Auto-ignition temperature	: Not available.
upper flammability limit	: Not determined.
Lower flammability limit	: Not determined.
Appearance	: Emerald green.
Odor	: Solvent.
Odor threshold	: Not available.
Specific gravity	: 1,267
pH	: Not available.
Boiling/condensation point	: Not available.
Melting/freezing point	: Not available.
Vapor pressure	: Not available.
Vapor density	: Heavier than air
Density	: 10,57 lbs/gal 1,267 g/cm ³
Evaporation rate	: Not determined.
Coefficient of water/oil distribution	: Not determined.
Weight Volatiles	: 39.98% (w/w)
Volume Volatiles	: 60,98 %(v/v)
Weight Solids	: 60,02 %(w/w)
Volume Solids	: 39,02 %(v/v)
VOC, minus water and exempt solvents	: 4,23 lbs/gal (507 g/l)

Section 10. Stability and reactivity

Stability	: The product is stable.
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.
Conditions to avoid	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
Materials to avoid	: Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose
-------------------------	--------	---------	------

Section 11. Toxicological information

xylene	LD50 Intraperitoneal	Rat	2459 mg/kg
	LD50 Oral	Rat	4300 mg/kg
	LD50 Subcutaneous	Rat	1700 mg/kg
titanium dioxide	TDLo Dermal	Rabbit	4300 mg/kg
	LD Intratracheal	Rat	>100 ug/kg
	TDLo Intratracheal	Rat	5 mg/kg
	TDLo Intratracheal	Rat	1,6 mg/kg
	TDLo Intratracheal	Rat	1,25 mg/kg
butanone	TDLo Oral	Rat	60 g/kg
	LD50 Dermal	Rabbit	6480 mg/kg
	LD50 Intraperitoneal	Rat	607 mg/kg
	LD50 Oral	Rat	2737 mg/kg
strontium chromate	TDLo Intraperitoneal	Rat	361 mg/kg
	LD50 Intratracheal	Rat	16,6 mg/kg
	LD50 Oral	Rat	3118 mg/kg
4-methylpentan-2-one	LD Dermal	Rabbit	>3 g/kg
	LD50 Intraperitoneal	Rat	400 mg/kg
	LD50 Oral	Rat	4600 mg/kg
	LD50 Oral	Rat	2080 mg/kg
cyclohexanone	TDLo Oral	Rat	500 mg/kg
	LD50 Dermal	Rabbit	1 mL/kg
	LD50 Intraperitoneal	Rat	1130 mg/kg
	LD50 Oral	Rat	1800 mg/kg
	LD50 Oral	Rat	1620 uL/kg
	LD50 Subcutaneous	Rat	2170 mg/kg
crystalline silica respirable	LDLo Intravenous	Rat	568 mg/kg
	LDLo Intratracheal	Rat	250 mg/kg
	LDLo Intratracheal	Rat	200 mg/kg
	LDLo Intravenous	Rat	90 mg/kg
	TDLo Intratracheal	Rat	150 mg/kg
	TDLo Intratracheal	Rat	100 mg/kg
	TDLo Intratracheal	Rat	50 mg/kg
	TDLo Intratracheal	Rat	30 mg/kg
	TDLo Intratracheal	Rat	25 mg/kg
	TDLo Intratracheal	Rat	15,69 mg/kg
	TDLo Intratracheal	Rat	10 mg/kg
	TDLo Intratracheal	Rat	5 mg/kg
	TDLo Intratracheal	Rat	1,5 mg/kg
	TDLo Intratracheal	Rat	1 mg/kg
	TDLo Intratracheal	Rat	1250 ug/kg
silicon dioxide	TDLo Oral	Rat	120 g/kg
	LDLo Oral	Rat	5 g/kg
ethylbenzene	TDLo Intratracheal	Rat	1 mg/kg
	LD50 Dermal	Rabbit	>5000 mg/kg
	LD50 Dermal	Rabbit	17800 uL/kg
	LD50 Oral	Rat	3500 mg/kg
	TDLo Dermal	Rat	0,08 mL/kg
	TDLo Intraperitoneal	Rat	1062 mg/kg

Not available.

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
-------------------------	--------	---------	-------	----------	-------------

Section 11. Toxicological information

Talc , not containing asbestiform fibres	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-
xylene	Eyes - Mild irritant	Rabbit	-	87 milligrams	-
	Eyes - Severe irritant	Rabbit	-	24 hours 5 milligrams	-
	Skin - Mild irritant	Rat	-	8 hours 60 microliters	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
	Skin - Moderate irritant	Rabbit	-	100 Percent	-
titanium dioxide	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-
butanone	Skin - Mild irritant	Rabbit	-	24 hours 14 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 milligrams	-
4-methylpentan-2-one	Eyes - Moderate irritant	Rabbit	-	24 hours 100 microliters	-
	Eyes - Severe irritant	Rabbit	-	40 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
cyclohexanone	Eyes - Severe irritant	Rabbit	-	24 hours 250 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	20 milligrams	-
	Skin - Mild irritant	Human	-	48 hours 50 Percent	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
silicon dioxide	Eyes - Mild irritant	Rabbit	-	24 hours 25 milligrams	-
ethylbenzene	Eyes - Severe irritant	Rabbit	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 15 milligrams	-

Carcinogenicity

Not available.

Classification

Product/ingredient name	ACGIH	IARC	EPA	NIOSH	NTP	OSHA
butanone	-	-	-	None.	-	-
strontium chromate	A2	1	-	+	Proven.	+
4-methylpentan-2-one	A3	-	-	None.	-	-
xylene	A4	-	-	None.	-	-
Talc , not containing asbestiform fibres	A4	3	-	-	-	-
titanium dioxide	A4	2B	-	+	-	-
cyclohexanone	A3	3	-	None.	-	-
silicon dioxide	-	3	-	-	-	-
ethylbenzene	A3	2B	-	None.	-	-
crystalline silica respirable	A2	1	-	+	Proven.	-

Mutagenicity

Not available.

Teratogenicity

Conclusion/Summary : Not available.

Section 11. Toxicological information

Reproductive toxicity

Not available.

Section 12. Ecological information

Environmental effects : No known significant effects or critical hazards.

Aquatic ecotoxicity : Not available.

Biodegradability : Not available.

:

Other adverse effects : No known significant effects or critical hazards.

Ecotoxicological data for one or more components are known and will be made available on request.

Section 13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

Section 14. Transport information

The transportation description provided below is based on a one gallon container shipped within the United States, by highway only.

UN number Proper shipping name Class Packing group Additional information

UN1263 PAINT 3 II

Section 15. Other Regulatory Information and Pictograms

United States

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

United States inventory (TSCA 8b) : All components are listed or exempted.

SARA 313

Form R - Reporting requirements

Product name

CAS number

Concentration

butanone

78-93-3

10 - 25

strontium chromate

7789-06-2

5 - 10

4-methylpentan-2-one

108-10-1

5 - 10

xylene

1330-20-7

5 - 10

ethylbenzene

100-41-4

1 - 5

Section 15. Other Regulatory Information and Pictograms

[California Prop. 65](#)

: WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

[Canada](#)

WHMIS (Canada)

- : Class B-2: Flammable liquid
- Class D-1B: Material causing immediate and serious toxic effects (Toxic).
- Class D-2A: Material causing other toxic effects (Very toxic).
- Class D-2B: Material causing other toxic effects (Toxic).



This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

[Canada inventory](#)

: At least one component is not listed in DSL but all such components are listed in NDSL.

[International regulations](#)

International lists

- : **Australia inventory (AICS):** All components are listed or exempted.
- China inventory (IECSC):** All components are listed or exempted.
- Japan inventory:** At least one component is not listed.
- Korea inventory:** At least one component is not listed.
- New Zealand Inventory of Chemicals (NZIoC):** At least one component is not listed.
- Philippines inventory (PICCS):** At least one component is not listed.

Section 16. Other information

Health	*	2
Flammability		3
Physical hazards		0

[Notice to reader](#)

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.