

Carbon Filter Boxes

CFS SERIES

Used for odour abatement.

*Side Panel Not Shown

FEATURES

- Easy to install and maintain
- Galvanized steel housing
- Replaceable pleated carbon filters
- 700 to 5600 CFM range
- Side access door

The Canarm CFS Filter box is designed to improve air quality in a commercial or industrial environment where odour removal is necessary. The replaceable pleated Carbon filters eliminate odours, captures organic and inorganic materials, and removes pathogens from the air stream.

They can be used for intake, exhaust, or recirculation.

PERFORMANCE SPECIFICATIONS

Model #	Description	Recommended Airflow @ 350 FPM	Pressure Drop @ 500 FPM
CFS1-12	Carbon filter section with 1 - 24"x12"x1"	700 CFM	0.48
CFS1-24	Carbon filter section with 1 - 24"x24"x1"	1400 CFM	0.48
CFS2-12	Carbon filter section with 2 - 24"x12"x1"	1400 CFM	0.48
CFS2-24	Carbon filter section with 2 - 24"x24"x1"	2800 CFM	0.48
CFS3-12	Carbon filter section with 3 - 24"x12"x1"	2100 CFM	0.48
CFS3-24	Carbon filter section with 3 - 24"x24"x1"	4200 CFM	0.48
CFS4-12	Carbon filter section with 4 - 24"x12"x1"	2800 CFM	0.48
CFS4-24	Carbon filter section with 4 - 24"x24"x1"	5600 CFM	0.48

Note: Change Filters when static pressure doubles across the filters.

DIMENSIONS

MODEL #	UNIT	OVERALL WIDTH	OVERALL HEIGHT	OVERALL LENGTH	DISCHARGE HEIGHT	DISCHARGE WIDTH
CFS1-12	1 FILTER 24" x 12"	11 5/8"	6 1/4"	24 7/8"	4 3/4"	10 1/8"
CFS1-24	1 FILTER 24" x 24"	23 5/8"	6 1/4"	24 7/8"	4 3/4"	22 1/8"
CFS2-12	2 FILTER 24" x 12"	11 5/8"	11 1/4"	24 7/8"	9 3/4"	10 1/8"
CFS2-24	2 FILTER 24" x 24"	23 5/8"	11 1/4"	24 7/8"	9 3/4"	22 1/8"
CFS3-12	3 FILTER 24" x 12"	11 5/8"	16 3/4"	24 7/8"	15 1/4"	10 1/8"
CFS3-24	3 FILTER 24" x 24"	23 5/8"	16 3/4"	24 7/8"	15 1/4"	22 1/8"
CFS4-12	4 FILTER 24" x 12"	11 5/8"	22 1/4"	24 7/8"	20 3/4"	10 1/8"
CFS4-24	4 FILTER 24" x 24"	23 5/8"	22 1/4"	24 7/8"	20 3/4"	22 1/8"

