



Inline Duct Fans

DFRC-ES SERIES

High efficiency inline duct fans are ideal for residential and commercial ventilation applications such as range hoods, bath fans & dryers.

FEATURING EC MOTORS
- UP TO 70% EFFICIENCY



ENERGY SAVINGS OF UP TO 70% OVER
REGULAR DUTY PSC MOTORS

FEATURES

- Energy efficient and can effectively ventilate meeting rooms, bathrooms and other hard to ventilate areas
- Available in 4", 5", 6", 8", 10" and 12" diameters.
- Powerful, efficient external rotor motor
- Speed controllable with Canarm MC series controls
- Backward curved impeller for high flow against high static pressure
- Remove noise from main living area by mounting remotely as fan can be used to boost airflow in long runs of round duct.
- Quick and easy installation.
- 4", 5" and 6" models sealed for use in radon mitigation systems




DFRC-6ES also
available with carbon
filter option

PERFORMANCE SPECIFICATIONS

MODEL	DIAMETER	POWER RATING (V)	INPUT POWER (W)	ELECTRIC CURRENT (A)	SPEED (RPM)	SOUND LEVEL (dB)	NET WEIGHT	CFM @ STATIC PRESSURE									ENERGY EFFICIENCY (CFM/WATT)
								0.0"	0.2"	0.4"	0.6"	0.8"	1.0"	1.5"	2.2"	2.5"	
DFRC-4ES	4"	120	40	0.35	2912	60	7 lbs	157	135	113	89	67	29	--	--	--	3.2
DFRC-5ES	5"	120	53	0.45	2593	62	7 lbs	202	167	133	107	81	52	21	--	--	3.0
DFRC-6ES	6"	120	74	0.63	2534	61	8 lbs	273	236	198	163	131	92	47	--	--	3.1
DFRC-8ES	8"	120	128	1.19	3158	70	13 lbs	484	457	426	393	350	306	241	89	--	3.5
DFRC-10ES	10"	120	140	1.20	3028	71	13 lbs	598	556	509	460	412	359	260	87	--	3.9
DFRC-12ES	12"	120	203	1.77	2443	70	16 lbs	815	710	579	424	319	263	185	93	62	3.5

DIMENSIONS

MODEL	ØA	ØB	C	D	E	IMPELLER DIAMETER
DFRC-4ES	4"	9 1/2"	5/8"	8 3/8"	5/8"	Ø6 1/8"
DFRC-5ES	5"	9 1/2"	7/8"	7 1/2"	1"	Ø6 7/8"
DFRC-6ES	6"	10 5/8"	3/4"	7 5/8"	5/8"	Ø7 1/2"
DFRC-8ES	8"	13 1/2"	1 1/8"	9"	7/8"	Ø8 5/8"
DFRC-10ES	10"	13 1/2"	1 1/8"	9"	1 1/8"	Ø9 1/2"
DFRC-12ES	12"	15 3/4"	1 1/8"	10 1/4"	1 1/8"	Ø9 7/8"



ACCESSORIES



MOUNTING CLAMPS



BACKDRAFT DAMPERS



EXHAUST & SUPPLY GRILL



MC CONTROLS

