

High Velocity Circulating Fans

HVF SERIES

Effectively cools large areas in factories, stores, offices, restaurants. These fans economically provide relief from summer heat by creating a gentle air movement.



HVFA12 & HVF20G

WALL MOUNT
BRACKET ASSEMBLY



FEATURES

- Painted silver finish.
- 3 speed dial control.
- Sturdy aluminum blades.
- 12", 18" and 20" sizes available.
- Model HVF20G with 5'9" 120V grounded cord set.
- Models HVFA12 & HVF18L with 6' 120V cord with fuse (2 prong).
- Convenient carrying handle.
- Cord wrap on HVF20G model.
- Ergonomic tilt adjustment knobs.
- Complete with wall mount bracket.
- OSHA guard.
- Easy assembly - no tools required.



HVFA12

WALL MOUNT
BRACKET ASSEMBLY



DIMENSIONS

MODEL	BLADE DIAMETER	DESCRIPTION	DIMENSIONS	H.P.	WEIGHT
HVFA12	12"	3 Speed Floor/Table Fan	15 3/4" W x 7 1/2" D x 15" H	1/10	11 lbs
HVF18L	18"	3 Speed Floor/Table Fan	20 5/8" W x 8 1/4" D x 20 1/10" H	1/16	12.3 lbs
HVF20G	20"	3 Speed Floor/Table Fan	23 3/4" W x 10 1/4" D x 23" H	1/4	24 lbs

PERFORMANCE SPECIFICATIONS

MODEL	HIGH SPEED						MEDIUM SPEED						LOW SPEED					
	CFM	AMPS	WATTS	RPM	DB(A)	VELOCITY @ 5ft (FT/MIN)	CFM	AMPS	WATTS	RPM	DB(A)	VELOCITY @ 5ft (FT/MIN)	CFM	AMPS	WATTS	RPM	DB(A)	VELOCITY @ 5ft (FT/MIN)
HVFA12	1,500	0.57	50	1450	48	284	1,200	0.52	42	1275	42	254	800	0.37	30	966	40	191
HVF18L	3,815	0.85	98	1530	58	586	2,828	0.76	80	1360	55	550	2,540	0.57	67	1120	50	480
HVF20G	5160 30.0	1.37	172	1332	62	866	4654 31.0	1.20	150	1187	57	782	4178 32.5	1.03	128	1050	53	675