

High Stand Industrial Mancoolers

MCS, MCSA

Designed to provide cooling effects to large open areas



FEATURES

- Drums and motor supports are constructed of heavy gauge steel.
- TEFC continuous duty, ball bearing motors are standard.
- All models are direct drive and available with steel blades or cast aluminum blades.
- Heavy duty, concentric circle, OSHA wire guards are standard on all sizes.
- Consult factory for availability of explosion-proof motors.
- Casters and lift handle are standard, allowing easy maneuverability.
- Fan flow direction on the tube section can easily be rotated 180°.

OPTIONS

- Junction box installed on the outside of the fan body.



CURRENTLY ONLY AVAILABLE IN CANADA

MCS, MCSA

High Stand Industrial Mancoolers

PERFORMANCE SPECIFICATIONS

MCS STEEL FAN BLADE						
	MODEL		RPM	HP	MCS CFM	dBA @ 5 Ft
	SINGLE PHASE	THREE PHASE				
18"	MCS18T10033C	MCS18T30033C*	1140	1/3	2654	64
	MCS18T10050B	MCS18T30050B*	1750	1/2	4016	74
24"	MCS24T10075C	MCS24T30075C*	1140	3/4	6549	73
	MCS24T10100B	MCS24T30100B*	1750	1	6761	81
30"	MCS24T10300B	MCS24T30300B*	1750	3	9909	84
	--	MCS30T30150C*	1140	1 1/2	11600	79
36"	MCS30T10500B	MCS30T30500B*	1750	5	17552	90
	--	MCS36T30200D*	860	2	16364	80
42"	--	MCS36T30500C*	1140	5	21692	88
	--	MCS42T30500D*	860	5	24499	85
48"	--	MCS42T30500C*	1140	5	23209	88
	--	MCS48T30750D*	860	7 1/2	35654	89
	--	MCS48T30750C*	1140	7 1/2	32563	92


MCSA CAST ALUMINUM BLADE						
	MODEL		RPM	HP	MCSA CFM	dBA @ 5 Ft
	SINGLE PHASE	THREE PHASE				
18"	MCSA18T10033C	MCSA18T30033C*	1140	1/3	2990	60
	MCSA18T10075B	MCSA18T30075B*	1750	3/4	4590	71
24"	MCSA24T10100C	MCSA24T30100C*	1140	1	6520	69
	--	MCSA24T30150B*	1750	1 1/2	7660	72
30"	MCSA24T10300B	MCSA24T30300B*	1750	3	11500	79
	MCSA30T10100C	MCSA30T30100C*	1140	1	8680	69
36"	--	MCSA30T30150C*	1140	1 1/2	11800	73
	MCSA30T10300B	MCSA30T30300B*	1750	3	13300	78
42"	MCSA30T10500B	MCSA30T30500B*	1750	5	18200	82
	--	MCSA36T30200C*	1140	2	14000	76
48"	--	MCSA36T30300C*	1140	3	19400	77
	MCSA36T10500B	MCSA36T30500B*	1750	5	16200	78
54"	--	MCSA36T30750B*	1750	7 1/2	21500	85
	--	MCSA42T30200D*	860	2	19200	73
60"	--	MCSA42T30300D*	860	3	23210	75
	--	MCSA42T30500C*	1140	5	25500	79
66"	--	MCSA42T30750C*	1140	7 1/2	30690	81
	--	MCSA42T31000B*	1750	10	26700	86
72"	--	MCSA48T30500D*	860	5	29820	78
	--	MCSA48T30750D*	860	7 1/2	35700	80
78"	--	MCSA48T31000C*	1140	10	39500	84
	--	MCSA48T31500C*	1140	15	47300	86

For three phase motors, substitute "*" with "M" for 230/460 volt (If 208V required please specify) or "P" for 575 volt
dBA ratings shown are measured at 0" static pressure and should be used as a guideline only.


DIMENSIONS

FAN SIZE	A	B	C	D	E (Tube I.D.)	F
18"	30 1/2"	30 1/4"	58 2/3"	21"	18 3/8"	17 4/7"
24"	36 1/2"	30 1/4"	61 2/3"	21"	24 3/8"	23 4/7"
30"	42 1/2"	30 1/4"	64 2/3"	21"	30 3/8"	29 4/7"
36"	--	--	67 2/3"	27"	36 3/8"	--
42"	--	--	70 2/3"	32"	42 3/8"	--
48"	--	--	73 2/3"	32"	48 3/8"	--

Side View



Front View



Non-stock, made-to-order products are non-returnable and cannot be cancelled.