

Panel Mounted Fans

WITH EC MOTOR

P-EC SERIES

Designed for industrial, commercial & farming applications.

**FEATURING EC MOTORS
- UP TO 70% EFFICIENCY**



**ENERGY SAVINGS OF UP TO 70% OVER
REGULAR DUTY PSC MOTORS**

The P-EC series exhaust fan is a sturdily constructed, direct drive, horizontal discharge fan that is typically used for industrial, commercial and farming applications. The P-EC fans are available variable speed motors.

FEATURES

- Sturdily constructed direct drive, horizontal discharge fan.
- Durable powder coated finish.
- 8" - 24" models have heavy wire chrome plated OSHA guards on intake side of fan.
- 30" & 36" models have grey powder coated guards.
- Totally enclosed air over motor with overload protection.
- Ships fully assembled.
- Fans up to 24" can ship via UPS.

ACCESSORIES

- Front guards
- Wall sleeve
- Thermostats
- Backdraft dampers
- Weather hoods
- Controls

Consult factory to have accessories installed.

PERFORMANCE SPECIFICATIONS

MODEL	SPEED	BLADE DIAMETER	RPM	HP	VOLTAGE	AMPS (FLA)	WEIGHT (LBS)	dB(A) @5 ft	CFM @ STATIC PRESSURE				FRAMING DIMENSIONS
									0.00"	0.10"	0.125"	0.25"	
P08-EC	Variable	8"	1800	1/4	115/208-280	2.8/1.7-1.3	12	48	360	270	230	0	11" X 11"
P10-EC	Variable	10"	1800	1/4	115/208-280	2.8/1.7-1.3	13	56	690	590	570	0	13" X 13"
P12-EC	Variable	12"	1800	1/4	115/208-280	2.8/1.7-1.3	32	60	1650	1540	1510	1390	15" X 15"
P14-EC	Variable	14"	1800	1/4	115/208-280	2.8/1.7-1.3	34	65	2180	2080	2060	1890	17" X 17"
P16-EC	Variable	16"	1800	1/4	115/208-280	2.8/1.7-1.3	36	63	2370	2270	2210	2063	19" X 19"
P18-EC	Variable	18"	1800	1/2	115/208-280	3.5/2.2-1.7	37	73	3200	3090	3040	2920	21" X 21"
P20-EC	Variable	20"	1800	1/2	115/208-280	5.3/3.3-2.6	45	77	3440	3240	3180	2930	23" X 23"
P24-EC	Variable	24"	1200	1/2	115/208-280	5.7/3.5-2.8	56	70	5050	4910	4810	4400	27" X 27"
P30-EC	Variable	30"	1000	3/4	115/208-280	9.5/5.2-4.2	72	82	8000	7000	6000	5000	33" X 33"
P36-EC	Variable	36"	1000	3/4	115/208-280	9.5/5.2-4.2	88	84	10000	8500	8000	6200	39" X 39"

DIMENSIONS

MODEL	A X A SQUARE	B	C c/c
P08	13 3/8"	5 1/4"	12"
P10	15 3/8"	5 1/2"	14"
P12	17 1/4"	11"	16"
P14	19 1/4"	11"	18"
P16	21 1/4"	11"	20"
P18	23 1/4"	11 1/4"	22"
P20	25 1/4"	11 1/4"	24"
P24	29 1/4"	11"	28"
P30	35 1/4"	13 1/4"	34"
P36	41 1/4"	13 1/2"	40"

