

# Panel Mounted Exhaust Fans

## P SERIES

Designed for industrial, commercial & farming applications.



The P series exhaust fan is a sturdily constructed, direct drive, horizontal discharge fan that is typically used for industrial, commercial and farming applications. The P fans are available in single-speed variations as well as two-speed and variable speed models.

### FEATURES


- Sturdily constructed direct drive, horizontal discharge fan.
- Durable powder coated finish.
- 8" - 24" models have heavy wire chrome plated OSHA guards on intake side of fan.
- 30" & 36" models have grey powder coated guards.
- Totally enclosed air over motor with overload protection.
- Ships fully assembled.
- Fans up to 24" can ship via UPS.
- 8 & 10" models feature a cord & plug and pull chain control.



8" & 10" MODEL



P4 SERIES



### ACCESSORIES



- Front guards
- Wall sleeve
- Thermostats
- Backdraft dampers
- Weather hoods
- Controls

# Panel Mounted Exhaust Fans

## DIMENSIONS

| MODEL | A X A<br>SQUARE | B<br>P  | P-4~    | C<br>c/c |
|-------|-----------------|---------|---------|----------|
| P08   | 13 3/8"         | 5 1/4"  | -       | 12"      |
| P10   | 15 3/8"         | 5 1/2"  | -       | 14"      |
| P12   | 17 1/4"         | 11"     | 13 3/4" | 16"      |
| P14   | 19 1/4"         | 11"     | 13 3/4" | 18"      |
| P16   | 21 1/4"         | 11"     | 13 3/4" | 20"      |
| P18   | 23 1/4"         | 11 1/4" | 14"     | 22"      |
| P20   | 25 1/4"         | 11 1/4" | 14"     | 24"      |
| P24   | 29 1/4"         | 11"     | 13 3/4" | 28"      |
| P30   | 35 1/4"         | 13 1/4" | -       | 34"      |
| P36   | 41 1/4"         | 13 1/2" | -       | 40"      |

~EXPLOSION PROOF MOTOR, 50 HZ OR 3 PHASE



## PERFORMANCE SPECIFICATIONS

| SINGLE PHASE | THREE PHASE *** | BLADE DIAMETER | RPM | HP (SINGLE PHASE) | VOLTAGE (SINGLE PHASE) | AMPS (FLA) (SINGLE PHASE) | WEIGHT (LBS) | dB(A) @5 ft | CFM @ STATIC PRESSURE |       |        |       |
|--------------|-----------------|----------------|-----|-------------------|------------------------|---------------------------|--------------|-------------|-----------------------|-------|--------|-------|
|              |                 |                |     |                   |                        |                           |              |             | 0.00"                 | 0.10" | 0.125" | 0.25" |

### SINGLE SPEED - VARIABLE SPEED FANS

|          |        |     |      |      |         |         |    |    |      |      |      |      |
|----------|--------|-----|------|------|---------|---------|----|----|------|------|------|------|
| P12-1V   | P12-1* | 12" | 1700 | 1/3  | 115/230 | 3.8/1.9 | 26 | 63 | 1650 | 1560 | 1525 | 1400 |
| P12-1VHE | --     | 12" | 1450 | 1/15 | 115     | 1.0     | 22 | 60 | 1350 | 1290 | 1275 | 1150 |
| P14-1V   | P14-1* | 14" | 1700 | 1/3  | 115/230 | 3.8/1.9 | 29 | 67 | 2170 | 2030 | 1950 | 1900 |
| P14-1VHE | --     | 14" | 1450 | 1/15 | 115     | 1.0     | 25 | 64 | 1600 | 1525 | 1500 | 1300 |
| P16-1V   | P16-1* | 16" | 1700 | 1/3  | 115/230 | 3.8/1.9 | 30 | 68 | 2570 | 2470 | 2410 | 2260 |
| P16-1VHE | --     | 16" | 1450 | 1/15 | 115     | 1.0     | 26 | 63 | 1850 | 1750 | 1700 | 1550 |
| P18-1V   | P18-1* | 18" | 1700 | 1/3  | 115/230 | 3.8/1.9 | 36 | 71 | 3150 | 3000 | 2900 | 2575 |
| P20-1V   | P20-1* | 20" | 1700 | 1/3  | 115/230 | 3.8/1.9 | 39 | 77 | 3620 | 3420 | 3340 | 3120 |
| P24-1V   | --     | 24" | 1100 | 1/3  | 115/230 | 4.4/2.2 | 43 | 72 | 5500 | 5400 | 5310 | 5100 |
| --       | P24-1* | 24" | 1700 | 1/3  | --      | --      | 57 | 77 | 5520 | 5410 | 5330 | 5130 |

### SINGLE SPEED FANS

|       |          |     |      |     |         |         |    |    |       |      |      |      |
|-------|----------|-----|------|-----|---------|---------|----|----|-------|------|------|------|
| P12-2 | --       | 12" | 1625 | 1/4 | 115     | 2.7     | 27 | 63 | 1640  | 1540 | 1510 | 1390 |
| P14-2 | --       | 14" | 1625 | 1/4 | 115     | 2.7     | 30 | 67 | 2170  | 2070 | 2030 | 1860 |
| P16-2 | --       | 16" | 1625 | 1/4 | 115     | 2.7     | 31 | 68 | 2370  | 2270 | 2210 | 2060 |
| P18-2 | --       | 18" | 1625 | 1/3 | 115     | 4.1     | 37 | 73 | 3200  | 3090 | 3040 | 2920 |
| P20-2 | --       | 20" | 1625 | 1/3 | 115     | 4.1     | 39 | 77 | 3420  | 3220 | 3170 | 2920 |
| P24-2 | --       | 24" | 1100 | 1/3 | 115     | 5.4     | 45 | 70 | 5000  | 4500 | 4300 | 3600 |
| P30-2 | --       | 30" | 1100 | 1/3 | 115/230 | 4.4/2.2 | 72 | 82 | 8000  | 7000 | 6000 | 5000 |
| P36-7 | P36-7M** | 36" | 850  | 1/2 | 115/230 | 6.6/3.3 | 88 | 72 | 10000 | 8500 | 8000 | 6200 |

### TWO SPEED FANS

\*NOTE: 8 & 10" models feature a cord & plug and pull chain control.

|       |    |     |           |     |     |         |    |    |           |           |           |           |
|-------|----|-----|-----------|-----|-----|---------|----|----|-----------|-----------|-----------|-----------|
| *P08  | -- | 8"  | 1600/1300 | 25W | 115 | 0.2     | 14 | 48 | 360/292   | 270/150   | 230/110   | --        |
| *P10  | -- | 10" | 1480/1150 | 60W | 115 | 0.5     | 14 | 55 | 500/388   | 420/300   | 400/250   | --        |
| P12-3 | -- | 12" | 1725/1140 | 1/4 | 115 | 3.4     | 27 | 64 | 1670/1100 | 1600/950  | 1575/900  | 1450/625  |
| P14-3 | -- | 14" | 1725/1140 | 1/4 | 115 | 3.4     | 31 | 67 | 2190/1440 | 2080/1325 | 2000/1300 | 1950/850  |
| P16-3 | -- | 16" | 1725/1140 | 1/4 | 115 | 3.4     | 34 | 69 | 2580/1770 | 2480/1620 | 2430/1560 | 2270/1020 |
| P18-3 | -- | 18" | 1725/1140 | 1/3 | 115 | 5.5/2.9 | 38 | 74 | 3200/2310 | 3050/2030 | 2950/1960 | 2625/1750 |
| P20-3 | -- | 20" | 1725/1140 | 1/3 | 115 | 5.5/2.9 | 41 | 77 | 3640/2420 | 3440/2270 | 3360/2210 | 3140/1890 |

### SINGLE SPEED EXPLOSION PROOF FANS

(Explosion Proof Motors are DIVISION 1 - CLASS 1 - GROUP C & D and CLASS 2 - GROUP F & G)

Class I, Group C - Atmospheres containing ethyl ether, ethylene, gases or vapors of equivalent hazard.

Class I, Group D - Atmospheres such as acetone, ammonia, benzene, butane, cyclopropane, ethanol, gasoline, hexane, methane, natural gas, naphtha, propane, or gases or vapors of equivalent hazard.

Class II Group F - Atmospheres containing carbonaceous dust, including carbon black, charcoal, coal, or coke dusts that have more than 8% total entrapped volatiles, or dusts that have been sensitized by other materials so that they present an explosion hazard.

Class II Group G - Atmospheres containing combustible dusts not included in group E or F, including flour, grain, wood, plastic and chemicals.

|       |        |     |      |     |         |         |    |    |      |      |      |      |
|-------|--------|-----|------|-----|---------|---------|----|----|------|------|------|------|
| P12-4 | P12-4* | 12" | 1725 | 1/3 | 115/230 | 6.6/3.3 | 49 | 63 | 1670 | 1600 | 1575 | 1450 |
| P14-4 | P14-4* | 14" | 1725 | 1/3 | 115/230 | 6.6/3.3 | 49 | 67 | 2190 | 2080 | 2000 | 1950 |
| P16-4 | P16-4* | 16" | 1725 | 1/3 | 115/230 | 6.6/3.3 | 51 | 68 | 2580 | 2480 | 2430 | 2270 |
| P18-4 | P18-4* | 18" | 1725 | 1/3 | 115/230 | 6.6/3.3 | 56 | 73 | 3200 | 3050 | 2950 | 2625 |
| P20-4 | P20-4* | 20" | 1725 | 1/3 | 115/230 | 6.6/3.3 | 57 | 77 | 3640 | 3440 | 3360 | 3140 |
| P24-4 | P24-4* | 24" | 1725 | 1/3 | 115/230 | 6.6/3.3 | 57 | 77 | 5520 | 5410 | 5330 | 5130 |

For three phase motors, substitute "\*" with "M" for 230/460 volt or "P" for 575 volt

\*\*NOTE: P36-7M is only available in 208-230/460 volt for three phase applications

Other voltages in single or three phase are available. 50HZ voltages are available. Consult factory.

\*\*\*These models are not cETLus certified.