

Panel Mounted Supply Fans

P SERIES



Designed for industrial & commercial supply applications.

FEATURES

- Fully assembled.
- Sturdily constructed direct drive, horizontal fan.
- Durable powder coated finish.
- Heavy duty OSHA motor mount/guard is standard.
- Totally enclosed air over motor with overload protection.

ACCESSORIES

- Thermostats
- Front guard
- Weather hoods



P12-1RS9M1115

Fan shown complete with sleeve and motorized damper.

PERFORMANCE SPECIFICATIONS

MODEL	BLADE DIAMETER	RPM	HP	VOLTAGE	AMPS (FLA)	WEIGHT (LBS)	CFM @ STATIC PRESSURE			
							0.00"	0.10"	0.125"	0.25"
P SERIES SUPPLY FAN										
P12-1R	12"	1700	1/3	115/230	3.8/1.9	26	1450	1400	1370	1260
P14-1R	14"	1700	1/3	115/230	3.8/1.9	29	1950	1825	1750	1700
P16-1R	16"	1700	1/3	115/230	3.8/1.9	30	2310	2200	2150	2030
P18-1R	18"	1700	1/3	115/230	3.8/1.9	36	2835	2700	2600	2315
P20-1R	20"	1700	1/3	115/230	3.8/1.9	39	3250	3075	3000	2800
P24-1R	24"	1100	1/3	115/230	6.4/3.2	43	4040	3928	3848	3520
P SERIES SUPPLY FAN										
Complete with 9" sleeve and 120 Volt motorized damper (specs are for fan motor only and not damper motor)										
For exhaust models, replace "1R" in the model name with "1V".										
P12-1RS9M115	12"	1700	1/3	115/230	3.8/1.9	45	1450	1400	1370	1260
P14-1RS9M115	14"	1700	1/3	115/230	3.8/1.9	50	1950	1825	1750	1700
P16-1RS9M115	16"	1700	1/3	115/230	3.8/1.9	54	2310	2200	2150	2030
P18-1RS9M115	18"	1700	1/3	115/230	3.8/1.9	60	2835	2700	2600	2315
P20-1RS9M115	20"	1700	1/3	115/230	3.8/1.9	66	3250	3075	3000	2800
P24-1RS9M115	24"	1100	1/3	115/230	4.4/2.2	73	4040	3928	3848	3520

DIMENSIONS

MODEL	A X A SQUARE	B	C c/c
P12-1R	17 1/4"	11"	16"
P14-1R	19 1/4"	11"	18"
P16-1R	21 1/4"	11"	20"
P18-1R	23 1/4"	12"	22"
P20-1R	25 1/4"	12"	24"
P24-1R	29 1/4"	12"	28"

