

Direct Drive Roof Exhausters

RD SERIES

Sturdy constructed direct drive roof exhausters ideal for industrial & commercial applications.



FEATURES


- Heavy duty galvanized blades.
- Galvanized steel wind-band and rain-proof butterfly dampers that rotate easily on brass bushings.
- TEFC, ball bearing motor is in the air stream, within the building, maximum ambient temperature of 40°C (104°F).
- Not recommended for dirty or dust laden applications.

DISCONNECT SWITCHES

- Wire disconnect switches are available.

ACCESSORIES

RC ROOF CURB



- For Canarm Roof Exhaust fans.
- Sturdy powder coated, 16 gauge steel.
 - 3" flanges
 - 1" SM insulation
 - Damper shelf

FAN SIZE	MODEL
18"	RC18
24"	RC24
30"	RC30
36"	RC36
42"	RC42
48"	RC48
54"	RC54
60"	RC60

RD SERIES


Direct Drive Roof Exhausters

PERFORMANCE SPECIFICATIONS

	MODEL	RPM	HP	0" S.P.				1/8" S.P.				1/4" S.P.				3/8" S.P.				Min. CFM	dBA @ 10Ft.	
				CFM	BHP	FEI	FEP (kW)	CFM	BHP	FEI	FEP (kW)	CFM	BHP	FEI	FEP (kW)	CFM	BHP	FEI	FEP (kW)			
BLADE DIAMETER	SINGLE PHASE																					
	24"	RD24T10075C	1140	3/4	6549	0.74	-	-	6017	0.78	-	-	5527	0.83	-	-	-	-	-	-	4700	73
		RD24T10100B	1725	1	5843	0.71	0.99	0.65	5324	0.75	1.11	0.68	4854	0.80	1.17	0.72	4213	0.85	1.15	0.77	4700	84
	30"	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	
		RD30T10500B	1725	5	14553	3.78	0.46	3.15	14011	3.89	0.56	3.24	13354	4.01	0.64	3.34	12558	4.04	0.70	3.36	7300	90
	THREE PHASE																					
	24"	RD24T30075C*	1140	3/4	6549	0.74	-	-	6017	0.78	-	-	5527	0.83	-	-	-	-	-	-	4700	73
		RD24T30100B*	1725	1	5843	0.71	1.02	0.63	5324	0.75	1.15	0.66	4854	0.80	1.21	0.70	4213	0.85	1.19	0.74	4700	84
	30"	RD30T30150C*	1140	1 1/2	9402	1.22	0.95	1.05	8542	1.29	1.06	1.10	6945	1.27	1.09	1.09	6129	1.38	1.05	1.18		79
		RD30T30500B*	1725	5	14553	3.78	0.47	3.13	14011	3.89	0.56	3.22	13354	4.01	0.64	3.32	12558	4.04	0.71	3.35		90
36"	RD36T30200D*	860	2	13604	1.61	0.91	1.48	11909	1.66	1.01	1.53	10082	1.72	1.03	1.58	8991	1.90	0.99	1.74	10000	80	
	RD36T30500C*	1140	5	18126	3.79	0.55	3.15	16925	3.87	0.66	3.21	15431	3.90	0.74	3.24	13982	3.94	0.79	3.27	10000	88	
42"	RD42T30500C*	1140	5	21704	3.13	0.79	2.61	20742	3.28	0.94	2.73	19510	3.47	1.03	2.89	18192	3.69	1.07	3.07	14000	85	
	RD42T30750C*	1140	7 1/2	32476	7.70	-	-	31490	7.70	-	-	30518	7.76	-	-	29586	8.02	-	-	14000	88	
48"	RD48T30750D*	860	7 1/2	35654	5.93	-	-	33411	6.06	-	-	31857	6.34	-	-	30219	6.62	-	-	18000	89	
	RD48T30750C*	1140	7 1/2	29216	4.62	0.72	3.79	28169	4.87	0.85	3.98	26784	5.16	0.95	4.22	25291	5.48	1.00	4.47	18000	92	

For three phase motors, substitute "*" with "M" for 230/460 volt (If 208V required please specify) or "P" for 575 volt. BHP does not include drive losses. dBA ratings shown are measured at 0" static pressure and should be used as a guideline only.

DIMENSIONS



MODEL #	A I.D.	B O.D.	C SQ.	D
RD24	25"	31 1/2"	29 1/2"	19"
RD30	31"	37 1/2"	35 1/2"	22"
RD36	37"	43 1/2"	41 1/2"	25"
RD42	43"	49 1/2"	47 1/2"	27"
RD48	49"	55 1/2"	53 1/2"	30"