

# Belt Drive Roof Exhausters

## RTA SERIES

Belt drive, heavy duty construction ideal for industrial & commercial applications.

### FEATURES

- TEFC, ball bearing motor is out of air stream and is accessible from the roof, maximum ambient temperature of 40° C (104° F).
  - Galvanized steel wind-band and rain-proof butterfly dampers.
  - Cast iron pillow block bearings (out of air stream), complete with external grease fittings.
  - Cast aluminum blades on 12" to 48" sizes.
  - Polypropylene blades reinforced with fiberglass on 54" to 60" sizes.
  - Heavy duty pulleys and belts out of air stream.
- Roof Exhausters are non-stock items and are non-cancelable and non-refundable without prior authorization.*

### DISCONNECT SWITCHES


- Wire disconnect switches are available. See Controls & Thermostats section for details.

### ACCESSORIES


#### RC ROOF CURB

- For Canarm Roof Exhaust fans.
- Sturdy powder coated, 16 gauge steel.
- 3" flanges
- 1" SM insulation
- Damper shelf

| FAN SIZE | MODEL |
|----------|-------|
| 18"      | RC18  |
| 24"      | RC24  |
| 30"      | RC30  |
| 36"      | RC36  |
| 42"      | RC42  |
| 48"      | RC48  |
| 54"      | RC54  |
| 60"      | RC60  |



### DIMENSIONS



| MODEL | A Dia.  | B Dia.  | C Sq. | D      | E | F  | G  |
|-------|---------|---------|-------|--------|---|----|----|
| RTA18 | 18 3/8" | 24 5/8" | 24"   | 2 1/2" | 2 | 17 | 18 |
| RTA24 | 24 3/8" | 30 5/8" | 30"   | 2 1/2" | 2 | 19 | 21 |
| RTA30 | 30 3/8" | 36 5/8" | 36"   | 2 1/2" | 2 | 23 | 21 |
| RTA36 | 36 3/8" | 42 5/8" | 42"   | 2 1/2" | 2 | 25 | 27 |
| RTA42 | 42 3/8" | 48 5/8" | 48"   | 2 1/2" | 2 | 27 | 27 |
| RTA48 | 48 1/2" | 54 5/8" | 54"   | 2 1/2" | 2 | 30 | 31 |
| RTA54 | 54 1/2" | 60 5/8" | 60"   | 2 1/2" | 2 | 36 | 40 |
| RTA60 | 60 1/2" | 66 5/8" | 68"   | 2 1/2" | 2 | 36 | 40 |

# Belt Drive Roof Exhausters

## PERFORMANCE SPECIFICATIONS

RTA model suitable for use in clean, dry air with a maximum ambient temperature of 93° C (200° F).

RWTA models are suitable for use in moisture laden air with a maximum ambient temperature of 93° C (200° F). They feature a Teflon shaft seal, poly housing bearings and stainless steel insert.

| MODEL # |              | CFM @ STATIC PRESSURE |       |         |             |       |      |      |             |       |      |      |             |       |      |      |             |       |      |      |             |       |      |      |             |       |      |      |             |
|---------|--------------|-----------------------|-------|---------|-------------|-------|------|------|-------------|-------|------|------|-------------|-------|------|------|-------------|-------|------|------|-------------|-------|------|------|-------------|-------|------|------|-------------|
|         |              | RPM                   | HP    | MIN CFM | dBA @ 10 ft | 0"    |      |      |             | 1/8"  |      |      |             | 1/4"  |      |      |             | 1/2"  |      |      |             | 3/4"  |      |      |             | 1"    |      |      |             |
|         |              |                       |       |         |             | CFM   | BHP  | FEI  | FEPAct (kW) | CFM   | BHP  | FEI  | FEPAct (kW) | CFM   | BHP  | FEI  | FEPAct (kW) | CFM   | BHP  | FEI  | FEPAct (kW) | CFM   | BHP  | FEI  | FEPAct (kW) | CFM   | BHP  | FEI  | FEPAct (kW) |
| 18"     | RTA18T10075A | 1556                  | 3/4   | 2600    | 59          | 2794  | 0.45 | -    | -           | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    | -    |             |
|         | RTA18T10075B | 1785                  | 3/4   | 2600    | 62          | 3203  | 0.68 | -    | -           | 2976  | 0.72 | -    | -           | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    |      |             |
|         | RTA18T10100  | 1920                  | 1     | 2600    | 64          | 3449  | 0.85 | 0.51 | 0.84        | 3244  | 0.89 | 0.59 | 0.88        | 2815  | 0.85 | 0.65 | 0.84        | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    |      |             |
|         | RTA18T10150  | 2255                  | 1 1/2 | 2600    | 68          | 4043  | 1.38 | 0.37 | 1.31        | 3901  | 1.43 | 0.44 | 1.36        | 3653  | 1.45 | 0.50 | 1.37        | 2863  | 1.30 | 0.60 | 1.24        | -     | -    | -    | -           | -     | -    |      |             |
|         | RTA18T10200  | 2510                  | 2     | 2600    | 72          | 4508  | 1.90 | 0.30 | 1.76        | 4368  | 1.95 | 0.37 | 1.80        | 4175  | 1.99 | 0.42 | 1.84        | 3483  | 1.84 | 0.51 | 1.71        | 2897  | 1.92 | 0.53 | 1.92        | -     | -    |      |             |
|         | RTA24T10075  | 1180                  | 3/4   | 4700    | 58          | 5095  | 0.51 | -    | -           | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    |      |             |
|         | RTA24T10100  | 1295                  | 1     | 4700    | 61          | 5582  | 0.68 | 0.91 | 0.69        | 5094  | 0.71 | 1.03 | 0.72        | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    | -    | -           | -     |      |      |             |
|         | RTA24T10150  | 1475                  | 1 1/2 | 4700    | 65          | 6371  | 1.00 | 0.72 | 0.98        | 5969  | 1.04 | 0.84 | 1.02        | 5418  | 1.05 | 0.93 | 1.03        | -     | -    | -    | -           | -     | -    | -    | -           | -     |      |      |             |
|         | RTA24T10200  | 1620                  | 2     | 4700    | 67          | 6976  | 1.32 | 0.61 | 1.26        | 6638  | 1.37 | 0.72 | 1.30        | 6164  | 1.39 | 0.81 | 1.32        | 4848  | 1.35 | 0.90 | 1.29        | -     | -    | -    | -           | -     |      |      |             |
|         | RTA24T10300  | 1890                  | 3     | 4700    | 72          | 8178  | 2.19 | 0.44 | 2.01        | 7910  | 2.17 | 0.55 | 1.99        | 7486  | 2.19 | 0.63 | 2.01        | 6579  | 2.20 | 0.75 | 2.02        | 5165  | 2.11 | 0.79 | 1.94        | -     | -    |      |             |
| 24"     | RTA30T10100  | 965                   | 1     | 7300    | 59          | 8874  | 0.88 | 1.08 | 0.87        | 7942  | 0.94 | 1.18 | 0.93        | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    |      |             |
|         | RTA30T10150  | 1095                  | 1 1/2 | 7300    | 62          | 10068 | 1.29 | 0.85 | 1.23        | 9266  | 1.36 | 0.97 | 1.30        | 8240  | 1.36 | 1.06 | 1.30        | -     | -    | -    | -           | -     | -    | -    | -           | -     |      |      |             |
|         | RTA30T10200  | 1225                  | 2     | 7300    | 65          | 11270 | 1.80 | 0.70 | 1.68        | 10618 | 1.87 | 0.82 | 1.74        | 9723  | 1.91 | 0.90 | 1.77        | -     | -    | -    | -           | -     | -    | -    | -           |       |      |      |             |
|         | RTA30T10300  | 1380                  | 3     | 7300    | 67          | 12727 | 2.58 | 0.56 | 2.34        | 12106 | 2.66 | 0.66 | 2.41        | 11388 | 2.72 | 0.75 | 2.46        | 9483  | 2.67 | 0.87 | 2.42        | -     | -    | -    | -           |       |      |      |             |
|         | RTA30T10500  | 1635                  | 5     | 7300    | 72          | 15033 | 4.31 | 0.40 | 3.80        | 14626 | 4.43 | 0.49 | 3.90        | 13989 | 4.48 | 0.56 | 3.94        | 12654 | 4.54 | 0.69 | 3.99        | 10756 | 4.40 | 0.77 | 3.87        | 7922  | 4.21 | 0.73 | 3.71        |
|         | RTA36T10200  | 910                   | 2     | 10000   | 63          | 14346 | 1.67 | 0.93 | 1.56        | 13047 | 1.72 | 1.06 | 1.61        | 11483 | 1.72 | 1.15 | 1.61        | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    |      |             |
|         | RTA36T10300  | 1045                  | 3     | 10000   | 66          | 16498 | 2.53 | 0.71 | 2.30        | 15381 | 2.59 | 0.84 | 2.35        | 14076 | 2.62 | 0.94 | 2.37        | 10528 | 2.44 | 1.04 | 2.22        | -     | -    | -    | -           | -     | -    |      |             |
|         | RTA36T10500  | 1245                  | 5     | 10000   | 71          | 19661 | 4.28 | 0.51 | 3.77        | 18751 | 4.36 | 0.62 | 3.84        | 17655 | 4.40 | 0.71 | 3.87        | 15341 | 4.40 | 0.85 | 3.87        | 10821 | 3.97 | 0.85 | 3.51        | -     | -    |      |             |
|         | RTA36T10750  | 1425                  | 7 1/2 | 10000   | 75          | 22467 | 6.42 | 0.39 | 5.56        | 21719 | 6.51 | 0.48 | 5.63        | 20850 | 6.58 | 0.56 | 5.69        | 18910 | 6.61 | 0.70 | 5.72        | 16624 | 6.49 | 0.79 | 5.62        | 11635 | 5.92 | 0.62 | 5.14        |
|         | RTA42T10200  | 770                   | 2     | 14000   | 61          | 18272 | 1.60 | 1.20 | 1.50        | 16358 | 1.68 | 1.33 | 1.57        | 14045 | 1.69 | 1.41 | 1.58        | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    |      |             |
| 42"     | RTA42T10300  | 895                   | 3     | 14000   | 65          | 21244 | 2.50 | 0.91 | 2.27        | 19639 | 2.61 | 1.05 | 2.37        | 17776 | 2.64 | 1.16 | 2.39        | 11631 | 2.41 | 1.15 | 2.20        | -     | -    | -    | -           | -     | -    |      |             |
|         | RTA42T10500  | 1005                  | 5     | 14000   | 67          | 23874 | 3.55 | 0.73 | 3.16        | 22458 | 3.67 | 0.86 | 3.26        | 20848 | 3.75 | 0.96 | 3.33        | 17008 | 3.69 | 1.10 | 3.28        | -     | -    | -    | -           | -     | -    |      |             |
|         | RTA42T10750  | 1205                  | 7 1/2 | 14000   | 72          | 28574 | 6.14 | 0.51 | 5.33        | 27469 | 6.28 | 0.62 | 5.44        | 26215 | 6.39 | 0.72 | 5.53        | 23360 | 6.47 | 0.87 | 5.60        | 19760 | 6.32 | 0.96 | 5.48        | -     | -    |      |             |
|         | RTA48T1000   | 1335                  | 10    | 14000   | 75          | 31680 | 8.34 | 0.42 | 7.15        | 30684 | 8.50 | 0.52 | 7.28        | 29494 | 8.60 | 0.60 | 7.37        | 27123 | 8.81 | 0.74 | 7.54        | 24259 | 8.76 | 0.85 | 7.50        | 20471 | 8.37 | 0.91 | 7.18        |
|         | RTA48T10300  | 670                   | 3     | 18000   | 63          | 24932 | 2.77 | 0.96 | 2.50        | 22900 | 2.11 | 1.47 | 1.94        | 19736 | 2.87 | 1.18 | 2.59        | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    |      |             |
|         | RTA48T10500  | 790                   | 5     | 18000   | 67          | 29538 | 4.54 | 0.70 | 3.99        | 27800 | 4.66 | 0.84 | 4.09        | 25504 | 4.72 | 0.94 | 4.14        | 21029 | 4.68 | 1.07 | 4.11        | -     | -    | -    | -           | -     | -    |      |             |
|         | RTA48T10750  | 900                   | 7 1/2 | 18000   | 71          | 33386 | 6.70 | 0.54 | 5.79        | 32200 | 6.85 | 0.67 | 5.92        | 30303 | 6.93 | 0.76 | 5.98        | 25877 | 6.96 | 0.89 | 6.01        | -     | -    | -    | -           | -     | -    |      |             |
|         | RTA48T11000  | 990                   | 10    | 18000   | 73          | 36822 | 8.88 | 0.45 | 7.60        | 35700 | 9.08 | 0.50 | 7.75        | 34056 | 9.15 | 0.65 | 7.82        | 29829 | 9.33 | 0.77 | 7.97        | 26410 | 9.21 | 0.88 | 7.87        | -     | -    |      |             |
|         | RTA54T10500  | 710                   | 5     | 23000   | 68          | 37130 | 4.26 | -    | -           | 34615 | 4.46 | -    | -           | 31680 | 4.67 | -    | -           | -     | -    | -    | -           | -     | -    | -    | -           | -     | -    |      |             |
|         | RTA54T10750  | 810                   | 7 1/2 | 23000   | 71          | 42890 | 6.20 | -    | -           | 41128 | 6.50 | -    | -           | 38660 | 6.85 | -    | -           | 33210 | 6.99 | -    | -           | 25390 | 6.87 | -    | -           | -     | -    |      |             |
| 54"     | RTA54T11000  | 905                   | 10    | 23000   | 74          | 48450 | 8.54 | -    | -           | 46911 | 8.94 | -    | -           | 44640 | 9.41 | -    | -           | 40140 | 9.73 | -    | -           | 34980 | 9.78 | -    | -           | 27220 | 9.53 | -    |             |
|         | RTA60T10750  | 690                   | 7 1/2 | 29000   | 68          | 51240 | 6.45 | -    | -           | 49020 | 6.85 | -    | -           | 45760 | 7.18 | -    | -           | 35770 | 7.09 | -    | -           | -     | -    | -    | -           | -     | -    |      |             |
|         | RTA60T11000  | 755                   | 10    | 29000   | 70          | 56770 | 8.48 | -    | -           | 54440 | 8.88 | -    | -           | 51490 | 9.21 | -    | -           | 40470 | 9.43 | -    | -           | 31650 | 8.72 | -    | -           | -     | -    |      |             |
|         | RTA60T11000  | 755                   | 10    | 29000   | 70          | 56770 | 8.48 | -    | -           | 54440 | 8.88 | -    | -           | 51490 | 9.21 | -    | -           | 40470 | 9.43 | -    | -           | 31650 | 8.72 | -    | -           | -     | -    |      |             |
|         | RTA60T11000  | 755                   | 10    | 29000   | 70          | 56770 | 8.48 | -    | -           | 54440 | 8.88 | -    | -           | 51490 | 9.21 | -    | -           | 40470 | 9.43 | -    | -           | 31650 | 8.72 | -    | -           | -     | -    |      |             |
|         | RTA60T11000  | 755                   | 10    | 29000   | 70          | 56770 | 8.48 | -    | -           | 54440 | 8.88 | -    | -           | 51490 | 9.21 | -    | -           | 40470 | 9.43 | -    | -           | 31650 | 8.72 | -    | -           | -     | -    |      |             |
|         | RTA60T11000  | 755                   | 10    | 29000   | 70          | 56770 | 8.48 | -    | -           | 54440 | 8.88 | -    | -           | 51490 | 9.21 | -    | -           | 40470 | 9.43 | -    | -           | 31650 | 8.72 | -    | -           | -     | -    |      |             |
|         | RTA60T11000  | 755                   | 10    | 29000   | 70          | 56770 | 8.48 | -    | -           | 54440 | 8.88 | -    | -           | 51490 | 9.21 | -    | -           | 40470 | 9.43 | -    | -           | 31650 | 8.72 | -    | -           | -     | -    |      |             |
|         | RTA60T11000  | 755                   | 10    | 29000   | 70          | 56770 | 8.48 | -    | -           | 54440 | 8.88 | -    | -           | 51490 | 9.21 | -    | -           | 40470 | 9.43 | -    | -           | 31650 | 8.72 | -    | -           | -     | -    |      |             |
|         | RTA60T11000  | 755                   | 10    | 29000   | 70          | 56770 | 8.48 | -    | -           | 54440 | 8.88 | -    | -           | 51490 | 9.21 | -    | -           | 40470 | 9.43 | -    | -           | 31650 | 8.72 | -    | -           | -     | -    |      |             |