



Steel Control Dampers

SCD Standard

The **SCD** series control dampers have been designed and tested to provide a reliable cost effective control damper where tight sealing is NOT of primary importance (for tight sealing dampers, use model SCD-LL). Its design lets it to be used in either exhaust or intake applications.

FEATURES

- **FRAME:** roll-formed galvanized steel hat section with staked corners with integral bracing.
SCD-LL-HD Also includes roll-formed galvanized steel C channel insert welded to provide equivalent of 12 gauge steel.
- **BLADE:** 16-18 gauge triple-vee profile roll-formed galvanized steel. Minimum width: 4.25". Maximum width: 7.25". Opposed blades are standard (for parallel, please specify). **SCD-LL-HD** 16 gauge roll-formed galvanized steel & 18 gauge roll-formed galvanized steel continuous rigidizing section to provide equivalent of 10 gauge steel.
- **BEARINGS:** bronze oilite, press fit into frame
- **AXLES:** square, plated steel PVC
- **LINKAGES:** concealed in frame. **SCD, SCD-LL-HD** Leakage bars are 12 gauge thick galvanized steel.
SCD-LL Leakage bars are .125" thick plated steel.
- **FINISH:** mill galvanized
- **EXTENDED SHAFT:** 0.5" diameter, plated steel
- **MAXIMUM TEMPERATURE:** 250°F
- **SEALS:** **SCD, SCD-LL-HD** pressure sensitive, dual durometer blade edge seals and flexible metal jamb seals
- **SIZES:** **SCD & SCD-LL** Minimum size: 5" W x 4" H; Maximum size: single section - 48" W x 72" H; Multiple section - unlimited size **SCD-LL-HD** Minimum size: 8" W x 8" H (203 mm x 203 mm); Maximum size: single section - 60" W x 72" H (1524 mm x 1829 mm); Multiple section - unlimited size.



BELIMO MOTORS OPTIONS AVAILABLE.

See Controls & Thermostats section