

Downblast Belt Drive Spun Aluminum Exhausters

ALX-DB SERIES



Ideal for exhausting air from factories, offices, warehouses or commercial buildings.

FEATURES

- Spun aluminum housing will not rust, chip or peel.
- Aluminum backward inclined wheel is non-overloading.
- Belt drive.
- Units up to 24" (max 2HP) can be wall mounted. All units can be roof mounted.
- Quick release latches for easy motor access.
- For motor options consult our fan selection software Delair.
www.canarm.com/delair

OPTIONS & ACCESSORIES

- Motorized damper
- Gravity (automatic) damper
- Wall mount bracket (for all sizes up to 24")
- Roof curb
- Disconnect switch
- Hinge kits
- VFD for 3 phase motors
- Other base (curb cap) options available. See C2 in dimensions table.



AVAILABLE WITH MOTORS & DRIVES FACTORY INSTALLED.
Consult Delair Software for details



**QUICK RELEASE LATCHES
FOR EASY MOTOR ACCESS**

DISCONNECT SWITCHES

Disconnect switches are available.





ALX-DB SERIES Downblast Belt Drive Spun Aluminum Exhausters

PERFORMANCE SPECIFICATIONS

WITH MOTOR & DRIVES

MODEL	RPM RANGE	HP	RPM	Values @ 0.5" SP		0" SP			1/2" SP				1" SP				1-1/4" SP				1-1/2" SP				
				BHP	Sones	CFM	BHP	FEI	FEPack (kW)	CFM	BHP	FEI	FEPack (kW)	CFM	BHP	FEI	FEPack (kW)	CFM	BHP	FEI	FEPack (kW)	CFM	BHP	FEI	FEPack (kW)
SINGLE PHASE AND WIRED DISCONNECT																									
ALX135DBT10025**	862-1293	1/4	1091	0.21	9.6	1423	0.17	-	-	1091	0.21	-	-	-	-	-	-	-	-	-	-	-	-	-	
ALX135DBT10033**	932-1398	1/3	1255	0.29	12.9	1630	0.29	-	-	1285	0.29	-	-	-	-	-	-	-	-	-	-	-	-	-	
ALX135DBT10050**	1121 - 1552	1/2	1380	0.39	16.3	1802	0.35	-	-	1501	0.39	-	-	1086	0.39	-	-	-	-	-	-	-	-	-	
ALX150DBT10050**	932-1398	3/4	1039	0.30	12.4	1951	0.26	-	-	1497	0.30	-	-	-	-	-	-	-	-	-	-	-	-	-	
ALX150DBT10075**	1078-1617	3/4	1222	0.48	17.6	2294	0.43	-	-	1920	0.48	-	-	1396	0.48	-	-	-	-	-	-	-	-	-	
ALX150DBT10100	1113 - 1511	1	1318	0.59	23	2466	0.53	0.58	0.56	2132	0.59	0.95	0.61	1727	0.62	1.14	0.54	-	-	-	-	-	-	-	
ALX165DBT10100	1097-1489	1	1250	0.64	21	2697	0.59	0.56	0.61	2243	0.64	0.92	0.66	1708	0.68	1.04	0.69	1301	0.66	1.01	0.67	-	-	-	
ALX165DBT10150	1254-1646	1 1/2	1455	0.99	26	3143	0.93	0.42	0.92	2764	0.99	0.74	0.97	2330	1.05	0.90	1.03	2099	1.07	0.95	1.04	1802	1.08	0.95	1.05
ALX180DBT10100	909 - 1195	1	1176	0.90	21	3340	0.81	0.50	0.81	2894	0.90	0.83	0.89	2308	0.93	1.00	0.92	1911	0.92	1.01	0.91	-	-	-	
ALX180DBT10200	1113 - 1511	2	1393	1.44	32	3969	1.44	0.34	1.37	3605	1.44	0.65	1.37	3145	1.56	0.81	1.47	2909	1.56	0.88	1.47	2638	1.56	0.92	1.47
ALX210DBT10150	862-1132	1 1/2	977	1.20	19.3	4852	1.21	0.48	1.17	4104	1.20	0.87	1.16	3130	1.16	1.06	1.12	2275	1.25	0.88	1.20	-	-	-	
ALX245DBT10150	673-889	1 1/2	795	1.32	19.4	5969	1.30	0.53	1.24	4759	1.32	0.90	1.26	3063	1.17	1.03	1.13	-	-	-	-	-	-	-	
ALX245DBT10200	745-979	2	867	1.71	22	6544	1.72	0.44	1.61	5404	1.71	0.79	1.60	4100	1.64	0.97	1.54	3078	1.47	1.03	1.13	-	-	-	
ALX245DBT10300	862-1132	3	971	2.41	27	7265	2.35	0.36	2.14	6313	2.41	0.66	2.20	5251	2.37	0.86	2.16	4592	2.30	0.91	2.10	3703	2.14	0.92	1.97
THREE PHASE WITH NO DISCONNECT																									
ALX150DB30100*	1113 - 1511	1	1318	0.59	23	2466	0.53	0.60	0.54	2132	0.59	0.99	0.59	1727	0.62	1.18	0.62	-	-	-	-	-	-	-	
ALX165DB30100*	1097-1489	1	1250	0.64	21	2697	0.59	0.58	0.59	2243	0.64	0.95	0.63	1708	0.68	1.08	0.67	1301	0.66	1.04	0.65	-	-	-	
ALX165DB30150*	1254-1646	1 1/2	1455	0.99	26	3143	0.93	0.43	0.90	2764	0.99	0.75	0.95	2330	1.05	0.92	1.01	2099	1.07	0.96	1.03	1802	1.08	0.96	1.03
ALX180DB30100*	909 - 1195	1	1176	0.90	21	3340	0.81	0.51	0.78	2894	0.90	0.85	0.87	2308	0.93	1.02	0.89	1911	0.92	1.03	0.88	-	-	-	
ALX180DB30200*	1113 - 1511	2	1393	1.44	32	3969	1.44	0.34	1.36	3605	1.44	0.65	1.36	3145	1.56	0.81	1.47	2909	1.56	0.88	1.47	2638	1.56	0.92	1.47
ALX210DB30150*	862-1132	1 1/2	977	1.20	19.3	4852	1.21	0.49	1.15	4104	1.20	0.88	1.14	3130	1.16	1.08	1.10	2275	1.25	0.90	1.18	-	-	-	
ALX245DB30150*	673-889	1 1/2	795	1.32	19.4	5969	1.30	0.54	1.23	4759	1.32	0.91	1.25	3063	1.17	1.05	1.11	-	-	-	-	-	-	-	
ALX245DB30200*	745-979	2	867	1.71	22	6544	1.72	0.44	1.61	5404	1.71	0.79	1.60	4100	1.64	0.97	1.54	3078	1.47	0.98	1.39	-	-	-	
ALX245DB30300*	862-1132	3	971	2.41	27	7265	2.35	0.37	2.11	6313	2.41	0.67	2.16	5251	2.37	0.87	2.13	4592	2.30	0.93	2.07	3703	2.14	0.94	1.93

** 115V only. All other motors will be wired at high voltage.

For three phase motors, substitute "" with "M" for 230/460 volt (wired for 460V) or "P" for 575 volt

WITHOUT MOTOR & DRIVES


MODEL	MIN HP	MAX HP	MAX RPM	TYPICAL MAXIMUM CFM @ SP																							
				0" SP				1/2" SP				1" SP				1-1/2" SP				2"				2-1/4"			
				CFM	BHP	FEI	FEPA _{CT} (kW)	CFM	BHP	FEI	FEPA _{CT} (kW)	CFM	BHP	FEI	FEPA _{CT} (kW)	CFM	BHP	FEI	FEPA _{CT} (kW)	CFM	BHP	FEI	FEPA _{CT} (kW)	CFM	BHP	FEI	FEPA _{CT} (kW)
ALX135-DB	-	3/4	1800	2200	0.64	0.45	0.66	1993	0.74	0.74	0.75	1681	0.74	0.95	0.75	1366	0.74	1.07	0.75	-	-	-	-	-	-	-	-
ALX150-DB	1/4	1	1800	2975	0.93	0.41	0.92	2689	0.98	0.73	0.96	2298	0.99	0.95	0.97	1851	0.97	1.07	0.95	-	-	-	-	-	-	-	-
ALX165-DB	1/4	2	1800	3880	1.76	0.28	1.64	3582	1.81	0.53	1.68	3244	1.91	0.69	1.77	2850	1.92	0.81	1.78	2451	1.98	0.86	1.83	2187	1.97	0.87	1.82
ALX180-DB	1/4	2	1500	4257	1.68	0.31	1.57	3929	1.76	0.58	1.64	3502	1.90	0.74	1.76	3052	1.92	0.86	1.78	2451	1.89	0.90	1.75	-	-	-	-
ALX210-DB	1/2	3	1300	6394	2.77	0.28	0.25	5903	2.83	0.54	2.55	5278	2.78	0.74	2.51	4551	2.74	0.88	2.48	3627	2.63	0.93	2.38	2830	2.42	0.89	2.20
ALX245-DB	1/2	5	1200	8955	4.43	0.24	3.90	8197	4.48	0.46	3.94	7374	4.50	0.63	3.96	6505	4.43	0.77	3.90	5405	4.25	0.84	3.75	4656	4.03	0.85	3.56

* Motor adaptor plate required for 3HP+

DIMENSIONS

MODEL	DIMENSIONS (INCHES)								Shaft Size	Wheel Diameter	Roof Opening	WEIGHT (lbs) without motors
	A	B	C	C2	D	E	F	G Ø				
ALX135-DB	25.25	31.25	21.00	24.75	3.13	2.00	3.75	0.44	3/4"	13.50	17.00	41
ALX150-DB	26.13	31.25	21.00	24.75	3.75	2.00	3.75	0.44	3/4"	15.00	17.00	43
ALX165-DB	31.13	36.25	24.75	28.00	5.00	2.00	4.00	0.44	3/4"	16.50	20.75	106
ALX180-DB	31.75	36.25	28.00	24.75	5.50	2.00	4.00	0.44	3/4"	18.25	20.75	114
ALX210-DB	36.25	43.75	33.13	40.00	5.25	2.50	4.00	0.44	1"	21.25	29.00	176
ALX245-DB	37.00	43.75	33.13	40.00	5.88	2.50	4.00	0.44	1"	24.50	29.00	181

Net weights for belt drive units do not include motor & drives.
Due to motor manufacturers variances in design, please see user manual for motor dimensional guidelines.



SCAN TO
VIEW FEI
CHARTS




SCAN TO
USE DELAIR
SOFTWARE



Canarm certifies that the ALX-DB Series shown herein are licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publications 211 & 311 and comply with the requirements of the AMCA Certified Ratings Programme.
The AMCA certified ratings seal applies to air and sound performance only. The ALX-DB Series shown herein are not approved by AMCA for FEI ratings. May 2026

Options & Accessories Roof Curbs

NON-VENTED FOR 300, 700, SIS, ALX, SB-SBRM & SD-SDUB SERIES




RCG ROOF CURB

- RCG are 18" high, RCGL are 12" high
- 18 gauge galvanized steel construction
- 1 3/4" flanges
- Insulated curbs available (RCGI or RCGLI)
- Shipped fully assembled

Please note Galvanized Curbs (RCG's) are for UL705 only.
For UL762 the curb must be vented and be a minimum of 40" from roof to outlet - use RCGV curbs (below)

Part # (Non-Insulated)	Part # (Insulated)	Curb OD Dimension sq	Curb fits Models
RCG17.5 / RCGL17.5	RCGI17.5 / RCGLI17.5	17.5"	ALX105, ALX120, SD-SDUB-10, SD-SDUB-12
RCG18.5 / RCGL18.5	RCGI18.5 / RCGLI18.5	18.5"	307
RCG19.5 / RCGL19.5	RCGI19.5 / RCGLI19.5	19.5"	ALX135, ALX150, SB-SBRM-13, SD-SDUB-30, SD-SDUB-33, SD-SDUB-50, ALX105-C2, ALX120-C2
RCG22.5 / RCGL22.5	RCGI22.5 / RCGLI22.5	22.5"	309,709,SIS-09
RCG23.25 / RCGL23.25	RCGI23.25 / RCGLI23.25	23.25"	ALX165, SB-SBRM-15, SD-SDUB-85, ALX135-C2, ALX150-C2, ALX180-C2
RCG26.5 / RCGL26.5	RCGI26.5 / RCGLI26.5	26.5"	ALX180, SIS-10, SB-SBRM-18, ALX165-C2
RCG30.5 / RCGL30.5	RCGI30.5 / RCGLI30.5	30.5"	312,712,715, SIS-12, SIG-12, SIG-15
RCG31.5 / RCGL31.5	RCGI31.5 / RCGLI31.5	31.5"	ALX210, ALX245, SB-SBRM-24
RCG34.5 / RCGL34.5	RCGI34.5 / RCGLI34.5	34.5"	315,718,SIS-15,SIS-18
RCG38.5 / RCGL38.5	RCGI38.5 / RCGLI38.5	38.5"	318, SB-SBRM-30, ALX210-C2, ALX245-C2, ALX300
RCG42.5 / RCGL42.5	RCGI42.5 / RCGLI42.5	42.5"	SIS-20, ALX360, SB-SBRM36

NON-VENTED FOR RTA, RB & RD SERIES



- 16 gauge galvanized or painted steel construction
- RC are insulated, painted, with 3" flanges and damper shelf
- RCG are non-insulated, galvanized, with 1 3/4" flanges
- RCGI are insulated, galvanized, with 1 3/4" flanges
- All are 10 1/4" high
- Shipped fully assembled

ROOF CURBS FOR RTA, RB & RD SERIES (Non-vented) 10 1/4" High

Part # Painted	Part # Galv (Non-Insulated)	Part # Galv (Insulated)	Curb OD Dimension sq	Curb fits Models
RC18	RCG21.625	RCGI21.625	21.6"	RTA18
RC24	RCG29.125	RCGI29.125	29.1"	RTA-RB-RD24
RC30	RCG35.125	RCGI35.125	35.1"	RTA-RB-RD30
RC36	RCG41.125	RCGI41.125	41.1"	RTA-RB-RD36
RC42	RCG47.125	RCGI47.125	47.1"	RTA-RB-RD42-RTASH
RC48	RCG53.125	RCGI53.125	53.1"	RTA-RB-RD48-RTASH
RC54	RCG59.125	RCGI59.125	59.1"	RTA-RB54-RTASH
RC60	RCG67.125	RCGI67.125	67.1"	RTA-RB60

VENTED FOR ALX, SB-SBRM & SD-SDUB SERIES



RCGV ROOF CURB

- UL762 requires vents and minimum 40" from roof to outlet
- Curb height varies to meet UL762 (see table)
- RCGV are 18" high, RCGVL are 12" high
- RCGVH vary to meet UL762
- 18 gauge galvanized steel construction
- 1 3/4" flanges
- Non-insulated & shipped fully assembled

Part #	Part #	UL762 Curb Height	Curb OD Dimension sq	Curb Fits Models
Vented 18" high (RCGV) Vented 12" high (RCGVL)	To Meet UL762			
RCGV17.5 / RCGVL17.5	RCGVH17.5	27"	17.5"	ALX105, ALX120, SD-SDUB-10, SD-SDUB-12
RCGV19.5 / RCGVL19.5	RCGVH19.5	25"	19.5"	ALX135, ALX150, SB-SBRM-13, SD-SDUB-30, SD-SDUB-33, SD-SDUB-50, HRE-13, ALX105-C2, ALX105-C2
RCGV23.25 / RCGVL23.25	RCGV23.25	18"	23.25"	ALX165, SB-SBRM-15, SD-SDUB-85, HRE-16, ALX135-C2, ALX150-C2, ALX180-C2
RCGV26.5 / RCGVL26.5	RCGV26.5	18"	26.5"	ALX180, SB-SBRM-18, HRE-20, ALX165-C2
RCGV31.5 / RCGVL31.5	RCGV31.5	18"	31.5"	ALX210, ALX245, SB-SBRM-24, HRE-24
RCGV38.5 / RCGVL38.5	RCGV38.5	18"	38.5"	SB-SBRM-30, ALX210-C2, ALX245-C2, ALX300

Options & Accessories Disconnect Switches



**EL1/3-25A
MOISTURE RESISTANT SWITCH**

Single or Three Phase
Moisture resistant, IP65
25 Amps, 3 Poles

HP Ratings
120V AC - 3hp
240V AC - 7.5hp
480V AC - 15hp
600V AC - 20hp



**DS1/3-30A
DISCONNECT SWITCH**

Single or Three Phase
Disconnect NEMA 3R (3030D)
30 Amps, 3 Poles

HP Ratings
120V AC - 3hp
240V AC - 7.5hp
480V AC - 15hp
600V AC - 20hp



**KG1-2P1PH
TOGGLE SWITCH**

Single Phase, Non-reversing,
toggle operation NEMA 1
(2510KG1)
30 Amps, 2 Poles

HP Ratings
120V AC - 2hp
240V AC - 2hp
480V AC - 2hp



**8890-5426-1
TOGGLE SWITCH WITH PILOT LIGHT**

15 Amps, 2 Poles

HP Ratings
120V AC - 0.5hp



**8890-54522-W
TOGGLE SWITCH**

20 Amps, 2 Poles

HP Ratings
120V AC - 1hp
240V AC - 2hp



**8890-MS403
TOGGLE SWITCH**

40 Amps, 3 Poles

HP Ratings
120V AC - 7.5hp
240V AC - 15hp
480V AC - 20hp
600V AC - 40hp



**8890-N13NC
SWITCH ENCLOSURE
WITH LOCKOUT**

NEMA 1 Steel switch