



Upblast Belt Drive Spun Aluminum Exhausters

ALX-UB SERIES

Ideal for exhausting air from restaurants, offices, warehouses or commercial buildings.

FEATURES

- Spun aluminum housing will not rust, chip or peel.
- Aluminum backward inclined wheel is non-overloading.
- Belt drive.
- Units up to 24" (max 2HP) can be wall mounted. All units can be roof mounted.
- Quick release latches for easy motor access.
- For motor options consult our fan selection software Delair.
www.canarm.com/delair



AVAILABLE WITH MOTORS & DRIVES FACTORY INSTALLED.
Consult Delair Software for details

OPTIONS & ACCESSORIES

- Wall mount bracket (for all sizes up to 24")
- Grease collection box (required for restaurant exhaust applications)
- Curb hinge
- Disconnect switches
- Roof curbs
- Other base (curb cap) options available. See C2 in dimensions table.



**QUICK RELEASE LATCHES
FOR EASY MOTOR ACCESS**


OPTIONS FOR NON-RESTAURANT APPLICATIONS:

- Motorized damper
- Gravity (automatic) damper
- Bird screen

DIMENSIONS

MODEL	DIMENSIONS (INCHES)											WEIGHT (lbs) without motors
	A	B	C	C2	D	E	F	G Ø	Shaft Size	Wheel Diameter	Roof Opening	
ALX135-UB	25.25	32.13	21.00	24.75	17.13	2.00	3.75	0.44	3/4"	13.50	17.00	43
ALX150-UB	26.13	32.13	21.00	24.75	17.13	2.00	3.75	0.44	3/4"	15.00	17.00	45
ALX165-UB	31.13	37.50	24.75	28.00	21.13	2.00	4.00	0.44	3/4"	16.50	20.75	108
ALX180-UB	31.75	37.50	28.00	24.75	21.13	2.00	4.00	0.44	3/4"	18.25	20.75	116
ALX210-UB	36.25	43.75	33.13	40.00	25.50	2.50	4.00	0.44	1"	21.00	29.00	178
ALX245-UB	37.00	43.75	33.13	40.00	25.50	2.50	4.00	0.44	1"	24.50	29.00	183

Net weights for belt drive units do not include motor & drives.
Due to motor manufacturers variances in design, please see
user manual for motor dimensional guidelines.



DISCONNECT SWITCHES

Disconnect switches are available. See Controls & Thermostats section for details.



ALX-UB SERIES

Upblast Belt Drive Spun Aluminum Exhausters

PERFORMANCE SPECIFICATIONS

WITH MOTOR & DRIVES

MODEL	RPM RANGE	HP	RPM	Sones @ 1/2" SP	0" SP				1/4" SP				1/2" SP				3/4" SP				1" SP				1-1/4" SP				1-1/2" SP			
					CFM	BHP	FEI	FEPAct (kW)	CFM	BHP	FEI	FEPAct (kW)	CFM	BHP	FEI	FEPAct (kW)	CFM	BHP	FEI	FEPAct (kW)	CFM	BHP	FEI	FEPAct (kW)	CFM	BHP	FEI	FEPAct (kW)	CFM	BHP	FEI	FEPAct (kW)
SINGLE PHASE AND WIRED DISCONNECT																																
ALX135UBT10025**	862-1293	1/4	1042	8.6	1221	0.15	-	-	1031	0.16	-	-	810	0.16	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
ALX135UBT10033**	932-1398	1/3	1212	12.1	1417	0.23	-	-	1263	0.24	-	-	1079	0.25	-	-	870	0.25	-	-	-	-	-	-	-	-	-	-	-	-		
ALX135UBT10050**	1122-1552	1/2	1394	16.6	1629	0.36	-	-	1499	0.37	-	-	1345	0.37	-	-	1180	0.38	-	-	987	0.38	-	-	-	-	-	-	-	-		
ALX150UBT10050**	932-1398	1/2	1165	15.6	1928	0.33	-	-	1762	0.34	-	-	1547	0.36	-	-	1283	0.36	-	-	-	-	-	-	-	-	-	-	-	-		
ALX150UBT10075**	1078-1617	3/4	1367	21	2257	0.53	-	-	2124	0.54	-	-	1956	0.56	-	-	1757	0.58	-	-	1534	0.58	-	-	1268	0.57	-	-	-	-		
ALX150UBT10100	1341-1820	1	1473	23	2439	0.66	0.49	0.68	2313	0.68	0.68	0.70	2164	0.70	0.84	0.72	1987	0.71	0.96	0.72	1786	0.73	1.02	0.74	1575	0.72	1.09	0.73	1294	0.71	1.08	0.72
ALX165UBT10100	1097-1489	1	1379	25	2885	0.77	0.48	0.77	2737	0.79	0.68	0.79	2567	0.82	0.83	0.82	2375	0.84	0.95	0.84	2130	0.85	1.03	0.84	1880	0.86	1.07	0.85	1591	0.85	1.07	0.84
ALX165UBT10150	1254-1646	1 1/2	1605	33	3351	1.21	0.36	1.17	3230	1.24	0.52	1.19	3094	1.27	0.65	1.22	2943	1.30	0.76	1.24	2769	1.31	0.86	1.25	2573	1.33	0.93	1.27	2355	1.34	0.97	1.28
ALX180UBT10100	980-1293	1	1222	25	3403	0.89	0.48	0.88	3229	0.91	0.69	0.90	3007	0.94	0.84	0.92	2722	0.97	0.93	0.95	2417	0.98	1.00	0.96	2025	0.97	1.02	0.95	1291	0.82	0.95	0.82
ALX180UBT10200	1097-1489	2	1419	33	3944	1.38	0.37	1.31	3809	1.42	0.53	1.35	3634	1.45	0.66	1.37	3425	1.49	0.77	1.41	3185	1.52	0.85	1.43	2924	1.54	0.90	1.45	2611	1.53	0.94	1.44
ALX210UBT10150	862-1132	1 1/2	1021	26	4744	1.33	0.44	1.27	4509	1.35	0.63	1.29	4213	1.36	0.79	1.30	3897	1.37	0.92	1.30	3458	1.34	1.02	1.28	2937	1.29	1.06	1.23	1969	1.11	1.00	1.08
ALX245UBT10150	673-889	1 1/2	790	23	5785	1.24	0.55	1.19	5364	1.26	0.78	1.21	4828	1.26	0.96	1.21	4124	1.25	1.05	1.20	3306	1.18	1.10	1.14	-	-	-	-	-	-	-	
ALX245UBT10200	745-979	2	864	28	6311	1.62	0.46	1.52	5944	1.65	0.67	1.55	5468	1.64	0.84	1.54	4923	1.64	0.96	1.54	4209	1.61	1.02	1.51	3336	1.50	1.03	1.42	-	-	-	-
ALX245UBT10300	862-1132	3	964	35	7066	2.27	0.37	2.08	6729	2.29	0.55	2.09	6333	2.30	0.70	2.10	5904	2.30	0.82	2.10	5326	2.28	0.91	2.09	4704	2.24	0.96	2.05	3970	2.14	0.99	1.97
THREE PHASE WITH NO DISCONNECT																																
ALX150UB30100*	1341-1820	1	1473	23	2439	0.66	0.50	0.66	2313	0.68	0.71	0.67	2164	0.70	0.87	0.69	1987	0.71	0.99	0.70	1786	0.73	1.06	0.72	1575	0.72	1.12	0.71	1294	0.71	1.11	0.70
ALX165UB30100*	1097-1489	1	1379	25	2885	0.77	0.49	0.71	2737	0.79	0.66	0.76	2567	0.82	0.80	0.78	2375	0.85	0.90	0.78	2130	0.85	0.95	0.80	1880	0.85	0.95	0.80	1591	0.85	0.93	0.75
ALX165UB30150*	1254-1646	1 1/2	1605	33	3351	1.21	0.37	1.15	3230	1.24	0.53	1.18	3094	1.27	0.66	1.20	2943	1.30	0.77	1.23	2769	1.31	0.87	1.24	2573	1.33	0.94	1.26	2355	1.34	0.98	1.26
ALX180UB30100*	980-1293	1	1222	25	3403	0.89	0.50	0.86	3229	0.91	0.70	0.87	3007	0.94	0.86	0.90	2722	0.97	0.95	0.93	2417	0.98	1.02	0.94	2025	0.97	1.04	0.93	1291	0.82	0.97	0.79
ALX180UB30200*	1097-1489	2	1419	33	3944	1.38	0.37	1.31	3809	1.42	0.53	1.35	3634	1.45	0.66	1.37	3425	1.49	0.77	1.41	3185	1.52	0.84	1.43	2924	1.54	0.90	1.45	2611	1.53	0.94	1.44
ALX210UB30150*	862-1132	1 1/2	1021	26	4744	1.33	0.44	1.26	4509	1.35	0.64	1.27	4213	1.36	0.80	1.28	3897	1.37	0.93	1.29	3458	1.34	1.03	1.26	2937	1.29	1.08	1.22	1969	1.11	1.01	1.06
ALX245UB30150*	673-889	1 1/2	790	23	5785	1.24	0.56	1.18	5364	1.26	0.79	1.19	4828	1.26	0.97	1.19	4124	1.25	1.07	1.18	3306	1.18	1.11	1.12	-	-	-	-	-	-	-	-
ALX245UB30200*	745-979	2	864	28	6311	1.62	0.46	1.52	5944	1.65	0.67	1.55	5468	1.64	0.84	1.54	4923	1.64	0.96	1.54	4209	1.61	1.02	1.51	3336	1.50	1.03	1.42	-	-	-	-
ALX245UB30300*	862-1132	3	964	35	7066	2.27	0.38	2.04	6729	2.29	0.56	2.06	6333	2.30	0.71	2.07	5904	2.30	0.83	2.07	5326	2.28	0.92	2.05	4704	2.24	0.98	2.02	3970	2.14	1.00	1.93

Performance certified is for installation type A: Free inlet, free outlet with partition.

Power rating does not include transmission losses.

Performance ratings do not include the effects of appurtenances.

The sound ratings shown are loudness values in hemispherical sones at a distance of 1.5 m (5 ft) in a hemispherical free field calculated per ANSI/AMCA Standard 301.

Values shown are for installation type A: free outlet hemispherical sone levels.

** 115V only. All other motors will be wired at high voltage.

For three phase motors, substitute "" with "M" for 230/460 volt (wired for 460V) or "P" for 575 volt

WITHOUT MOTOR & DRIVES

MODEL	MIN HP	MAX HP	MAX WHEEL RPM	TYPICAL MAXIMUM CFM @ SP																																				
				FAN 0" SP				1/4" SP				1/2" SP				3/4" SP				1" SP				1-1/4" SP				1-1/2" SP				2" SP				2-1/4" SP				
				CFM	BHP	FEI	FEPA(kW)	CFM	BHP	FEI	FEPA(kW)	CFM	BHP	FEI	FEPA(kW)	CFM	BHP	FEI	FEPA(kW)	CFM	BHP	FEI	FEPA(kW)	CFM	BHP	FEI	FEPA(kW)	CFM	BHP	FEI	FEPA(kW)	CFM	BHP	FEI	FEPA(kW)	CFM	BHP	FEI	FEPA(kW)	
ALX135-UB	-	3/4	2400	1736	2033	0.69	0.41	0.70	1926	0.73	0.56	0.74	1817	0.71	0.72	0.72	1691	0.73	0.83	0.74	1560	0.73	0.92	0.74	1424	0.74	0.98	0.75	1264	0.74	1.02	0.75	-	-	-	-	-	-	-	-
ALX150-UB	1/4	1	1800	1627	2692	0.89	0.40	0.88	2579	0.90	0.58	0.89	2453	0.93	0.72	0.92	2308	0.95	0.83	0.93	2137	0.97	0.91	0.95	1956	0.98	0.98	0.96	1766	0.98	1.02	0.96	-	-	-	-	-	-	-	-
ALX165-UB	1/4	2	1800	1800	3745	1.68	0.29	1.57	3640	1.72	0.43	1.61	3514	1.75	0.54	1.63	3385	1.78	0.64	1.66	3245	1.81	0.73	1.68	3088	1.83	0.81	1.70	2914	1.85	0.86	1.72	2522	1.87	0.94	1.74	2323	1.87	0.96	1.74
ALX180-UB	1/4	2	1500	1500	4180	1.64	0.33	1.54	4044	1.67	0.48	1.56	3881	1.70	0.60	1.59	3690	1.74	0.71	1.62	3476	1.78	0.79	1.66	3244	1.81	0.85	1.68	2967	1.81	0.90	1.68	2311	1.77	0.92	1.65	1632	1.55	0.86	1.46
ALX210-UB*	1/2	3	1300	1300	6026	2.73	0.28	2.47	5854	2.76	0.41	2.49	5652	2.79	0.53	2.52	5421	2.80	0.63	2.53	5180	2.81	0.73	2.54	4905	2.80	0.81	2.53	4571	2.78	0.87	2.51	3759	2.65	0.96	2.40	3145	2.51	0.95	2.28
ALX245-UB*	1/2	5	1200	1200	8779	4.35	0.24	3.83	8529	4.39	0.37	3.86	8234	4.41	0.48	3.88	7910	4.42	0.58	3.89	7540	4.42	0.66	3.89	7180	4.41	0.74	3.88	6708	4.38	0.80	3.86	5719	4.29	0.88	3.78	5174	4.19	0.91	3.70

Performance certified is for installation type A: Free inlet, free outlet with partition.

Power rating does not include transmission losses.

Performance ratings do not include the effects of appurtenances.

* Motor adaptor plate required for 3HP+



SCAN TO
VIEW FEI
CHARTS



SCAN TO
USE DELTA
SOFTWARE



UL705 Supplement SC - Power Ventilator for Restaurant Exhaust Appliances certified
Refer to our UL705 Supplement SC catalogue page in Roof Mount Ventilation for all installation requirements.



Canarm Ltd. certifies that the ALX-UB Series shown herein is licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and comply with the requirements of the AMCA Certified Ratings Program. May 2026

Options & Accessories Roof Curbs

NON-VENTED FOR 300, 700, SIS, ALX, SB-SBRM & SD-SDUB SERIES




RCG ROOF CURB

- RCG are 18" high, RCGL are 12" high
- 18 gauge galvanized steel construction
- 1 3/4" flanges
- Insulated curbs available (RCGI or RCGLI)
- Shipped fully assembled

Please note Galvanized Curbs (RCG's) are for UL705 only.
For UL762 the curb must be vented and be a minimum of 40" from roof to outlet - use RCGV curbs (below)

Part # (Non-Insulated)	Part # (Insulated)	Curb OD Dimension sq	Curb fits Models
RCG17.5 / RCGL17.5	RCGI17.5 / RCGLI17.5	17.5"	ALX105, ALX120, SD-SDUB-10, SD-SDUB-12
RCG18.5 / RCGL18.5	RCGI18.5 / RCGLI18.5	18.5"	307
RCG19.5 / RCGL19.5	RCGI19.5 / RCGLI19.5	19.5"	ALX135, ALX150, SB-SBRM-13, SD-SDUB-30, SD-SDUB-33, SD-SDUB-50, ALX105-C2, ALX120-C2
RCG22.5 / RCGL22.5	RCGI22.5 / RCGLI22.5	22.5"	309,709,SIS-09
RCG23.25 / RCGL23.25	RCGI23.25 / RCGLI23.25	23.25"	ALX165, SB-SBRM-15, SD-SDUB-85, ALX135-C2, ALX150-C2, ALX180-C2
RCG26.5 / RCGL26.5	RCGI26.5 / RCGLI26.5	26.5"	ALX180, SIS-10, SB-SBRM-18, ALX165-C2
RCG30.5 / RCGL30.5	RCGI30.5 / RCGLI30.5	30.5"	312,712,715, SIS-12, SIG-12, SIG-15
RCG31.5 / RCGL31.5	RCGI31.5 / RCGLI31.5	31.5"	ALX210, ALX245, SB-SBRM-24
RCG34.5 / RCGL34.5	RCGI34.5 / RCGLI34.5	34.5"	315,718,SIS-15,SIS-18
RCG38.5 / RCGL38.5	RCGI38.5 / RCGLI38.5	38.5"	318, SB-SBRM-30, ALX210-C2, ALX245-C2, ALX300
RCG42.5 / RCGL42.5	RCGI42.5 / RCGLI42.5	42.5"	SIS-20, ALX360, SB-SBRM36

NON-VENTED FOR RTA, RB & RD SERIES



- 16 gauge galvanized or painted steel construction
- RC are insulated, painted, with 3" flanges and damper shelf
- RCG are non-insulated, galvanized, with 1 3/4" flanges
- RCGI are insulated, galvanized, with 1 3/4" flanges
- All are 10 1/4" high
- Shipped fully assembled

ROOF CURBS FOR RTA, RB & RD SERIES (Non-vented) 10 1/4" High				
Part # Painted	Part # Galv (Non-Insulated)	Part # Galv (Insulated)	Curb OD Dimension sq	Curb fits Models
RC18	RCG21.625	RCGI21.625	21.6"	RTA18
RC24	RCG29.125	RCGI29.125	29.1"	RTA-RB-RD24
RC30	RCG35.125	RCGI35.125	35.1"	RTA-RB-RD30
RC36	RCG41.125	RCGI41.125	41.1"	RTA-RB-RD36
RC42	RCG47.125	RCGI47.125	47.1"	RTA-RB-RD42-RTASH
RC48	RCG53.125	RCGI53.125	53.1"	RTA-RB-RD48-RTASH
RC54	RCG59.125	RCGI59.125	59.1"	RTA-RB54-RTASH
RC60	RCG67.125	RCGI67.125	67.1"	RTA-RB60

VENTED FOR ALX, SB-SBRM & SD-SDUB SERIES



RCGV ROOF CURB

- UL762 requires vents and minimum 40" from roof to outlet
- Curb height varies to meet UL762 (see table)
- RCGV are 18" high, RCGVL are 12" high
- RCGVH vary to meet UL762
- 18 gauge galvanized steel construction
- 1 3/4" flanges
- Non-insulated & shipped fully assembled

Part #	Part #	UL762 Curb Height	Curb OD Dimension sq	Curb Fits Models
Vented 18" high (RCGV) Vented 12" high (RCGVL)	To Meet UL762			
RCGV17.5 / RCGVL17.5	RCGVH17.5	27"	17.5"	ALX105, ALX120, SD-SDUB-10, SD-SDUB-12
RCGV19.5 / RCGVL19.5	RCGVH19.5	25"	19.5"	ALX135, ALX150, SB-SBRM-13, SD-SDUB-30, SD-SDUB-33, SD-SDUB-50, HRE-13, ALX105-C2, ALX105-C2
RCGV23.25 / RCGVL23.25	RCGV23.25	18"	23.25"	ALX165, SB-SBRM-15, SD-SDUB-85, HRE-16, ALX135-C2, ALX150-C2, ALX180-C2
RCGV26.5 / RCGVL26.5	RCGV26.5	18"	26.5"	ALX180, SB-SBRM-18, HRE-20, ALX165-C2
RCGV31.5 / RCGVL31.5	RCGV31.5	18"	31.5"	ALX210, ALX245, SB-SBRM-24, HRE-24
RCGV38.5 / RCGVL38.5	RCGV38.5	18"	38.5"	SB-SBRM-30, ALX210-C2, ALX245-C2, ALX300

Options & Accessories Disconnect Switches



**EL1/3-25A
MOISTURE RESISTANT SWITCH**

Single or Three Phase
Moisture resistant, IP65
25 Amps, 3 Poles

HP Ratings
120V AC - 3hp
240V AC - 7.5hp
480V AC - 15hp
600V AC - 20hp



**DS1/3-30A
DISCONNECT SWITCH**

Single or Three Phase
Disconnect NEMA 3R (3030D)
30 Amps, 3 Poles

HP Ratings
120V AC - 3hp
240V AC - 7.5hp
480V AC - 15hp
600V AC - 20hp



**KG1-2P1PH
TOGGLE SWITCH**

Single Phase, Non-reversing,
toggle operation NEMA 1
(2510KG1)
30 Amps, 2 Poles

HP Ratings
120V AC - 2hp
240V AC - 2hp
480V AC - 2hp



**8890-5426-1
TOGGLE SWITCH WITH PILOT LIGHT**

15 Amps, 2 Poles

HP Ratings
120V AC - 0.5hp



**8890-54522-W
TOGGLE SWITCH**

20 Amps, 2 Poles

HP Ratings
120V AC - 1hp
240V AC - 2hp



**8890-MS403
TOGGLE SWITCH**

40 Amps, 3 Poles

HP Ratings
120V AC - 7.5hp
240V AC - 15hp
480V AC - 20hp
600V AC - 40hp



**8890-N13NC
SWITCH ENCLOSURE
WITH LOCKOUT**

NEMA 1 Steel switch



ALX-UB SERIES

Built for hot menus.



WHAT IS UL705 SUPPLEMENT SC?

Power Ventilation for Restaurant Exhaust Appliances

Power ventilators for restaurant exhaust appliances covered by these requirements are intended for installation in accordance with the Standard of the National Fire Protection Association for the Installation of Equipment for the Removal of Smoke and Grease-Laden Vapors from Commercial Cooking Equipment, NFPA 96.

Power ventilators for restaurant appliances shall comply with the Standard for Power Ventilators, UL 705 - Power Ventilator for Restaurant Exhaust Appliances, modified in that wiring system shall not be located in the path of travel of exhaust products.

REQUIREMENTS

REQUIREMENT	ALX SERIES		BI-RM		HRE	
	STANDARD	ACCESSORY	STANDARD	ACCESSORY	STANDARD	ACCESSORY
Designed for removal of smoke and/or grease laden air	•		•		•	
Air temperatures up to 300°F	•		•		•	
Access for cleanout	•		•		•	
Grease drain	•		•		•	
Grease collection box		•		•		•
Minimum 500 FPM airflow in duct**	•		•		•	
Vented roof curb extending discharge minimum 40" above roofline		•	N/A*			•
Curb hinge		•	N/A			•


* must be mounted to extend outlet minimum 40" above roofline

** based on standard Canarm configurations with Motors and Drives, LMLD models must refer to Delair for minimum rPM to reach 500 FPM


UL705 SUPPLEMENT SC LISTED PRODUCTS



ALX SERIES
(upblast models only)



BI-RM SERIES



HRE SERIES