

Radiation Dampers

CRD.CEP, CRD.CP, CRD.CNP



CRD.CEP

CRD.CNP

CRD.CP

Designed to help limit the transfer of heat & fire through HVAC duct openings in fire-rated assemblies.



FEATURES

- For use in 1, 2 and 3 hour rated floor-ceiling and roof-ceiling constructions
- Galvanized steel frame
- High temperature, non-asbestos, reinforced fiber thermal fabric
- Stainless steel closure springs
- 165°F fusible link
- Separate outer frame allows complete fan and damper serviceability without disturbing the surrounding ceiling material
- Meets or exceeds NFPA-90A
- ETL Classified (UL-555C)

CANARM FAN COMPATIBILITY

MODEL	CORRESPONDING CANARM FAN MODEL
CRD.CEP	CESD100-3, CEP80, CEP110, CEP150
CRD.CP	CP50, CP80, CP80LED
CRD.CNP	CNP80, CNP100, CNP100-3

DIMENSIONS

MODEL	NOMINAL FRAME SIZE (W x L x H)
CRD.CEP	11 1/4" x 12 1/4" x 3"
CRD.CP	8 1/8" x 8 1/4" x 4 1/8"
CRD.CNP	10 3/8" x 9 7/8" x 3"

