

Back Curved Impeller Inline Centrifugal Fans

VKP SERIES

Designed for extract and input ventilation. Ideal for apartments & condos.

FEATURES

- Excellent aerodynamics and low noise.
- External rotor motor on ball bearings and the backward curved, balanced impeller is suitable for high pressure application, prevent vibration and ensure quiet operation.
- Fan housing is made of galvanized steel.
- VKP 125/125-2 and VKP 150/150-2 models are available with two inlets.
- Suitable for low ceilings and tight spaces.
- Hinges provide quick and fast access to the motor for easy cleaning and maintenance.
- Vertical or horizontal installation.
- 2 year warranty.

ACCESSORIES

For more information on available accessories, see Accessories & Motors section.

DIMENSIONS

MODEL	DIMENSIONS (Inches)					Figure
	ØD	ØD1	L	B	H	
VKP100	3 15/16"	3 15/16"	13 7/8"	9 7/8"	6 3/8"	1
VKP125	4 7/8"	4 7/8"	16 3/16"	12 3/16"	7 1/2"	1
VKP150	5 7/8"	5 7/8"	18 3/16"	15 7/16"	7 1/2"	1
VKP125/125-2	4 7/8"	4 7/8"	16 3/16"	12 3/16"	7 1/2"	2
VKP150/150-2	5 7/8"	5 7/8"	18 3/16"	15 7/16"	7 1/2"	2




FIGURE 1 - Inline Dryer Booster Fan




FIGURE 2 - Twin Intake Fan

PERFORMANCE SPECIFICATIONS

MODEL	WATTS*	AMPS*	DUCT DIA.	CFM VS. STATIC PRESSURE (Ps) IN WG												MAX Ps	VOLTS / HZ
				0"	0.1"	0.2"	0.3"	0.4"	0.5"	0.6"	0.7"	0.8"	0.9"	1"			
VKP100	30	0.27	4"	104	98	94	89	84	77	69	61	52	43	33	1.2	120 / 60	
VKP125	67	0.56	5"	212	208	201	192	182	172	162	152	142	132	120	1.6	120 / 60	
VKP150	102	0.85	6"	295	287	278	270	260	251	242	233	225	215	206	3	120 / 60	
VKP125/125-2	74	0.61	5" / 5"	244	234	223	213	204	194	183	170	160	150	140	1.9	120 / 60	
VKP150/150-2	119	1	6" / 6"	360	348	332	316	302	289	272	259	245	233	220	3	120 / 60	