

Industrial Grade Circulating Fans

CA SERIES

Effectively cools large areas in factories, stores, offices, restaurants. These fans economically provide relief from summer heat by creating a gentle air movement.

MOUNTING ACCESSORIES (not included)



WALL BRACKET
CFWB - 6 Lbs



**KNOCKDOWN
PEDISTAL BASE**
CFKPB - 36 Lbs



CEILING MOUNT
CFCM - 9 Lbs
Non-oscillating fans only

FEATURES

- Rugged, high performance model.
- Available in 24" & 30" sizes.
- 1/4 HP, 3 speed, totally enclosed ball bearing motor with thermal overload protection.
- Fan motor, low RPM - 1100/950/850 - for quiet operation.
- Available with oscillating motor on the pedestal and wall models.
- Heavy gauge aluminum, well balanced fan blades.
- Air stream adjustable in all directions via the tilting swivel bracket feature..
- Complete with 10', 120V grounded cord set.
- Attractive powder coated front and rear guards, meet OSHA standards.



CA fan heads replace CFH fan heads.

PERFORMANCE SPECIFICATIONS

MODEL	FAN SIZE	DESCRIPTION	CFM	CFM / W	VOLT	AMPS	SHIPPING WEIGHT (LBS)
FAN HEAD ONLY							
CA24OSC-C	24"	3 SPEED OSCILLATING	8145 / 6795 / 5793	32.7 / 31.9 / 28.1	120	2.4	40
CA30OSC-C	30"	3 SPEED OSCILLATING	11100 / 9068 / 7658	44.0 / 42.9 / 37.1	120	2.5	50

VELOCITY MAPPING CHARTS

Air distribution patterns of the CA fans - a graphic illustration of air velocity in feet per minute.

