

Fixed Louvers

EL2, EL2F

EL4, EL4F

EL6, EL6F

EL4, EL4F, EL6, EL6F

Designs provide high free area and can exhaust a high volume of air with little static pressure.

FEATURES

- MATERIAL: **EL2, EL2F, EL4, EL4F** .081" (2.06 mm) thick, 6063-T5 alloy, extruded aluminum. **EL6, EL6F** .085" (2.16 mm) thick, 6063-T5 alloy, extruded aluminum
- BLADE DESIGN: **EL2, EL2F**: set at 30° spaced 2" (50 mm) on centres with storm proof performance. **EL4, EL4F** set at 37° spaced 4" (100 mm) on centres with storm proof performance. **EL6, EL6F**: set at 45° spaced 7 1/4" (184.2 mm) on centres with storm proof performance
- CONSTRUCTION: blade assembly is designed to prevent bowing and distortions. All corners are mitered to provide a neat, uniform extrusion profile at the perimeter.
- SCREENS: 1/2" x 1/2" regalanized, 19 gauge wire bird screen
- FINISHES: mill is standard finish, anodized or baked enamel available at additional cost.
- SIZES: per customer specification multiple sections may be required. Consult factory for sizes.

EL2, EL2F Min. size: 12" x 8"

EL4, EL4F Min.size 12" x 12"

EL6, EL6F Min. size: 16" x 16"

EL2, EL2F are 2" deep louvres with blades set at a 30° angle. Their slim design may be used in curtain wall, interior or exterior partitions and window walls.

EL4, EL4F are 4" deep louvres with blades set at a 35° angle, ensuring positive drainage which prevents discoloration of building walls.

EL6, EL6F are 6" deep louvres with blades set at a 45° angle. Their slim design may be used in curtain wall, interior or exterior partitions and window walls. The design provides protection from water penetration while retaining high free area.



EL2, EL2F

Normally used as an exhaust louver where the total CFM is relatively low