

Fixed Louvers

EL2, EL2F

EL4, EL4F

EL6, EL6F

EL4, EL4F, EL6, EL6F

Designs provide high free area and can exhaust a high volume of air with little static pressure.

FEATURES

- MATERIAL: **EL2, EL2F, EL4, EL4F** .081" (2.06 mm) thick, 6063-T5 alloy, extruded aluminum. **EL6, EL6F** .085" (2.16 mm) thick, 6063-T5 alloy, extruded aluminum
- BLADE DESIGN: **EL2, EL2F**: set at 30° spaced 2" (50 mm) on centres with storm proof performance. **EL4, EL4F** set at 37° spaced 4" (100 mm) on centres with storm proof performance. **EL6, EL6F**: set at 45° spaced 7 1/4" (184.2 mm) on centres with storm proof performance
- CONSTRUCTION: blade assembly is designed to prevent bowing and distortions. All corners are mitered to provide a neat, uniform extrusion profile at the perimeter.
- SCREENS: 1/2" x 1/2" regalanized, 19 gauge wire bird screen
- FINISHES: mill is standard finish, anodized or baked enamel available at additional cost.
- SIZES: per customer specification multiple sections may be required. Consult factory for sizes.

EL2, EL2F Min. size: 12" x 8"

EL4, EL4F Min.size 12" x 12"

EL6, EL6F Min. size: 16" x 16"



EL2, EL2F

Normally used as an exhaust louvre where the total CFM is relatively low

EL2, EL2F are 2" deep louvres with blades set at a 30° angle. Their slim design may be used in curtain wall, interior or exterior partitions and window walls.

EL4, EL4F are 4" deep louvres with blades set at a 35° angle, ensuring positive drainage which prevents discoloration of building walls.

EL6, EL6F are 6" deep louvres with blades set at a 45° angle. Their slim design may be used in curtain wall, interior or exterior partitions and window walls. The design provides protection from water penetration while retaining high free area.