

Steel Control Dampers

SCD-LL Low Leakage

SCD-LL -HD Low Leakage, Heavy Duty



PERFORMANCE DATA

SCD-LL Designed and tested to provide an extremely tight sealing damper which is cost effective for the majority of HVAC applications. They are generally recommended for face velocities up to 2000 fpm and static pressures to 2.5" w.g. (Note: for systems in excess of 2.5 w.g., contact the factory.)

The SCD-LL dampers have been tested to AMCA Standard 500-D with the following results:			
	AT 1.0" w.g.	AT 2.5" w.g.	AT 4.0" w.g.
LEAKAGE (cfm/SQ FT)	3.5	5.0	7.0

SCD-LL-HD Designed and tested to provide rigid, robust and yet cost effective control dampers for special applications involving high pressure up to 9.0" w.g.

The SCD-LL-HD dampers have been tested to AMCA Standard 500-D with the following results:				
	AT 1.0" w.g.	AT 4.0" w.g.	AT 8.0" w.g.	AT 8.0" w.g.
LEAKAGE (cfm/SQ FT)	3.5	7.0	9.8	11.2

SCD-LL -HD OPTIONAL CONSTRUCTION

- BEARINGS: nylon, press fit into frame
- Silicone blade edge seals



ORDERING METHOD

DAMPER STYLES: SCD = SD; SCD-LL = SL

SD24.00x24.000A A = MOUNTED IN AIRSTREAM
B = MOUNTED OUT OF AIRSTREAM
DAMPER STYLE WIDTH HEIGHT PLACEHOLDER FOR ACTUATOR (IF REQUIRED)

FOR DAMPER STYLES: SCD-LL-HD = SL-HD:

SL-HD24.00x24.000B A = MOUNTED IN AIRSTREAM
B = MOUNTED OUT OF AIRSTREAM
DAMPER STYLE WIDTH HEIGHT PLACEHOLDER FOR ACTUATOR (IF REQUIRED)

NOTE: dampers are furnished approximately 1/4" smaller than given duct dimensions. Not recommended with blades running vertically. All dampers 32" and over are supplied with Jack shafting.