

Portable Utility Fan


U SERIES

U series utility fans - formerly known as FANTRAXX smoke ejectors - are ideal for many utility applications and have been designed to meet fire service needs.




FEATURES

- Available in 12" to 24" sizes.
- Totally enclosed ball bearing motor and explosion proof models available.
- Powder coated housing.
- Fans come complete with 6 foot 115V cord and plug (explosion proof motors come without a plug).



2U121CLFI




2U121LFI

UTILITY GUARDS

Utility Guards have the centers cut out. To order with centre, do not include C in the model number.

MODEL	SIZE
2U121CLF I	12"
2U161CLF I	16"
2U181CLF I	18"
2U202CLF I	20"
MC27GC	27"
MC30CG	30"



COLLAR ADAPTORS

Collar Adaptors are required when using flexible hose. Easily attached to the inlet or discharge of a Smoke Ejector with spring clips (included).

MODEL	HOSE SIZE	FAN SIZE	WEIGHT (lbs)
CA12-12	12"	U12	7
CA16	16"	U16	8
CA18	18"	U18	9
CA20	20"	U20	15
CA24	24"	U24	TBA

U SERIES

Portable Utility Fans

All Explosion Proof Fans have a single speed, dual voltage explosion proof motor that meets and conforms to all the standards that are listed below.

CLASS I, GROUP C	Atmospheres containing ethyl ether, ethylene, gases or vapors of equivalent hazard.
CLASS I, GROUP D	Atmospheres such as acetone, ammonia, benzene, butane, cyclopropane, ethanol, gasoline, hexane, methane, natural gas, naphtha, propane, or gasses or vapors of equivalent hazard.
CLASS II GROUP E	Atmospheres containing Aluminum, Magnesium and other metal dusts with similar characteristics.
CLASS II GROUP F	Atmospheres containing carbonaceous dust, including carbon black, charcoal, coal, or coke dusts that have more than 8% total entrapped volatiles, or dusts that have been sensitized by other materials so that they present an explosion hazard.
CLASS II GROUP G	Atmospheres containing combustible dusts not included in group E or F, including flour, grain, wood, plastic and chemicals.

PERFORMANCE SPECIFICATIONS

U SERIES

MODEL	BLADE DIAMETER	MOTOR	HP	RPM	INPUT POWER (W)	VOLTAGE/ PHASE/HZ	FULL LOAD AMPERAGE (115)	CFM	EFFICACY (CFM / W)	WEIGHT (LBS)	FAN DIMENSIONS
U12-1	12"	Totally enclosed	1/3	1725	253.2	115/1/60	3.8	1151	4.5	40	14 1/8" H X 14 1/8" W X 17" L
U16-1	16"	Totally enclosed	1/3	1725	290.7	115/1/60	3.8	1728	5.9	49	19 1/8" H X 19 1/8" W X 17" L
U16-4		Explosion proof	1/3	1725	290.7	115/1/60	6.8	1728	5.9	54	
U18-1	18"	Totally enclosed	1/3	1725	358.8	115/1/60	3.8	2509	7	52	21 3/8" H X 21 3/8" W X 17" L
U18-4		Explosion proof	1/3	1725	358.8	115/1/60	6.8	2509	7	57	

U-HD SERIES - HEAVY DUTY

MODEL	BLADE DIAMETER	MOTOR	HP	RPM	INPUT POWER (W)	VOLTAGE/ PHASE/HZ	FULL LOAD AMPERAGE (115)	CFM	EFFICACY (CFM / W)	WEIGHT (LBS)	FAN DIMENSIONS
U16-1HD	16"	Totally enclosed	1/2	1725	462.2	115/230/1/60	8.8	2232	4.8	64	19 1/8" H X 19 1/8" W X 17" L
U16-4HD		Explosion proof	1/2	1725	462.2	115/230/1/60	8.0	2232	4.8	83	
U18-1HD	18"	Totally enclosed	3/4	1725	562.8	115/230/1/60	11	2836	5	78	21 3/8" H X 21 3/8" W X 17" L
U18-4HD		Explosion proof	3/4	1725	562.8	115/230/1/60	10.8	2836	5	96	
U20-1HD	20"	Totally enclosed	1	1725	885	115/230/1/60	13.4	3650	4.1	98	24 3/8" H X 24 5/14" W X 17" L
U20-4HD		Explosion proof	1	1725	885	115/230/1/60	13.4	3650	4.1	118	
U24-1HD	24"	Totally enclosed	1 1/2	1725	1060.8	115/230/1/60	15.2	4822	4.5	112	26 1/8" H X 26 1/8" W X 17" L
U24-4HD		Explosion proof	1 1/2	1725	1060.8	115/230/1/60	19	4822	4.5	134	

Fan testing and performance was determined in accordance with ANSI/AMCA Standard 230-15, Figure 2B1 setup.

Speed (rpm) shown is nominal. Performance is based on actual speed of test.

Performance ratings apply at free delivery only.

Performance ratings DO NOT include the effect of appurtenances.

All -4HD utility fans have a single speed, dual voltage explosion proof motor that meets and conforms to all the standards that are listed below.

The units are available in various configurations and sizes to satisfy almost any application. These fans produce high volumes of air in compact and efficient designs. Sizes range from 12" up to 24" blade diameters. Available with totally enclosed or explosion proof motors ranging in size from 1/3HP to 1/2HP. Entire fan assemblies are certified as shown.

All U series utility fans are finished in a tough powder coat finish with cadmium plated safety guards. All motors are ball bearing and require no maintenance. Voltages other than those listed (including 50HZ) are available. Consult factory. All units are equipped with 6 feet of cord with a plug (explosion proof units are minus plug). Available accessories include hanger bars and hooks, collar adaptors, flexible hoses, hose connectors and misting adaptor kits.