



2 Speed Standard Wall Exhaust Fans with EC Motor

SD08-EC, SD10-EC



FEATURES

- Smooth, quiet, reliable, maintenance free operation.
- Durable steel construction with grey powder coat finish.
- 8" and 10" sizes.
- High efficiency EC motor
- 2 speed with optional speed control CNSC08/10EC (sold separately)
- Totally enclosed with sealed ball bearings
- Quiet, aluminum shutters with tie bar to maximize airflow and a magnet to prevent flapping and provide a superior seal.
- Zinc plated OSHA guard.
- Fans fully assembled.
- Easy to install. Mount fan using four screws.

AIR CHANGES PER MINUTE

To determine the proper fan for your applications, use the following formula.

Number of cubic feet in room / Number of minutes per air change
= Required CFM Capacity

EXAMPLE: A general office, (see chart) which requires an air change every ten minutes, would require the following fan capacity.

If the office is 100' x 40' x 10' = 40,000 cubic ft
40,000 cubic ft / 10 minutes per air change = 4000 Required CFM

From the chart, you would select a fan that is rated at 4000 CFM at 1/8" S.P. (Static Pressure)

PERFORMANCE SPECIFICATIONS

MODEL	BLADE DIAMETER	HP	SPEED	VOLTAGE	MAX AMPS	RPM	CFM	dB(A) @5 ft	WEIGHT (LBS)
SD08-EC	8"	32W	2 Speed	115	0.27	1800/1300	360/300	48	13
SD10-EC	10"	32W	2 Speed	115	0.27	1800/1300	690/580	55	15

Please note: The above is subject to change without notice as these are still in development.

DIMENSIONS

MODEL	A x A SQUARE	B	C	D (c/c)	E SQR	N (# OF LOUVRES)	FRAMING
SD08-EC	13 x 13	8 7/8"	5 3/16"	11"	9 3/4"	2	10" x 10"
SD10-EC	15 x 15	8 7/8"	5 3/16"	13"	11 3/4"	3	12" x 12"

Canarm/LFI's standard fans follow a tradition of quality in design, materials and construction. All our standard fans are developed to be efficient and economically priced. Fans are now available with EC motors allowing you to save up to 70% on energy costs.

ACCESSORIES

- Grey plastic weather hood
- Galvanized metal hood
 - 2 speed switch
 - Thermostat

For a complete listing of all available hoods, see Hoods page.

For all available control options, see Controls & Thermostats section.

Application	Minutes per Air Change	Application	Minutes per Air Change
Assembly Hall	7	Church	15
Attic	2	Classroom	6
Auditorium	10	Dance Hall	5
Barber Shop	6	Department Store	6
Basement	8	Dry Cleaning	5
Battery Room	4	Engine Room	6
Boiler Room	1	Factory	6
Bowling Alley	5	Forge Room	3
Foundry	4	Pressing Room	1
Garage	5	Projection Booth	2
General Office	10	Summer Cooling	1
Gymnasium	8	Toilet	3
Laundry	2	Transformer Room	1
Locker Room	3	Warehouse	12
Machine Shop	8	Welding Shop	2
Plating Room	3		

