

PREMIUM COURSE BOOK

React Hooks — **useState**

þ°þēþŽþŸ • þ–þ×þí þñþƒ þòþÓ þŽþìþß þÊþŸþ-þ• • þ±þ-þîþÜþßþ• þæþǣ þ”þôþ
 þ”þÊþŽþ’þǺþàþß A 4 þ•þŽþóþîþ~þǣþǣ þŸþíþªþŸ þ—þŽþ’þóþíþ®þ— þ—þŽþ
 þ”þôþØþôþØþ£ þ•þŽþªþÔþ» þ

5 Key Words

ბ•ბჭობიბ~ბაბაბბ•

ბობ•ბჭიბებბ• ბაბობაბ~ბ~ბბ• ბაბა ბ"ბობობობობე ბ•ბჭობობ» პაბჭ

3.....

1 ბბბ¼ბობბ•
ბობე ბჭა — ბ"ბაბაბობაბბ• R e a c t

4.....

2 ბბბ¼ბობბ•
u s e S t a t e — ბ"ბობობ×ბაბბ• ბ"ბ

5.....

3 ბბბ¼ბობბ•
ბ|ბÓ — ბ"ბებაბ•ბ°ბ~ბაბბ• ბ®ბობი ბ"ბბჭბ

6.....

4 ბბბ¼ბობბ•
ბბბები ბობობობობე ბÝბჭბაბა — ბაბობაბ

7.....

5 ბბბ¼ბობბ•
u s e E f f e c t — ბობობებებ~ბბ•ბი ბ"ბიბ-ბჭობ

CHAPTER 1

React Hooks.

þéþóþ· þþþû þþþäþìþç þ-þ^aþøþç þðþ·þíþ^aþðþ· þ·þžþçþîþüþã þÊþã þåþõþ· .þ"þðþžþαþà

oäp'p— pÝp

[illegible]

ՈՐԻՔԻՆՅԻՒՆ ԻՔԻՆՅԻՒՆ

[02:15]

CHAPTER 2

useState — Ё"ёёёёёёёёёё

```
@ё' ёёёёёё ёёёёёёёёё useState. ёёёё ё"ёёёёёёёёёё ё"ёёёёёёёёё: const [count, setCount] =
  useState(0)
  ёёёёёёёёёё ё"ёёёёёёёёё ё"ёёёёёёёёё ёёёё ёёёёёёёёё - count. ёёёёёёёёёё
  useState(0) ёёёёёё — Ёёёёёёёёёёёёё ёёёёёё ёёёёёёёёёёёёёёёё ёёёёёёёёёёёёёёёё.
  ёёёёёёёёё useState.
```

0) — Ё"ёё
 ёё ё"ёёёёёё
 ёёёё ёёёё

[04:20]

CHAPTER 3

ʁiˈbɔ — ʁˈpɛ̃pãpˈbɔpˈpãpɪʁp• ʁˈpɔ̃pĩ ʁˈp

ʁñp© ʁˈpÄpàpðpɪʁp• ʁòbÓ ʁÊpðpˈpˈ ʁ±pŽpèpɪʁp• ʁâpÈpìpã ʁêpçp÷ ʁ°pÛp®pç ʁápˌpû ʁŽpèpè — ʁâp
 ʁÝpîpðpˈpˈ ʁÖpˌpŽpˈpîpɪʁp• .ʁˈpɛ̃pãpˈbɔpˈpã ʁ®pɔ̃pĩ ʁòpè .Kp•p-ʁîpÓ
 ʁ-pàpãpÈ ʁîpɪ setCount(count + 1) ʁæpóʁpìpˈpĩ console.log(count) ʁåp÷ .ʁˈp
 ʁòbÓ KpŽpÈpîpðp• ʁêpŽpÄpðp÷p• ʁ®pœpÛpf ʁæpã ʁép-ʁè .
 ʁòpɪʁp•pªpɪʁp• ʁšpóʁpªpˈpˈpɪʁp• ʁápªpˈpˈp³p• ʁˈpªpóʁp ʁɪʁp• ʁˈpãpðpðpɪʁp• ʁ•pðp ʁ— ʁñp•pˌp‡ : s e t
 ʁ™pªp£p÷p• .

ʁû — ʁˈpɛ̃
 ʁɪ ʁÊpðpãp
 ʁˈpɪʁp• ʁápª

[06:10]

CHAPTER 4

How to Use useEffect to Update the UI

When you use `useEffect` to update the UI, you need to make sure that the effect is only run once. This is because `useEffect` is called every time the component re-renders. If you don't make sure it's only run once, you'll end up with a stale closure.

For example, if you have a component that updates the UI every 1000ms, you can use `useEffect` to update the UI. However, you need to make sure that the effect is only run once. This is because `useEffect` is called every time the component re-renders. If you don't make sure it's only run once, you'll end up with a stale closure.

Here's an example of how to use `useEffect` to update the UI:

```

import { useState, useEffect } from 'react';

function App() {
  const [count, setCount] = useState(0);

  // This effect will only run once, when the component is first rendered.
  // It will update the UI every 1000ms.
  useEffect(() => {
    setCount(count + 1);
  }, [count]);

  return (
    <div>
      <span>Count: {count}</span>
      <button onClick={() => setCount(count + 1)}>Increment</button>
    </div>
  );
}

```

CHAPTER 5

```

    useEffect(() => { console.log('runs once') }, []).useEffect(() => {
      componentDidMount()
      useEffect(() => {
        return () => clearInterval(timer)
      })
    })
  }
}

```