

Lecture 3 – Types and Classes

Violet Ka I Pun

violet@ifi.uio.no

- ▶ A type represents a number of values

- ▶ A type represents a number of values
- ▶ Examples:
 - **integers** $\dots, -2, -1, 0, 1, 2, \dots$, type `Int`
 - **pairs** of integers, type `(Int, Int)`
 - **lists** of pair of integers, type `[(Int, Int)]`
 - **functions** from integers to integers, type `Int -> Int`
 - **user-defined types** as data `Mybool = Usann | Sann`

- ▶ A type represents a number of values
- ▶ Examples:
 - integers $\dots, -2, -1, 0, 1, 2, \dots$, type `Int`
 - pairs of integers, type `(Int, Int)`
 - lists of pair of integers, type `[(Int, Int)]`
 - functions from integers to integers, type `Int -> Int`
 - user-defined types as data `Mybool = Usann | Sann`
- ▶ Each Haskell expression has a type: `<expr> :: <type>`

- ▶ A type represents a number of values
- ▶ Examples:
 - integers $\dots, -2, -1, 0, 1, 2, \dots$, type `Int`
 - pairs of integers, type `(Int, Int)`
 - lists of pair of integers, type `[(Int, Int)]`
 - functions from integers to integers, type `Int -> Int`
 - user-defined types as data `Mybool = Usann | Sann`
- ▶ Each Haskell expression has a type: `<expr> :: <type>`
`> :type expr` (or `:t expr`) returns the type in GHCi

- ▶ A type represents a number of values
- ▶ Examples:
 - integers $\dots, -2, -1, 0, 1, 2, \dots$, type `Int`
 - pairs of integers, type `(Int, Int)`
 - lists of pair of integers, type `[(Int, Int)]`
 - functions from integers to integers, type `Int -> Int`
 - user-defined types as data `Mybool = Usann | Sann`
- ▶ Each Haskell expression has a type: `<expr> :: <type>`
`> :type expr` (or `:t expr`) returns the type in GHCi
- ▶ Type does not change during [evaluation](#)

Apply a function to one or more arguments of the wrong type, e.g.,

```
> 1 + False  
ERROR
```


Apply a function to one or more arguments of the wrong type, e.g.,

```
> 1 + False  
ERROR
```

- ▶ + is supposed to add two **numbers**, but False is a **logical** value

Apply a function to one or more arguments of the wrong type, e.g.,

```
> 1 + False  
ERROR
```

- ▶ + is supposed to add two **numbers**, but False is a **logical** value

All type errors are found at **compile** time

- ▶ makes programs **safer** and **faster**
by removing the need for type checks at run time.

- ▶ integers: $\dots, -2, -1, 0, 1, 2, \dots$ type `Int` and `Integer`

Basic types

- ▶ integers: `..., -2, -1, 0, 1, 2, ...,` type `Int` and `Integer`
- ▶ boolean values: `True, False,` type `Bool`

Basic types

- ▶ integers: `..., -2, -1, 0, 1, 2, ...,` type `Int` and `Integer`
- ▶ boolean values: `True, False,` type `Bool`
- ▶ symbols: `..., 'A', ..., 'z', ...,` type `Char`

Basic types

- ▶ integers: `..., -2, -1, 0, 1, 2, ...,` type `Int` and `Integer`
- ▶ boolean values: `True, False,` type `Bool`
- ▶ symbols: `..., 'A', ..., 'z', ...,` type `Char`
- ▶ strings: `'abc',` type `String`

Basic types

- ▶ integers: `..., -2, -1, 0, 1, 2, ...,` type `Int` and `Integer`
- ▶ boolean values: `True, False,` type `Bool`
- ▶ symbols: `..., 'A', ..., 'z', ...,` type `Char`
- ▶ strings: `'abc',` type `String`
- ▶ fractions: `1.2, 1.234,` type `Float`

Basic types, each with a set of operators

- ▶ integers: `..., -2, -1, 0, 1, 2, ...`, type `Int` and `Integer`
`+, -, *, div, mod`
- ▶ boolean values: `True, False`, type `Bool`
- ▶ symbols: `..., 'A', ..., 'z', ...`, type `Char`
- ▶ strings: `'abc'`, type `String`
- ▶ fractions: `1.2, 1.234`, type `Float`

Basic types, each with a set of operators

- ▶ integers: `..., -2, -1, 0, 1, 2, ...`, type `Int` and `Integer`
`+, -, *, div, mod`
- ▶ boolean values: `True, False`, type `Bool`
`not, ||, &&, or, and`
- ▶ symbols: `..., 'A', ..., 'z', ...`, type `Char`
- ▶ strings: `'abc'`, type `String`
- ▶ fractions: `1.2, 1.234`, type `Float`

Basic types, each with a set of operators

- ▶ integers: `..., -2, -1, 0, 1, 2, ...`, type `Int` and `Integer`
`+, -, *, div, mod`
- ▶ boolean values: `True, False`, type `Bool`
`not, ||, &&, or, and`
- ▶ symbols: `..., 'A', ..., 'z', ...`, type `Char`
`toUpper, toLower` in `Data.Char`
- ▶ strings: `'abc'`, type `String`
- ▶ fractions: `1.2, 1.234`, type `Float`

Basic types, each with a set of operators

- ▶ integers: `..., -2, -1, 0, 1, 2, ...`, type `Int` and `Integer`
`+, -, *, div, mod`
- ▶ boolean values: `True, False`, type `Bool`
`not, ||, &&, or, and`
- ▶ symbols: `..., 'A', ..., 'z', ...`, type `Char`
`toUpper, toLower` in `Data.Char`
- ▶ strings: `'abc'`, type `String`
`++, head, tail`
- ▶ fractions: `1.2, 1.234`, type `Float`

Basic types, each with a set of operators

- ▶ integers: `..., -2, -1, 0, 1, 2, ...`, type `Int` and `Integer`
`+, -, *, div, mod`
- ▶ boolean values: `True, False`, type `Bool`
`not, ||, &&, or, and`
- ▶ symbols: `..., 'A', ..., 'z', ...`, type `Char`
`toUpper, toLower` in [Data.Char](#)
- ▶ strings: `'abc'`, type `String`
`++, head, tail`
- ▶ fractions: `1.2, 1.234`, type `Float`
`+, -, *, /`

Basic types come also with operators that return values of another types

- ▶ Float:

`==,<,... :: (Float,Float) -> Bool`

- ▶ Int:

`==,<,... :: (Int, Int) -> Bool`

- ▶ String:

`length :: [a] -> Int,`

`==,<,... :: (String,String) -> Bool`

Basic types come also with operators that return values of another types

- ▶ Float:

`==,<,... :: (Float,Float) -> Bool`

- ▶ Int:

`==,<,... :: (Int, Int) -> Bool`

- ▶ String:

`length :: [a] -> Int,`

`==,<,... :: (String,String) -> Bool`

- ▶ Char:

`ord :: Char -> Int, chr :: Int -> Char,`

`isDigit :: Char -> Bool`

- ▶ Lists: `[typeE]`
- ▶ Product (Cartesian): `(typeL, typeR)`
- ▶ Functions: `typeK -> typeM`

- ▶ Lists: `[typeE]`
- ▶ Product (Cartesian): `(typeL, typeR)`
- ▶ Functions: `typeK -> typeM`
- ▶ Syntax for types:

`T ::= name | [T] | ({T,} T, T) | T->T | (T->T)`

- ▶ Lists: $[\text{typeE}]$
- ▶ Product (Cartesian): $(\text{typeL}, \text{typeR})$
- ▶ Functions: $\text{typeK} \rightarrow \text{typeM}$
- ▶ Syntax for types:
$$T ::= \text{name} \mid [T] \mid (\{T, \} T, T) \mid T \rightarrow T \mid (T \rightarrow T)$$
- ▶ **Unique** AST for $a \rightarrow b \rightarrow c$?

A sequence of values of the **same** type

```
[False, True, False]  ::  [Bool]
```

A sequence of values of the **same** type

```
[False, True, False]  ::  [Bool]
['a', 'b', 'c', 'd']  ::  [Char]
```

A sequence of values of the **same** type

```
[False,True,False]  ::  [Bool]
['a','b','c','d']   ::  [Char]
[1,2,3]              ::  [Int]
```

A sequence of values of the **same** type

```
[False,True,False]  ::  [Bool]
['a','b','c','d']   ::  [Char]
      [1,2,3]        ::  [Int]
      [3.5,1.4,7.8]  ::  [Float]
```

A sequence of values of the **same** type

```
[False,True,False]  ::  [Bool]
['a','b','c','d']   ::  [Char]
[1,2,3]              ::  [Int]
[3.5,1.4,7.8]        ::  [Float]
[5,6,9.2]            ::  [Float]
```

A sequence of values of the **same** type

```
[False,True,False]  ::  [Bool]
['a','b','c','d']   ::  [Char]
[1,2,3]              ::  [Int]
[3.5,1.4,7.8]        ::  [Float]
[5,6,9.2]            ::  [Float]
```

A sequence of values of the **same** type

```
[False,True,False]  ::  [Bool]
['a','b','c','d']   ::  [Char]
[1,2,3]              ::  [Int]
[3.5,1.4,7.8]        ::  [Float]
[5,6,9.2]            ::  [Float]
```

- The type of the elements are unrestricted

A sequence of values of the **same** type

```
[False,True,False]  ::  [Bool]
['a','b','c','d']   ::  [Char]
[1,2,3]              ::  [Int]
[3.5,1.4,7.8]        ::  [Float]
[5,6,9.2]            ::  [Float]
```

- ▶ The type of the elements are unrestricted
- ▶ What is the size of a list of type **[Int]**?

Lists

- ▶ Given `typeE` we have a type of lists `[typeE]`

- ▶ Given `typeE` we have a type of lists `[typeE]`
- ▶ **Construction:** `[]` and
for `x::typeE, l::[typeE]`, becomes `x:l :: [typeE]`

- ▶ Given `typeE` we have a type of lists `[typeE]`
- ▶ **Construction:** `[]` and
for `x::typeE, l::[typeE]`, becomes `x:l :: [typeE]`
`[1, 1.2] = 1 : 1.2 : [] :: (Fractional t) => [t]`

- ▶ Given `typeE` we have a type of lists `[typeE]`
- ▶ **Construction:** `[]` and
for `x::typeE, l::[typeE]`, becomes `x:l :: [typeE]`
`[1, 1.2] = 1 : 1.2 : [] :: (Fractional t) => [t]`
- ▶ **Destruction:** `head (x:l) = x` `tail (x:l) = l`

- ▶ Given `typeE` we have a type of lists `[typeE]`
- ▶ **Construction:** `[]` and
for `x::typeE, l::[typeE]`, becomes `x:l :: [typeE]`
`[1, 1.2] = 1 : 1.2 : [] :: (Fractional t) => [t]`
- ▶ **Destruction:** `head (x:l) = x` `tail (x:l) = l`
- ▶ Length function: `length : [a] -> Int` (polymorphic!)

- ▶ Given `typeE` we have a type of lists `[typeE]`
- ▶ **Construction:** `[]` and
for `x::typeE, l::[typeE]`, becomes `x:l :: [typeE]`
`[1, 1.2] = 1 : 1.2 : [] :: (Fractional t) => [t]`
- ▶ **Destruction:** `head (x:l) = x` `tail (x:l) = l`
- ▶ Length function: `length : [a] -> Int` (polymorphic!)
- ▶ Try: `let e=1 in [e]==[1]`, `let e=12 in [e]==[1,2]`

- ▶ Given `typeE` we have a type of lists `[typeE]`
- ▶ **Construction:** `[]` and
for `x::typeE, l::[typeE]`, becomes `x:l :: [typeE]`
`[1, 1.2] = 1 : 1.2 : [] :: (Fractional t) => [t]`
- ▶ **Destruction:** `head (x:l) = x` `tail (x:l) = l`
- ▶ Length function: `length : [a] -> Int` (polymorphic!)
- ▶ Try: **let** `e=1 in [e]==[1]`, **let** `e=12 in [e]==[1,2]`
- ▶ Alternative notation
`[1,2,3] = 1:[2,3] = 1:2:[3] = 1:2:3:[]`

- ▶ Given typeE we have a type of lists `[typeE]`
- ▶ **Construction**: `[]` and
for `x::typeE, l::[typeE]`, becomes `x:l :: [typeE]`
`[1, 1.2] = 1 : 1.2 : [] :: (Fractional t) => [t]`
- ▶ **Destruction**: `head (x:l) = x` `tail (x:l) = l`
- ▶ Length function: `length : [a] -> Int` (polymorphic!)
- ▶ Try: `let e=1 in [e]==[1]`, `let e=12 in [e]==[1,2]`
- ▶ Alternative notation
`[1,2,3] = 1:[2,3] = 1:2:[3] = 1:2:3:[]`
- ▶ **Equality**: if typeE has `==`,
then `[typeE]` has `==`,
namely: same length and element-wise equality

- ▶ Given `typeE` we have a type of lists `[typeE]`
- ▶ **Construction**: `[]` and
for `x::typeE, l::[typeE]`, becomes `x:l :: [typeE]`
`[1, 1.2] = 1 : 1.2 : [] :: (Fractional t) => [t]`
- ▶ **Destruction**: `head (x:l) = x` `tail (x:l) = l`
- ▶ Length function: `length : [a] -> Int` (polymorphic!)
- ▶ Try: `let e=1 in [e]==[1]`, `let e=1.2 in [e]==[1,2]`
- ▶ Alternative notation
`[1,2,3] = 1:[2,3] = 1:2:[3] = 1:2:3:[]`
- ▶ **Equality**: if `typeE` has `==`,
then `[typeE]` has `==`,
namely: same length and element-wise equality
- ▶ If `typeE` is an instance of `Show`, so is `[typeE]`.

- ▶ Given `typeE` we have a type of lists `[typeE]`
- ▶ **Construction:** `[]` and
for `x::typeE, l::[typeE]`, becomes `x:l :: [typeE]`
`[1, 1.2] = 1 : 1.2 : [] :: (Fractional t) => [t]`
- ▶ **Destruction:** `head (x:l) = x` `tail (x:l) = l`
- ▶ Length function: `length : [a] -> Int` (polymorphic!)
- ▶ Try: `let e=1 in [e]==[1]`, `let e=1.2 in [e]==[1,2]`
- ▶ Alternative notation
`[1,2,3] = 1:[2,3] = 1:2:[3] = 1:2:3:[]`
- ▶ **Equality:** if `typeE` has `==`,
then `[typeE]` has `==`,
namely: same length and element-wise equality
- ▶ If `typeE` is an instance of `Show`, so is `[typeE]`.
- ▶ If `typeE` is an instance of `Ord`, so is `[typeE]`.

- ▶ Given `typeE` we have a type of lists `[typeE]`
- ▶ **Construction**: `[]` and
for `x::typeE, l::[typeE]`, becomes `x:l :: [typeE]`
`[1, 1.2] = 1 : 1.2 : [] :: (Fractional t) => [t]`
- ▶ **Destruction**: `head (x:l) = x` `tail (x:l) = l`
- ▶ Length function: `length : [a] -> Int` (polymorphic!)
- ▶ Try: `let e=1 in [e]==[1]`, `let e=1.2 in [e]==[1,2]`
- ▶ Alternative notation
`[1,2,3] = 1:[2,3] = 1:2:[3] = 1:2:3:[]`
- ▶ **Equality**: if `typeE` has `==`,
then `[typeE]` has `==`,
namely: same length and element-wise equality
- ▶ If `typeE` is an instance of `Show`, so is `[typeE]`.
- ▶ If `typeE` is an instance of `Ord`, so is `[typeE]`.

`Show` and `Ord` are type classes

Cartesian Product (pairs/tuples)

A sequence of values of **different** types:

Cartesian Product (pairs/tuples)

A sequence of values of **different** types:

`(False, True) :: (Bool, Bool)` **(pair)**

Cartesian Product (pairs/tuples)

A sequence of values of **different** types:

```
(False,True)    :: (Bool,Bool)      (pair)
(“Yes”, 'a', True) :: (String,Char,Bool) (triple)
```

Cartesian Product (pairs/tuples)

A sequence of values of **different** types:

<code>(False,True)</code>	<code>::</code>	<code>(Bool,Bool)</code>	(pair)
<code>('‘Yes’’,’a’,True)</code>	<code>::</code>	<code>(String,Char,Bool)</code>	(triple)
<code>(t₁, t₂, ...t_n)</code>			(n-tuple)

Cartesian Product (pairs/tuples)

A sequence of values of **different** types:

<code>(False, True)</code>	<code>::</code>	<code>(Bool, Bool)</code>	(pair)
<code>(“Yes”, 'a', True)</code>	<code>::</code>	<code>(String, Char, Bool)</code>	(triple)
<code>(t₁, t₂, ... t_n)</code>			(n-tuple)
<code>(t)</code>			not permitted

Cartesian Product (pairs/tuples)

A sequence of values of **different** types:

<code>(False, True)</code>	<code>::</code>	<code>(Bool, Bool)</code>	(pair)
<code>(“Yes”, 'a', True)</code>	<code>::</code>	<code>(String, Char, Bool)</code>	(triple)
<code>(t₁, t₂, ... t_n)</code>			(n-tuple)
<code>(t)</code>			not permitted

- The number of components in a tuple is called its **arity**

Cartesian Product (pairs/tuples)

A sequence of values of **different** types:

<code>(False, True)</code>	<code>::</code>	<code>(Bool, Bool)</code>	(pair)
<code>('Yes', 'a', True)</code>	<code>::</code>	<code>(String, Char, Bool)</code>	(triple)
<code>(t₁, t₂, ... t_n)</code>			(n-tuple)
<code>(t)</code>			not permitted

- ▶ The number of components in a tuple is called its **arity**
- ▶ The type of the components is unrestricted, e.g.:

Cartesian Product (pairs/tuples)

A sequence of values of **different** types:

<code>(False,True)</code>	<code>::</code>	<code>(Bool,Bool)</code>	(pair)
<code>('‘Yes’’,’a’,True)</code>	<code>::</code>	<code>(String,Char,Bool)</code>	(triple)
<code>(t₁, t₂, ...t_n)</code>			(n-tuple)
<code>(t)</code>			not permitted

- ▶ The number of components in a tuple is called its **arity**
- ▶ The type of the components is unrestricted, e.g.:
 - `('a',(False,'b')) :: (Char,(Bool,Char))`
 - `(True,['a','b']) :: (Bool,[Char])`

Cartesian Product (pairs/tuples)

A sequence of values of **different** types:

<code>(False,True)</code>	<code>::</code>	<code>(Bool,Bool)</code>	(pair)
<code>('Yes','a',True)</code>	<code>::</code>	<code>(String,Char,Bool)</code>	(triple)
<code>(t₁, t₂, ...t_n)</code>			(n-tuple)
<code>(t)</code>			not permitted

- ▶ The number of components in a tuple is called its **arity**
- ▶ The type of the components is unrestricted, e.g.:
 - `('a',(False,'b')) :: (Char,(Bool,Char))`
 - `(True,['a','b']) :: (Bool,[Char])`
- ▶ What is the size of a tuple of type `(Char,(Bool,Char))`

Cartesian Product (pairs/tuples)

- ▶ Given `typeL` and `typeR`, we have a type of pairs `(typeL, typeR)`

Cartesian Product (pairs/tuples)

- ▶ Given `typeL` and `typeR`, we have a type of pairs `(typeL, typeR)`
- ▶ **Construction**: for `x :: typeL`, `y :: typeR`,

Cartesian Product (pairs/tuples)

- ▶ Given `typeL` and `typeR`, we have a type of pairs `(typeL, typeR)`
- ▶ **Construction**: for `x :: typeL`, `y :: typeR`,
become `(x,y) :: (typeL, typeR)`

Cartesian Product (pairs/tuples)

- ▶ Given `typeL` and `typeR`, we have a type of pairs `(typeL, typeR)`
- ▶ **Construction**: for `x :: typeL`, `y :: typeR`,
become `(x,y) :: (typeL, typeR)`
`(1, 1.2) :: (Num t, Fractional t1) => (t, t1)`

Cartesian Product (pairs/tuples)

- ▶ Given `typeL` and `typeR`, we have a type of pairs `(typeL, typeR)`
- ▶ **Construction**: for `x :: typeL`, `y :: typeR`,
become `(x,y) :: (typeL, typeR)`
`(1, 1.2) :: (Num t, Fractional t1) => (t, t1)`
- ▶ **Destruction**: `fst (x,y) = x` `snd (x,y) = y`

Cartesian Product (pairs/tuples)

- ▶ Given `typeL` and `typeR`, we have a type of pairs `(typeL, typeR)`
- ▶ **Construction**: for `x :: typeL`, `y :: typeR`,
become `(x,y) :: (typeL, typeR)`
`(1, 1.2) :: (Num t, Fractional t1) => (t, t1)`
- ▶ **Destruction**: `fst (x,y) = x` `snd (x,y) = y`
- ▶ **Equality**: if `typeL` and `typeR` have `==`,
then `(typeL, typeR)` has `==`,
namely: `(x,y) == (x',y')` iff `x==x'` and `y==y'`

Cartesian Product (pairs/tuples)

- ▶ Given `typeL` and `typeR`, we have a type of pairs `(typeL, typeR)`
- ▶ **Construction**: for `x :: typeL`, `y :: typeR`,
become `(x,y) :: (typeL, typeR)`
`(1, 1.2) :: (Num t, Fractional t1) => (t, t1)`
- ▶ **Destruction**: `fst (x,y) = x` `snd (x,y) = y`
- ▶ **Equality**: if `typeL` and `typeR` have `==`,
then `(typeL, typeR)` has `==`,
namely: `(x,y) == (x',y')` iff `x==x'` and `y==y'`
 - If `typeL` and `typeR` are both instances of `Show`,
so is `(typeL, typeR)`.

Cartesian Product (pairs/tuples)

- ▶ Given `typeL` and `typeR`, we have a type of pairs `(typeL, typeR)`
- ▶ **Construction**: for `x :: typeL`, `y :: typeR`,
become `(x,y) :: (typeL, typeR)`
`(1, 1.2) :: (Num t, Fractional t1) => (t, t1)`
- ▶ **Destruction**: `fst (x,y) = x` `snd (x,y) = y`
- ▶ **Equality**: if `typeL` and `typeR` have `==`,
then `(typeL, typeR)` has `==`,
namely: `(x,y) == (x',y')` iff `x==x'` and `y==y'`
 - If `typeL` and `typeR` are both instances of `Show`,
so is `(typeL, typeR)`.
 - If `typeL` and `typeR` are both instances of `Ord`,
so is `(typeL, typeR)`.

Cartesian Product (pairs/tuples)

- ▶ Given `typeL` and `typeR`, we have a type of pairs `(typeL, typeR)`
- ▶ **Construction**: for `x :: typeL`, `y :: typeR`,
become `(x,y) :: (typeL, typeR)`
`(1, 1.2) :: (Num t, Fractional t1) => (t, t1)`
- ▶ **Destruction**: `fst (x,y) = x` `snd (x,y) = y`
- ▶ **Equality**: if `typeL` and `typeR` have `==`,
then `(typeL, typeR)` has `==`,
namely: `(x,y) == (x',y')` iff `x==x'` and `y==y'`
 - If `typeL` and `typeR` are both instances of `Show`,
so is `(typeL, typeR)`.
 - If `typeL` and `typeR` are both instances of `Ord`,
so is `(typeL, typeR)`.

`Show` and `Ord` are type classes

Examples – value :: type

Examples – value :: type

1

Examples – value :: type

1 :: Int

Examples – value :: type

1 :: Int

Num t => t

Examples – value :: type

1 :: Int Num t => t
Int, Float are types Num, Fract are type **classes**
 “1” is overloaded

Examples – value :: type

1 :: Int
2.0 + 1.2 :: Float

Num t => t

Examples – value :: type

1 :: Int
2.0 + 1.2 :: Float

Num t => t
Fractional t => t

Examples – value :: type

1 :: Int
2.0 + 1.2 :: Float
[1, 1.2]

Num t => t
Fractional t => t

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2]			

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2]	=	1.0	

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)			

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1			

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]			

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'			

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []			

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"			

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"	::	[Char]	i.e., String

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"	::	[Char]	i.e., String
["ab", "ab", "cd"]			

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"	::	[Char]	i.e., String
["ab", "ab", "cd"]	::	[[Char]]	i.e., [String]

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"	::	[Char]	i.e., String
["ab", "ab", "cd"]	::	[[Char]]	i.e., [String]
("ab", 12)			

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"	::	[Char]	i.e., String
["ab", "ab", "cd"]	::	[[Char]]	i.e., [String]
("ab", 12)	::	(String, Int)	

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"	::	[Char]	i.e., String
["ab", "ab", "cd"]	::	[[Char]]	i.e., [String]
("ab", 12)	::	(String, Int)	Num t => (String, t)

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"	::	[Char]	i.e., String
["ab", "ab", "cd"]	::	[[Char]]	i.e., [String]
("ab", 12)	::	(String, Int)	Num t => (String, t)
["ab", 12]			

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"	::	[Char]	i.e., String
["ab", "ab", "cd"]	::	[[Char]]	i.e., [String]
("ab", 12)	::	(String, Int)	Num t => (String, t)
["ab", 12]	::	error – list elements must have same type : [t]	

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"	::	[Char]	i.e., String
["ab", "ab", "cd"]	::	[[Char]]	i.e., [String]
("ab", 12)	::	(String, Int)	Num t => (String, t)
["ab", 12]	::	error – list elements must have same type : [t]	
[("ab", 12), ("cd", 24)]			

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"	::	[Char]	i.e., String
["ab", "ab", "cd"]	::	[[Char]]	i.e., [String]
("ab", 12)	::	(String, Int)	Num t => (String, t)
["ab", 12]	::	error – list elements must have same type : [t]	
[("ab", 12), ("cd", 24)]	::	[(String,Num)]	

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"	::	[Char]	i.e., String
["ab", "ab", "cd"]	::	[[Char]]	i.e., [String]
("ab", 12)	::	(String, Int)	Num t => (String, t)
["ab", 12]	::	error – list elements must have same type : [t]	
[("ab", 12), ("cd", 24)]	::	[(String,Num)]	
1 + x			

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"	::	[Char]	i.e., String
["ab", "ab", "cd"]	::	[[Char]]	i.e., [String]
("ab", 12)	::	(String, Int)	Num t => (String, t)
["ab", 12]	::	error – list elements must have same type : [t]	
[("ab", 12), ("cd", 24)]	::	[(String,Num)]	
1 + x	::	error	

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"	::	[Char]	i.e., String
["ab", "ab", "cd"]	::	[[Char]]	i.e., [String]
("ab", 12)	::	(String, Int)	Num t => (String, t)
["ab", 12]	::	error – list elements must have same type : [t]	
[("ab", 12), ("cd", 24)]	::	[(String,Num)]	
1 + x	::	error	
(1 +)			

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"	::	[Char]	i.e., String
["ab", "ab", "cd"]	::	[[Char]]	i.e., [String]
("ab", 12)	::	(String, Int)	Num t => (String, t)
["ab", 12]	::	error – list elements must have same type : [t]	
[("ab", 12), ("cd", 24)]	::	[(String,Num)]	
1 + x	::	error	
(1 +)	::		

Examples – value :: type

1	::	Int	Num t => t
2.0 + 1.2	::	Float	Fractional t => t
[1, 1.2]	::	[Float]	Fractional t => [t]
head [1, 1.2] = 1.0	::		Fractional t => t
-(-1)	::	Int	Num t => t
- - 1	::	error	
[1,2,3]	::	[Int]	Num t => [t]
'a'	::	Char	
'a' : 'b' : []	::	[Char]	
"abc"	::	[Char]	i.e., String
["ab", "ab", "cd"]	::	[[Char]]	i.e., [String]
("ab", 12)	::	(String, Int)	Num t => (String, t)
["ab", 12]	::	error – list elements must have same type : [t]	
[("ab", 12), ("cd", 24)]	::	[(String,Num)]	
1 + x	::	error	
(1 +)	::	Int -> Int	Num a => a -> a

A function:

- ▶ A **mapping** from values of **one** type to values of **another** type

`not :: Bool -> Bool`

A function:

- ▶ A **mapping** from values of **one** type to values of **another** type

```
not   :: Bool -> Bool
even  :: Int  -> Bool
```

Function Types

- ▶ Given `typeK` and `typeM`, we have a type `typeK -> typeM`

Function Types

- ▶ Given `typeK` and `typeM`, we have a type `typeK -> typeM`
- ▶ **Construction**: for `x :: typeK`, `<expr> :: typeM`
`<name> x = <expr>`
 - e.g.: `double x = x+x`

Function Types

- ▶ Given `typeK` and `typeM`, we have a type `typeK -> typeM`
- ▶ **Construction:** for `x :: typeK`, `<expr> :: typeM`
 `<name> x = <expr>`
 - e.g.: `double x = x+x` or
 - e.g.: `\ x -> x+x`

Function Types

- ▶ Given `typeK` and `typeM`, we have a type `typeK -> typeM`
- ▶ **Construction**: for `x :: typeK`, `<expr> :: typeM`
 `<name> x = <expr>`
 – e.g.: `double x = x+x` or
- ▶ `\ x -> <expr>` anonymous function / lambda expression
 – e.g.: `\ x -> x+x`

Function Types

- ▶ Given `typeK` and `typeM`, we have a type `typeK -> typeM`
- ▶ **Construction:** for `x :: typeK`, `<expr> :: typeM`
 `<name> x = <expr>`
 – e.g.: `double x = x+x` or
- ▶ `\ x -> <expr>` **anonymous function / lambda expression**
 – e.g.: `\ x -> x+x` :: `Num t => t -> t`

Function Types

- ▶ Given `typeK` and `typeM`, we have a type `typeK -> typeM`
- ▶ **Construction:** for `x :: typeK`, `<expr> :: typeM`
 `<name> x = <expr>`
 – e.g.: `double x = x+x` or
- ▶ `\ x -> <expr>` **anonymous function / lambda expression**
 – e.g.: `\ x -> x+x :: Num t => t -> t`
 – e.g.: `\ x -> \ y -> x+y`

Function Types

- ▶ Given `typeK` and `typeM`, we have a type `typeK -> typeM`
- ▶ **Construction:** for `x :: typeK`, `<expr> :: typeM`
 `<name> x = <expr>`
 – e.g.: `double x = x+x` or
- ▶ `\ x -> <expr>.....anonymous function / lambda expression`
 – e.g.: `\ x -> x+x :: Num t => t -> t`
 – e.g.: `\ x -> \ y -> x+y :: Num t => t -> t -> t`

Function Types

- ▶ Given `typeK` and `typeM`, we have a type `typeK -> typeM`
- ▶ **Construction:** for `x :: typeK`, `<expr> :: typeM`
 `<name> x = <expr>`
 – e.g.: `double x = x+x` or
- ▶ `\ x -> <expr>.....` **anonymous function / lambda expression**
 – e.g.: `\ x -> x+x :: Num t => t -> t`
 – e.g.: `\ x -> \ y -> x+y :: Num t => t -> t -> t`
- ▶ `f g = \ x -> g x + 1`

Function Types

- ▶ Given `typeK` and `typeM`, we have a type `typeK -> typeM`
- ▶ **Construction:** for `x :: typeK`, `<expr> :: typeM`
 `<name> x = <expr>`
 – e.g.: `double x = x+x` or
- ▶ `\ x -> <expr>.....` **anonymous function / lambda expression**
 – e.g.: `\ x -> x+x :: Num t => t -> t`
 – e.g.: `\ x -> \ y -> x+y :: Num t => t -> t -> t`
- ▶ `f g = \ x -> (g x) + 1`

Function Types

- ▶ Given `typeK` and `typeM`, we have a type `typeK -> typeM`
- ▶ **Construction:** for `x :: typeK`, `<expr> :: typeM`
 `<name> x = <expr>`
 – e.g.: `double x = x+x` or
- ▶ `\ x -> <expr>.....` **anonymous function / lambda expression**
 – e.g.: `\ x -> x+x` `:: Num t => t -> t`
 – e.g.: `\ x -> \ y -> x+y` `:: Num t => t -> t -> t`
- ▶ `f g = \ x -> (g x) + 1`
 `f = \ g -> \ x -> (g x) + 1`

Function Types

- ▶ Given `typeK` and `typeM`, we have a type `typeK -> typeM`
- ▶ **Construction:** for `x :: typeK`, `<expr> :: typeM`
 `<name> x = <expr>`
 – e.g.: `double x = x+x` or
- ▶ `\ x -> <expr>.....` **anonymous function / lambda expression**
 – e.g.: `\ x -> x+x :: Num t => t -> t`
 – e.g.: `\ x -> \ y -> x+y :: Num t => t -> t -> t`
- ▶ `f g = \ x -> (g x) + 1`
 `f = \ g -> \ x -> (g x) + 1 , or f = \ g x -> (g x) + 1`

Function Types

- ▶ Given typeK and typeM, we have a type **typeK -> typeM**
- ▶ **Construction**: for $x :: \text{typeK}$, $\langle \text{expr} \rangle :: \text{typeM}$
 - $\langle \text{name} \rangle \ x = \langle \text{expr} \rangle$
 - e.g.: `double x = x+x` or
- ▶ $\backslash \ x \rightarrow \langle \text{expr} \rangle \dots\dots\dots$ **anonymous function / lambda expression**
 - e.g.: $\backslash \ x \rightarrow x+x \quad :: \text{Num } t \Rightarrow t \rightarrow t$
 - e.g.: $\backslash \ x \rightarrow \backslash \ y \rightarrow x+y \quad :: \text{Num } t \Rightarrow t \rightarrow t \rightarrow t$
- ▶ $f \ g = \backslash \ x \rightarrow (g \ x) + 1$
 $f = \backslash \ g \rightarrow \backslash \ x \rightarrow (g \ x) + 1$, or **$f = \backslash \ g \ x \rightarrow (g \ x) + 1$**

NOT lambda expression

Function Types

- ▶ Given `typeK` and `typeM`, we have a type `typeK -> typeM`
- ▶ **Construction:** for `x :: typeK`, `<expr> :: typeM`
 `<name> x = <expr>`
 – e.g.: `double x = x+x` or
- ▶ `\ x -> <expr>.....` **anonymous function / lambda expression**
 – e.g.: `\ x -> x+x` `:: Num t => t -> t`
 – e.g.: `\ x -> \ y -> x+y` `:: Num t => t -> t -> t`
- ▶ `f g = \ x -> (g x) + 1`
 `f = \ g -> \ x -> (g x) + 1` , or `f = \ g x -> (g x) + 1`
 `f ::`

Function Types

- ▶ Given typeK and typeM, we have a type **typeK -> typeM**
- ▶ **Construction:** for $x :: \text{typeK}$, $\langle \text{expr} \rangle :: \text{typeM}$
 $\langle \text{name} \rangle \ x = \langle \text{expr} \rangle$
 – e.g.: `double x = x+x` or
- ▶ $\backslash \ x \rightarrow \langle \text{expr} \rangle \dots\dots\dots$ **anonymous function / lambda expression**
 – e.g.: $\backslash \ x \rightarrow x+x \quad :: \text{Num } t \Rightarrow t \rightarrow t$
 – e.g.: $\backslash \ x \rightarrow \backslash \ y \rightarrow x+y \quad :: \text{Num } t \Rightarrow t \rightarrow t \rightarrow t$
- ▶ $f \ g = \backslash \ x \rightarrow (g \ x) + 1$
 $f = \backslash \ g \rightarrow \backslash \ x \rightarrow (g \ x) + 1$, or $f = \backslash \ g \ x \rightarrow (g \ x) + 1$
 $f :: \text{Num } a \Rightarrow (t \rightarrow a) \rightarrow t \rightarrow a$

Function Types

- ▶ Given typeK and typeM, we have a type **typeK -> typeM**
- ▶ **Construction:** for $x :: \text{typeK}$, $\langle \text{expr} \rangle :: \text{typeM}$
 $\langle \text{name} \rangle \ x = \langle \text{expr} \rangle$
 – e.g.: `double x = x+x` or
- ▶ $\backslash \ x \rightarrow \langle \text{expr} \rangle \dots\dots\dots$ **anonymous function / lambda expression**
 – e.g.: $\backslash \ x \rightarrow x+x \quad :: \text{Num } t \Rightarrow t \rightarrow t$
 – e.g.: $\backslash \ x \rightarrow \backslash \ y \rightarrow x+y \quad :: \text{Num } t \Rightarrow t \rightarrow t \rightarrow t$
- ▶ $f \ g = \backslash \ x \rightarrow (g \ x) + 1$
 $f = \backslash \ g \rightarrow \backslash \ x \rightarrow (g \ x) + 1$, or $f = \backslash \ g \ x \rightarrow (g \ x) + 1$
 $f :: \text{Num } a \Rightarrow (t \rightarrow a) \rightarrow t \rightarrow a$ **$g :: ?$**

Function Types

- ▶ Given typeK and typeM, we have a type **typeK -> typeM**
- ▶ **Construction:** for $x :: \text{typeK}$, $\langle \text{expr} \rangle :: \text{typeM}$
 $\langle \text{name} \rangle \ x = \langle \text{expr} \rangle$
– e.g.: `double x = x+x` or
- ▶ $\backslash \ x \rightarrow \langle \text{expr} \rangle \dots\dots\dots$ **anonymous function / lambda expression**
– e.g.: $\backslash \ x \rightarrow x+x \quad :: \text{Num } t \Rightarrow t \rightarrow t$
– e.g.: $\backslash \ x \rightarrow \backslash \ y \rightarrow x+y \quad :: \text{Num } t \Rightarrow t \rightarrow t \rightarrow t$
- ▶ $f \ g = \backslash \ x \rightarrow (g \ x) + 1$
 $f = \backslash \ g \rightarrow \backslash \ x \rightarrow (g \ x) + 1$, or $f = \backslash \ g \ x \rightarrow (g \ x) + 1$
 $f :: \text{Num } a \Rightarrow (t \rightarrow a) \rightarrow t \rightarrow a$ **$g :: ?$**
- ▶ **Destruction:** function application, $\langle \text{function} \rangle \ \langle \text{expr} \rangle$:
– `double 2` $(\backslash \ x \rightarrow x+x) \ 2$

Function Types

- ▶ Given typeK and typeM, we have a type **typeK -> typeM**
- ▶ **Construction:** for $x :: \text{typeK}$, $\langle \text{expr} \rangle :: \text{typeM}$
 $\langle \text{name} \rangle \ x = \langle \text{expr} \rangle$
– e.g.: `double x = x+x` or
- ▶ $\backslash \ x \rightarrow \langle \text{expr} \rangle \dots\dots\dots$ **anonymous function / lambda expression**
– e.g.: $\backslash \ x \rightarrow x+x \quad :: \text{Num } t \Rightarrow t \rightarrow t$
– e.g.: $\backslash \ x \rightarrow \backslash \ y \rightarrow x+y \quad :: \text{Num } t \Rightarrow t \rightarrow t \rightarrow t$
- ▶ $f \ g = \backslash \ x \rightarrow (g \ x) + 1$
 $f = \backslash \ g \rightarrow \backslash \ x \rightarrow (g \ x) + 1$, or $f = \backslash \ g \ x \rightarrow (g \ x) + 1$
 $f :: \text{Num } a \Rightarrow (t \rightarrow a) \rightarrow t \rightarrow a$ **$g :: ?$**
- ▶ **Destruction:** function application, $\langle \text{function} \rangle \ \langle \text{expr} \rangle$:
– `double 2 ($\backslash \ x \rightarrow x+x$) 2 == 4`

Function Types

- ▶ Given typeK and typeM, we have a type **typeK -> typeM**
- ▶ **Construction:** for $x :: \text{typeK}$, $\langle \text{expr} \rangle :: \text{typeM}$
 $\langle \text{name} \rangle \ x = \langle \text{expr} \rangle$
– e.g.: `double x = x+x` or
- ▶ $\backslash \ x \rightarrow \langle \text{expr} \rangle \dots\dots\dots$ **anonymous function / lambda expression**
– e.g.: $\backslash \ x \rightarrow x+x \quad :: \text{Num } t \Rightarrow t \rightarrow t$
– e.g.: $\backslash \ x \rightarrow \backslash \ y \rightarrow x+y \quad :: \text{Num } t \Rightarrow t \rightarrow t \rightarrow t$
- ▶ $f \ g = \backslash \ x \rightarrow (g \ x) + 1$
 $f = \backslash \ g \rightarrow \backslash \ x \rightarrow (g \ x) + 1$, or $f = \backslash \ g \ x \rightarrow (g \ x) + 1$
 $f :: \text{Num } a \Rightarrow (t \rightarrow a) \rightarrow t \rightarrow a$ **$g :: ?$**
- ▶ **Destruction:** function application, $\langle \text{function} \rangle \ \langle \text{expr} \rangle$:
– `double 2` $(\backslash \ x \rightarrow x+x) \ 2 == 4$
– `f (\y -> y*y)`

Function Types

- ▶ Given typeK and typeM, we have a type **typeK -> typeM**
- ▶ **Construction:** for $x :: \text{typeK}$, $\langle \text{expr} \rangle :: \text{typeM}$
 $\langle \text{name} \rangle \ x = \langle \text{expr} \rangle$
– e.g.: `double x = x+x` or
- ▶ $\backslash \ x \rightarrow \langle \text{expr} \rangle \dots\dots\dots$ **anonymous function / lambda expression**
– e.g.: $\backslash \ x \rightarrow x+x \quad :: \text{Num } t \Rightarrow t \rightarrow t$
– e.g.: $\backslash \ x \rightarrow \backslash \ y \rightarrow x+y \quad :: \text{Num } t \Rightarrow t \rightarrow t \rightarrow t$
- ▶ $f \ g = \backslash \ x \rightarrow (g \ x) + 1$
 $f = \backslash \ g \rightarrow \backslash \ x \rightarrow (g \ x) + 1$, or $f = \backslash \ g \ x \rightarrow (g \ x) + 1$
 $f :: \text{Num } a \Rightarrow (t \rightarrow a) \rightarrow t \rightarrow a$ **$g :: ?$**
- ▶ **Destruction:** function application, $\langle \text{function} \rangle \ \langle \text{expr} \rangle$:
– `double 2` $(\backslash \ x \rightarrow x+x) \ 2 == 4$
– $f \ (\backslash y \rightarrow y*y)$ $\backslash x \rightarrow ((\backslash y \rightarrow y*y) \ x)+1$

Function Types

- ▶ Given typeK and typeM, we have a type **typeK -> typeM**
- ▶ **Construction:** for $x :: \text{typeK}$, $\langle \text{expr} \rangle :: \text{typeM}$
 $\langle \text{name} \rangle \ x = \langle \text{expr} \rangle$
– e.g.: `double x = x+x` or
- ▶ $\backslash \ x \rightarrow \langle \text{expr} \rangle \dots\dots\dots$ **anonymous function / lambda expression**
– e.g.: $\backslash \ x \rightarrow x+x \quad :: \text{Num } t \Rightarrow t \rightarrow t$
– e.g.: $\backslash \ x \rightarrow \backslash \ y \rightarrow x+y \quad :: \text{Num } t \Rightarrow t \rightarrow t \rightarrow t$
- ▶ $f \ g = \backslash \ x \rightarrow (g \ x) + 1$
 $f = \backslash \ g \rightarrow \backslash \ x \rightarrow (g \ x) + 1$, or $f = \backslash \ g \ x \rightarrow (g \ x) + 1$
 $f :: \text{Num } a \Rightarrow (t \rightarrow a) \rightarrow t \rightarrow a$ **$g :: ?$**
- ▶ **Destruction:** function application, $\langle \text{function} \rangle \ \langle \text{expr} \rangle$:
– `double 2` $(\backslash \ x \rightarrow x+x) \ 2 == 4$
– $f \ (\backslash \ y \rightarrow y*y) \quad \backslash \ x \rightarrow ((\backslash \ y \rightarrow y*y) \ x)+1$
 $== \backslash \ x \rightarrow x*x + 1$

Function Types

- ▶ Given typeK and typeM, we have a type **typeK -> typeM**
- ▶ **Construction**: for $x :: \text{typeK}$, $\langle \text{expr} \rangle :: \text{typeM}$
 - $\langle \text{name} \rangle \ x = \langle \text{expr} \rangle$
 - e.g.: `double x = x+x` or
- ▶ $\backslash x \rightarrow \langle \text{expr} \rangle \dots\dots\dots$ **anonymous function / lambda expression**
 - e.g.: $\backslash x \rightarrow x+x \quad :: \text{Num } t \Rightarrow t \rightarrow t$
 - e.g.: $\backslash x \rightarrow \backslash y \rightarrow x+y \quad :: \text{Num } t \Rightarrow t \rightarrow t \rightarrow t$
- ▶ $f\ g = \backslash x \rightarrow (g\ x) + 1$
 - $f = \backslash g \rightarrow \backslash x \rightarrow (g\ x) + 1$, or $f = \backslash g\ x \rightarrow (g\ x) + 1$
 - $f :: \text{Num } a \Rightarrow (t \rightarrow a) \rightarrow t \rightarrow a$ **$g :: ?$**
- ▶ **Destruction**: function application, $\langle \text{function} \rangle \ \langle \text{expr} \rangle$:
 - `double 2` $(\backslash x \rightarrow x+x)\ 2 == 4$
 - $f\ (\backslash y \rightarrow y*y) \quad \backslash x \rightarrow ((\backslash y \rightarrow y*y)\ x)+1$

$$== \backslash x \rightarrow x*x + 1$$
- ▶ **Equality** in principle impossible

Function Types

- ▶ Given `typeK` and `typeM`, we have a type `typeK -> typeM`
- ▶ **Construction**: for `x :: typeK`, `<expr> :: typeM`
`<name> x = <expr>`
– e.g.: `double x = x+x` or
- ▶ `\ x -> <expr>.....` **anonymous function / lambda expression**
– e.g.: `\ x -> x+x :: Num t => t -> t`
– e.g.: `\ x -> \ y -> x+y :: Num t => t -> t -> t`
- ▶ `f g = \ x -> (g x) + 1`
`f = \ g -> \ x -> (g x) + 1`, or `f = \ g x -> (g x) + 1`
`f :: Num a => (t -> a) -> t -> a` **`g :: ?`**
- ▶ **Destruction**: function application, `<function> <expr>`:
– `double 2 (\ x -> x+x) 2 == 4`
– `f (\y -> y*y) \x -> ((\y -> y*y) x)+1`
$$== \lambda x \rightarrow x*x + 1$$
- ▶ **Equality** in principle impossible
- ▶ **Show** in principle impossible

prefix

`div :: Integral t => t -> t -> t`

`div 7 2 == 3`

prefix

infix

`div :: Integral t => t -> t -> t`

`div 7 2 == 3`

\gg

`'div'` can be written in infix notat.

`7 'div' 2 == 3`

prefix

$\text{div} :: \text{Integral } t \Rightarrow t \rightarrow t \rightarrow t$	\gg	<code>'div'</code> can be written in infix notat.
$\text{div } 7 \ 2 == 3$		$7 \text{ 'div' } 2 == 3$

$+$ $:: (\text{Int}, \text{Int}) \rightarrow \text{Int}$
 $3 + 4 == + (3,4) == 7$

prefix

$\text{div} :: \text{Integral } t \Rightarrow t \rightarrow t \rightarrow t$	\gg	'div' can be written in infix notat.
$\text{div } 7 \ 2 == 3$		$7 \text{ 'div' } 2 == 3$

$(+) :: \text{Int} \rightarrow \text{Int} \rightarrow \text{Int}$	\ll	$+$ $:: (\text{Int}, \text{Int}) \rightarrow \text{Int}$
$(+) \ 3 \ 4 == 7$		$3 + 4 == + (3,4) == 7$

prefix

$\text{div} :: \text{Integral } t \Rightarrow t \rightarrow t \rightarrow t$	\gg	'div' can be written in infix notat.
$\text{div } 7 \ 2 == 3$		$7 \text{ 'div' } 2 == 3$

$(+) :: \text{Int} \rightarrow \text{Int} \rightarrow \text{Int}$	\ll	$+$ $:: (\text{Int}, \text{Int}) \rightarrow \text{Int}$
$(+) \ 3 \ 4 == 7$		$3 + 4 == + (3,4) == 7$
$(-) :: \text{Int} \rightarrow \text{Int} \rightarrow \text{Int}$	\ll	$-$ $:: (\text{Int}, \text{Int}) \rightarrow \text{Int}$

prefix

$\text{div} :: \text{Integral } t \Rightarrow t \rightarrow t \rightarrow t$	\gg	'div' can be written in infix notat.
$\text{div } 7 \ 2 == 3$		$7 \text{ 'div' } 2 == 3$

$(+) :: \text{Int} \rightarrow \text{Int} \rightarrow \text{Int}$	\ll	$+$	$:: (\text{Int}, \text{Int}) \rightarrow \text{Int}$
$(+) \ 3 \ 4 == 7$		$3 + 4 == + (3,4) == 7$	
$(-) :: \text{Int} \rightarrow \text{Int} \rightarrow \text{Int}$	\ll	$-$	$:: (\text{Int}, \text{Int}) \rightarrow \text{Int}$

Two types are isomorphic:

$$A \rightarrow (B \rightarrow C) \simeq (A, B) \rightarrow C$$

prefix

$\text{div} :: \text{Integral } t \Rightarrow t \rightarrow t \rightarrow t$	\gg	'div' can be written in infix notat.
$\text{div } 7 \ 2 == 3$		$7 \text{ 'div' } 2 == 3$

$(+) :: \text{Int} \rightarrow \text{Int} \rightarrow \text{Int}$	\ll	$+$	$:: (\text{Int}, \text{Int}) \rightarrow \text{Int}$
$(+) \ 3 \ 4 == 7$		$3 + 4 == + (3,4) == 7$	
$(-) :: \text{Int} \rightarrow \text{Int} \rightarrow \text{Int}$	\ll	$-$	$:: (\text{Int}, \text{Int}) \rightarrow \text{Int}$

Two types are isomorphic:

$A \rightarrow (B \rightarrow C)$	\simeq	$(A, B) \rightarrow C$
$(f) :: A \rightarrow (B \rightarrow C)$	\ll	$f :: (A, B) \rightarrow C$

prefix

$\text{div} :: \text{Integral } t \Rightarrow t \rightarrow t \rightarrow t$	\gg	'div' can be written in infix notat.
$\text{div } 7 \ 2 == 3$		$7 \text{ 'div' } 2 == 3$

$(+) :: \text{Int} \rightarrow \text{Int} \rightarrow \text{Int}$	\ll	$+$	$:: (\text{Int}, \text{Int}) \rightarrow \text{Int}$
$(+) \ 3 \ 4 == 7$		$3 + 4 == + (3,4) == 7$	
$(-) :: \text{Int} \rightarrow \text{Int} \rightarrow \text{Int}$	\ll	$-$	$:: (\text{Int}, \text{Int}) \rightarrow \text{Int}$

Two types are isomorphic:

$A \rightarrow (B \rightarrow C)$	\simeq	$(A, B) \rightarrow C$
$(f) :: A \rightarrow (B \rightarrow C)$	\ll	$f :: (A, B) \rightarrow C$
$(f) \ a \ b$	$=$	$f(a,b)$

prefix

$\text{div} :: \text{Integral } t \Rightarrow t \rightarrow t \rightarrow t$	\gg	'div' can be written in infix notat.
$\text{div } 7 \ 2 == 3$		$7 \text{ 'div' } 2 == 3$

$(+) :: \text{Int} \rightarrow \text{Int} \rightarrow \text{Int}$	\ll	$+$	$:: (\text{Int}, \text{Int}) \rightarrow \text{Int}$
$(+) \ 3 \ 4 == 7$		$3 + 4 == + (3,4) == 7$	
$(-) :: \text{Int} \rightarrow \text{Int} \rightarrow \text{Int}$	\ll	$-$	$:: (\text{Int}, \text{Int}) \rightarrow \text{Int}$

Two types are isomorphic:

$A \rightarrow (B \rightarrow C)$	\simeq	$(A, B) \rightarrow C$
$(f) :: A \rightarrow (B \rightarrow C)$	\ll	$f :: (A, B) \rightarrow C$
$(f) \ a \ b$	$=$	$f(a,b)$

$(+2) = (+) \ 2 :: \text{Int} \rightarrow \text{Int}$	"section"
$(+2) \ 1 = 3, \text{ etc.}$	

Currying

Introduced by [Gottlob Frege](#), developed by [Moses Schönfinkel](#)

Currying

Introduced by [Gottlob Frege](#), developed by [Moses Schönfinkel](#)



Haskell Brooks Curry

Three programming languages named after him:

- ▶ Haskell
- ▶ Brook
- ▶ Curry

Basic types, each with a set of operators

- ▶ integers `..., -2, -1, 0, 1, 2, ..., ...` :: `Int`
`+, -, *, div, mod`
- ▶ boolean values `True, False, ...` :: `Bool`
`not, ||, &&, or, and`
- ▶ symbols `..., 'A', ..., 'z', ..., ...` :: `Char`
`toUpper, toLower, isDigit (Bool)` in `Data.Char`
- ▶ strings like `“abc”`, `...` :: `String`
`++, head, tail`
- ▶ fractions ... `1.2, 3.5 ...` :: `Float`
`+, -, *, /`

Basic types, what is the type of the operators?

- ▶ integers `..., -2, -1, 0, 1, 2, ..., ...` :: `Int`
`(+), (-), (*), (div)` ::
- ▶ boolean values `True, False, ...` :: `Bool`
- ▶ symbols `..., 'A', ..., 'z', ..., ...` :: `Char`
- ▶ strings like `'abc', ...` :: `String`
- ▶ fractions `... 1.2, 3.5 ...` :: `Float`

Basic types, what is the type of the operators?

- ▶ integers `..., -2, -1, 0, 1, 2, ...,` :: `Int`
`(+), (-), (*), (div)` :: `Num a => a -> a -> a`
- ▶ boolean values `True, False,` :: `Bool`
- ▶ symbols `..., 'A', ..., 'z',` :: `Char`
- ▶ strings like `'abc',` :: `String`
- ▶ fractions ... `1.2, 3.5` :: `Float`

Basic types, [what is the type of the operators?](#)

- ▶ integers `..., -2, -1, 0, 1, 2, ...,` :: `Int`
`(+), (-), (*), (div) :: Num a => a -> a -> a`
- ▶ boolean values `True, False,` :: `Bool`
`not ::` `or, and ::`
- ▶ symbols `..., 'A', ..., 'z', ...,` :: `Char`
- ▶ strings like `'abc',` :: `String`
- ▶ fractions ... `1.2, 3.5` :: `Float`

Basic types, what is the type of the operators?

- ▶ integers `..., -2, -1, 0, 1, 2, ...,` :: `Int`
`(+), (-), (*), (div) :: Num a => a -> a -> a`
- ▶ boolean values `True, False,` :: `Bool`
`not :: Bool -> Bool; or, and ::`
- ▶ symbols `..., 'A', ..., 'z', ...,` :: `Char`
- ▶ strings like `'abc',` :: `String`
- ▶ fractions ... `1.2, 3.5` :: `Float`

Basic types, what is the type of the operators?

- ▶ integers `..., -2, -1, 0, 1, 2, ...` :: `Int`
`(+), (-), (*), (div)` :: `Num a => a -> a -> a`
- ▶ boolean values `True, False, ...` :: `Bool`
`not` :: `Bool -> Bool`; `or, and` :: `[Bool] -> Bool`
- ▶ symbols `..., 'A', ..., 'z', ...` :: `Char`
- ▶ strings like `'abc'`, ... :: `String`
- ▶ fractions ... `1.2, 3.5` ... :: `Float`

Basic types, what is the type of the operators?

- ▶ integers $\dots, -2, -1, 0, 1, 2, \dots$:: Int
 $(+), (-), (*), (\text{div}) :: \text{Num } a \Rightarrow a \rightarrow a \rightarrow a$
- ▶ boolean values True, False, ... :: Bool
 $\text{not} :: \text{Bool} \rightarrow \text{Bool}; \text{or}, \text{and} :: [\text{Bool}] \rightarrow \text{Bool}$
 $(||), (\&\&) ::$
- ▶ symbols $\dots, 'A', \dots 'z', \dots$:: Char
- ▶ strings like `“abc”`, ... :: String
- ▶ fractions ... 1.2, 3.5 ... :: Float

Basic types, what is the type of the operators?

- ▶ integers $\dots, -2, -1, 0, 1, 2, \dots$:: Int
 $(+), (-), (*), (\text{div}) :: \text{Num } a \Rightarrow a \rightarrow a \rightarrow a$
- ▶ boolean values True, False, ... :: Bool
 $\text{not} :: \text{Bool} \rightarrow \text{Bool}$; $\text{or}, \text{and} :: [\text{Bool}] \rightarrow \text{Bool}$
 $(||), (\&\&) :: \text{Bool} \rightarrow \text{Bool} \rightarrow \text{Bool}$
- ▶ symbols $\dots, 'A', \dots 'z', \dots$:: Char
- ▶ strings like `“abc”`, ... :: String
- ▶ fractions ... 1.2, 3.5 ... :: Float

Basic types, what is the type of the operators?

- ▶ integers `..., -2, -1, 0, 1, 2, ...` :: `Int`
`(+), (-), (*), (div)` :: `Num a => a -> a -> a`
- ▶ boolean values `True, False, ...` :: `Bool`
`not` :: `Bool -> Bool`; `or, and` :: `[Bool] -> Bool`
`(||), (&&)` :: `Bool -> Bool -> Bool`
- ▶ symbols `..., 'A', ..., 'z', ...` :: `Char`
`toUpper` :: `Char -> Char`; `isDigit` :: `Char -> Bool`
- ▶ strings like `"abc"`, `"123"`, `"True"`, `"1.2"`, `"3.5"` :: `String`
- ▶ fractions `... 1.2, 3.5 ...` :: `Float`

Basic types, what is the type of the operators?

- ▶ integers `..., -2, -1, 0, 1, 2, ...` :: `Int`
`(+), (-), (*), (div)` :: `Num a => a -> a -> a`
- ▶ boolean values `True, False, ...` :: `Bool`
`not` :: `Bool -> Bool`; `or, and` :: `[Bool] -> Bool`
`(||), (&&)` :: `Bool -> Bool -> Bool`
- ▶ symbols `..., 'A', ..., 'z', ...` :: `Char`
`toUpper` :: `Char -> Char`; `isDigit` ::
- ▶ strings like `'abc'`, :: `String`
- ▶ fractions ... `1.2, 3.5` ... :: `Float`

Basic types, what is the type of the operators?

- ▶ integers `..., -2, -1, 0, 1, 2, ...` :: `Int`
`(+), (-), (*), (div)` :: `Num a => a -> a -> a`
- ▶ boolean values `True, False, ...` :: `Bool`
`not` :: `Bool -> Bool`; `or, and` :: `[Bool] -> Bool`
`(||), (&&)` :: `Bool -> Bool -> Bool`
- ▶ symbols `..., 'A', ..., 'z', ...` :: `Char`
`toUpper` :: `Char -> Char`; `isDigit` :: `Char -> Bool`
- ▶ strings like `"abc"`, :: `String`
- ▶ fractions ... `1.2, 3.5` ... :: `Float`

Basic types, what is the type of the operators?

- ▶ integers `..., -2, -1, 0, 1, 2, ...` :: `Int`
`(+), (-), (*), (div)` :: `Num a => a -> a -> a`
- ▶ boolean values `True, False, ...` :: `Bool`
`not` :: `Bool -> Bool`; `or, and` :: `[Bool] -> Bool`
`(||), (&&)` :: `Bool -> Bool -> Bool`
- ▶ symbols `..., 'A', ..., 'z', ...` :: `Char`
`toUpper` :: `Char -> Char`; `isDigit` :: `Char -> Bool`
- ▶ strings like `"abc"`, :: `String`
`head` :: `String -> Char`; `(++)` :: `String -> String -> String`
- ▶ fractions ... `1.2, 3.5` ... :: `Float`

Basic types, what is the type of the operators?

- ▶ integers `..., -2, -1, 0, 1, 2, ..., ...` :: `Int`
`(+), (-), (*), (div)` :: `Num a => a -> a -> a`
- ▶ boolean values `True, False, ...` :: `Bool`
`not` :: `Bool -> Bool`; `or, and` :: `[Bool] -> Bool`
`(||), (&&)` :: `Bool -> Bool -> Bool`
- ▶ symbols `..., 'A', ..., 'z', ..., ...` :: `Char`
`toUpper` :: `Char -> Char`; `isDigit` :: `Char -> Bool`
- ▶ strings like `"abc"`, `...` :: `String`
`head` :: `[a] -> a`; `(++)` ::
- ▶ fractions ... `1.2, 3.5 ...` :: `Float`

Basic types, what is the type of the operators?

- ▶ integers `..., -2, -1, 0, 1, 2, ...` :: `Int`
`(+), (-), (*), (div)` :: `Num a => a -> a -> a`
- ▶ boolean values `True, False, ...` :: `Bool`
`not` :: `Bool -> Bool`; `or, and` :: `[Bool] -> Bool`
`(||), (&&)` :: `Bool -> Bool -> Bool`
- ▶ symbols `..., 'A', ..., 'z', ...` :: `Char`
`toUpper` :: `Char -> Char`; `isDigit` :: `Char -> Bool`
- ▶ strings like `"abc"`, ... :: `String`
`head` :: `[a] -> a`; `(++)` :: `[a] -> [a] -> [a]`
- ▶ fractions ... `1.2, 3.5` ... :: `Float`

Basic types, what is the type of the operators?

- ▶ integers `..., -2, -1, 0, 1, 2, ...` :: `Int`
`(+), (-), (*), (div)` :: `Num a => a -> a -> a`
- ▶ boolean values `True, False, ...` :: `Bool`
`not` :: `Bool -> Bool`; `or, and` :: `[Bool] -> Bool`
`(||), (&&)` :: `Bool -> Bool -> Bool`
- ▶ symbols `..., 'A', ..., 'z', ...` :: `Char`
`toUpper` :: `Char -> Char`; `isDigit` :: `Char -> Bool`
- ▶ strings like `"abc"`, ... :: `String`
`head` :: `[a] -> a`; `(++)` :: `[a] -> [a] -> [a]`
- ▶ fractions ... `1.2, 3.5` ... :: `Float`
`(/)` ::

Basic types, what is the type of the operators?

- ▶ integers `..., -2, -1, 0, 1, 2, ...` :: `Int`
`(+), (-), (*), (div)` :: `Num a => a -> a -> a`
- ▶ boolean values `True, False, ...` :: `Bool`
`not` :: `Bool -> Bool`; `or, and` :: `[Bool] -> Bool`
`(||), (&&)` :: `Bool -> Bool -> Bool`
- ▶ symbols `..., 'A', ..., 'z', ...` :: `Char`
`toUpper` :: `Char -> Char`; `isDigit` :: `Char -> Bool`
- ▶ strings like `"abc"`, :: `String`
`head` :: `[a] -> a`; `(++)` :: `[a] -> [a] -> [a]`
- ▶ fractions ... `1.2, 3.5` ... :: `Float`
`(/)` :: `Fractional a => a -> a -> a`

Types are (most often) instances of type “classes”

- **Show**, with an operation `show :: a -> String`
Read, with an operation `read :: String -> a`

Types are (most often) instances of type “classes”

- ▶ **Show**, with an operation `show :: a -> String`
- ▶ **Read**, with an operation `read :: String -> a`
- ▶ **Eq**, with `==, /= :: a -> a -> Bool`

Types are (most often) instances of type “classes”

- ▶ **Show**, with an operation `show :: a -> String`
- ▶ **Read**, with an operation `read :: String -> a`
- ▶ **Eq**, with `==, /= :: a -> a -> Bool`
- ▶ **Num**, `(+), (-), (*), abs, negate...`,
 - a subclass of **Eq** and **Show** with subclasses like

Types are (most often) instances of type “classes”

- ▶ **Show**, with an operation `show :: a -> String`
- ▶ **Read**, with an operation `read :: String -> a`
- ▶ **Eq**, with `==, /= :: a -> a -> Bool`
- ▶ **Num**, `(+)`, `(-)`, `(*)`, `abs`, `negate...`,
 - a subclass of **Eq** and **Show** with subclasses like
 - **Integral**

Types are (most often) instances of type “classes”

- ▶ **Show**, with an operation `show :: a -> String`
- ▶ **Read**, with an operation `read :: String -> a`
- ▶ **Eq**, with `==, /= :: a -> a -> Bool`
- ▶ **Num**, `(+)`, `(-)`, `(*)`, `abs`, `negate...`,
 - a subclass of **Eq** and **Show** with subclasses like
 - **Integral**
 - **Fractional**

Types are (most often) instances of type “classes”

- ▶ **Show**, with an operation `show :: a -> String`
- ▶ **Read**, with an operation `read :: String -> a`
- ▶ **Eq**, with `==, /= :: a -> a -> Bool`
- ▶ **Num**, `(+)`, `(-)`, `(*)`, `abs`, `negate...`,
 - a subclass of `Eq` and `Show` with subclasses like
 - **Integral**
 - **Fractional**
 - ...

Types are (most often) instances of type “classes”

- ▶ **Show**, with an operation `show :: a -> String`
- Read**, with an operation `read :: String -> a`
- ▶ **Eq**, with `==, /= :: a -> a -> Bool`
- ▶ **Num**, `(+), (-), (*), abs, negate...`,
 - a subclass of **Eq** and **Show** with subclasses like
 - **Integral**
 - **Fractional**
 - ...
- ▶ **Ord**, a subclass of **Eq**, with instances (types) that are totally ordered; operations like
 - `(<), (<=), (>), (>=) :: a -> a -> Bool`
 - `min, max :: a -> a -> a`

Types are (most often) instances of type “classes”

- ▶ **Show**, with an operation `show :: a -> String`
- Read**, with an operation `read :: String -> a`
- ▶ **Eq**, with `==, /= :: a -> a -> Bool`
- ▶ **Num**, `(+), (-), (*), abs, negate...`,
 - a subclass of **Eq** and **Show** with subclasses like
 - **Integral**
 - **Fractional**
 - ...
- ▶ **Ord**, a subclass of **Eq**, with instances (types) that are totally ordered; operations like
 - `(<), (<=), (>), (>=) :: a -> a -> Bool`
 - `min, max :: a -> a -> a`
- ▶ ...

Types are (most often) instances of type “classes”

- ▶ **Show**, with an operation `show :: a -> String`
Read, with an operation `read :: String -> a`
- ▶ **Eq**, with `==, /= :: a -> a -> Bool`
- ▶ **Num**, `(+), (-), (*), abs, negate...`,
 - a subclass of **Eq** and **Show** with subclasses like
 - **Integral**
 - **Fractional**
 - ...
- ▶ **Ord**, a subclass of **Eq**, with instances (types) that are totally ordered; operations like
 - `(<), (<=), (>), (>=) :: a -> a -> Bool`
 - `min, max :: a -> a -> a`
- ▶ ...
- ▶ All basic types are instances of **Eq**, **Ord**, **Show** and **Read**. Also, lists and tuples are of such types, if the types of their elements/components are so.

- ▶ `class Eq t where`
 `(==), (/=) :: t -> t -> Bool`

- ▶ `class Eq t where`
 `(==), (/=) :: t -> t -> Bool`
 `x /= y = not(x == y)`

- ▶ `class Eq t where`
 `(==), (/=) :: t -> t -> Bool`
 `x /= y = not(x == y)`
- ▶ classes can have subclasses
 `class Eq t => Ord t where`

- ▶ `class Eq t where`
 `(==), (/=) :: t -> t -> Bool`
 `x /= y = not(x == y)`
- ▶ classes can have subclasses
 `class Eq t => Ord t where`
 `(>), (<), (>=), (<=) :: t -> t -> Bool`

- ▶ `class Eq t where`
 `(==), (/=) :: t -> t -> Bool`
 `x /= y = not(x == y)`
- ▶ classes can have subclasses
 `class Eq t => Ord t where`
 `(>), (<), (>=), (<=) :: t -> t -> Bool`
 `min, max :: t -> t -> t`
 ...

- ▶ `class Eq t where`
 `(==), (/=) :: t -> t -> Bool`
 `x /= y = not(x == y)`
- ▶ classes can have subclasses
 `class Eq t => Ord t where`
 `(>), (<), (>=), (<=) :: t -> t -> Bool`
 `min, max :: t -> t -> t`
 ...
- ▶ types declared with `data` and `newtype` can be instances of classes

- ▶ `class Eq t where`
 `(==), (/=) :: t -> t -> Bool`
 `x /= y = not(x == y)`
- ▶ classes can have subclasses
 `class Eq t => Ord t where`
 `(>), (<), (>=), (<=) :: t -> t -> Bool`
 `min, max :: t -> t -> t`
 ...
- ▶ types declared with `data` and `newtype` can be instances of classes
- i) `instance Ord Bool where`
 `False < True = True`

- ▶ `class Eq t where`
 `(==), (/=) :: t -> t -> Bool`
 `x /= y = not(x == y)`
- ▶ classes can have subclasses
 `class Eq t => Ord t where`
 `(>), (<), (>=), (<=) :: t -> t -> Bool`
 `min, max :: t -> t -> t`
 ...
- ▶ types declared with `data` and `newtype` can be instances of classes
 - i) `instance Ord Bool where`
 `False < True = True`
 - ii) `data Bool = False | True deriving (Eq, Ord)`

- ▶ `class Eq t where`
 `(==), (/=) :: t -> t -> Bool`
 `x /= y = not(x == y)`
- ▶ classes can have subclasses
 `class Eq t => Ord t where`
 `(>), (<), (>=), (<=) :: t -> t -> Bool`
 `min, max :: t -> t -> t`
 ...
- ▶ types declared with `data` and `newtype` can be instances of classes
 - i) `instance Ord Bool where`
 `False < True = True`
 - ii) `data Bool = False | True deriving (Eq, Ord)`

User-defined types

- ▶ **Type synonyms:** `type Pos = (Int,Int)`

User-defined types

- ▶ **Type synonyms:** `type` `Pos` = `(Int,Int)`
- ▶ **New data types:** `data` `Direction` = `Ne | Se | Sw | Nw`
`newtype` `Nat` = `Na Int`

User-defined types

- ▶ **Type synonyms:** `type` Pos = (Int,Int)
- ▶ **New data types:** `data` Direction = Ne | Se | Sw | Nw
`newtype` Nat = Na Int

```
data BTreInt = Leaf Int | Node Int Int
```

Leaf and Node are **constructors**

User-defined types

- ▶ **Type synonyms:** `type` Pos = (Int,Int)
- ▶ **New data types:** `data` Direction = Ne | Se | Sw | Nw
`newtype` Nat = Na Int

```
data BTreInt = Leaf Int | Node Int Int
```

Leaf and Node are **constructors**

(unique constructor name: ... | Node Int – error)

User-defined types

- ▶ **Type synonyms:** `type Pos = (Int,Int)`
- ▶ **New data types:** `data Direction = Ne | Se | Sw | Nw`
`newtype Nat = Na Int`

```
data BTreeInt = Leaf Int | Node Int Int
```

Leaf and Node are **constructors**

(unique constructor name: ... | Node Int – error)

User-defined types

- ▶ **Type synonyms:** `type Pos = (Int,Int)`
- ▶ **New data types:** `data Direction = Ne | Se | Sw | Nw`
`newtype Nat = Na Int`

```
data BTreInt = Leaf Int | Node Int Int
```

Leaf and Node are **constructors**

(unique constructor name: ... | Node Int – error)

- ▶ **Names of types and constructors must start with capital letters!**

User-defined types

- ▶ **Type synonyms:** `type Pos = (Int,Int)`
- ▶ **New data types:** `data Direction = Ne | Se | Sw | Nw`
`newtype Nat = Na Int`

the type can be declared as an instance of a class `deriving (Eq, Ord)`
`instance Eq Direction where...`

`data BTreeInt = Leaf Int | Node Int Int`
Leaf and Node are **constructors**
(unique constructor name: ... | Node Int – error)

- ▶ Names of types and constructors must start with **capital letters**!

User-defined types

- ▶ **Type synonyms:** `type Pos = (Int,Int)`
- ▶ **New data types:** `data Direction = Ne | Se | Sw | Nw`
`newtype Nat = Na Int`

the type can be declared as an instance of a class `deriving (Eq, Ord)`
`instance Eq Direction where...`

`data BTreeInt = Leaf Int | Node Int Int`
Leaf and Node are **constructors**
(unique constructor name: ... | Node Int – error)

- ▶ Names of types and constructors must start with **capital letters!**
- ▶ For simple types, functions which are inherited through **deriving**
 - from Show, Read, Eq, Ord, Enum, Bounded –

are automatically derived by Haskell. However, one can redefine them, if desired.

Type synonyms – `type`

```
type Pos = (Int,Int)
```

Type synonyms – **type**

```
type Pos = (Int,Int)
```

Parametrised types:

```
► type Anypair a = (a,a)
```

Type synonyms – **type**

```
type Pos = (Int,Int)
```

Parametrised types:

```
► type Anypair a = (a,a)
```

← a is a **type parameter**

```
type Pos = (Int,Int)
```

Parametrised types:

- ▶ `type Anypair a = (a,a)` ← a is a **type parameter**
- ▶ Given the types `Key` and `Value`, we can declare a new type:
`type Dict = [(Key, Value)]`

```
type Pos = (Int,Int)
```

Parametrised types:

- ▶ `type Anypair a = (a,a)` ← a is a **type parameter**
- ▶ Given the types **Key** and **Value**, we can declare a new type:
`type Dict = [(Key, Value)]`
`find n d =`

```
type Pos = (Int,Int)
```

Parametrised types:

- ▶ `type Anypair a = (a,a)` ← a is a **type parameter**
- ▶ Given the types `Key` and `Value`, we can declare a new type:

```
type Dict = [(Key, Value)]
```

```
find n d =      [ v' | (k',v') <- d, k' == n ]
```

```
type Pos = (Int,Int)
```

Parametrised types:

- ▶ `type Anypair a = (a,a)` \leftarrow `a` is a **type parameter**
- ▶ Given the types `Key` and `Value`, we can declare a new type:

```
type Dict = [(Key, Value)]
```



```
find n d = [ v' | (k',v') <- d, k' == n ]
```



```
type Pos = (Int,Int)
```

Parametrised types:

- ▶ `type Anypair a = (a,a)` ← a is a **type parameter**
- ▶ Given the types `Key` and `Value`, we can declare a new type:

```
type Dict = [(Key, Value)] instance Eq Key
```

```
find n d = [ v' | (k',v') <- d, k' == n ]
```

```
type Pos = (Int,Int)
```

Parametrised types:

- ▶ `type Anypair a = (a,a)` ← a is a **type parameter**
- ▶ Given the types `Key` and `Value`, we can declare a new type:

```
type Dict = [(Key, Value)]           instance Eq Key
```

```
find n d = head [ v' | (k',v') <- d, k' == n ]
```

```
type Pos = (Int,Int)
```

Parametrised types:

- ▶ `type Anypair a = (a,a)` ← a is a **type parameter**
- ▶ Given the types **Key** and **Value**, we can declare a new type:
`type Dict = [(Key, Value)]` instance Eq Key
`find n d = head [v' | (k',v') <- d, k' == n]`

```
type Pos = (Int,Int)
```

Parametrised types:

- ▶ `type Anypair a = (a,a)` ← a is a **type parameter**
- ▶ Given the types `Key` and `Value`, we can declare a new type:

```
type Dict = [(Key, Value)]
```

instance Eq Key

```
find n d = head [ v' | (k',v') <- d, k' == n ]
```
- parametrise the type (with type variables)

```
type Dict k v = [(k,v)]
```

```
type Pos = (Int,Int)
```

Parametrised types:

- ▶ `type Anypair a = (a,a)` \leftarrow `a` is a **type parameter**
- ▶ Given the types `Key` and `Value`, we can declare a new type:

```
type Dict = [(Key, Value)]
```

`instance Eq Key`

```
find n d = head [ v' | (k',v') <- d, k' == n ]
```
- parametrise the type (with type variables)

```
type Dict k v = [(k,v)]
```

 \leftarrow `k`, `v` are **type parameters**

```
type Pos = (Int,Int)
```

Parametrised types:

- ▶ `type Anypair a = (a,a)` \leftarrow `a` is a **type parameter**
- ▶ Given the types `Key` and `Value`, we can declare a new type:

```
type Dict = [(Key, Value)]
```

`instance Eq Key`

```
find n d = head [ v' | (k',v') <- d, k' == n ]
```
- parametrise the type (with type variables)

```
type Dict k v = [(k,v)]
```

 \leftarrow `k`, `v` are **type parameters**
- ▶ `find ::`

```
type Pos = (Int,Int)
```

Parametrised types:

- ▶ `type Anypair a = (a,a)` \leftarrow `a` is a **type parameter**
- ▶ Given the types `Key` and `Value`, we can declare a new type:
`type Dict = [(Key, Value)]` instance Eq Key
`find n d = head [v' | (k',v') <- d, k' == n]`
- parametrise the type (with type variables)
`type Dict k v = [(k,v)]` \leftarrow `k`, `v` are **type parameters**
- ▶ `find :: k -> Dict k v -> v`

```
type Pos = (Int,Int)
```

Parametrised types:

- ▶ `type Anypair a = (a,a)` \leftarrow `a` is a **type parameter**
- ▶ Given the types `Key` and `Value`, we can declare a new type:
`type Dict = [(Key, Value)]` **instance Eq Key**
`find n d = head [v' | (k',v') <- d, k' == n]`
- parametrise the type (with type variables)
`type Dict k v = [(k,v)]` \leftarrow `k`, `v` are **type parameters**
- ▶ `find :: Eq k => k -> Dict k v -> v`

User-defined data types: `data`

```
data Direction = North | South | East | West
```

User-defined data types: `data`

```
data Direction = North | South | East | West
```

– own constructors of data type requires keyword `data...`

User-defined data types: **data**

- ▶ `data Fig = Circ Float | Rect Float Float`

User-defined data types: **data**

- ▶ `data Fig = Circ Float | Rect Float Float`
- ▶ data constructors are **functions** of the type, i.e.,

User-defined data types: **data**

- ▶ `data Fig = Circ Float | Rect Float Float`
- ▶ data constructors are **functions** of the type, i.e.,
`Circ :: Float -> Fig`
`Rect :: Float -> Float -> Fig`

User-defined data types: **data**

- ▶ `data Fig = Circ Float | Rect Float Float`
- ▶ data constructors are **functions** of the type, i.e.,
`Circ :: Float -> Fig`
`Rect :: Float -> Float -> Fig`
- > but they do not have any defining equations, because
`Rect 2 3` is already a completely evaluated value = `Rect 2 3 :: Fig`

User-defined data types: **data**

- ▶ `data Fig = Circ Float | Rect Float Float`
- ▶ data constructors are functions of the type, i.e.,
`Circ :: Float -> Fig`
`Rect :: Float -> Float -> Fig`
- > but they do not have any defining equations, because
`Rect 2 3` is already a completely evaluated value = `Rect 2 3 :: Fig`
- ▶ Functions can now be defined by using constructors as patterns:

User-defined data types: **data**

- ▶ `data Fig = Circ Float | Rect Float Float`
- ▶ data constructors are functions of the type, i.e.,
`Circ :: Float -> Fig`
`Rect :: Float -> Float -> Fig`
- > but they do not have any defining equations, because
`Rect 2 3` is already a completely evaluated value = `Rect 2 3 :: Fig`
- ▶ Functions can now be defined by using constructors as patterns:
`square n = Rect n n`

User-defined data types: **data**

- ▶ `data Fig = Circ Float | Rect Float Float`
- ▶ data constructors are functions of the type, i.e.,
`Circ :: Float -> Fig`
`Rect :: Float -> Float -> Fig`
- > but they do not have any defining equations, because
`Rect 2 3` is already a completely evaluated value = `Rect 2 3 :: Fig`
- ▶ Functions can now be defined by using constructors as patterns:
`square n = Rect n n`
`area (Rect n m) = n*m`

User-defined data types: **data**

- ▶ `data Fig = Circ Float | Rect Float Float`
- ▶ data constructors are functions of the type, i.e.,
`Circ :: Float -> Fig`
`Rect :: Float -> Float -> Fig`
- > but they do not have any defining equations, because
`Rect 2 3` is already a completely evaluated value = `Rect 2 3 :: Fig`
- ▶ Functions can now be defined by using constructors as patterns:
`square n = Rect n n`
`area (Rect n m) = n*m`
`area (Circ n) = pi * n^2`

User-defined data types: **data**

- ▶ `data Fig = Circ Float | Rect Float Float`
- ▶ data constructors are functions of the type, i.e.,
`Circ :: Float -> Fig`
`Rect :: Float -> Float -> Fig`
- > but they do not have any defining equations, because
`Rect 2 3` is already a completely evaluated value = `Rect 2 3 :: Fig`
- ▶ Functions can now be defined by using constructors as patterns:
`square n = Rect n n`
`area (Rect n m) = n*m`
`area (Circ n) = pi * n^2`
- ▶ `Circ/Rect` can informally be understood as “subtypes” of `Fig`

User-defined data types: **data**

- ▶ `data Fig = Circ Float | Rect Float Float`
- ▶ data constructors are functions of the type, i.e.,
`Circ :: Float -> Fig`
`Rect :: Float -> Float -> Fig`
- > but they do not have any defining equations, because
`Rect 2 3` is already a completely evaluated value = `Rect 2 3 :: Fig`
- ▶ Functions can now be defined by using constructors as patterns:
`square n = Rect n n`
`area (Rect n m) = n*m`
`area (Circ n) = pi * n^2`
- ▶ `Circ/Rect` can informally be understood as “subtypes” of `Fig`
- ▶ **`data Circ = Ci Int`**
`data Fig = Circ | ...`

User-defined data types: **data**

- ▶ `data Fig = Circ Float | Rect Float Float`
- ▶ data constructors are functions of the type, i.e.,
`Circ :: Float -> Fig`
`Rect :: Float -> Float -> Fig`
- but they do not have any defining equations, because
`Rect 2 3` is already a completely evaluated value = `Rect 2 3 :: Fig`
- ▶ Functions can now be defined by using constructors as patterns:
`square n = Rect n n`
`area (Rect n m) = n*m`
`area (Circ n) = pi * n^2`
- ▶ `Circ/Rect` can informally be understood as “subtypes” of `Fig`
- ▶ `data Circ = Ci Int`
`data Fig = Constr Circ | ...`

Example

► data Move = Up | Down | Left | Right

Example

- ▶ data Move = Up | Down | Left | Right
deriving (Eq, Ord, Read, Show)

Example

- ▶ data Move = Up | Down | Left | Right
deriving (Eq, Ord, Read, Show)
- ▶ type Pos = (Int, Int)

Example

- ▶ `data Move = Up | Down | Left | Right`
deriving (Eq, Ord, Read, Show)
- ▶ `type Pos = (Int, Int)`
- ▶ `mv :: Pos -> Move -> Pos`

Example

- ▶ `data Move = Up | Down | Left | Right`
deriving (Eq, Ord, Read, Show)
- ▶ `type Pos = (Int, Int)`
- ▶ `mv :: Pos -> Move -> Pos`
`mv (x,y) Left = (x-1,y) mv (x,y) Right = (x+1,y)`

Example

- ▶ `data Move = Up | Down | Left | Right`
deriving (Eq, Ord, Read, Show)
- ▶ `type Pos = (Int, Int)`
- ▶ `mv :: Pos -> Move -> Pos`
`mv (x,y) Left = (x-1,y) mv (x,y) Right = (x+1,y)`
`mv (x,y) Up = (x,y+1) mv (x,y) Down = (x,y-1)`

Example

- ▶ `data Move = Up | Down | Left | Right`
deriving (Eq, Ord, Read, Show)
- ▶ `type Pos = (Int, Int)`
- ▶ `mv :: Pos -> Move -> Pos`
`mv (x,y) Left = (x-1,y) mv (x,y) Right = (x+1,y)`
`mv (x,y) Up = (x,y+1) mv (x,y) Down = (x,y-1)`
- ▶ `mvs :: Pos -> [Move] -> Pos`

Example

- ▶ `data Move = Up | Down | Left | Right`
deriving (Eq, Ord, Read, Show)
- ▶ `type Pos = (Int, Int)`
- ▶ `mv :: Pos -> Move -> Pos`
`mv (x,y) Left = (x-1,y) mv (x,y) Right = (x+1,y)`
`mv (x,y) Up = (x,y+1) mv (x,y) Down = (x,y-1)`
- ▶ `mvs :: Pos -> [Move] -> Pos`
`mvs p [] = p`

Example

- ▶ `data Move = Up | Down | Left | Right`
deriving (Eq, Ord, Read, Show)
- ▶ `type Pos = (Int, Int)`
- ▶ `mv :: Pos -> Move -> Pos`
`mv (x,y) Left = (x-1,y) mv (x,y) Right = (x+1,y)`
`mv (x,y) Up = (x,y+1) mv (x,y) Down = (x,y-1)`
- ▶ `mvs :: Pos -> [Move] -> Pos`
`mvs p [] = p`
`mvs p (r:rs) =`

Example

- ▶ `data Move = Up | Down | Left | Right`
deriving (Eq, Ord, Read, Show)
- ▶ `type Pos = (Int, Int)`
- ▶ `mv :: Pos -> Move -> Pos`
`mv (x,y) Left = (x-1,y) mv (x,y) Right = (x+1,y)`
`mv (x,y) Up = (x,y+1) mv (x,y) Down = (x,y-1)`
- ▶ `mvs :: Pos -> [Move] -> Pos`
`mvs p [] = p`
`mvs p (r:rs) = mvs (mv p r) rs`

User-defined **recursive** data types

User-defined **recursive** data types

► `data Tree = Leaf Int | Node Tree Int Tree`

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree`
search: left subtrees have **only smaller** nodes than the root
right subtrees have **no smaller** nodes than the root

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree`
search: left subtrees have **only smaller** nodes than the root
right subtrees have **no smaller** nodes than the root
- ▶ `list (Leaf y) = [y]`
`list (Node l y r) = list l ++ [y] ++ list r`

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree`
search: left subtrees have **only smaller** nodes than the root
right subtrees have **no smaller** nodes than the root
- ▶ `list (Leaf y) = [y]`
`list (Node l y r) = list l ++ [y] ++ list r sorted list!`

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree`
search: left subtrees have **only smaller** nodes than the root
right subtrees have **no smaller** nodes than the root
- ▶ `list (Leaf y) = [y]`
`list (Node l y r) = list l ++ [y] ++ list r sorted list!`
- ▶ `find x (Leaf y) = if x==y then y else error "No "` ++ show x

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree`
search: left subtrees have **only smaller** nodes than the root
right subtrees have **no smaller** nodes than the root
- ▶ `list (Leaf y) = [y]`
`list (Node l y r) = list l ++ [y] ++ list r sorted list!`
- ▶ `find x (Leaf y) = if x==y then y else error "No "` ++ `show x`
`find x (Leaf x) = x - illegal: unique variables in patterns`

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree`
search: left subtrees have **only smaller** nodes than the root
right subtrees have **no smaller** nodes than the root
- ▶ `list (Leaf y) = [y]`
`list (Node l y r) = list l ++ [y] ++ list r sorted list!`
- ▶ `find x (Leaf y) = if x==y then y else error "No "` ++ show x
`find x (Leaf x) = x - illegal: unique variables in patterns`
`find x (Node l n r) | x==n = n`

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree`
search: left subtrees have **only smaller** nodes than the root
right subtrees have **no smaller** nodes than the root
- ▶ `list (Leaf y) = [y]`
`list (Node l y r) = list l ++ [y] ++ list r sorted list!`
- ▶ `find x (Leaf y) = if x==y then y else error "No "` ++ `show x`
`find x (Leaf x) = x - illegal: unique variables in patterns`
`find x (Node l n r) | x==n = n`
`| x<n = find x l`

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree`
search: left subtrees have **only smaller** nodes than the root
right subtrees have **no smaller** nodes than the root
- ▶ `list (Leaf y) = [y]`
`list (Node l y r) = list l ++ [y] ++ list r` sorted list!
- ▶ `find x (Leaf y) = if x==y then y else error "No "` ++ show x
`find x (Leaf x) = x` – illegal: unique variables in patterns
`find x (Node l n r) | x==n = n`
 | `x<n = find x l`
 | `otherwise = find x r`

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree`
search: left subtrees have **only smaller** nodes than the root
right subtrees have **no smaller** nodes than the root
- ▶ `list (Leaf y) = [y]`
`list (Node l y r) = list l ++ [y] ++ list r sorted list!`
- ▶ `find x (Leaf y) = if x==y then y else error "No "` ++ `show x`
`find x (Leaf x) = x - illegal: unique variables in patterns`
`find x (Node l n r) | x==n = n`
`| x<n = find x l`
`| otherwise = find x r` **case syntax!**

User-defined recursive data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree`
 search: left subtrees have **only smaller** nodes than the root
 right subtrees have **no smaller** nodes than the root
- ▶ `list (Leaf y) = [y]`
`list (Node l y r) = list l ++ [y] ++ list r sorted list!`
- ▶ `find x (Leaf y) = if x==y then y else error "No " ++ show x`
`find x (Leaf x) = x - illegal: unique variables in patterns`
`find x (Node l n r) | x==n = n`
 | `x<n = find x l`
 | `otherwise = find x r` case syntax!
- ▶ `insert x (Leaf y) = ?`

User-defined recursive data types

- ▶ data Tree = Leaf Int | Node Tree Int Tree
 search: left subtrees have **only smaller** nodes than the root
 right subtrees have **no smaller** nodes than the root
 - ▶ list (Leaf y) = [y]
 list (Node l y r) = list l ++ [y] ++ list r sorted list!
 - ▶ find x (Leaf y) = **if** x==y **then** y **else** error "No " ++ show x
 find x (Leaf x) = x – illegal: unique variables in patterns
 find x (Node l n r) | x==n = n
 | x<n = find x l
 | otherwise = find x r case syntax!
- insert x (Leaf y) = if x<y then

User-defined recursive data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree`
 search: left subtrees have **only smaller** nodes than the root
 right subtrees have **no smaller** nodes than the root
- ▶ `list (Leaf y) = [y]`
`list (Node l y r) = list l ++ [y] ++ list r sorted list!`
- ▶ `find x (Leaf y) = if x==y then y else error "No " ++ show x`
`find x (Leaf x) = x - illegal: unique variables in patterns`
`find x (Node l n r) | x==n = n`
 | `x<n = find x l`
 | `otherwise = find x r` case syntax!
- `insert x (Leaf y) = if x<y then Node (Leaf x) y Emp`

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
search: left subtrees have **only smaller** nodes than the root
right subtrees have **no smaller** nodes than the root
 - ▶ `list (Leaf y) = [y]`
`list (Node l y r) = list l ++ [y] ++ list r sorted list!`
 - ▶ `find x (Leaf y) = if x==y then y else error "No " ++ show x`
`find x (Leaf x) = x - illegal: unique variables in patterns`
`find x (Node l n r) | x==n = n`
`| x<n = find x l`
`| otherwise = find x r` case syntax!
- `insert x (Leaf y) = if x<y then Node (Leaf x) y Emp`

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
search: left subtrees have **only smaller** nodes than the root
right subtrees have **no smaller** nodes than the root
 - ▶ `list (Leaf y) = [y]`
`list (Node l y r) = list l ++ [y] ++ list r` sorted list!
 - ▶ `find x (Leaf y) = if x==y then y else error "No "` ++ show x
`find x (Leaf x) = x` – illegal: unique variables in patterns
`find x (Node l n r) | x==n = n`
 | `x<n = find x l`
 | `otherwise = find x r` case syntax!
- `insert x (Leaf y) = if x<y then Node (Leaf x) y Emp`
 `else Node Emp y (Leaf x)`

User-defined **recursive** data types

- ▶ data Tree = Leaf Int | Node Tree Int Tree | Emp
search: left subtrees have **only smaller** nodes than the root
right subtrees have **no smaller** nodes than the root
- ▶ list (Leaf y) = [y]
list (Node l y r) = list l ++ [y] ++ list r sorted list!
- ▶ find x (Leaf y) = **if** x==y **then** y **else** error "No " ++ show x
find x (Leaf x) = x – illegal: unique variables in patterns
find x (Node l n r) | x==n = n
 | x<n = find x l
 | otherwise = find x r case syntax!
- ▶ insert x **Emp** = Leaf x
insert x (Leaf y) = if x<y then Node (Leaf x) y Emp
 else Node Emp y (Leaf x)

User-defined recursive data types

- ▶ data Tree = Leaf Int | Node Tree Int Tree | Emp
- search: left subtrees have **only smaller** nodes than the root
- right subtrees have **no smaller** nodes than the root
- ▶ list (Leaf y) = [y]
- list (Node l y r) = list l ++ [y] ++ list r sorted list!
- ▶ find x (Leaf y) = **if** x==y **then** y **else** error "No " ++ show x
- find x (Leaf x) = x – illegal: unique variables in patterns
- find x (Node l n r) | x==n = n
- | x<n = find x l
- | otherwise = find x r
- case syntax!
- ▶ insert x Emp = Leaf x
- insert x (Leaf y) = if x<y then Node (Leaf x) y Emp
- else Node Emp y (Leaf x)
- insert x (Node l y r) =

User-defined **recursive** data types

- ▶ data Tree = Leaf Int | Node Tree Int Tree | Emp
search: left subtrees have **only smaller** nodes than the root
right subtrees have **no smaller** nodes than the root
- ▶ list (Leaf y) = [y]
list (Node l y r) = list l ++ [y] ++ list r sorted list!
- ▶ find x (Leaf y) = **if** x==y **then** y **else** error "No " ++ show x
find x (Leaf x) = x – illegal: unique variables in patterns
find x (Node l n r) | x==n = n
 | x<n = find x l
 | otherwise = find x r case syntax!
- ▶ insert x Emp = Leaf x
insert x (Leaf y) = if x<y then Node (Leaf x) y Emp
 else Node Emp y (Leaf x)
insert x (Node l y r) = if x<y then Node (insert x l) y r

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
search: left subtrees have **only smaller** nodes than the root
right subtrees have **no smaller** nodes than the root
- ▶ `list (Leaf y) = [y]`
`list (Node l y r) = list l ++ [y] ++ list r` sorted list!
- ▶ `find x (Leaf y) = if x==y then y else error "No "` ++ show x
`find x (Leaf x) = x` – illegal: unique variables in patterns
`find x (Node l n r) | x==n = n`
 | `x<n = find x l`
 | `otherwise = find x r` case syntax!
- ▶ `insert x Emp = Leaf x`
`insert x (Leaf y) = if x<y then Node (Leaf x) y Emp`
 else `Node Emp y (Leaf x)`
`insert x (Node l y r) = if x<y then Node (insert x l) y r`
 else `Node l y (insert x r)`

User-defined **recursive** data types

► `data Tree = Leaf Int | Node Tree Int Tree | Emp`

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?

User-defined recursive data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?
 $| \text{height}(\text{left subtree}) - \text{height}(\text{right subtree}) | \leq 1$

User-defined recursive data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?
 - | $\text{height}(\text{left subtree}) - \text{height}(\text{right subtree})| \leq 1$
 - in any subtree

User-defined recursive data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?
 - | $\text{height}(\text{left subtree}) - \text{height}(\text{right subtree})| \leq 1$
 - in any subtree
- ▶ $\text{height Emp} = 0$
 $\text{height (Leaf } y) = 1$
 $\text{height (Node } l \ a \ r) = 1 + \max (\text{height } l) (\text{height } r)$

User-defined recursive data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?
 - | $\text{height}(\text{left subtree}) - \text{height}(\text{right subtree})| \leq 1$
 - in any subtree
- ▶ `height Emp = 0`
`height (Leaf y) = 1`
`height (Node l a r) = 1 + max (height l) (height r)`
- ▶ `balanced Emp = True`
`balanced (Leaf y) = True`

User-defined recursive data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?
| $\text{height}(\text{left subtree}) - \text{height}(\text{right subtree})| \leq 1$
– in any subtree
- ▶ `height Emp = 0`
`height (Leaf y) = 1`
`height (Node l a r) = 1 + max (height l) (height r)`
- ▶ `balanced Emp = True`
`balanced (Leaf y) = True`
`balanced (Node l y r) =`
`abs((height l) - (height r)) <= 1`

User-defined recursive data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?
| $\text{height}(\text{left subtree}) - \text{height}(\text{right subtree})| \leq 1$
– in any subtree
- ▶ `height Emp = 0`
`height (Leaf y) = 1`
`height (Node l a r) = 1 + max (height l) (height r)`
- ▶ `balanced Emp = True`
`balanced (Leaf y) = True`
`balanced (Node l y r) =`
`[abs((height l) - (height r)) <= 1 , balanced(l), balanced(r)]`

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?
| $\text{height}(\text{left subtree}) - \text{height}(\text{right subtree})| \leq 1$
– in any subtree
- ▶ `height Emp = 0`
`height (Leaf y) = 1`
`height (Node l a r) = 1 + max (height l) (height r)`
- ▶ `balanced Emp = True`
`balanced (Leaf y) = True`
`balanced (Node l y r) =`
`and [abs((height l) - (height r)) <= 1 , balanced(l), balanced(r)]`
`and :: [Bool] -> Bool`

User-defined **recursive** data types

► `data Tree = Leaf Int | Node Tree Int Tree | Emp`

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?

User-defined recursive data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?
 $| \#(\text{leaves in the left tree}) - \#(\text{leaves in right subtree}) | \leq 1$

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?
 - | $\#(\text{leaves in the left tree}) - \#(\text{leaves in right subtree}) \mid \leq 1$
 - **in any subtree**

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?
 - | $\#(\text{leaves in the left tree}) - \#(\text{leaves in right subtree}) \mid \leq 1$
 - in any subtree
- ▶ `leaf Emp = 0`
 - `leaf (Leaf y) = 1`
 - `leaf (Node l a r) = leaf(l) + leaf(r)`

User-defined recursive data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?
 - | $\#(\text{leaves in the left tree}) - \#(\text{leaves in right subtree}) \mid \leq 1$
 - in any subtree
- ▶ `leaf Emp = 0`
 - `leaf (Leaf y) = 1`
 - `leaf (Node l a r) = leaf(l) + leaf(r)`
- ▶ `balanced Emp = True`
 - `balanced (Leaf y) = True`

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?
 $| \#(\text{leaves in the left tree}) - \#(\text{leaves in right subtree}) | \leq 1$
– in any subtree
- ▶ `leaf Emp = 0`
`leaf (Leaf y) = 1`
`leaf (Node l a r) = leaf(l) + leaf(r)`
- ▶ `balanced Emp = True`
`balanced (Leaf y) = True`
`balanced (Node l y r) =`
 $\text{abs}(\text{leaf}(l) - \text{leaf}(r)) \leq 1$

User-defined recursive data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?
 - $| \#(\text{leaves in the left tree}) - \#(\text{leaves in right subtree}) | \leq 1$
 - in any subtree
- ▶ `leaf Emp = 0`
 - `leaf (Leaf y) = 1`
 - `leaf (Node l a r) = leaf(l) + leaf(r)`
- ▶ `balanced Emp = True`
 - `balanced (Leaf y) = True`
 - `balanced (Node l y r) =`
 - `[abs(leaf(l) - leaf(r)) <= 1 , balanced(l), balanced(r)]`

User-defined **recursive** data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree | Emp`
- ▶ balanced binary tree?
 - | $\#(\text{leaves in the left tree}) - \#(\text{leaves in right subtree}) \mid \leq 1$
 - in any subtree
- ▶ `leaf Emp = 0`
`leaf (Leaf y) = 1`
`leaf (Node l a r) = leaf(l) + leaf(r)`
- ▶ `balanced Emp = True`
`balanced (Leaf y) = True`
`balanced (Node l y r) =`
`and [abs(leaf(l) - leaf(r)) <= 1 , balanced(l), balanced(r)]`
`and :: [Bool] -> Bool`

User-defined parametrised data types

► `data Tree = Leaf Int | Node Tree Int Tree`

User-defined parametrised data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree`
- ▶ `data Tree t = Leaf t | Node (Tree t) t (Tree t)`

User-defined parametrised data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree`
 - ▶ `data Tree t = Leaf t | Node (Tree t) t (Tree t)`
- `Tree t = Leaf t | Node (Tree t) (Tree t)`

User-defined parametrised data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree`
 - ▶ `data Tree t = Leaf t | Node (Tree t) t (Tree t)`
- `Tree t = Leaf t | Node (Tree t) (Tree t)`

User-defined parametrised data types

► data Tree = Leaf Int | Node Tree Int Tree

► data Tree t = Leaf t | Node (Tree t) t (Tree t)

Tree t = Leaf t | Node (Tree t) (Tree t)data only at leaves

User-defined parametrised data types

► data Tree = Leaf Int | Node Tree Int Tree

► data Tree t = Leaf t | Node (Tree t) t (Tree t)

Tree t = Leaf t | Node (Tree t) (Tree t)data only at leaves
= Leaf | Node (Tree t) t (Tree t)

User-defined parametrised data types

► data Tree = Leaf Int | Node Tree Int Tree

► data Tree t = Leaf t | Node (Tree t) t (Tree t)

Tree t = Leaf t | Node (Tree t) (Tree t)data only at leaves
= Leaf | Node (Tree t) t (Tree t)

User-defined parametrised data types

► data Tree = Leaf Int | Node Tree Int Tree

► data Tree t = Leaf t | Node (Tree t) t (Tree t)

Tree t = Leaf t | Node (Tree t) (Tree t) data only at leaves

= Leaf | Node (Tree t) t (Tree t) can only at internal nodes

User-defined parametrised data types

► data Tree = Leaf Int | Node Tree Int Tree

► data Tree t = Leaf t | Node (Tree t) t (Tree t)

Tree t = Leaf t | Node (Tree t) (Tree t)data only at leaves

= Leaf | Node (Tree t) t (Tree t)can only at internal nodes

= Node t [Tree t]

User-defined parametrised data types

► data Tree = Leaf Int | Node Tree Int Tree

► data Tree t = Leaf t | Node (Tree t) t (Tree t)

Tree t = Leaf t | Node (Tree t) (Tree t)data only at leaves

= Leaf | Node (Tree t) t (Tree t)can only at internal nodes

= Node t [Tree t]

User-defined parametrised data types

► data Tree = Leaf Int | Node Tree Int Tree

► data Tree t = Leaf t | Node (Tree t) t (Tree t)

Tree t = Leaf t | Node (Tree t) (Tree t)data only at leaves

= Leaf | Node (Tree t) t (Tree t)can only at internal nodes

= Node t [Tree t] several children (a leaf has empty child-list)

User-defined parametrised data types

► `data Tree = Leaf Int | Node Tree Int Tree`

► `data Tree t = Leaf t | Node (Tree t) t (Tree t)`

`Tree t = Leaf t | Node (Tree t) (Tree t)` data only at leaves

`= Leaf | Node (Tree t) t (Tree t)` can only at internal nodes

`= Node t [Tree t]` several children (a leaf has empty child-list)

► `left (Leaf x) =`

User-defined parametrised data types

► data Tree = Leaf Int | Node Tree Int Tree

► data Tree t = Leaf t | Node (Tree t) t (Tree t)

Tree t = Leaf t | Node (Tree t) (Tree t)data only at leaves

= Leaf | Node (Tree t) t (Tree t)can only at internal nodes

= Node t [Tree t] several children (a leaf has empty child-list)

► left (Leaf x) = (???)

User-defined parametrised data types

► data Tree = Leaf Int | Node Tree Int Tree

► data Tree t = Leaf t | Node (Tree t) t (Tree t)

Tree t = Leaf t | Node (Tree t) (Tree t)data only at leaves

= Leaf | Node (Tree t) t (Tree t)can only at internal nodes

= Node t [Tree t] several children (a leaf has empty child-list)

► left (Leaf x) = Nothing

User-defined parametrised data types

► data Tree = Leaf Int | Node Tree Int Tree

► data Tree t = Leaf t | Node (Tree t) t (Tree t)

Tree t = Leaf t | Node (Tree t) (Tree t)data only at leaves

= Leaf | Node (Tree t) t (Tree t)can only at internal nodes

= Node t [Tree t] several children (a leaf has empty child-list)

► left (Leaf x) = Nothing

left (Node l x r) = Just l

User-defined parametrised data types

► `data Tree = Leaf Int | Node Tree Int Tree`

► `data Tree t = Leaf t | Node (Tree t) t (Tree t)`

`Tree t = Leaf t | Node (Tree t) (Tree t)` data only at leaves

`= Leaf | Node (Tree t) t (Tree t)` can only at internal nodes

`= Node t [Tree t]` several children (a leaf has empty child-list)

► `left (Leaf x) = Nothing`

`left (Node l x r) = Just l`

► `data Maybe t = Nothing | Just t` `(import Data.Maybe)`

User-defined parametrised data types

- ▶ `data Tree = Leaf Int | Node Tree Int Tree`

- ▶ `data Tree t = Leaf t | Node (Tree t) t (Tree t)`

`Tree t = Leaf t | Node (Tree t) (Tree t)` data only at leaves

`= Leaf | Node (Tree t) t (Tree t)` can only at internal nodes

`= Node t [Tree t]` several children (a leaf has empty child-list)

- ▶ `left (Leaf x) = Nothing`

`left (Node l x r) = Just l`

- ▶ `data Maybe t = Nothing | Just t` (import Data.Maybe)

for partial functions – which returns values of type `t`

User-defined parametrised data types

► `data Tree = Leaf Int | Node Tree Int Tree`

► `data Tree t = Leaf t | Node (Tree t) t (Tree t)`

`Tree t = Leaf t | Node (Tree t) (Tree t)` data only at leaves

`= Leaf | Node (Tree t) t (Tree t)` can only at internal nodes

`= Node t [Tree t]` several children (a leaf has empty child-list)

► `left (Leaf x) = Nothing`

`left (Node l x r) = Just l`

► `data Maybe t = Nothing | Just t` (import Data.Maybe)

for partial functions – which returns values of type `t`

`phead [] = Nothing`

`phead (x:xs) = Just x`

User-defined parametrised data types

► `data Tree = Leaf Int | Node Tree Int Tree`

► `data Tree t = Leaf t | Node (Tree t) t (Tree t)`

`Tree t = Leaf t | Node (Tree t) (Tree t)` data only at leaves

`= Leaf | Node (Tree t) t (Tree t)` can only at internal nodes

`= Node t [Tree t]` several children (a leaf has empty child-list)

► `left (Leaf x) = Nothing`

`left (Node l x r) = Just l`

► `data Maybe t = Nothing | Just t` (import Data.Maybe)

for partial functions – which returns values of type `t`

`phead [] = Nothing`

`phead (x:xs) = Just x :: Maybe t (the type of x)`

User-defined parametrised data types

▶ `data Tree = Leaf Int | Node Tree Int Tree`

▶ `data Tree t = Leaf t | Node (Tree t) t (Tree t)`

`Tree t = Leaf t | Node (Tree t) (Tree t)` data only at leaves

`= Leaf | Node (Tree t) t (Tree t)` can only at internal nodes

`= Node t [Tree t]` several children (a leaf has empty child-list)

▶ `left (Leaf x) = Nothing`

`left (Node l x r) = Just l`

▶ `data Maybe t = Nothing | Just t` (import Data.Maybe)

for partial functions – which returns values of type `t`

`phead [] = Nothing`

`phead (x:xs) = Just x :: Maybe t` (the type of `x`)

Sometimes, requires `cast` (back) to get the correct type of the correct result, e.g.,

`fromJust :: Maybe t -> t`

`fromJust (Just x) = x`

which is often required when Maybe-values can be returned

User-defined data types – `newtype`

Creates a new type in a similar way as `data`,

User-defined data types – **newtype**

Creates a new type in a similar way as **data**,
but has only a **single** constructor

```
newtype Nat = N Int
```

User-defined data types – **newtype**

Creates a new type in a similar way as **data**,
but has only a **single** constructor

```
newtype Nat = N Int
```

- ▶ **type** Nat = Int

- Nat and Int are the same in this case

User-defined data types – **newtype**

Creates a new type in a similar way as **data**,
but has only a **single** constructor

newtype Nat = N Int

► **type** Nat = Int

- Nat and Int are the same in this case

► **data** Nat = N Int

- Almost the same, but the constructor is removed after type checking

Creates a new type in a similar way as **data**,
but has only a **single** constructor

newtype Nat = N Int

▶ **type** Nat = Int

- Nat and Int are the same in this case

▶ **data** Nat = N Int

- Almost the same, but the constructor is removed after type checking

▶ Improve **type safety**, maintain **performance**

User-defined data types – **newtype**