

EC 504 – Spring 2023 – Homework 2

Due Wednesday, Feb 22, 11:59PM, 2023. Submit the coding and graphic in the directory `/projectnb/ec504rb/students/yourname/HW2` on your SCC account. The figures will be returned to gradescope. More information in class next week on what to return!

GOAL: This is a short exercise to learn how to measure and fit performance to curves. Also to present. The result will be presented in graphical form. On the EC504 GitHub at `Plotting_and_Fitting` there is information on how to use gnuplot and even in **LittleGnuplot.pdf** instructions on how to install gnuplot in your laptop. This is convenient but all can be done easily using gnuplot on the SCC through the SCC OnDemand interface. Use Slack to exchange helpful hints on graphing!

1 Sorting Problem

The main file on GitHub has a range of sorting algorithms and the ability to construct random lists of varying sizes N . The exercise is to run them for a range of the sizes $N = 16, 32, 64, 128, \dots$, average over at an ensemble of cases (as much as 100). to get good statistics. Report the average behavior a function of N for each sorting method as to determine the scaling empirically as function of the number the mean number of swap operations vs N .

The main code `sortScaling.cpp` runs the example:

```
insertionSort  mergeSort  quickSort  shellSort
```

1.1 Part 2: Sorting Plotting Exercise

The exercise is to make a table of average performance for all 4 algorithms and plot them to see how the scale with N .

For the standard $O(N^2)$ search algorithms involve local (nearest neighbor) exchanges of element of the given list

$$A_{list} = a[0], a[1], a[2], a[3], \dots, a[N-1] \quad (1)$$

You should find for `insertionSort` you should verify empirically average the algorithm would have

$$\text{Number of Exchanges} = \frac{N(N-1)}{4} \quad (2)$$

For `mergeSort` it should be exactly $\Theta(N \log N)$ and for `quickSort` on average $O(N \log N)$. Finally see if you can find the value of the γ for shell sort $O(N^\gamma)$.

The exercise is to modify the main file to build an output data file to plot. The code will be tested to see that it does give output but the grade is mostly on the figure and explanation put in gradescope.

# N	insertionSort	mergeSort	quickSort	shellSort
16	xxxx	xxxx	xxxx	xxxxx
32	xxxx	xxxx	xxxx	xxxxx
64	xxxx	xxxx	xxxx	xxxxx
128	xxxx	xxxx	xxxx	xxxxx
....				

where **xxxx** are the average values. This is convenient for using gnuplot to plot and fit the curves.

This output file can be made by a **hack** by printing to the standard output. Just run the code in a terminal (aka shell) with `./sort > datafile.txt`. Then you take what you need using an editor. This is a useful quick trick, however you should really set up a separate **output** file. This is necessary if you want to submit your code in queue. To set up an output file see the example to do this on GitHub at [HW1_codes/makeSortedList.cpp](#) (Hey basic software technique. Steal method from other codes!)

You should turn in on gradescope figures and fits for all 4 sorting as function of size N. Can comment on how well the theoretical scaling is verified numerically. It is up to you to do this as you wish. You may choose to combine different algorithms on the same plot.

1.2 Part 2: Get better Statistics and Fit with Error bars

For full credit you should also run statistics to estimate error bars and to a least square fit to estimate the goodness of fit. If you have time you could add error bars to the table above and fit with error bars. The average of random cases defined as mean square deviation (called σ or standard error) a second. Add error bars to the average (called σ) defined as mean square deviation a second column next to the tabulated averages **xxxx**. These are defined for each algorithm and size N by

$$\sigma^2 = \frac{1}{N_{trials}} \sum_{i=1}^{N_{trials}} (Swaps[i] - Mean)^2 = \frac{1}{N_{trials}} \sum_{i=1}^{N_{trials}} Swaps[i]^2 - Mean^2$$

where above we suggested fixing $N_{trials} = 10 - 100$ range. The average numbers of swaps in the 100 trials for each algorithm and size N in the table are:

$$Mean = \frac{1}{N_{trials}} \sum_{i=1}^{N_{trials}} Swaps[i]$$

You will want to have your code compute the standard error and put into another column in your output file. By the way all these analysis skills will likely come in handy for the team project.

Not you want a enlarge output table something like:

```
# N  insertion Mean Error | merge  Mean  Error  | ...
16  xxxx    xxxx    xxxx    xxxx    ....
32  xxxx    xxxx    xxxx    xxxx    ....
64  xxxx    xxxx    xxxx    xxxx    ....
128 xxxx    xxxx    xxxx    xxxx    ....
....
```

I used a print statements C style fprintf I O which is easier to format. The synatac

```
fprintf(cFile,"#          N          Insertion      Mean      Error      |
                Merge      Mean      Error      |
                Quick      Mean      Error      |
                Shell      Mean      Error      | \n ");

// Compute loops and averaging.

fprintf(cFile," %10d %10d %10.5e %10.5e %10d %10.5e %10.5e %10d %10.5e
               %10.5e %10d %10.5e %10.5e \n", N, TotInsert,MeanInsert, rmsInsert,
               TotMerge, MeanMerge, rmsMerge, TotQuick, MeanQuick, rmsQuick,
               TotShell , MeanShell, rmsShell );
```

The syntax for opening and closing a file are:

```
FILE* cFile;
cFile = fopen ("Plotfile.txt","w+");

// Print lots of stuff accumulated from the loops to file in tabular form

fclose(cFile);
```

You should turn in on gradescope figures and fits for all 4 sorting including errors to give a chisqr of fit. Can comment on how well the theoretical scaling is verified numerically. It is up to you to do this as you wish. You may choose to combine different algorityms on the same plot.

For general background information the `sorting.h` files has a few more sorting algorithms to play with. We could add others like bucket and improve pivots for quicksort etc.

COMMENT: In real time in class there will be help next week on all that is need to do these plots and fits.